

TEST DATA OF GT3.5-24

Regulated DC Power Supply

July 23, 2010

Approved by : Eiyoshi Wakamatsu
Eiyoshi Wakamatsu Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Line Regulation	8
9. Load Regulation	9
10. Dynamic Load Response	10
11. Ripple Voltage (by Load Current)	11
12. Ripple Voltage (by Ambient Temperature)	12
13. Ambient Temperature Drift	13
14. Output Voltage Accuracy	14
15. Time Lapse Drift	15
16. Rise and Fall Time	16
17. Hold-Up Time	17
18. Instantaneous Interruption Compensation	18
19. Minimum Input Voltage for Regulated Output Voltage	19
20. Overcurrent Protection	20
21. Figure of Testing Circuitry	21

(Final Page 21)

COSEL

Model	GT3.5-24		
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A
Object	_____		
1.Graph	Input Volt. 90V Input Volt. 100V Input Volt. 110V	2.Values	
<p>Note: Slanted line shows the range of the rated load current.</p>			
Load Current [A]	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]
0.0	0.042	0.041	0.043
0.6	0.430	0.439	0.446
1.2	0.752	0.766	0.778
1.8	1.046	1.066	1.084
2.4	1.326	1.350	1.372
3.0	1.592	1.622	1.648
3.3	1.722	1.754	1.782
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	GT3.5-24
Item	Input Power (by Load Current)
Object	_____
1. Graph	
<p style="text-align: center;"> —△— Input Volt. 90V ---□--- Input Volt. 100V -·○-· Input Volt. 110V </p> <p>The graph plots Input Power [W] on the y-axis against Load Current [A] on the x-axis. Three sets of data points are shown for input voltages of 90V, 100V, and 110V. Each set includes a solid line connecting open triangles (90V), dashed lines connecting open squares (100V), and dash-dot lines connecting open circles (110V). A slanted line is drawn through the data points at approximately 2.4A to indicate the rated load current range.</p>	
<p style="text-align: center;">Input Power [W]</p> <p style="text-align: center;">Load Current [A]</p>	

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]
0.0	2.1	2.4	2.8
0.6	22.7	25.3	28.0
1.2	43.0	48.0	52.9
1.8	63.2	70.3	77.6
2.4	83.2	92.6	102.2
3.0	103.2	114.9	126.6
3.3	112.9	126.0	138.9
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	GT3.5-24	Temperature Testing Circuitry 25°C Figure A
Item	Efficiency (by Input Voltage)	
Object	—	

1. Graph

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
85	72.4	74.4
90	68.0	70.0
100	61.0	62.9
110	55.3	57.0
115	52.8	54.5

Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
85	72.4	74.4
90	68.0	70.0
100	61.0	62.9
110	55.3	57.0
115	52.8	54.5
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	GT3.5-24	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	—																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 90V Input Volt. 100V Input Volt. 110V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.6</td><td>63.7</td><td>57.2</td><td>51.7</td></tr> <tr><td>1.2</td><td>67.3</td><td>60.3</td><td>54.7</td></tr> <tr><td>1.8</td><td>68.7</td><td>61.8</td><td>56.0</td></tr> <tr><td>2.4</td><td>69.6</td><td>62.5</td><td>56.6</td></tr> <tr><td>3.0</td><td>70.0</td><td>62.9</td><td>57.1</td></tr> <tr><td>3.3</td><td>70.4</td><td>63.1</td><td>57.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.0	-	-	-	0.6	63.7	57.2	51.7	1.2	67.3	60.3	54.7	1.8	68.7	61.8	56.0	2.4	69.6	62.5	56.6	3.0	70.0	62.9	57.1	3.3	70.4	63.1	57.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.0	-	-	-																																																			
0.6	63.7	57.2	51.7																																																			
1.2	67.3	60.3	54.7																																																			
1.8	68.7	61.8	56.0																																																			
2.4	69.6	62.5	56.6																																																			
3.0	70.0	62.9	57.1																																																			
3.3	70.4	63.1	57.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL


Model	GT3.5-24																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—																																	
1. Graph																																		
		2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>0.658</td><td>0.725</td></tr> <tr> <td>90</td><td>0.654</td><td>0.720</td></tr> <tr> <td>100</td><td>0.644</td><td>0.708</td></tr> <tr> <td>110</td><td>0.635</td><td>0.699</td></tr> <tr> <td>115</td><td>0.631</td><td>0.693</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.658	0.725	90	0.654	0.720	100	0.644	0.708	110	0.635	0.699	115	0.631	0.693	--	-	-	--	-	-	--	-	-	--	-	-	
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
85	0.658	0.725																																
90	0.654	0.720																																
100	0.644	0.708																																
110	0.635	0.699																																
115	0.631	0.693																																
--	-	-																																
--	-	-																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	GT3.5-24																																																					
Item	Power Factor (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	—	—	—																																																			
1.Graph																																																						
<p style="text-align: center;"> △— Input Volt. 90V □— Input Volt. 100V ○— Input Volt. 110V </p>																																																						
2.Values																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.6</td><td>0.587</td><td>0.576</td><td>0.569</td></tr> <tr><td>1.2</td><td>0.635</td><td>0.627</td><td>0.617</td></tr> <tr><td>1.8</td><td>0.671</td><td>0.659</td><td>0.650</td></tr> <tr><td>2.4</td><td>0.697</td><td>0.685</td><td>0.677</td></tr> <tr><td>3.0</td><td>0.721</td><td>0.708</td><td>0.698</td></tr> <tr><td>3.3</td><td>0.729</td><td>0.718</td><td>0.709</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.0	-	-	-	0.6	0.587	0.576	0.569	1.2	0.635	0.627	0.617	1.8	0.671	0.659	0.650	2.4	0.697	0.685	0.677	3.0	0.721	0.708	0.698	3.3	0.729	0.718	0.709	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.0	-	-	-																																																			
0.6	0.587	0.576	0.569																																																			
1.2	0.635	0.627	0.617																																																			
1.8	0.671	0.659	0.650																																																			
2.4	0.697	0.685	0.677																																																			
3.0	0.721	0.708	0.698																																																			
3.3	0.729	0.718	0.709																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						


COSEL

Model	GT3.5-24	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	—		



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %

Primary inrush current 28.0 A




COSEL

Model	GT3.5-24																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+24V3A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>24.034</td><td>24.015</td></tr> <tr> <td>90</td><td>24.034</td><td>24.035</td></tr> <tr> <td>100</td><td>24.034</td><td>24.035</td></tr> <tr> <td>110</td><td>24.034</td><td>24.035</td></tr> <tr> <td>115</td><td>24.034</td><td>24.035</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	24.034	24.015	90	24.034	24.035	100	24.034	24.035	110	24.034	24.035	115	24.034	24.035	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	24.034	24.015																																
90	24.034	24.035																																
100	24.034	24.035																																
110	24.034	24.035																																
115	24.034	24.035																																
--	-	-																																
--	-	-																																
--	-	-																																
--	-	-																																

COSEL

Model	GT3.5-24	Temperature	25°C																																																				
Item	Load Regulation	Testing Circuitry	Figure A																																																				
Object	+24V3A																																																						
1.Graph	<p>—▲— Input Volt. 90V - - - □ - - Input Volt. 100V - - ○ - - Input Volt. 110V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (90V)</th> <th>Output Voltage [V] (100V)</th> <th>Output Voltage [V] (110V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.034</td><td>24.034</td><td>24.035</td></tr> <tr><td>0.6</td><td>24.034</td><td>24.034</td><td>24.034</td></tr> <tr><td>1.2</td><td>24.034</td><td>24.034</td><td>24.034</td></tr> <tr><td>1.8</td><td>24.034</td><td>24.035</td><td>24.035</td></tr> <tr><td>2.4</td><td>24.035</td><td>24.035</td><td>24.035</td></tr> <tr><td>3.0</td><td>24.035</td><td>24.035</td><td>24.035</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V] (90V)	Output Voltage [V] (100V)	Output Voltage [V] (110V)	0.0	24.034	24.034	24.035	0.6	24.034	24.034	24.034	1.2	24.034	24.034	24.034	1.8	24.034	24.035	24.035	2.4	24.035	24.035	24.035	3.0	24.035	24.035	24.035																							
Load Current [A]	Output Voltage [V] (90V)	Output Voltage [V] (100V)	Output Voltage [V] (110V)																																																				
0.0	24.034	24.034	24.035																																																				
0.6	24.034	24.034	24.034																																																				
1.2	24.034	24.034	24.034																																																				
1.8	24.034	24.035	24.035																																																				
2.4	24.035	24.035	24.035																																																				
3.0	24.035	24.035	24.035																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.034</td><td>24.034</td><td>24.035</td></tr> <tr><td>0.6</td><td>24.034</td><td>24.034</td><td>24.034</td></tr> <tr><td>1.2</td><td>24.034</td><td>24.034</td><td>24.034</td></tr> <tr><td>1.8</td><td>24.034</td><td>24.035</td><td>24.035</td></tr> <tr><td>2.4</td><td>24.035</td><td>24.035</td><td>24.035</td></tr> <tr><td>3.0</td><td>24.035</td><td>24.035</td><td>24.035</td></tr> <tr><td>3.3</td><td>24.035</td><td>24.035</td><td>24.035</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.0	24.034	24.034	24.035	0.6	24.034	24.034	24.034	1.2	24.034	24.034	24.034	1.8	24.034	24.035	24.035	2.4	24.035	24.035	24.035	3.0	24.035	24.035	24.035	3.3	24.035	24.035	24.035	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																				
0.0	24.034	24.034	24.035																																																				
0.6	24.034	24.034	24.034																																																				
1.2	24.034	24.034	24.034																																																				
1.8	24.034	24.035	24.035																																																				
2.4	24.035	24.035	24.035																																																				
3.0	24.035	24.035	24.035																																																				
3.3	24.035	24.035	24.035																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

COSEL

COSEL

Model	GT3.5-24																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																						
Object	+24V3A																																							
1.Graph																																								
		2.Values																																						
<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 90V (Solid Line with open circles) Input Volt. 110V (Dashed Line with open circles) 																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 90 [V]</th> <th>Input Volt. 110 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>2.4</td> <td>2.4</td> </tr> <tr> <td>1.5</td> <td>2.6</td> <td>2.6</td> </tr> <tr> <td>3.0</td> <td>2.8</td> <td>2.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.0	2.4	2.4	1.5	2.6	2.6	3.0	2.8	2.8	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 90 [V]	Input Volt. 110 [V]																																						
0.0	2.4	2.4																																						
1.5	2.6	2.6																																						
3.0	2.8	2.8																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>																																								

COSEL


Model GT3.5-24

Item Ripple Voltage (by Ambient Temp.)

Object +24V3A

1. Graph

---□--- Load 50%
—△— Load 100%



Measured by 20 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	2.8	3.0
-10	2.6	2.8
25	2.6	2.8
50	2.4	2.6
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	GT3.5-24	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+24V3A																																																						
1.Graph	<p>—▲— Input Volt. 90V - - - □ - - Input Volt. 100V - - - ○ - - Input Volt. 110V</p>  <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>23.983</td> <td>23.983</td> <td>23.983</td> </tr> <tr> <td>-10</td> <td>23.995</td> <td>23.995</td> <td>23.995</td> </tr> <tr> <td>0</td> <td>24.008</td> <td>24.008</td> <td>24.008</td> </tr> <tr> <td>10</td> <td>24.019</td> <td>24.019</td> <td>24.019</td> </tr> <tr> <td>20</td> <td>24.028</td> <td>24.028</td> <td>24.028</td> </tr> <tr> <td>25</td> <td>24.031</td> <td>24.031</td> <td>24.031</td> </tr> <tr> <td>30</td> <td>24.033</td> <td>24.033</td> <td>24.033</td> </tr> <tr> <td>40</td> <td>24.034</td> <td>24.034</td> <td>24.035</td> </tr> <tr> <td>50</td> <td>24.033</td> <td>24.033</td> <td>24.034</td> </tr> <tr> <td>60</td> <td>24.030</td> <td>24.030</td> <td>24.030</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	23.983	23.983	23.983	-10	23.995	23.995	23.995	0	24.008	24.008	24.008	10	24.019	24.019	24.019	20	24.028	24.028	24.028	25	24.031	24.031	24.031	30	24.033	24.033	24.033	40	24.034	24.034	24.035	50	24.033	24.033	24.034	60	24.030	24.030	24.030	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																				
-20	23.983	23.983	23.983																																																				
-10	23.995	23.995	23.995																																																				
0	24.008	24.008	24.008																																																				
10	24.019	24.019	24.019																																																				
20	24.028	24.028	24.028																																																				
25	24.031	24.031	24.031																																																				
30	24.033	24.033	24.033																																																				
40	24.034	24.034	24.035																																																				
50	24.033	24.033	24.034																																																				
60	24.030	24.030	24.030																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated ambient temperature.



Model	GT3.5-24	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+24V3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 90 - 110V

Load Current : 0 - 3A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	40	110	3	24.035	±21	±0.1
Minimum Voltage	-10	90	0	23.993		

COSEL

Model	GT3.5-24	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+24V3A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.031</td></tr> <tr><td>0.5</td><td>24.028</td></tr> <tr><td>1.0</td><td>24.028</td></tr> <tr><td>2.0</td><td>24.028</td></tr> <tr><td>3.0</td><td>24.028</td></tr> <tr><td>4.0</td><td>24.028</td></tr> <tr><td>5.0</td><td>24.028</td></tr> <tr><td>6.0</td><td>24.028</td></tr> <tr><td>7.0</td><td>24.028</td></tr> <tr><td>8.0</td><td>24.028</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	24.031	0.5	24.028	1.0	24.028	2.0	24.028	3.0	24.028	4.0	24.028	5.0	24.028	6.0	24.028	7.0	24.028	8.0	24.028
Time since start [H]	Output Voltage [V]																								
0.0	24.031																								
0.5	24.028																								
1.0	24.028																								
2.0	24.028																								
3.0	24.028																								
4.0	24.028																								
5.0	24.028																								
6.0	24.028																								
7.0	24.028																								
8.0	24.028																								

COSEL


Model GT3.5-24

Item Rise and Fall Time

Temperature 25°C
Testing Circuitry Figure A

Object +24V3A


1. Graph



2. Values

[ms]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		14.5	29.5	44.0	65.0	321.5
100 %		16.8	28.3	45.1	27.0	200.5



COSEL

Model	GT3.5-24	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+24V3A																																		
1.Graph			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>19</td><td>4</td></tr> <tr> <td>90</td><td>31</td><td>10</td></tr> <tr> <td>100</td><td>55</td><td>22</td></tr> <tr> <td>110</td><td>80</td><td>34</td></tr> <tr> <td>115</td><td>92</td><td>40</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	19	4	90	31	10	100	55	22	110	80	34	115	92	40	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	19	4																																	
90	31	10																																	
100	55	22																																	
110	80	34																																	
115	92	40																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	GT3.5-24	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+24V3A																																																					
1.Graph	<p>—△— Input Volt. 90V - - -□- Input Volt. 100V - - -○- Input Volt. 110V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.6</td><td>103</td><td>157</td><td>213</td></tr> <tr> <td>1.2</td><td>38</td><td>72</td><td>100</td></tr> <tr> <td>1.8</td><td>21</td><td>39</td><td>62</td></tr> <tr> <td>2.4</td><td>5</td><td>22</td><td>39</td></tr> <tr> <td>3.0</td><td>4</td><td>21</td><td>23</td></tr> <tr> <td>3.3</td><td>4</td><td>5</td><td>22</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.0	-	-	-	0.6	103	157	213	1.2	38	72	100	1.8	21	39	62	2.4	5	22	39	3.0	4	21	23	3.3	4	5	22	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.0	-	-	-																																																			
0.6	103	157	213																																																			
1.2	38	72	100																																																			
1.8	21	39	62																																																			
2.4	5	22	39																																																			
3.0	4	21	23																																																			
3.3	4	5	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					



Model Item Object	GT3.5-24	Testing Circuitry Figure A																																						
	Minimum Input Voltage for Regulated Output Voltage																																							
	+24V3A																																							
1.Graph		2.Values																																						
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (dashed line with squares) Load 100% (solid line with triangles) 		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>73</td><td>79</td> </tr> <tr> <td>-10</td><td>73</td><td>79</td> </tr> <tr> <td>0</td><td>73</td><td>79</td> </tr> <tr> <td>10</td><td>73</td><td>79</td> </tr> <tr> <td>20</td><td>73</td><td>79</td> </tr> <tr> <td>25</td><td>73</td><td>80</td> </tr> <tr> <td>30</td><td>73</td><td>80</td> </tr> <tr> <td>40</td><td>73</td><td>80</td> </tr> <tr> <td>50</td><td>73</td><td>80</td> </tr> <tr> <td>60</td><td>73</td><td>80</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	73	79	-10	73	79	0	73	79	10	73	79	20	73	79	25	73	80	30	73	80	40	73	80	50	73	80	60	73	80	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-20	73	79																																						
-10	73	79																																						
0	73	79																																						
10	73	79																																						
20	73	79																																						
25	73	80																																						
30	73	80																																						
40	73	80																																						
50	73	80																																						
60	73	80																																						
--	-	-																																						

Note: Slanted line shows the range of the rated ambient temperature.

COSEL


Model GT3.5-24

Item Overcurrent Protection

Object +24V3A

1.Graph

— Input Volt. 90V
 — Input Volt. 100V
 - - - Input Volt. 110V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]
24.0	3.81	3.82	3.82
22.8	3.73	3.73	3.73
21.6	3.62	3.62	3.62
19.2	3.36	3.36	3.36
16.8	3.06	3.07	3.07
14.4	2.82	2.82	2.82
12.0	2.54	2.54	2.54
9.6	2.27	2.27	2.27
7.2	2.02	2.02	2.02
4.8	1.76	1.76	1.76
2.4	1.49	1.49	1.49
0.0	1.22	1.22	1.22


coSEL

Figure A