

TEST DATA OF KHNA30F-12

Regulated DC Power Supply
April 28, 2014

Approved by : Yukihiro Takehashi
Yukihiro Takehashi Design Manager

Prepared by : Yasunari Hirano
Yasunari Hirano Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 25)

COSEL


Model KHNA30F-12

Item Input Current (by Load Current)

Object _____

1. Graph

—△— Input Volt. 100V
 - -□--- Input Volt. 115V
 - -○--- Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2. Values


Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	0.022	0.022	0.021
0.10	0.051	0.048	0.038
0.20	0.077	0.071	0.051
0.30	0.101	0.093	0.064
0.50	0.149	0.136	0.089
0.70	0.195	0.177	0.114
0.92	0.245	0.222	0.140
1.15	0.298	0.268	0.167
1.83	0.454	0.407	0.246
2.30	0.563	0.502	0.301
2.53	0.618	0.551	0.328

COSEL

Model	KHNA30F-12
Item	Input Power (by Load Current)
Object	_____

1. Graph

—△— Input Volt. 100V
 - -□--- Input Volt. 115V
 - -○--- Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A


2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	0.68	0.73	0.55
0.10	2.03	2.06	2.44
0.20	3.34	3.37	3.76
0.30	4.66	4.68	5.10
0.50	7.38	7.38	7.77
0.70	10.07	10.07	10.49
0.92	13.06	13.02	13.33
1.15	16.18	16.12	16.35
1.83	25.91	25.77	25.50
2.30	32.58	32.29	31.90
2.53	35.89	35.53	34.90

COSEL

Model	KHNA30F-12
Item	Efficiency (by Input Voltage)
Object	_____

1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
80	85.8	85.0
85	86.3	85.8
90	86.5	86.3
100	86.9	87.1
115	87.3	87.9
200	86.9	89.2
230	86.0	88.9
264	84.7	88.6
280	83.9	88.4


COSEL

Model	KHNA30F-12																																																					
Item	Efficiency (by Load Current)	Temperature	25°C																																																			
Object		Testing Circuitry	Figure A																																																			
1. Graph																																																						
<p>The graph plots Efficiency [%] on the Y-axis (50 to 100) against Load Current [A] on the X-axis (0.0 to 3.0). Three data series are shown for different input voltages: 100V (solid line with triangle markers), 115V (dashed line with square markers), and 230V (dash-dot line with circle markers). All curves show efficiency increasing with load current. A slanted line on the right side of the graph indicates the rated load current range.</p>																																																						
2. Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.10</td><td>60.0</td><td>59.3</td><td>50.1</td></tr> <tr><td>0.20</td><td>73.1</td><td>72.5</td><td>64.9</td></tr> <tr><td>0.30</td><td>78.4</td><td>78.1</td><td>71.7</td></tr> <tr><td>0.50</td><td>82.7</td><td>82.7</td><td>78.5</td></tr> <tr><td>0.70</td><td>84.8</td><td>84.9</td><td>81.4</td></tr> <tr><td>0.92</td><td>86.0</td><td>86.3</td><td>84.3</td></tr> <tr><td>1.15</td><td>86.9</td><td>87.3</td><td>86.0</td></tr> <tr><td>1.83</td><td>87.0</td><td>87.5</td><td>88.4</td></tr> <tr><td>2.30</td><td>87.1</td><td>87.9</td><td>88.9</td></tr> <tr><td>2.53</td><td>86.6</td><td>87.5</td><td>89.0</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	0.10	60.0	59.3	50.1	0.20	73.1	72.5	64.9	0.30	78.4	78.1	71.7	0.50	82.7	82.7	78.5	0.70	84.8	84.9	81.4	0.92	86.0	86.3	84.3	1.15	86.9	87.3	86.0	1.83	87.0	87.5	88.4	2.30	87.1	87.9	88.9	2.53	86.6	87.5	89.0
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.10	60.0	59.3	50.1																																																			
0.20	73.1	72.5	64.9																																																			
0.30	78.4	78.1	71.7																																																			
0.50	82.7	82.7	78.5																																																			
0.70	84.8	84.9	81.4																																																			
0.92	86.0	86.3	84.3																																																			
1.15	86.9	87.3	86.0																																																			
1.83	87.0	87.5	88.4																																																			
2.30	87.1	87.9	88.9																																																			
2.53	86.6	87.5	89.0																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL




Model	KHNA30F-12																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Legend:</p> <ul style="list-style-type: none"> --□-- Load 50% —△— Load 100% 																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td><td>0.576</td><td>0.611</td></tr> <tr> <td>85</td><td>0.563</td><td>0.596</td></tr> <tr> <td>90</td><td>0.552</td><td>0.585</td></tr> <tr> <td>100</td><td>0.543</td><td>0.579</td></tr> <tr> <td>115</td><td>0.523</td><td>0.558</td></tr> <tr> <td>200</td><td>0.436</td><td>0.467</td></tr> <tr> <td>230</td><td>0.426</td><td>0.462</td></tr> <tr> <td>264</td><td>0.404</td><td>0.433</td></tr> <tr> <td>280</td><td>0.397</td><td>0.427</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	80	0.576	0.611	85	0.563	0.596	90	0.552	0.585	100	0.543	0.579	115	0.523	0.558	200	0.436	0.467	230	0.426	0.462	264	0.404	0.433	280	0.397	0.427
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
80	0.576	0.611																																
85	0.563	0.596																																
90	0.552	0.585																																
100	0.543	0.579																																
115	0.523	0.558																																
200	0.436	0.467																																
230	0.426	0.462																																
264	0.404	0.433																																
280	0.397	0.427																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	KHNA30F-12																																																					
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
Object	_____	Testing Circuitry	Figure A																																																			
1.Graph	<p style="text-align: center;"> Input Volt. 100V Input Volt. 115V Input Volt. 230V </p>  <p>Note: Slanted line shows the range of the rated load current.</p>																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.314</td><td>0.293</td><td>0.116</td></tr> <tr><td>0.10</td><td>0.399</td><td>0.377</td><td>0.281</td></tr> <tr><td>0.20</td><td>0.435</td><td>0.413</td><td>0.322</td></tr> <tr><td>0.30</td><td>0.461</td><td>0.439</td><td>0.348</td></tr> <tr><td>0.50</td><td>0.495</td><td>0.473</td><td>0.379</td></tr> <tr><td>0.70</td><td>0.516</td><td>0.495</td><td>0.399</td></tr> <tr><td>0.92</td><td>0.533</td><td>0.511</td><td>0.414</td></tr> <tr><td>1.15</td><td>0.543</td><td>0.523</td><td>0.426</td></tr> <tr><td>1.83</td><td>0.570</td><td>0.550</td><td>0.450</td></tr> <tr><td>2.30</td><td>0.579</td><td>0.558</td><td>0.462</td></tr> <tr><td>2.53</td><td>0.580</td><td>0.560</td><td>0.463</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.314	0.293	0.116	0.10	0.399	0.377	0.281	0.20	0.435	0.413	0.322	0.30	0.461	0.439	0.348	0.50	0.495	0.473	0.379	0.70	0.516	0.495	0.399	0.92	0.533	0.511	0.414	1.15	0.543	0.523	0.426	1.83	0.570	0.550	0.450	2.30	0.579	0.558	0.462	2.53	0.580	0.560	0.463
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.314	0.293	0.116																																																			
0.10	0.399	0.377	0.281																																																			
0.20	0.435	0.413	0.322																																																			
0.30	0.461	0.439	0.348																																																			
0.50	0.495	0.473	0.379																																																			
0.70	0.516	0.495	0.399																																																			
0.92	0.533	0.511	0.414																																																			
1.15	0.543	0.523	0.426																																																			
1.83	0.570	0.550	0.450																																																			
2.30	0.579	0.558	0.462																																																			
2.53	0.580	0.560	0.463																																																			

COSEL

Model	KHNA30F-12	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	KHNA30F-12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

[mA]

Standards	Input Volt.			Note	
	100 [V]	115 [V]	240 [V]		
DEN-AN	Both phases	0.13	0.15	0.32	Operation
	One of phases	0.27	0.31	0.69	Stand by
IEC60950-1	Both phases	0.20	0.22	0.46	Operation
	One of phases	0.41	0.46	0.70	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	KHNA30F-12
Item	Line Regulation
Object	+12V2.3A

Temperature 25°C
 Testing Circuitry Figure A

1. Graph




2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	12.237	12.235
85	12.237	12.234
90	12.237	12.234
100	12.237	12.233
115	12.237	12.232
200	12.238	12.232
230	12.239	12.232
264	12.240	12.233
280	12.240	12.234

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	KHNA30F-12
Item	Load Regulation
Object	+12V2.3A



Temperature 25°C
Testing Circuitry Figure A

2. Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	12.237	12.236	12.236
0.10	12.238	12.239	12.236
0.20	12.239	12.239	12.235
0.30	12.239	12.240	12.238
0.50	12.237	12.237	12.240
0.70	12.237	12.237	12.239
0.92	12.237	12.237	12.239
1.15	12.237	12.237	12.239
1.83	12.235	12.235	12.236
2.30	12.233	12.232	12.232
2.53	12.229	12.228	12.230

Note: Slanted line shows the range of the rated load current.



COSEL

Model	KHNA30F-12	Temperature Testing Circuitry 25°C Figure A
Item	Dynamic Load Response	
Object	+12V2.3A	



Input Volt. 230 V
Cycle 1000 ms

Response. $t_1=t_2=50\mu s$. Typ

Min.Load (0A) \longleftrightarrow
Load 100% (2.3A)



Load 30%(0.69A) \longleftrightarrow
Load 100% (2.3A)




* The characteristic of AC115V is equal.

COSEL

Model	KHNA30F-12
Item	Ripple Voltage (by Load Current)
Object	+12V2.3A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure C

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0.00	10	45
0.10	10	30
0.20	10	55
0.30	10	10
0.50	50	40
0.70	10	10
0.92	10	10
1.15	10	10
1.83	25	15
2.30	40	20
2.53	45	20

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	KHNA30F-12
Item	Ripple-Noise
Object	+12V2.3A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0.00	15	60
0.10	15	45
0.20	15	65
0.30	15	20
0.50	65	55
0.70	25	25
0.92	25	25
1.15	25	25
1.83	35	40
2.30	40	45
2.53	50	50

T1: Due to AC Input Line
T2: Due to Switching




Fig. Complex Ripple Wave Form


COSEL

Model KHNA30F-12

Item Ripple Voltage (by Ambient Temp.)

Object +5V5A

1. Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
-30	95	45
-20	70	30
-10	55	25
0	45	20
25	40	20
60	20	15
70	20	20
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	KHNA30F-12																																																					
Item	Ambient Temperature Drift																																																					
Object	+12V2.3A																																																					
1. Graph																																																						
			2. Values																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-30</td><td>12.253</td><td>12.250</td><td>12.250</td></tr> <tr> <td>-20</td><td>12.250</td><td>12.249</td><td>12.249</td></tr> <tr> <td>-10</td><td>12.248</td><td>12.247</td><td>12.248</td></tr> <tr> <td>0</td><td>12.246</td><td>12.245</td><td>12.245</td></tr> <tr> <td>25</td><td>12.233</td><td>12.232</td><td>12.232</td></tr> <tr> <td>60</td><td>12.218</td><td>12.217</td><td>12.217</td></tr> <tr> <td>70</td><td>12.209</td><td>12.208</td><td>12.208</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	-30	12.253	12.250	12.250	-20	12.250	12.249	12.249	-10	12.248	12.247	12.248	0	12.246	12.245	12.245	25	12.233	12.232	12.232	60	12.218	12.217	12.217	70	12.209	12.208	12.208	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
-30	12.253	12.250	12.250																																																			
-20	12.250	12.249	12.249																																																			
-10	12.248	12.247	12.248																																																			
0	12.246	12.245	12.245																																																			
25	12.233	12.232	12.232																																																			
60	12.218	12.217	12.217																																																			
70	12.209	12.208	12.208																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						



Model	KHNA30F-12	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V2.3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 85 - 264V

Load Current : 0 - 2.3A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	100	2.3	12.250	± 17	± 0.1
Minimum Voltage	60	230	2.3	12.217		

COSEL

Model	KHNA30F-12	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V2.3A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 230V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.232</td></tr> <tr><td>0.5</td><td>12.231</td></tr> <tr><td>1.0</td><td>12.231</td></tr> <tr><td>2.0</td><td>12.231</td></tr> <tr><td>3.0</td><td>12.231</td></tr> <tr><td>4.0</td><td>12.231</td></tr> <tr><td>5.0</td><td>12.231</td></tr> <tr><td>6.0</td><td>12.231</td></tr> <tr><td>7.0</td><td>12.231</td></tr> <tr><td>8.0</td><td>12.231</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.232	0.5	12.231	1.0	12.231	2.0	12.231	3.0	12.231	4.0	12.231	5.0	12.231	6.0	12.231	7.0	12.231	8.0	12.231
Time since start [H]	Output Voltage [V]																								
0.0	12.232																								
0.5	12.231																								
1.0	12.231																								
2.0	12.231																								
3.0	12.231																								
4.0	12.231																								
5.0	12.231																								
6.0	12.231																								
7.0	12.231																								
8.0	12.231																								


* The characteristic of AC115V is equal.

COSEL

Model	KHNA30F-12
Item	Rise and Fall Time
Object	+12V2.3A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Volt	Time	Td	Tr	Ts	Th	Tf
115V		48.3	4.5	52.8	39.5	4.8
230V		54.8	4.5	59.3	187.8	4.8



COSEL

Model	KHNA30F-12																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+12V2.3A																																	
1. Graph																																		
<p>Legend: - - □ - - Load 50% — △ — Load 100% </p> <p>Y-axis: Hold-Up Time [ms] X-axis: Input Voltage [V]</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>34</td> <td>12</td> </tr> <tr> <td>85</td> <td>39</td> <td>14</td> </tr> <tr> <td>90</td> <td>45</td> <td>18</td> </tr> <tr> <td>100</td> <td>59</td> <td>24</td> </tr> <tr> <td>115</td> <td>82</td> <td>36</td> </tr> <tr> <td>200</td> <td>278</td> <td>135</td> </tr> <tr> <td>230</td> <td>374</td> <td>185</td> </tr> <tr> <td>264</td> <td>502</td> <td>251</td> </tr> <tr> <td>280</td> <td>567</td> <td>286</td> </tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	80	34	12	85	39	14	90	45	18	100	59	24	115	82	36	200	278	135	230	374	185	264	502	251	280	567	286
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
80	34	12																																
85	39	14																																
90	45	18																																
100	59	24																																
115	82	36																																
200	278	135																																
230	374	185																																
264	502	251																																
280	567	286																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	KHNA30F-12																																																						
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																				
Object	+12V2.3A																																																						
1.Graph	<p style="text-align: center;">—△— Input Volt. 100V - - -□- - Input Volt. 115V - - ○ - - Input Volt. 230V</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.10</td><td>499</td><td>680</td><td>-</td></tr> <tr><td>0.20</td><td>301</td><td>412</td><td>1740</td></tr> <tr><td>0.30</td><td>213</td><td>290</td><td>1265</td></tr> <tr><td>0.50</td><td>136</td><td>186</td><td>818</td></tr> <tr><td>0.70</td><td>97</td><td>136</td><td>602</td></tr> <tr><td>0.92</td><td>73</td><td>104</td><td>465</td></tr> <tr><td>1.15</td><td>59</td><td>82</td><td>374</td></tr> <tr><td>1.83</td><td>35</td><td>49</td><td>237</td></tr> <tr><td>2.30</td><td>24</td><td>36</td><td>185</td></tr> <tr><td>2.53</td><td>20</td><td>30</td><td>167</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	0.10	499	680	-	0.20	301	412	1740	0.30	213	290	1265	0.50	136	186	818	0.70	97	136	602	0.92	73	104	465	1.15	59	82	374	1.83	35	49	237	2.30	24	36	185	2.53	20	30	167
Load Current [A]	Time [ms]																																																						
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																				
0.00	-	-	-																																																				
0.10	499	680	-																																																				
0.20	301	412	1740																																																				
0.30	213	290	1265																																																				
0.50	136	186	818																																																				
0.70	97	136	602																																																				
0.92	73	104	465																																																				
1.15	59	82	374																																																				
1.83	35	49	237																																																				
2.30	24	36	185																																																				
2.53	20	30	167																																																				

Note: Slanted line shows the range of the rated load current.


COSEL

Model KHNA30F-12

Item Minimum Input Voltage
for Regulated Output Voltage

Object +12V2.3A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A


2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	49	67
-20	47	66
-10	46	64
0	46	63
25	44	61
60	43	59
70	42	59
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	KHNA30F-12
Item	Overcurrent Protection
Object	+12V2.3A

1. Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when overcurrent protection is activated.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 115[V]	Input Volt. 230[V]
12.24	3.03	3.04
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	KHNA30F-12																																							
Item	Overvoltage Protection	Testing Circuitry Figure A																																						
Object	+12V2.3A																																							
1. Graph																																								
		2. Values																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>15.80</td><td>15.80</td></tr> <tr><td>-20</td><td>15.80</td><td>15.80</td></tr> <tr><td>-10</td><td>15.90</td><td>15.90</td></tr> <tr><td>0</td><td>16.10</td><td>16.10</td></tr> <tr><td>25</td><td>16.30</td><td>16.30</td></tr> <tr><td>60</td><td>16.30</td><td>16.30</td></tr> <tr><td>70</td><td>16.40</td><td>16.40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 115[V]	Input Volt. 230[V]	-30	15.80	15.80	-20	15.80	15.80	-10	15.90	15.90	0	16.10	16.10	25	16.30	16.30	60	16.30	16.30	70	16.40	16.40	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 115[V]	Input Volt. 230[V]																																						
-30	15.80	15.80																																						
-20	15.80	15.80																																						
-10	15.90	15.90																																						
0	16.10	16.10																																						
25	16.30	16.30																																						
60	16.30	16.30																																						
70	16.40	16.40																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						




Figure A




Figure B (DEN-AN)





Figure B (IEC60950-1)



C1= 0.1 μF
(Ceramic capacitor)
C2= 22 μF
(Electrolytic capacitor)

Figure C