

TEST DATA OF KHNA30F-5

Regulated DC Power Supply
April 28, 2014

Approved by : Yukihiro Takehashi
Yukihiro Takehashi Design Manager

Prepared by : Yasunari Hirano
Yasunari Hirano Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model	KHNA30F-5																																																					
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 115V Input Volt. 230V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.015</td><td>0.015</td><td>0.020</td></tr> <tr><td>0.25</td><td>0.051</td><td>0.048</td><td>0.037</td></tr> <tr><td>0.50</td><td>0.079</td><td>0.072</td><td>0.052</td></tr> <tr><td>0.75</td><td>0.106</td><td>0.097</td><td>0.067</td></tr> <tr><td>1.00</td><td>0.131</td><td>0.119</td><td>0.081</td></tr> <tr><td>1.50</td><td>0.180</td><td>0.163</td><td>0.106</td></tr> <tr><td>2.00</td><td>0.230</td><td>0.208</td><td>0.132</td></tr> <tr><td>2.50</td><td>0.278</td><td>0.251</td><td>0.157</td></tr> <tr><td>4.00</td><td>0.424</td><td>0.380</td><td>0.230</td></tr> <tr><td>5.00</td><td>0.526</td><td>0.469</td><td>0.280</td></tr> <tr><td>5.50</td><td>0.579</td><td>0.516</td><td>0.305</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.015	0.015	0.020	0.25	0.051	0.048	0.037	0.50	0.079	0.072	0.052	0.75	0.106	0.097	0.067	1.00	0.131	0.119	0.081	1.50	0.180	0.163	0.106	2.00	0.230	0.208	0.132	2.50	0.278	0.251	0.157	4.00	0.424	0.380	0.230	5.00	0.526	0.469	0.280	5.50	0.579	0.516	0.305
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.015	0.015	0.020																																																			
0.25	0.051	0.048	0.037																																																			
0.50	0.079	0.072	0.052																																																			
0.75	0.106	0.097	0.067																																																			
1.00	0.131	0.119	0.081																																																			
1.50	0.180	0.163	0.106																																																			
2.00	0.230	0.208	0.132																																																			
2.50	0.278	0.251	0.157																																																			
4.00	0.424	0.380	0.230																																																			
5.00	0.526	0.469	0.280																																																			
5.50	0.579	0.516	0.305																																																			

Note: Slanted line shows the range of the rated load current.


COSEL

Model	KHNA30F-5																																																					
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Temperature 25°C Testing Circuitry Figure A</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.42</td><td>0.44</td><td>0.51</td></tr> <tr><td>0.25</td><td>2.02</td><td>2.06</td><td>2.42</td></tr> <tr><td>0.50</td><td>3.45</td><td>3.47</td><td>3.88</td></tr> <tr><td>0.75</td><td>4.94</td><td>4.95</td><td>5.44</td></tr> <tr><td>1.00</td><td>6.35</td><td>6.37</td><td>6.96</td></tr> <tr><td>1.50</td><td>9.19</td><td>9.18</td><td>9.65</td></tr> <tr><td>2.00</td><td>12.15</td><td>12.12</td><td>12.48</td></tr> <tr><td>2.50</td><td>15.06</td><td>14.99</td><td>15.24</td></tr> <tr><td>4.00</td><td>24.05</td><td>23.84</td><td>23.70</td></tr> <tr><td>5.00</td><td>30.24</td><td>29.90</td><td>29.40</td></tr> <tr><td>5.50</td><td>33.44</td><td>33.03</td><td>32.30</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.42	0.44	0.51	0.25	2.02	2.06	2.42	0.50	3.45	3.47	3.88	0.75	4.94	4.95	5.44	1.00	6.35	6.37	6.96	1.50	9.19	9.18	9.65	2.00	12.15	12.12	12.48	2.50	15.06	14.99	15.24	4.00	24.05	23.84	23.70	5.00	30.24	29.90	29.40	5.50	33.44	33.03	32.30
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.42	0.44	0.51																																																			
0.25	2.02	2.06	2.42																																																			
0.50	3.45	3.47	3.88																																																			
0.75	4.94	4.95	5.44																																																			
1.00	6.35	6.37	6.96																																																			
1.50	9.19	9.18	9.65																																																			
2.00	12.15	12.12	12.48																																																			
2.50	15.06	14.99	15.24																																																			
4.00	24.05	23.84	23.70																																																			
5.00	30.24	29.90	29.40																																																			
5.50	33.44	33.03	32.30																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	KHNA30F-5
Item	Efficiency (by Input Voltage)
Object	—

1.Graph



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
80	83.7	81.9
85	84.1	82.8
90	84.4	83.4
100	84.6	84.3
115	85.2	85.3
200	84.6	86.7
230	83.7	86.4
264	82.3	86.1
280	81.4	85.8


COSEL

Model	KHNA30F-5																																																					
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Graph showing Efficiency [%] vs Load Current [A]. The Y-axis ranges from 50 to 100 in increments of 10. The X-axis ranges from 0 to 6 in increments of 2. Three curves are plotted for different input voltages: 100V (solid line with triangle markers), 115V (dashed line with square markers), and 230V (dash-dot line with circle markers). All curves show efficiency increasing with load current. A slanted line on the graph indicates the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.25</td><td>62.7</td><td>61.6</td><td>52.3</td></tr> <tr> <td>0.50</td><td>73.3</td><td>73.0</td><td>65.3</td></tr> <tr> <td>0.75</td><td>76.9</td><td>76.7</td><td>69.8</td></tr> <tr> <td>1.00</td><td>79.7</td><td>79.5</td><td>72.8</td></tr> <tr> <td>1.50</td><td>82.7</td><td>82.8</td><td>78.8</td></tr> <tr> <td>2.00</td><td>84.1</td><td>84.3</td><td>81.9</td></tr> <tr> <td>2.50</td><td>84.6</td><td>85.2</td><td>83.7</td></tr> <tr> <td>4.00</td><td>84.6</td><td>85.3</td><td>85.8</td></tr> <tr> <td>5.00</td><td>84.3</td><td>85.3</td><td>86.4</td></tr> <tr> <td>5.50</td><td>83.5</td><td>84.6</td><td>86.5</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	0.25	62.7	61.6	52.3	0.50	73.3	73.0	65.3	0.75	76.9	76.7	69.8	1.00	79.7	79.5	72.8	1.50	82.7	82.8	78.8	2.00	84.1	84.3	81.9	2.50	84.6	85.2	83.7	4.00	84.6	85.3	85.8	5.00	84.3	85.3	86.4	5.50	83.5	84.6	86.5
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.25	62.7	61.6	52.3																																																			
0.50	73.3	73.0	65.3																																																			
0.75	76.9	76.7	69.8																																																			
1.00	79.7	79.5	72.8																																																			
1.50	82.7	82.8	78.8																																																			
2.00	84.1	84.3	81.9																																																			
2.50	84.6	85.2	83.7																																																			
4.00	84.6	85.3	85.8																																																			
5.00	84.3	85.3	86.4																																																			
5.50	83.5	84.6	86.5																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	KHNA30F-5
Item	Power Factor (by Input Voltage)
Object	—

1. Graph



Note: Slanted line shows the range of the rated input voltage.


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
80	0.572	0.608
85	0.560	0.594
90	0.550	0.583
100	0.541	0.575
115	0.519	0.554
200	0.435	0.465
230	0.417	0.452
264	0.401	0.430
280	0.394	0.425

COSEL

Model	KHNA30F-5
Item	Power Factor (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Power Factor		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	0.274	0.250	0.112
0.25	0.400	0.377	0.282
0.50	0.439	0.418	0.326
0.75	0.466	0.444	0.353
1.00	0.485	0.464	0.372
1.50	0.511	0.489	0.395
2.00	0.529	0.508	0.411
2.50	0.541	0.519	0.417
4.00	0.568	0.546	0.449
5.00	0.575	0.554	0.452
5.50	0.578	0.556	0.460




Note: Slanted line shows the range of the rated load current.

COSEL

Model KHNA30F-5

Item Inrush Current

Object _____

Temperature 25°C
Testing Circuitry Figure A



Model	KHNA30F-5	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards		Input Volt.			Note
		100 [V]	115 [V]	240 [V]	
DEN-AN	Both phases	0.13	0.15	0.32	Operation
	One of phases	0.27	0.31	0.69	Stand by
IEC60950-1	Both phases	0.20	0.22	0.46	Operation
	One of phases	0.41	0.46	0.70	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	KHNA30F-5
Item	Line Regulation
Object	+5V5A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	5.078	5.075
85	5.078	5.074
90	5.077	5.073
100	5.077	5.072
115	5.077	5.071
200	5.077	5.070
230	5.078	5.070
264	5.079	5.070
280	5.079	5.070


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model KHNA30F-5

Item Load Regulation

Object +5V5A




Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	5.082	5.082	5.082
0.25	5.080	5.080	5.080
0.50	5.079	5.079	5.079
0.75	5.079	5.079	5.079
1.00	5.078	5.078	5.079
1.50	5.078	5.078	5.078
2.00	5.077	5.077	5.078
2.50	5.077	5.077	5.078
4.00	5.074	5.074	5.074
5.00	5.072	5.071	5.070
5.50	5.070	5.068	5.066


COSEL

COSEL

Model	KHNA30F-5
Item	Ripple Voltage (by Load Current)
Object	+5V5A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0.00	25	45
0.25	35	40
0.50	30	50
0.75	35	10
1.00	10	10
1.50	10	10
2.00	10	10
2.50	10	10
4.00	20	15
5.00	40	20
5.50	50	25

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line
T2: Due to Switching




Fig. Complex Ripple Wave Form


COSEL

Model KHNA30F-5

Item Ripple-Noise

Object +5V5A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure C

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0.00	35	55
0.25	40	50
0.50	40	75
0.75	50	20
1.00	20	15
1.50	25	20
2.00	30	20
2.50	30	35
4.00	35	40
5.00	60	55
5.50	70	55

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	KHNA30F-5
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V5A

1.Graph



Measured by 20 MHz Oscilloscope.
Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
-30	65	30
-20	50	25
-10	45	20
0	40	20
25	40	20
60	45	25
70	45	25
--	-	-
--	-	-
--	-	-
--	-	-

COSEL


Model KHNA30F-5

Item Ambient Temperature Drift

Object +5V5A

1. Graph

—△— Input Volt. 100V
 - -□--- Input Volt. 115V
 - -○--- Input Volt. 230V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
-30	5.081	5.080	5.079
-20	5.079	5.078	5.078
-10	5.075	5.074	5.073
0	5.072	5.071	5.071
25	5.072	5.071	5.070
60	5.066	5.065	5.064
70	5.064	5.063	5.062
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	KHNA30F-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 85 - 264V

Load Current : 0 - 5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	100	0	5.079	±8	±0.2
Minimum Voltage	60	230	5	5.064		

COSEL

Model	KHNA30F-5
Item	Time Lapse Drift
Object	+5V5A

1. Graph



Input Volt. 230V
Load 100%

* The characteristic of AC115V is equal.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Time since start [H]	Output Voltage [V]
0.0	5.070
0.5	5.068
1.0	5.067
2.0	5.067
3.0	5.067
4.0	5.067
5.0	5.067
6.0	5.067
7.0	5.067
8.0	5.067

COSEL


Model	KHNA30F-5	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V5A		

1. Graph



2. Values

Input Volt	Time	Td	Tr	Ts	Th	Tf	[ms]
115V		48.8	16.3	65.1	41.5	3.3	
230V		48.5	15.5	64.0	202.0	3.5	



COSEL

Model	KHNA30F-5																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+5V5A																																	
1.Graph																																		
<p>Hold-Up Time [ms]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>37</td> <td>5</td> </tr> <tr> <td>85</td> <td>43</td> <td>8</td> </tr> <tr> <td>90</td> <td>50</td> <td>12</td> </tr> <tr> <td>100</td> <td>64</td> <td>24</td> </tr> <tr> <td>115</td> <td>89</td> <td>36</td> </tr> <tr> <td>200</td> <td>304</td> <td>138</td> </tr> <tr> <td>230</td> <td>408</td> <td>199</td> </tr> <tr> <td>264</td> <td>550</td> <td>270</td> </tr> <tr> <td>280</td> <td>621</td> <td>307</td> </tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	80	37	5	85	43	8	90	50	12	100	64	24	115	89	36	200	304	138	230	408	199	264	550	270	280	621	307
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
80	37	5																																
85	43	8																																
90	50	12																																
100	64	24																																
115	89	36																																
200	304	138																																
230	408	199																																
264	550	270																																
280	621	307																																

COSEL


Model	KHNA30F-5																																																					
Item	Instantaneous Interruption Compensation																																																					
Object	+5V5A																																																					
1.Graph																																																						
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.25</td><td>505</td><td>690</td><td>-</td></tr> <tr><td>0.50</td><td>295</td><td>404</td><td>1716</td></tr> <tr><td>0.75</td><td>205</td><td>281</td><td>1215</td></tr> <tr><td>1.00</td><td>157</td><td>215</td><td>940</td></tr> <tr><td>1.50</td><td>107</td><td>148</td><td>657</td></tr> <tr><td>2.00</td><td>81</td><td>112</td><td>506</td></tr> <tr><td>2.50</td><td>64</td><td>89</td><td>408</td></tr> <tr><td>4.00</td><td>35</td><td>50</td><td>253</td></tr> <tr><td>5.00</td><td>24</td><td>36</td><td>199</td></tr> <tr><td>5.50</td><td>20</td><td>31</td><td>178</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	0.25	505	690	-	0.50	295	404	1716	0.75	205	281	1215	1.00	157	215	940	1.50	107	148	657	2.00	81	112	506	2.50	64	89	408	4.00	35	50	253	5.00	24	36	199	5.50	20	31	178
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.25	505	690	-																																																			
0.50	295	404	1716																																																			
0.75	205	281	1215																																																			
1.00	157	215	940																																																			
1.50	107	148	657																																																			
2.00	81	112	506																																																			
2.50	64	89	408																																																			
4.00	35	50	253																																																			
5.00	24	36	199																																																			
5.50	20	31	178																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	KHNA30F-5
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V5A

Testing Circuitry Figure A

1.Graph



2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	48	64
-20	47	65
-10	46	64
0	45	63
25	44	61
60	42	59
70	42	59
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	KHNA30F-5
Item	Overcurrent Protection
Object	+5V5A

1.Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when overcurrent protection is activated.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 115[V]	Input Volt. 230[V]
5.07	6.63	6.84
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-


COSEL

Model KHNA30F-5

Item Overvoltage Protection

Object +5V5A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 115[V]	Input Volt. 230[V]
-30	6.70	6.70
-20	6.80	6.80
-10	6.90	6.90
0	6.95	6.95
25	7.06	7.06
60	7.14	7.14
70	7.14	7.14
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A




Figure B (DEN-AN)





Figure B (IEC60950-1)

COSEL

C1= 0.1 μF
(Ceramic capacitor)
C2= 22 μF
(Electrolytic capacitor)

Figure C