

TEST DATA OF KLNA120F-48

Regulated DC Power Supply
May 25, 2015

Approved by : Yukihiro Takehashi
Yukihiro Takehashi Design Manager

Prepared by : Yasunari Hirano
Yasunari Hirano Design Engineer

COSEL CO.,LTD.




CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model	KLNA120F-48
Item	Input Current (by Load Current)
Object	_____



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	0.038	0.036	0.039
0.50	0.332	0.292	0.180
0.75	0.467	0.410	0.241
1.00	0.614	0.528	0.301
1.50	0.880	0.765	0.414
2.00	1.138	0.991	0.525
2.50	1.407	1.217	0.637
2.75	1.558	1.342	0.696
--	-	-	-
--	-	-	-
--	-	-	-

COSEL


Model KLNA120F-48

Item Input Power (by Load Current)

Object _____

1.Graph

—△— Input Volt. 100V
 - - □ - - Input Volt. 115V
 - - ○ - - Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	2.0	2.0	2.2
0.50	31.6	31.3	31.9
0.75	45.4	45.0	45.2
1.00	59.1	58.6	58.4
1.50	86.2	85.4	84.5
2.00	113.0	112.1	110.0
2.50	140.1	138.7	135.7
2.75	155.4	153.1	149.5
--	-	-	-
--	-	-	-
--	-	-	-

COSEL


Model KLNA120F-48

Item Efficiency (by Input Voltage)

Object _____

1. Graph

---□--- Load 50%
—△— Load 100%



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
80	82.3	83.6
85	82.9	84.4
100	83.9	86.2
115	84.4	87.1
200	85.7	89.0
230	85.3	89.0
264	85.6	88.8
280	85.0	89.0
--	-	-

COSEL

Model	KLNA120F-48																																																					
Item	Efficiency (by Load Current)	Temperature	25°C																																																			
Object	 Testing Circuitry Figure A																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Input Volt. 100V Input Volt. 115V Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.50</td><td>78.1</td><td>78.9</td><td>77.5</td></tr> <tr> <td>0.75</td><td>80.9</td><td>81.6</td><td>81.3</td></tr> <tr> <td>1.00</td><td>82.5</td><td>83.3</td><td>83.5</td></tr> <tr> <td>1.50</td><td>84.5</td><td>85.4</td><td>86.3</td></tr> <tr> <td>2.00</td><td>85.8</td><td>86.5</td><td>88.2</td></tr> <tr> <td>2.50</td><td>86.2</td><td>87.1</td><td>89.0</td></tr> <tr> <td>2.75</td><td>85.6</td><td>87.0</td><td>89.0</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	0.50	78.1	78.9	77.5	0.75	80.9	81.6	81.3	1.00	82.5	83.3	83.5	1.50	84.5	85.4	86.3	2.00	85.8	86.5	88.2	2.50	86.2	87.1	89.0	2.75	85.6	87.0	89.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.50	78.1	78.9	77.5																																																			
0.75	80.9	81.6	81.3																																																			
1.00	82.5	83.3	83.5																																																			
1.50	84.5	85.4	86.3																																																			
2.00	85.8	86.5	88.2																																																			
2.50	86.2	87.1	89.0																																																			
2.75	85.6	87.0	89.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	KLNA120F-48																																
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																															
Object																																	
1.Graph																																	
		2.Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td><td>0.992</td><td>0.999</td></tr> <tr> <td>85</td><td>0.992</td><td>0.999</td></tr> <tr> <td>100</td><td>0.955</td><td>0.996</td></tr> <tr> <td>115</td><td>0.959</td><td>0.991</td></tr> <tr> <td>200</td><td>0.896</td><td>0.946</td></tr> <tr> <td>230</td><td>0.869</td><td>0.926</td></tr> <tr> <td>264</td><td>0.480</td><td>0.581</td></tr> <tr> <td>280</td><td>0.469</td><td>0.492</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	80	0.992	0.999	85	0.992	0.999	100	0.955	0.996	115	0.959	0.991	200	0.896	0.946	230	0.869	0.926	264	0.480	0.581	280	0.469	0.492	--	-	-
Input Voltage [V]	Power Factor																																
	Load 50%	Load 100%																															
80	0.992	0.999																															
85	0.992	0.999																															
100	0.955	0.996																															
115	0.959	0.991																															
200	0.896	0.946																															
230	0.869	0.926																															
264	0.480	0.581																															
280	0.469	0.492																															
--	-	-																															
Note: Slanted line shows the range of the rated input voltage.																																	

COSEL

Model	KLNA120F-48																																																					
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
Object	Testing Circuitry	Figure A																																																				
1. Graph			2. Values																																																			
<p>The graph plots Power Factor (Y-axis, 0.0 to 1.0) against Load Current [A] (X-axis, 0 to 3). Three curves are shown for Input Voltages: 100V (solid line with triangles), 115V (dashed line with squares), and 230V (dash-dot line with circles). All curves start at approximately (0, 0.5) and rise towards 1.0 as load current increases. A vertical slanted line is drawn at a load current of approximately 2.5A, indicating the rated load current range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.533</td><td>0.473</td><td>0.247</td></tr> <tr> <td>0.50</td><td>0.951</td><td>0.934</td><td>0.769</td></tr> <tr> <td>0.75</td><td>0.970</td><td>0.955</td><td>0.814</td></tr> <tr> <td>1.00</td><td>0.961</td><td>0.965</td><td>0.843</td></tr> <tr> <td>1.50</td><td>0.980</td><td>0.970</td><td>0.887</td></tr> <tr> <td>2.00</td><td>0.994</td><td>0.983</td><td>0.911</td></tr> <tr> <td>2.50</td><td>0.996</td><td>0.991</td><td>0.926</td></tr> <tr> <td>2.75</td><td>0.997</td><td>0.993</td><td>0.933</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.533	0.473	0.247	0.50	0.951	0.934	0.769	0.75	0.970	0.955	0.814	1.00	0.961	0.965	0.843	1.50	0.980	0.970	0.887	2.00	0.994	0.983	0.911	2.50	0.996	0.991	0.926	2.75	0.997	0.993	0.933	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.533	0.473	0.247																																																			
0.50	0.951	0.934	0.769																																																			
0.75	0.970	0.955	0.814																																																			
1.00	0.961	0.965	0.843																																																			
1.50	0.980	0.970	0.887																																																			
2.00	0.994	0.983	0.911																																																			
2.50	0.996	0.991	0.926																																																			
2.75	0.997	0.993	0.933																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Note: Slanted line shows the range of the rated load current.

COSEL

Model KLNA120F-48


Item Inrush Current

Object _____

Temperature 25°C
Testing Circuitry Figure AInput
Current
[20A/div]


Input Voltage 115 V
Frequency 60 Hz
Load 100 %

Primary inrush current 14.3 A
Secondary inrush current 4.8 A

Input
Voltage
[100V/div]Input
Current
[20A/div]

Input Voltage 230 V
Frequency 60 Hz
Load 100 %

Primary inrush current 29.1 A
Secondary inrush current 2.1 A

Input
Voltage
[200V/div]



Model	KLNA120F-48	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	<hr/>		

1. Results

Standards		Input Volt.			Note
		100 [V]	115 [V]	240 [V]	
DEN-AN	Both phases	0.15	0.18	0.40	Operation
	One of phases	0.28	0.34	0.73	Stand by
IEC60950-1	Both phases	0.16	0.19	0.39	Operation
	One of phases	0.30	0.35	0.73	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL


Model KLNA120F-48

Item Line Regulation

Object +48V2.5A

1. Graph

---□--- Load 50%
 —△— Load 100%



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A


2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	48.314	48.313
85	48.315	48.313
100	48.315	48.314
115	48.316	48.314
200	48.314	48.313
230	48.314	48.315
264	48.315	48.315
280	48.316	48.315
--	-	-

COSEL

Model	KLNA120F-48																																																						
Item	Load Regulation	Temperature Testing Circuitry	25°C Figure A																																																				
Object	+48V2.5A																																																						
1.Graph	<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 115V ---○--- Input Volt. 230V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>48.333</td><td>48.342</td><td>48.342</td></tr> <tr> <td>0.50</td><td>48.320</td><td>48.320</td><td>48.322</td></tr> <tr> <td>0.75</td><td>48.319</td><td>48.319</td><td>48.319</td></tr> <tr> <td>1.00</td><td>48.318</td><td>48.318</td><td>48.319</td></tr> <tr> <td>1.50</td><td>48.317</td><td>48.317</td><td>48.318</td></tr> <tr> <td>2.00</td><td>48.315</td><td>48.316</td><td>48.317</td></tr> <tr> <td>2.50</td><td>48.314</td><td>48.314</td><td>48.315</td></tr> <tr> <td>2.75</td><td>48.313</td><td>48.313</td><td>48.314</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	48.333	48.342	48.342	0.50	48.320	48.320	48.322	0.75	48.319	48.319	48.319	1.00	48.318	48.318	48.319	1.50	48.317	48.317	48.318	2.00	48.315	48.316	48.317	2.50	48.314	48.314	48.315	2.75	48.313	48.313	48.314	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																				
0.00	48.333	48.342	48.342																																																				
0.50	48.320	48.320	48.322																																																				
0.75	48.319	48.319	48.319																																																				
1.00	48.318	48.318	48.319																																																				
1.50	48.317	48.317	48.318																																																				
2.00	48.315	48.316	48.317																																																				
2.50	48.314	48.314	48.315																																																				
2.75	48.313	48.313	48.314																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.

COSSEL

COSEL


Model KLNA120F-48

Item Ripple Voltage (by Load Current)

Object +48V2.5A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0.00	330	330
0.25	30	30
0.50	25	25
0.75	20	15
1.00	45	45
1.50	20	25
2.00	25	25
2.50	30	30
2.75	35	35
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


T1: Due to AC Input Line
T2: Due to Switching


Fig. Complex Ripple Wave Form

COSEL

Model	KLNA120F-48
Item	Ripple-Noise
Object	+48V2.5A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0.00	330	340
0.25	35	35
0.50	30	30
0.75	25	20
1.00	50	50
1.25	25	30
2.00	30	30
2.50	35	35
2.75	40	40
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line
T2: Due to Switching




Fig. Complex Ripple Wave Form

COSEL


Model KLNA120F-48

Item Ripple Voltage (by Ambient Temp.)

Object +48V2.5A

1.Graph

--- □ --- Input Volt. 115V
 —△— Input Volt. 230V



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
-30	190	190
-20	100	100
-10	70	70
0	35	35
10	30	30
25	30	30
50	20	20
55	20	20
70	20	20
--	-	-
--	-	-



<p>Model KLNA120F-48</p> <p>Item Ambient Temperature Drift</p> <p>Object +48V2.5A</p>	Testing Circuitry Figure A																																																				
	2.Values																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-30</td><td>48.156</td><td>48.160</td><td>48.164</td></tr> <tr> <td>-20</td><td>48.201</td><td>48.202</td><td>48.203</td></tr> <tr> <td>-10</td><td>48.246</td><td>48.247</td><td>48.247</td></tr> <tr> <td>0</td><td>48.272</td><td>48.272</td><td>48.272</td></tr> <tr> <td>10</td><td>48.291</td><td>48.291</td><td>48.292</td></tr> <tr> <td>25</td><td>48.314</td><td>48.314</td><td>48.315</td></tr> <tr> <td>50</td><td>48.337</td><td>48.338</td><td>48.337</td></tr> <tr> <td>55</td><td>48.347</td><td>48.347</td><td>48.347</td></tr> <tr> <td>70</td><td>48.350</td><td>48.349</td><td>48.349</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	-30	48.156	48.160	48.164	-20	48.201	48.202	48.203	-10	48.246	48.247	48.247	0	48.272	48.272	48.272	10	48.291	48.291	48.292	25	48.314	48.314	48.315	50	48.337	48.338	48.337	55	48.347	48.347	48.347	70	48.350	48.349	48.349	--	-	-	-	--	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																		
-30	48.156	48.160	48.164																																																		
-20	48.201	48.202	48.203																																																		
-10	48.246	48.247	48.247																																																		
0	48.272	48.272	48.272																																																		
10	48.291	48.291	48.292																																																		
25	48.314	48.314	48.315																																																		
50	48.337	48.338	48.337																																																		
55	48.347	48.347	48.347																																																		
70	48.350	48.349	48.349																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>1.Graph</p> <p>—▲— Input Volt. 100V - - □ - - Input Volt. 115V - - ○ - - Input Volt. 230V</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																					



Model	KLNA120F-48	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+48V2.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 70°C

Input Voltage : 85 - 264V

Load Current : 0.75 - 2.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	70	100	0.75	48.355	±77	±0.2
Minimum Voltage	-20	100	2.5	48.201		

COSEL

Model	KLNA120F-48
Item	Time Lapse Drift
Object	+48V2.5A

1.Graph



Temperature 25°C
Testing Circuitry Figure A


2.Values

Time since start [H]	Output Voltage [V]
0.0	48.315
0.5	48.333
1.0	48.333
2.0	48.333
3.0	48.333
4.0	48.333
5.0	48.333
6.0	48.332
7.0	48.332
8.0	48.332

COSEL


Model	KLNA120F-48	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+48V2.5A		

1. Graph



2. Values

Input Volt \ Time	Td	Tr	Ts	Th	Tf
115 V	493.5	43.0	536.5	30.8	43.8
230 V	483.5	44.5	528.0	37.0	44.5



COSEL

<table border="1"> <tr> <td>Model</td><td>KLNA120F-48</td></tr> <tr> <td>Item</td><td>Hold-Up Time</td></tr> <tr> <td>Object</td><td>+48V2.5A</td></tr> </table>	Model	KLNA120F-48	Item	Hold-Up Time	Object	+48V2.5A	Temperature 25°C Testing Circuitry Figure A																										
Model	KLNA120F-48																																
Item	Hold-Up Time																																
Object	+48V2.5A																																
2.Values																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [ms]</th></tr> <tr> <th>Load 50%</th><th>Load 100%</th></tr> </thead> <tbody> <tr> <td>80</td><td>57</td><td>27</td></tr> <tr> <td>85</td><td>58</td><td>27</td></tr> <tr> <td>100</td><td>57</td><td>29</td></tr> <tr> <td>115</td><td>58</td><td>31</td></tr> <tr> <td>200</td><td>60</td><td>31</td></tr> <tr> <td>230</td><td>71</td><td>37</td></tr> <tr> <td>264</td><td>74</td><td>37</td></tr> <tr> <td>280</td><td>84</td><td>39</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	80	57	27	85	58	27	100	57	29	115	58	31	200	60	31	230	71	37	264	74	37	280	84	39	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																
	Load 50%	Load 100%																															
80	57	27																															
85	58	27																															
100	57	29																															
115	58	31																															
200	60	31																															
230	71	37																															
264	74	37																															
280	84	39																															
--	-	-																															
<p>1.Graph</p> <p>Hold-Up Time [ms]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																	

COSEL

Model	KLNA120F-48																																																					
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+48V2.5A																																																					
1.Graph	<p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 115V</p> <p>Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.50</td><td>130</td><td>131</td><td>162</td></tr> <tr> <td>0.75</td><td>95</td><td>95</td><td>115</td></tr> <tr> <td>1.00</td><td>71</td><td>72</td><td>89</td></tr> <tr> <td>1.50</td><td>48</td><td>48</td><td>60</td></tr> <tr> <td>2.00</td><td>35</td><td>36</td><td>45</td></tr> <tr> <td>2.50</td><td>29</td><td>31</td><td>37</td></tr> <tr> <td>2.75</td><td>22</td><td>22</td><td>30</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	0.50	130	131	162	0.75	95	95	115	1.00	71	72	89	1.50	48	48	60	2.00	35	36	45	2.50	29	31	37	2.75	22	22	30	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.50	130	131	162																																																			
0.75	95	95	115																																																			
1.00	71	72	89																																																			
1.50	48	48	60																																																			
2.00	35	36	45																																																			
2.50	29	31	37																																																			
2.75	22	22	30																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					




Model KLNA120F-48

Item Minimum Input Voltage
for Regulated Output Voltage

Object +48V2.5A

1.Graph

--□-- Load 50%
—△— Load 100%



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	41	57
-20	41	57
-10	41	58
0	41	58
10	42	58
25	42	59
50	43	61
55	44	61
70	44	62
--	-	-
--	-	-


COSEL

Model KLNA120F-48

Item Overcurrent Protection

Object +48V2.5A

1.Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 10V to 0V.


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 115[V]	Input Volt. 230[V]
45.6	3.06	3.17
43.2	3.11	3.21
38.4	3.21	3.31
33.6	3.31	3.42
28.8	3.44	3.53
24.0	3.56	3.64
19.2	3.68	3.77
14.4	3.81	3.89
10.0	3.92	3.98
4.8	3.97	4.03
0.0	3.98	4.05
--	-	-



Model	KLNA120F-48
Item	Overvoltage Protection
Object	+48V2.5A

1.Graph


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A
2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 115[V]	Input Volt. 230[V]
-30	55.07	55.13
-20	55.48	55.48
-10	56.12	56.12
0	56.59	56.53
10	57.00	57.00
25	57.58	57.58
50	58.75	58.75
55	58.99	58.99
70	59.68	59.62
--	-	-
--	-	-




Figure A




Figure B (DEN-AN)





Figure B (IEC60950-1)



C1= 0.1 μ F

(Ceramic capacitor)

C2= 22 μ F

(Electrolytic capacitor)

Figure C