



TEST DATA OF LCA100S-24-H
(100V INPUT)

Regulated DC Power Supply

Apr. 21, 2000

Approved by : M. Miyamae
Design Manager

Prepared by : J. Usane
Design Engineer

コーワセル株式会社

COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Overvoltage Protection	12
過電圧保護	
13. Inrush Current	13
突入電流	
14. Dynamic Load Responce	14
動的負荷変動	
15. Rise and Fall Time	15
立上り、立下り時間	
16. Ambient Temperature Drift	16
周囲温度変動	
17. Minimum Input Voltage for Regulated Output Voltage	17
最低レギュレーション電圧	
18. Ripple Voltage (by Ambient Temperature)	18
リップル電圧 (周囲温度特性)	
19. Time Lapse Drift	19
経時ドリフト	
20. Figure of Testing Circuitry	20
測定回路図	

(Final Page 21)




Model	LCA100S-24-H																																		
Item	Line Regulation 静的入力変動																																		
Object	+24.0V 4.3A																																		
1. Graph		Temperature Testing Circuitry																																	
		25°C Figure A																																	
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p>		<p>2. Values</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>24.019</td><td>24.019</td></tr> <tr><td>80</td><td>24.020</td><td>24.019</td></tr> <tr><td>85</td><td>24.020</td><td>24.020</td></tr> <tr><td>90</td><td>24.020</td><td>24.020</td></tr> <tr><td>100</td><td>24.019</td><td>24.020</td></tr> <tr><td>110</td><td>24.019</td><td>24.019</td></tr> <tr><td>120</td><td>24.019</td><td>24.019</td></tr> <tr><td>132</td><td>24.019</td><td>24.019</td></tr> <tr><td>140</td><td>24.018</td><td>24.018</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	24.019	24.019	80	24.020	24.019	85	24.020	24.020	90	24.020	24.020	100	24.019	24.020	110	24.019	24.019	120	24.019	24.019	132	24.019	24.019	140	24.018	24.018
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	24.019	24.019																																	
80	24.020	24.019																																	
85	24.020	24.020																																	
90	24.020	24.020																																	
100	24.019	24.020																																	
110	24.019	24.019																																	
120	24.019	24.019																																	
132	24.019	24.019																																	
140	24.018	24.018																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LCA100S-24-H																																																									
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object	<hr/>																																																									
1. Graph	<p style="text-align: center;"> Input Volt. 85V Input Volt. 100V Input Volt. 132V </p> 																																																									
2. Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.118</td><td>0.119</td><td>0.124</td></tr> <tr><td>0.80</td><td>0.696</td><td>0.631</td><td>0.535</td></tr> <tr><td>1.60</td><td>1.179</td><td>1.064</td><td>0.898</td></tr> <tr><td>2.40</td><td>1.630</td><td>1.465</td><td>1.223</td></tr> <tr><td>3.20</td><td>2.070</td><td>1.853</td><td>1.537</td></tr> <tr><td>4.00</td><td>2.503</td><td>2.238</td><td>1.847</td></tr> <tr><td>4.30</td><td>2.661</td><td>2.379</td><td>1.961</td></tr> <tr><td>4.73</td><td>2.896</td><td>2.591</td><td>2.132</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.118	0.119	0.124	0.80	0.696	0.631	0.535	1.60	1.179	1.064	0.898	2.40	1.630	1.465	1.223	3.20	2.070	1.853	1.537	4.00	2.503	2.238	1.847	4.30	2.661	2.379	1.961	4.73	2.896	2.591	2.132	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	0.118	0.119	0.124																																																							
0.80	0.696	0.631	0.535																																																							
1.60	1.179	1.064	0.898																																																							
2.40	1.630	1.465	1.223																																																							
3.20	2.070	1.853	1.537																																																							
4.00	2.503	2.238	1.847																																																							
4.30	2.661	2.379	1.961																																																							
4.73	2.896	2.591	2.132																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							


Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA100S-24-H																																																									
Item	Input Power (by Load Current) 入力電力（負荷特性）	Temperature 25°C	Testing Circuitry Figure A																																																							
Object	—																																																									
1. Graph	<p>Input Volt. 85V Input Volt. 100V Input Volt. 132V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3.46</td><td>3.97</td><td>5.21</td></tr> <tr><td>0.80</td><td>25.78</td><td>26.32</td><td>27.48</td></tr> <tr><td>1.60</td><td>47.29</td><td>47.95</td><td>49.60</td></tr> <tr><td>2.40</td><td>69.00</td><td>69.38</td><td>70.80</td></tr> <tr><td>3.20</td><td>91.30</td><td>91.30</td><td>92.20</td></tr> <tr><td>4.00</td><td>114.30</td><td>113.80</td><td>114.10</td></tr> <tr><td>4.30</td><td>122.90</td><td>122.20</td><td>122.30</td></tr> <tr><td>4.73</td><td>136.00</td><td>135.00</td><td>134.70</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	3.46	3.97	5.21	0.80	25.78	26.32	27.48	1.60	47.29	47.95	49.60	2.40	69.00	69.38	70.80	3.20	91.30	91.30	92.20	4.00	114.30	113.80	114.10	4.30	122.90	122.20	122.30	4.73	136.00	135.00	134.70	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	3.46	3.97	5.21																																																							
0.80	25.78	26.32	27.48																																																							
1.60	47.29	47.95	49.60																																																							
2.40	69.00	69.38	70.80																																																							
3.20	91.30	91.30	92.20																																																							
4.00	114.30	113.80	114.10																																																							
4.30	122.90	122.20	122.30																																																							
4.73	136.00	135.00	134.70																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current.																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

COSEL




Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	84.7	84.8
80	84.7	85.1
85	84.6	85.4
90	84.5	85.6
100	84.0	85.8
110	83.5	85.9
120	82.8	85.8
132	82.1	85.6
140	81.4	85.4


COSEL

Model	LCA100S-24-H																																																									
Item	Efficiency (by Load Current) 効率(負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Object	<hr/>																																																									
1. Graph	<p style="text-align: center;"> Input Volt. 85V Input Volt. 100V Input Volt. 132V </p>  <p>Efficiency [%]</p> <p>Load Current [A]</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.80</td><td>78.2</td><td>76.7</td><td>73.5</td></tr> <tr><td>1.60</td><td>83.3</td><td>82.3</td><td>79.6</td></tr> <tr><td>2.40</td><td>85.0</td><td>84.6</td><td>82.9</td></tr> <tr><td>3.20</td><td>85.4</td><td>85.4</td><td>84.6</td></tr> <tr><td>4.00</td><td>85.3</td><td>85.7</td><td>85.4</td></tr> <tr><td>4.30</td><td>85.1</td><td>85.7</td><td>85.5</td></tr> <tr><td>4.73</td><td>84.9</td><td>85.6</td><td>85.7</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.80	78.2	76.7	73.5	1.60	83.3	82.3	79.6	2.40	85.0	84.6	82.9	3.20	85.4	85.4	84.6	4.00	85.3	85.7	85.4	4.30	85.1	85.7	85.5	4.73	84.9	85.6	85.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.80	78.2	76.7	73.5																																																							
1.60	83.3	82.3	79.6																																																							
2.40	85.0	84.6	82.9																																																							
3.20	85.4	85.4	84.6																																																							
4.00	85.3	85.7	85.4																																																							
4.30	85.1	85.7	85.5																																																							
4.73	84.9	85.6	85.7																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL



Temperature 25°C
Testing Circuitry Figure A

COSEL

Model	LCA100S-24-H	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障	Testing Circuitry	Figure A																																																			
Object	+24.0V 4.3A	2. Values																																																				
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85 V (open triangle) Input Volt. 100 V (open square) Input Volt. 132 V (open circle) 																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.80</td><td>72</td><td>135</td><td>296</td></tr> <tr><td>1.60</td><td>37</td><td>69</td><td>155</td></tr> <tr><td>2.40</td><td>22</td><td>45</td><td>104</td></tr> <tr><td>3.20</td><td>13</td><td>31</td><td>78</td></tr> <tr><td>4.00</td><td>12</td><td>22</td><td>62</td></tr> <tr><td>4.30</td><td>11</td><td>22</td><td>56</td></tr> <tr><td>4.73</td><td>5</td><td>21</td><td>52</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.80	72	135	296	1.60	37	69	155	2.40	22	45	104	3.20	13	31	78	4.00	12	22	62	4.30	11	22	56	4.73	5	21	52	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	—	—	—																																																			
0.80	72	135	296																																																			
1.60	37	69	155																																																			
2.40	22	45	104																																																			
3.20	13	31	78																																																			
4.00	12	22	62																																																			
4.30	11	22	56																																																			
4.73	5	21	52																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
	<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																					

COSEL

Model	LCA100S-24-H	Temperature	25°C																																																
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																																
Object	+24.0V 4.3A																																																		
1. Graph	<p>—△— Input Volt. 85 V —□— Input Volt. 100 V —○— Input Volt. 132 V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage 85V [V]</th> <th>Output Voltage 100V [V]</th> <th>Output Voltage 132V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>24.020</td><td>24.021</td><td>24.020</td></tr> <tr><td>0.80</td><td>24.019</td><td>24.020</td><td>24.020</td></tr> <tr><td>1.60</td><td>24.020</td><td>24.020</td><td>24.019</td></tr> <tr><td>2.40</td><td>24.020</td><td>24.020</td><td>24.019</td></tr> <tr><td>3.20</td><td>24.020</td><td>24.019</td><td>24.019</td></tr> <tr><td>4.00</td><td>24.020</td><td>24.019</td><td>24.019</td></tr> <tr><td>4.30</td><td>24.020</td><td>24.019</td><td>24.019</td></tr> <tr><td>4.73</td><td>24.019</td><td>24.019</td><td>24.019</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Output Voltage 85V [V]	Output Voltage 100V [V]	Output Voltage 132V [V]	0.00	24.020	24.021	24.020	0.80	24.019	24.020	24.020	1.60	24.020	24.020	24.019	2.40	24.020	24.020	24.019	3.20	24.020	24.019	24.019	4.00	24.020	24.019	24.019	4.30	24.020	24.019	24.019	4.73	24.019	24.019	24.019	—	—	—	—	—	—	—	—						
Load Current [A]	Output Voltage 85V [V]	Output Voltage 100V [V]	Output Voltage 132V [V]																																																
0.00	24.020	24.021	24.020																																																
0.80	24.019	24.020	24.020																																																
1.60	24.020	24.020	24.019																																																
2.40	24.020	24.020	24.019																																																
3.20	24.020	24.019	24.019																																																
4.00	24.020	24.019	24.019																																																
4.30	24.020	24.019	24.019																																																
4.73	24.019	24.019	24.019																																																
—	—	—	—																																																
—	—	—	—																																																
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>24.020</td><td>24.021</td><td>24.020</td></tr> <tr><td>0.80</td><td>24.019</td><td>24.020</td><td>24.020</td></tr> <tr><td>1.60</td><td>24.020</td><td>24.020</td><td>24.019</td></tr> <tr><td>2.40</td><td>24.020</td><td>24.020</td><td>24.019</td></tr> <tr><td>3.20</td><td>24.020</td><td>24.019</td><td>24.019</td></tr> <tr><td>4.00</td><td>24.020</td><td>24.019</td><td>24.019</td></tr> <tr><td>4.30</td><td>24.020</td><td>24.019</td><td>24.019</td></tr> <tr><td>4.73</td><td>24.019</td><td>24.019</td><td>24.019</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	24.020	24.021	24.020	0.80	24.019	24.020	24.020	1.60	24.020	24.020	24.019	2.40	24.020	24.020	24.019	3.20	24.020	24.019	24.019	4.00	24.020	24.019	24.019	4.30	24.020	24.019	24.019	4.73	24.019	24.019	24.019	—	—	—	—	—	—	—	—			
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																
0.00	24.020	24.021	24.020																																																
0.80	24.019	24.020	24.020																																																
1.60	24.020	24.020	24.019																																																
2.40	24.020	24.020	24.019																																																
3.20	24.020	24.019	24.019																																																
4.00	24.020	24.019	24.019																																																
4.30	24.020	24.019	24.019																																																
4.73	24.019	24.019	24.019																																																
—	—	—	—																																																
—	—	—	—																																																

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。


COSEL

Model	LCA100S-24-H																																							
Item	Ripple Voltage(by Load Current) リップル電圧(負荷特性)	Temperature Testing Circuitry 25°C Figure A																																						
Object	+24V 4.3A																																							
1. Graph	—△— Input Volt. 85V [mV]	—○— Input Volt. 132V																																						
	<table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Voltage [mV] (Input 85V)</th> <th>Ripple Output Voltage [mV] (Input 132V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>1.0</td><td>15</td><td>20</td></tr> <tr><td>2.0</td><td>25</td><td>30</td></tr> <tr><td>3.0</td><td>25</td><td>35</td></tr> <tr><td>4.3</td><td>30</td><td>35</td></tr> <tr><td>5.0</td><td>30</td><td>40</td></tr> <tr><td>6.0</td><td>40</td><td>40</td></tr> <tr><td>7.0</td><td>40</td><td>40</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Ripple Output Voltage [mV] (Input 85V)	Ripple Output Voltage [mV] (Input 132V)	0.0	10	10	1.0	15	20	2.0	25	30	3.0	25	35	4.3	30	35	5.0	30	40	6.0	40	40	7.0	40	40	—	—	—	—	—	—	—	—	—		
Load Current [A]	Ripple Output Voltage [mV] (Input 85V)	Ripple Output Voltage [mV] (Input 132V)																																						
0.0	10	10																																						
1.0	15	20																																						
2.0	25	30																																						
3.0	25	35																																						
4.3	30	35																																						
5.0	30	40																																						
6.0	40	40																																						
7.0	40	40																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>1.0</td><td>15</td><td>20</td></tr> <tr><td>2.0</td><td>25</td><td>30</td></tr> <tr><td>3.0</td><td>25</td><td>35</td></tr> <tr><td>4.3</td><td>30</td><td>35</td></tr> <tr><td>5.0</td><td>30</td><td>40</td></tr> <tr><td>6.0</td><td>40</td><td>40</td></tr> <tr><td>7.0</td><td>40</td><td>40</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	10	10	1.0	15	20	2.0	25	30	3.0	25	35	4.3	30	35	5.0	30	40	6.0	40	40	7.0	40	40	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.0	10	10																																						
1.0	15	20																																						
2.0	25	30																																						
3.0	25	35																																						
4.3	30	35																																						
5.0	30	40																																						
6.0	40	40																																						
7.0	40	40																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
	<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p – p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																							




Model	LCA100S-24-H	Temperature	25°C																																						
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A																																						
Object	+24V 4.3A																																								
1. Graph		2. Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>15</td></tr> <tr><td>1.0</td><td>35</td><td>30</td></tr> <tr><td>2.0</td><td>50</td><td>50</td></tr> <tr><td>3.0</td><td>60</td><td>70</td></tr> <tr><td>4.3</td><td>70</td><td>70</td></tr> <tr><td>5.0</td><td>100</td><td>80</td></tr> <tr><td>6.0</td><td>120</td><td>110</td></tr> <tr><td>7.0</td><td>140</td><td>120</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	15	15	1.0	35	30	2.0	50	50	3.0	60	70	4.3	70	70	5.0	100	80	6.0	120	110	7.0	140	120	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.0	15	15																																							
1.0	35	30																																							
2.0	50	50																																							
3.0	60	70																																							
4.3	70	70																																							
5.0	100	80																																							
6.0	120	110																																							
7.0	140	120																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>T1: Due to AC Input Line T1: 入力商用周期 T2: Due to Switching T2: スイッチング周期</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL




Temperature 25°C
Testing Circuitry Figure A

COSEL

Model	LCA100S-24-H																																																					
Item	Overvoltage Protection 過電圧保護																																																					
Object	+24.0V 4.3A																																																					
1. Graph	<p style="text-align: center;"> Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V </p> 																																																					
2. Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>30.03</td><td>30.03</td><td>30.03</td></tr> <tr><td>-10</td><td>30.27</td><td>30.27</td><td>30.27</td></tr> <tr><td>0</td><td>30.56</td><td>30.56</td><td>30.56</td></tr> <tr><td>10</td><td>30.80</td><td>30.80</td><td>30.80</td></tr> <tr><td>20</td><td>31.10</td><td>31.10</td><td>31.10</td></tr> <tr><td>25</td><td>31.22</td><td>31.22</td><td>31.22</td></tr> <tr><td>30</td><td>31.34</td><td>31.34</td><td>31.34</td></tr> <tr><td>40</td><td>31.63</td><td>31.63</td><td>31.64</td></tr> <tr><td>50</td><td>31.87</td><td>31.87</td><td>31.87</td></tr> <tr><td>60</td><td>32.11</td><td>32.11</td><td>32.11</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	30.03	30.03	30.03	-10	30.27	30.27	30.27	0	30.56	30.56	30.56	10	30.80	30.80	30.80	20	31.10	31.10	31.10	25	31.22	31.22	31.22	30	31.34	31.34	31.34	40	31.63	31.63	31.64	50	31.87	31.87	31.87	60	32.11	32.11	32.11	—	—	—	—
Ambient Temperature [°C]	Operating Point [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	30.03	30.03	30.03																																																			
-10	30.27	30.27	30.27																																																			
0	30.56	30.56	30.56																																																			
10	30.80	30.80	30.80																																																			
20	31.10	31.10	31.10																																																			
25	31.22	31.22	31.22																																																			
30	31.34	31.34	31.34																																																			
40	31.63	31.63	31.64																																																			
50	31.87	31.87	31.87																																																			
60	32.11	32.11	32.11																																																			
—	—	—	—																																																			
Note:	Slanted line shows the range of the rated ambient temperature.																																																					
(注)	斜線は定格周囲温度範囲を示す。																																																					

COSEL

Model	LCA100S-24-H	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	—		



Input Voltage 100 V


Frequency 60 Hz

Load 100 %


Inrush Current

① 13.92 [A]


② 9.52 [A]



COSEL



COSEL



COSEL


Model LCA100S-24-H

Item Rise and Fall Time
立上り、立下り時間


Object +24.0V 4.3A

Temperature 25°C
Testing Circuitry Figure A

1. Graph




Input Volt. 85 V



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		152.5	22.0	174.5	33.4	46.4	
100 %		152.5	22.0	174.5	14.4	23.7	




COSEL

Model	LCA100S-24-H																																																					
Item	Ambient Temperature Drift 周围温度変動																																																					
Object	+24.0V 4.3A																																																					
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																					
Testing Circuitry	Figure A																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>24.121</td><td>24.121</td><td>24.121</td></tr> <tr> <td>-10</td><td>24.102</td><td>24.102</td><td>24.102</td></tr> <tr> <td>0</td><td>24.081</td><td>24.081</td><td>24.080</td></tr> <tr> <td>10</td><td>24.058</td><td>24.058</td><td>24.057</td></tr> <tr> <td>20</td><td>24.033</td><td>24.033</td><td>24.032</td></tr> <tr> <td>25</td><td>24.020</td><td>24.020</td><td>24.019</td></tr> <tr> <td>30</td><td>24.006</td><td>24.006</td><td>24.006</td></tr> <tr> <td>40</td><td>23.979</td><td>23.978</td><td>23.978</td></tr> <tr> <td>50</td><td>23.951</td><td>23.951</td><td>23.950</td></tr> <tr> <td>60</td><td>23.925</td><td>23.924</td><td>23.924</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	24.121	24.121	24.121	-10	24.102	24.102	24.102	0	24.081	24.081	24.080	10	24.058	24.058	24.057	20	24.033	24.033	24.032	25	24.020	24.020	24.019	30	24.006	24.006	24.006	40	23.979	23.978	23.978	50	23.951	23.951	23.950	60	23.925	23.924	23.924	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	24.121	24.121	24.121																																																			
-10	24.102	24.102	24.102																																																			
0	24.081	24.081	24.080																																																			
10	24.058	24.058	24.057																																																			
20	24.033	24.033	24.032																																																			
25	24.020	24.020	24.019																																																			
30	24.006	24.006	24.006																																																			
40	23.979	23.978	23.978																																																			
50	23.951	23.951	23.950																																																			
60	23.925	23.924	23.924																																																			
—	—	—	—																																																			

COSEL

Model	LCA100S-24-H
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+24.0V 4.3A



Testing Circuitry Figure A


2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	64	68
-10	64	68
0	63	68
10	63	68
20	63	68
25	63	68
30	63	68
40	63	68
50	63	68
60	63	68
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Output Voltage [mV]	
	Load 50%	Load 100%
-20	65	70
-10	60	65
0	50	55
10	40	40
20	35	35
25	35	35
30	35	35
40	30	30
50	30	30
60	30	30
—	—	—

COSEL

Model	LCA100S-24-H	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+24.0V 4.3A																								
1. Graph			2. Values																						
<p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.034</td></tr> <tr><td>0.5</td><td>24.027</td></tr> <tr><td>1.0</td><td>24.027</td></tr> <tr><td>2.0</td><td>24.027</td></tr> <tr><td>3.0</td><td>24.027</td></tr> <tr><td>4.0</td><td>24.027</td></tr> <tr><td>5.0</td><td>24.027</td></tr> <tr><td>6.0</td><td>24.027</td></tr> <tr><td>7.0</td><td>24.026</td></tr> <tr><td>8.0</td><td>24.026</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	24.034	0.5	24.027	1.0	24.027	2.0	24.027	3.0	24.027	4.0	24.027	5.0	24.027	6.0	24.027	7.0	24.026	8.0	24.026
Time since start [H]	Output Voltage [V]																								
0.0	24.034																								
0.5	24.027																								
1.0	24.027																								
2.0	24.027																								
3.0	24.027																								
4.0	24.027																								
5.0	24.027																								
6.0	24.027																								
7.0	24.026																								
8.0	24.026																								

COSEL




Figure A




Figure B (DENTORI)




Figure B (IEC60950)

COSEL




Figure C




Figure D




Figure E