



TEST DATA OF LCA150S-3

Regulated DC Power Supply
Aug.17. 2004

Approved by :

K.Shibutani

A handwritten signature in black ink, appearing to read "K. Shibutani".

Design Manager

Prepared by :

A.Kawai

A handwritten signature in black ink, appearing to read "A. Kawai".

Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Inrush Current	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Hold-Up Time	16
17. Instantaneous Interruption Compensation	17
18. Minimum Input Voltage for Regulated Output Voltage	18
19. Overcurrent Protection	19
20. Overvoltage Protection	20
21. Figure of Testing Circuitry	21


(Final Page 21)

COSEL

Model LCA150S-3

Item Input Current (by Load Current)

Object _____

Temperature 25°C
Testing Circuitry Figure A

2.Values


Load Current [A]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0	0.081	0.086	0.089
6	0.643	0.586	0.511
12	1.131	0.996	0.853
18	1.632	1.415	1.199
24	2.128	1.857	1.542
30	2.611	2.285	1.878
33	2.860	2.516	2.054
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

Model LCA150S-3

Item Input Power (by Load Current)

Object _____



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values


Load Current [A]	Input Power [W]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0	2.5	2.9	3.8
6	25.3	26.1	28.3
12	48.1	48.7	50.6
18	72.3	72.2	73.7
24	97.2	97.2	98.1
30	123.5	122.7	123.0
33	137.1	135.9	135.9
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Model LCA150S-3

Item Efficiency (by Input Voltage)

Object _____

1.Graph

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	75.5	72.8
80	75.8	73.1
85	75.8	73.5
90	75.7	73.7
100	75.2	74.2
110	74.9	74.2
120	74.3	74.2
132	73.4	74.1
140	72.7	73.9

Note: Slanted line shows the range of the rated input voltage.


Model	LCA150S-3																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6</td><td>71.8</td><td>69.6</td><td>64.2</td></tr> <tr><td>12</td><td>75.7</td><td>74.7</td><td>71.9</td></tr> <tr><td>18</td><td>75.6</td><td>75.7</td><td>74.1</td></tr> <tr><td>24</td><td>74.9</td><td>74.9</td><td>74.3</td></tr> <tr><td>30</td><td>73.7</td><td>74.2</td><td>74.0</td></tr> <tr><td>33</td><td>73.0</td><td>73.7</td><td>73.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	-	-	-	6	71.8	69.6	64.2	12	75.7	74.7	71.9	18	75.6	75.7	74.1	24	74.9	74.9	74.3	30	73.7	74.2	74.0	33	73.0	73.7	73.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	-	-	-																																																			
6	71.8	69.6	64.2																																																			
12	75.7	74.7	71.9																																																			
18	75.6	75.7	74.1																																																			
24	74.9	74.9	74.3																																																			
30	73.7	74.2	74.0																																																			
33	73.0	73.7	73.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model LCA150S-3

Item Inrush Current

Object _____

Temperature 25°C
Testing Circuitry Figure AInput
Current
[20A/div]


Input Voltage 100 V

Frequency 60 Hz


Load 100 %

Primary inrush current 13.2 A

Secondary inrush current 8.8 A



COSEL




COSEL

Model LCA150S-3

Item Ripple Voltage (by Load Current)

Object +3V30A

1. Graph



Measured by MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0	10	10
6	15	15
12	20	20
18	25	25
24	25	25
30	30	30
33	30	35
--	-	-
--	-	-
--	-	-
--	-	-

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	LCA150S-3
Item	Ripple-Noise
Object	+3V30A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0	15	15
6	25	30
12	30	35
18	40	40
24	45	50
30	50	50
33	55	55
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line
T2: Due to Switching




Fig. Complex Ripple Wave Form


COSEL

Model	LCA150S-3
-------	-----------

Item	Ripple Voltage (by Ambient Temp.)
------	-----------------------------------

Object	+3V30A
--------	--------

1. Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	35	50
-10	30	45
0	30	40
10	25	35
25	25	30
30	20	20
40	20	20
50	15	20
60	15	20
--	-	-
--	-	-



Model	LCA150S-3																																																					
Item	Ambient Temperature Drift																																																					
Object	+3V30A																																																					
1.Graph	<p>—△— Input Volt. 85V - - -□- Input Volt. 100V - - ○- Input Volt. 132V</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																					
Testing Circuitry	Figure A																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>3.050</td><td>3.050</td><td>3.050</td></tr> <tr> <td>-10</td><td>3.050</td><td>3.050</td><td>3.051</td></tr> <tr> <td>0</td><td>3.050</td><td>3.050</td><td>3.051</td></tr> <tr> <td>10</td><td>3.052</td><td>3.050</td><td>3.050</td></tr> <tr> <td>25</td><td>3.049</td><td>3.049</td><td>3.050</td></tr> <tr> <td>40</td><td>3.048</td><td>3.049</td><td>3.049</td></tr> <tr> <td>50</td><td>3.047</td><td>3.048</td><td>3.048</td></tr> <tr> <td>60</td><td>3.046</td><td>3.046</td><td>3.046</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	3.050	3.050	3.050	-10	3.050	3.050	3.051	0	3.050	3.050	3.051	10	3.052	3.050	3.050	25	3.049	3.049	3.050	40	3.048	3.049	3.049	50	3.047	3.048	3.048	60	3.046	3.046	3.046	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	3.050	3.050	3.050																																																			
-10	3.050	3.050	3.051																																																			
0	3.050	3.050	3.051																																																			
10	3.052	3.050	3.050																																																			
25	3.049	3.049	3.050																																																			
40	3.048	3.049	3.049																																																			
50	3.047	3.048	3.048																																																			
60	3.046	3.046	3.046																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated ambient temperature.																																																					



Model	LCA150S-3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3V30A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 132V

Load Current : 0 - 30A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	132	0	3.050	± 2	± 0.1
Minimum Voltage	50	85	30	3.047		

COSEL


Model LCA150S-3

Item Time Lapse Drift

Object +3V30A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values


Time since start [H]	Output Voltage [V]
0.0	3.050
0.5	3.049
1.0	3.049
2.0	3.049
3.0	3.049
4.0	3.049
5.0	3.049
6.0	3.049
7.0	3.049
8.0	3.049

COSEL

Model LCA150S-3


Temperature 25°C
Testing Circuitry Figure AItem Rise and Fall Time
Object +3V30A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		138.0	10.5	148.5	48.7	2.0	
100 %		138.3	13.0	151.3	27.8	1.3	




Model LCA150S-3

Item Hold-Up Time

Object +3V30A

1.Graph

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	43	19
80	54	25
85	66	30
90	79	37
100	107	50
110	137	65
120	170	82
132	216	105
140	248	121


This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.

Model	LCA150S-3																																																					
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+3V30A																																																					
1.Graph	<p>—△— Input Volt. 85V - -□--- Input Volt. 100V - -○--- Input Volt. 132V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>6</td><td>164</td><td>256</td><td>507</td></tr> <tr> <td>12</td><td>81</td><td>135</td><td>270</td></tr> <tr> <td>18</td><td>54</td><td>88</td><td>180</td></tr> <tr> <td>24</td><td>39</td><td>64</td><td>132</td></tr> <tr> <td>30</td><td>29</td><td>48</td><td>105</td></tr> <tr> <td>33</td><td>22</td><td>44</td><td>93</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	-	-	-	6	164	256	507	12	81	135	270	18	54	88	180	24	39	64	132	30	29	48	105	33	22	44	93	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	-	-	-																																																			
6	164	256	507																																																			
12	81	135	270																																																			
18	54	88	180																																																			
24	39	64	132																																																			
30	29	48	105																																																			
33	22	44	93																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

Model	LCA150S-3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3V30A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	59	65
-10	58	63
0	57	62
10	56	61
25	55	60
40	55	60
50	55	60
60	55	60
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.


COSEL

Model LCA150S-3

Item Overcurrent Protection

Object +3V30A

1.Graph




Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
3.00	34.17	33.79	33.63
2.85	36.99	37.31	38.03
2.70	37.07	37.37	38.14
2.40	37.21	37.49	38.34
2.10	37.38	37.70	38.50
1.80	37.52	37.86	38.68
1.50	37.63	38.02	38.86
1.20	37.80	38.21	38.94
0.90	37.75	38.41	39.14
0.60	38.11	38.36	38.93
0.30	37.90	38.01	38.43
0.00	37.29	37.30	37.27

Model	LCA150S-3					
Item	Overvoltage Protection					
Object	+3V30A					
1.Graph						
<p style="text-align: center;"> —△— Input Volt. 85V ---□--- Input Volt. 100V ---○--- Input Volt. 132V </p> 						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>						

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	4.84	4.84	4.84
-10	4.83	4.83	4.83
0	4.78	4.83	4.83
10	4.78	4.77	4.78
25	4.77	4.77	4.77
40	4.72	4.71	4.72
50	4.72	4.71	4.72
60	4.66	4.71	4.71
--	-	-	-
--	-	-	-
--	-	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)