



TEST DATA OF LCA150S-48

(100V INPUT)

Regulated DC Power Supply

Mar. 4, 2002

Approved by : K. Shibusawa
Design Manager

Prepared by : T. Miyakawa
Design Engineer

コーセル株式会社

COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的の入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的の負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Overvoltage Protection	12
過電圧保護	
13. Inrush Current	13
突入電流	
14. Rise and Fall Time	14
立上り、立下り時間	
15. Ambient Temperature Drift	15
周囲温度変動	
16. Minimum Input Voltage for Regulated Output Voltage	16
最低レギュレーション電圧	
17. Ripple Voltage (by Ambient Temperature)	17
リップル電圧 (周囲温度特性)	
18. Output Voltage Accuracy	18
定電圧精度	
19. Figure of Testing Circuitry	19
測定回路図	

(Final Page 19)


COSEL

Model	LCA150S-48																																		
Item	Line Regulation 静的入力変動	Temperature Testing Circuitry	25°C Figure A																																
Object	+48.0V 3.2A																																		
1. Graph																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>48.851</td><td>48.596</td></tr> <tr><td>80</td><td>48.851</td><td>48.848</td></tr> <tr><td>85</td><td>48.851</td><td>48.848</td></tr> <tr><td>90</td><td>48.850</td><td>48.848</td></tr> <tr><td>100</td><td>48.850</td><td>48.847</td></tr> <tr><td>110</td><td>48.849</td><td>48.846</td></tr> <tr><td>120</td><td>48.848</td><td>48.846</td></tr> <tr><td>132</td><td>48.847</td><td>48.844</td></tr> <tr><td>140</td><td>48.847</td><td>48.843</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	48.851	48.596	80	48.851	48.848	85	48.851	48.848	90	48.850	48.848	100	48.850	48.847	110	48.849	48.846	120	48.848	48.846	132	48.847	48.844	140	48.847	48.843
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	48.851	48.596																																	
80	48.851	48.848																																	
85	48.851	48.848																																	
90	48.850	48.848																																	
100	48.850	48.847																																	
110	48.849	48.846																																	
120	48.848	48.846																																	
132	48.847	48.844																																	
140	48.847	48.843																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LCA150S-48																																																									
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object	—																																																									
1. Graph	<p style="text-align: center;">—△— Input Volt. 85V □..... Input Volt. 100V ○..... Input Volt. 132V</p>  <p>The graph plots Input Current [A] on the y-axis (0 to 5) against Load Current [A] on the x-axis (0 to 4). Three curves are shown for different input voltages: 85V (triangles), 100V (squares), and 132V (circles). All curves show a positive linear relationship between input current and load current. A slanted line is drawn across the graph, starting from approximately (0.5, 0.5) and ending at (3.5, 4.5), representing the rated load current range.</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.157</td><td>0.158</td><td>0.163</td></tr> <tr><td>0.60</td><td>0.963</td><td>0.870</td><td>0.742</td></tr> <tr><td>1.20</td><td>1.669</td><td>1.493</td><td>1.239</td></tr> <tr><td>1.80</td><td>2.348</td><td>2.089</td><td>1.716</td></tr> <tr><td>2.40</td><td>3.047</td><td>2.714</td><td>2.223</td></tr> <tr><td>3.00</td><td>3.745</td><td>3.323</td><td>2.715</td></tr> <tr><td>3.20</td><td>3.975</td><td>3.527</td><td>2.879</td></tr> <tr><td>3.52</td><td>4.346</td><td>3.842</td><td>3.144</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.157	0.158	0.163	0.60	0.963	0.870	0.742	1.20	1.669	1.493	1.239	1.80	2.348	2.089	1.716	2.40	3.047	2.714	2.223	3.00	3.745	3.323	2.715	3.20	3.975	3.527	2.879	3.52	4.346	3.842	3.144	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	0.157	0.158	0.163																																																							
0.60	0.963	0.870	0.742																																																							
1.20	1.669	1.493	1.239																																																							
1.80	2.348	2.089	1.716																																																							
2.40	3.047	2.714	2.223																																																							
3.00	3.745	3.323	2.715																																																							
3.20	3.975	3.527	2.879																																																							
3.52	4.346	3.842	3.144																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA150S-48																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object	_____																																																									
1. Graph	<p>Input Volt. 85V Input Volt. 100V Input Volt. 132V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (85V)</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (132V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4.96</td><td>5.73</td><td>7.38</td></tr> <tr><td>0.60</td><td>38.56</td><td>39.52</td><td>41.90</td></tr> <tr><td>1.20</td><td>71.00</td><td>71.75</td><td>74.00</td></tr> <tr><td>1.80</td><td>103.80</td><td>104.20</td><td>106.20</td></tr> <tr><td>2.40</td><td>139.60</td><td>139.80</td><td>141.30</td></tr> <tr><td>3.00</td><td>176.60</td><td>176.00</td><td>176.80</td></tr> <tr><td>3.20</td><td>189.30</td><td>188.40</td><td>188.80</td></tr> <tr><td>3.52</td><td>209.40</td><td>207.90</td><td>207.70</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (85V)	Input Power [W] (100V)	Input Power [W] (132V)	0.00	4.96	5.73	7.38	0.60	38.56	39.52	41.90	1.20	71.00	71.75	74.00	1.80	103.80	104.20	106.20	2.40	139.60	139.80	141.30	3.00	176.60	176.00	176.80	3.20	189.30	188.40	188.80	3.52	209.40	207.90	207.70	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Load Current [A]	Input Power [W] (85V)	Input Power [W] (100V)	Input Power [W] (132V)																																																							
0.00	4.96	5.73	7.38																																																							
0.60	38.56	39.52	41.90																																																							
1.20	71.00	71.75	74.00																																																							
1.80	103.80	104.20	106.20																																																							
2.40	139.60	139.80	141.30																																																							
3.00	176.60	176.00	176.80																																																							
3.20	189.30	188.40	188.80																																																							
3.52	209.40	207.90	207.70																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4.96</td><td>5.73</td><td>7.38</td></tr> <tr><td>0.60</td><td>38.56</td><td>39.52</td><td>41.90</td></tr> <tr><td>1.20</td><td>71.00</td><td>71.75</td><td>74.00</td></tr> <tr><td>1.80</td><td>103.80</td><td>104.20</td><td>106.20</td></tr> <tr><td>2.40</td><td>139.60</td><td>139.80</td><td>141.30</td></tr> <tr><td>3.00</td><td>176.60</td><td>176.00</td><td>176.80</td></tr> <tr><td>3.20</td><td>189.30</td><td>188.40</td><td>188.80</td></tr> <tr><td>3.52</td><td>209.40</td><td>207.90</td><td>207.70</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	4.96	5.73	7.38	0.60	38.56	39.52	41.90	1.20	71.00	71.75	74.00	1.80	103.80	104.20	106.20	2.40	139.60	139.80	141.30	3.00	176.60	176.00	176.80	3.20	189.30	188.40	188.80	3.52	209.40	207.90	207.70	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	4.96	5.73	7.38																																																							
0.60	38.56	39.52	41.90																																																							
1.20	71.00	71.75	74.00																																																							
1.80	103.80	104.20	106.20																																																							
2.40	139.60	139.80	141.30																																																							
3.00	176.60	176.00	176.80																																																							
3.20	189.30	188.40	188.80																																																							
3.52	209.40	207.90	207.70																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA150S-48		Temperature Testing Circuitry 25°C Figure A																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)																																		
Object	<hr/>																																		
1. Graph																																			
 Load 50%			2. Values																																
 Load 100%																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>84.8</td><td>85.0</td></tr> <tr> <td>80</td><td>85.5</td><td>85.8</td></tr> <tr> <td>85</td><td>85.8</td><td>86.3</td></tr> <tr> <td>90</td><td>85.8</td><td>86.6</td></tr> <tr> <td>100</td><td>85.5</td><td>86.9</td></tr> <tr> <td>110</td><td>84.9</td><td>87.1</td></tr> <tr> <td>120</td><td>84.4</td><td>87.1</td></tr> <tr> <td>132</td><td>83.6</td><td>86.9</td></tr> <tr> <td>140</td><td>83.1</td><td>86.7</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	84.8	85.0	80	85.5	85.8	85	85.8	86.3	90	85.8	86.6	100	85.5	86.9	110	84.9	87.1	120	84.4	87.1	132	83.6	86.9	140	83.1	86.7
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	84.8	85.0																																	
80	85.5	85.8																																	
85	85.8	86.3																																	
90	85.8	86.6																																	
100	85.5	86.9																																	
110	84.9	87.1																																	
120	84.4	87.1																																	
132	83.6	86.9																																	
140	83.1	86.7																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	LCA150S-48																																																									
Item	Efficiency (by Load Current) 効率(負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object	_____																																																									
1. Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend: Input Volt. 85V (triangle), Input Volt. 100V (square), Input Volt. 132V (circle)</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.60</td><td>79.5</td><td>77.5</td><td>73.0</td></tr> <tr><td>1.20</td><td>84.8</td><td>83.9</td><td>81.4</td></tr> <tr><td>1.80</td><td>86.4</td><td>86.2</td><td>84.5</td></tr> <tr><td>2.40</td><td>87.0</td><td>87.1</td><td>86.2</td></tr> <tr><td>3.00</td><td>86.9</td><td>87.4</td><td>87.0</td></tr> <tr><td>3.20</td><td>86.7</td><td>87.2</td><td>87.1</td></tr> <tr><td>3.52</td><td>86.4</td><td>87.2</td><td>87.3</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.60	79.5	77.5	73.0	1.20	84.8	83.9	81.4	1.80	86.4	86.2	84.5	2.40	87.0	87.1	86.2	3.00	86.9	87.4	87.0	3.20	86.7	87.2	87.1	3.52	86.4	87.2	87.3	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.60	79.5	77.5	73.0																																																							
1.20	84.8	83.9	81.4																																																							
1.80	86.4	86.2	84.5																																																							
2.40	87.0	87.1	86.2																																																							
3.00	86.9	87.4	87.0																																																							
3.20	86.7	87.2	87.1																																																							
3.52	86.4	87.2	87.3																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current.																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

COSEL

Model	LCA150S-48																																		
Item	Hold-Up Time 出力保持時間	Temperature Testing Circuitry	25°C Figure A																																
Object	+48.0V 3.2A																																		
1. Graph																																			
			2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>16</td><td>8</td></tr> <tr> <td>80</td><td>23</td><td>12</td></tr> <tr> <td>85</td><td>31</td><td>16</td></tr> <tr> <td>90</td><td>38</td><td>21</td></tr> <tr> <td>100</td><td>54</td><td>31</td></tr> <tr> <td>110</td><td>73</td><td>43</td></tr> <tr> <td>120</td><td>93</td><td>55</td></tr> <tr> <td>132</td><td>120</td><td>71</td></tr> <tr> <td>140</td><td>140</td><td>83</td></tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	16	8	80	23	12	85	31	16	90	38	21	100	54	31	110	73	43	120	93	55	132	120	71	140	140	83
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	16	8																																	
80	23	12																																	
85	31	16																																	
90	38	21																																	
100	54	31																																	
110	73	43																																	
120	93	55																																	
132	120	71																																	
140	140	83																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。 (注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	LCA150S-48																																																					
Item	Instantaneous Interruption Compensation 瞬時停電保障	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+48V3.2A																																																					
1. Graph	<p>—△— Input Volt. 85V - - -□--- Input Volt. 100V - - ○--- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>85V [ms]</th> <th>100V [ms]</th> <th>132V [ms]</th> </tr> </thead> <tbody> <tr><td>0.60</td><td>72</td><td>139</td><td>322</td></tr> <tr><td>1.20</td><td>36</td><td>72</td><td>169</td></tr> <tr><td>1.80</td><td>22</td><td>47</td><td>115</td></tr> <tr><td>2.40</td><td>13</td><td>35</td><td>87</td></tr> <tr><td>3.00</td><td>12</td><td>22</td><td>65</td></tr> <tr><td>3.20</td><td>10</td><td>22</td><td>63</td></tr> <tr><td>3.52</td><td>8</td><td>22</td><td>56</td></tr> </tbody> </table>			Load Current [A]	85V [ms]	100V [ms]	132V [ms]	0.60	72	139	322	1.20	36	72	169	1.80	22	47	115	2.40	13	35	87	3.00	12	22	65	3.20	10	22	63	3.52	8	22	56																			
Load Current [A]	85V [ms]	100V [ms]	132V [ms]																																																			
0.60	72	139	322																																																			
1.20	36	72	169																																																			
1.80	22	47	115																																																			
2.40	13	35	87																																																			
3.00	12	22	65																																																			
3.20	10	22	63																																																			
3.52	8	22	56																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.60</td><td>72</td><td>139</td><td>322</td></tr> <tr><td>1.20</td><td>36</td><td>72</td><td>169</td></tr> <tr><td>1.80</td><td>22</td><td>47</td><td>115</td></tr> <tr><td>2.40</td><td>13</td><td>35</td><td>87</td></tr> <tr><td>3.00</td><td>12</td><td>22</td><td>65</td></tr> <tr><td>3.20</td><td>10</td><td>22</td><td>63</td></tr> <tr><td>3.52</td><td>8</td><td>22</td><td>56</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.60	72	139	322	1.20	36	72	169	1.80	22	47	115	2.40	13	35	87	3.00	12	22	65	3.20	10	22	63	3.52	8	22	56	---	—	—	—	---	—	—	—	---	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	—	—	—																																																			
0.60	72	139	322																																																			
1.20	36	72	169																																																			
1.80	22	47	115																																																			
2.40	13	35	87																																																			
3.00	12	22	65																																																			
3.20	10	22	63																																																			
3.52	8	22	56																																																			
---	—	—	—																																																			
---	—	—	—																																																			
---	—	—	—																																																			
Note: Slanted line shows the range of the rated load current.																																																						
(注) 斜線は定格負荷電流範囲を示す。																																																						

COSEL

Model	LCA150S-48	Temperature 25°C Testing Circuitry Figure A																																																	
Item	Load Regulation 静的負荷変動																																																		
Object	+48.0V 3.2A																																																		
1. Graph																																																			
		Input Volt. 85 V	Input Volt. 100 V	Input Volt. 132 V																																															
		△	□	○																																															
<p>The graph shows the relationship between Output Voltage [V] on the Y-axis (48.400 to 49.100) and Load Current [A] on the X-axis (0 to 4). Three data series are shown for Input Voltages of 85V (triangles), 100V (squares), and 132V (circles). All three series show a flat output voltage curve until a load current of approximately 3.2A, after which the output voltage drops sharply. A slanted line is drawn across the graph, starting from the origin and ending at a point corresponding to a load current of about 3.2A and an output voltage of about 48.55V.</p>																																																			
2. Values																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>48.849</td> <td>48.850</td> <td>48.849</td> </tr> <tr> <td>0.60</td> <td>48.844</td> <td>48.844</td> <td>48.844</td> </tr> <tr> <td>1.20</td> <td>48.844</td> <td>48.844</td> <td>48.843</td> </tr> <tr> <td>1.80</td> <td>48.844</td> <td>48.844</td> <td>48.842</td> </tr> <tr> <td>2.40</td> <td>48.844</td> <td>48.843</td> <td>48.841</td> </tr> <tr> <td>3.00</td> <td>48.843</td> <td>48.842</td> <td>48.841</td> </tr> <tr> <td>3.20</td> <td>48.843</td> <td>48.843</td> <td>48.840</td> </tr> <tr> <td>3.52</td> <td>48.842</td> <td>48.843</td> <td>48.840</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>					Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	48.849	48.850	48.849	0.60	48.844	48.844	48.844	1.20	48.844	48.844	48.843	1.80	48.844	48.844	48.842	2.40	48.844	48.843	48.841	3.00	48.843	48.842	48.841	3.20	48.843	48.843	48.840	3.52	48.842	48.843	48.840	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																
0.00	48.849	48.850	48.849																																																
0.60	48.844	48.844	48.844																																																
1.20	48.844	48.844	48.843																																																
1.80	48.844	48.844	48.842																																																
2.40	48.844	48.843	48.841																																																
3.00	48.843	48.842	48.841																																																
3.20	48.843	48.843	48.840																																																
3.52	48.842	48.843	48.840																																																
—	—	—	—																																																
—	—	—	—																																																

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA150S-48																																				
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	Temperature 25°C Testing Circuitry Figure A																																			
Object	+48V3.2A																																				
1. Graph																																					
<p>1. Graph</p> <p>—△— Input Volt. 85V ---○--- Input Volt. 132V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 85V)</th> <th>Ripple Voltage [mV] (Input Volt. 132V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.40</td><td>15</td><td>15</td></tr> <tr><td>0.80</td><td>20</td><td>20</td></tr> <tr><td>1.20</td><td>20</td><td>20</td></tr> <tr><td>1.60</td><td>20</td><td>20</td></tr> <tr><td>2.00</td><td>20</td><td>20</td></tr> <tr><td>2.40</td><td>25</td><td>20</td></tr> <tr><td>2.80</td><td>25</td><td>20</td></tr> <tr><td>3.20</td><td>30</td><td>20</td></tr> <tr><td>3.52</td><td>35</td><td>20</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)	0.00	10	10	0.40	15	15	0.80	20	20	1.20	20	20	1.60	20	20	2.00	20	20	2.40	25	20	2.80	25	20	3.20	30	20	3.52	35	20	--	--	--
Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)																																			
0.00	10	10																																			
0.40	15	15																																			
0.80	20	20																																			
1.20	20	20																																			
1.60	20	20																																			
2.00	20	20																																			
2.40	25	20																																			
2.80	25	20																																			
3.20	30	20																																			
3.52	35	20																																			
--	--	--																																			
2. Values																																					
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p – p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																					

COSEL

Model	LCA150S-48																																							
Item	Ripple-Noise リップルノイズ	Temperature 25°C Testing Circuitry Figure A																																						
Object	+48V3.2A																																							
1. Graph																																								
<p>—△— Input Volt. 85V ---○--- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input 85V)</th> <th>Ripple-Noise [mV] (Input 132V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>25</td><td>30</td></tr> <tr><td>0.40</td><td>35</td><td>40</td></tr> <tr><td>0.80</td><td>40</td><td>50</td></tr> <tr><td>1.20</td><td>45</td><td>55</td></tr> <tr><td>1.60</td><td>45</td><td>55</td></tr> <tr><td>2.00</td><td>55</td><td>55</td></tr> <tr><td>2.40</td><td>55</td><td>60</td></tr> <tr><td>2.80</td><td>60</td><td>70</td></tr> <tr><td>3.20</td><td>70</td><td>75</td></tr> <tr><td>3.52</td><td>70</td><td>75</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV] (Input 85V)	Ripple-Noise [mV] (Input 132V)	0.00	25	30	0.40	35	40	0.80	40	50	1.20	45	55	1.60	45	55	2.00	55	55	2.40	55	60	2.80	60	70	3.20	70	75	3.52	70	75						
Load Current [A]	Ripple-Noise [mV] (Input 85V)	Ripple-Noise [mV] (Input 132V)																																						
0.00	25	30																																						
0.40	35	40																																						
0.80	40	50																																						
1.20	45	55																																						
1.60	45	55																																						
2.00	55	55																																						
2.40	55	60																																						
2.80	60	70																																						
3.20	70	75																																						
3.52	70	75																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>25</td><td>30</td></tr> <tr><td>0.40</td><td>35</td><td>40</td></tr> <tr><td>0.80</td><td>40</td><td>50</td></tr> <tr><td>1.20</td><td>45</td><td>55</td></tr> <tr><td>1.60</td><td>45</td><td>55</td></tr> <tr><td>2.00</td><td>55</td><td>55</td></tr> <tr><td>2.40</td><td>55</td><td>60</td></tr> <tr><td>2.80</td><td>60</td><td>70</td></tr> <tr><td>3.20</td><td>70</td><td>75</td></tr> <tr><td>3.52</td><td>70</td><td>75</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	25	30	0.40	35	40	0.80	40	50	1.20	45	55	1.60	45	55	2.00	55	55	2.40	55	60	2.80	60	70	3.20	70	75	3.52	70	75	---	—	—
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.00	25	30																																						
0.40	35	40																																						
0.80	40	50																																						
1.20	45	55																																						
1.60	45	55																																						
2.00	55	55																																						
2.40	55	60																																						
2.80	60	70																																						
3.20	70	75																																						
3.52	70	75																																						
---	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL

Model	LCA150S-48																																																									
Item	Overcurrent Protection 過電流保護	Temperature Testing Circuitry	25°C Figure A																																																							
Object	+48.0 V 3.2 A																																																									
1. Graph																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>48.00</td><td>3.985</td><td>3.979</td><td>4.001</td></tr> <tr><td>45.60</td><td>3.993</td><td>3.987</td><td>4.015</td></tr> <tr><td>43.20</td><td>4.002</td><td>4.000</td><td>4.032</td></tr> <tr><td>38.40</td><td>4.031</td><td>4.036</td><td>4.058</td></tr> <tr><td>33.60</td><td>4.052</td><td>4.056</td><td>4.087</td></tr> <tr><td>28.80</td><td>4.078</td><td>4.079</td><td>4.114</td></tr> <tr><td>24.00</td><td>4.088</td><td>4.094</td><td>4.127</td></tr> <tr><td>19.20</td><td>4.092</td><td>4.093</td><td>4.132</td></tr> <tr><td>14.40</td><td>4.092</td><td>4.106</td><td>4.158</td></tr> <tr><td>9.60</td><td>4.112</td><td>4.106</td><td>4.131</td></tr> <tr><td>4.80</td><td>4.048</td><td>4.033</td><td>4.016</td></tr> <tr><td>0.00</td><td>4.240</td><td>4.332</td><td>4.618</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	48.00	3.985	3.979	4.001	45.60	3.993	3.987	4.015	43.20	4.002	4.000	4.032	38.40	4.031	4.036	4.058	33.60	4.052	4.056	4.087	28.80	4.078	4.079	4.114	24.00	4.088	4.094	4.127	19.20	4.092	4.093	4.132	14.40	4.092	4.106	4.158	9.60	4.112	4.106	4.131	4.80	4.048	4.033	4.016	0.00	4.240	4.332	4.618
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
48.00	3.985	3.979	4.001																																																							
45.60	3.993	3.987	4.015																																																							
43.20	4.002	4.000	4.032																																																							
38.40	4.031	4.036	4.058																																																							
33.60	4.052	4.056	4.087																																																							
28.80	4.078	4.079	4.114																																																							
24.00	4.088	4.094	4.127																																																							
19.20	4.092	4.093	4.132																																																							
14.40	4.092	4.106	4.158																																																							
9.60	4.112	4.106	4.131																																																							
4.80	4.048	4.033	4.016																																																							
0.00	4.240	4.332	4.618																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																										




Model	LCA150S-48																																																					
Item	Overvoltage Protection 過電圧保護																																																					
Object	+48.0V3.2A																																																					
Testing Circuitry Figure A																																																						
1. Graph	<p style="text-align: center;"> Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V </p> <p style="text-align: center;">[V]</p> <p style="text-align: center;">Operating Point [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 0%</p>																																																					
2. Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-30</td> <td>57.90</td> <td>57.90</td> <td>57.83</td> </tr> <tr> <td>-20</td> <td>58.25</td> <td>58.32</td> <td>58.25</td> </tr> <tr> <td>-10</td> <td>58.82</td> <td>58.74</td> <td>58.74</td> </tr> <tr> <td>0</td> <td>59.24</td> <td>59.24</td> <td>59.24</td> </tr> <tr> <td>10</td> <td>59.80</td> <td>59.73</td> <td>59.73</td> </tr> <tr> <td>25</td> <td>60.51</td> <td>60.51</td> <td>60.51</td> </tr> <tr> <td>30</td> <td>60.92</td> <td>60.78</td> <td>60.78</td> </tr> <tr> <td>40</td> <td>61.42</td> <td>61.35</td> <td>61.35</td> </tr> <tr> <td>55</td> <td>62.19</td> <td>62.12</td> <td>62.12</td> </tr> <tr> <td>60</td> <td>62.48</td> <td>62.33</td> <td>62.33</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-30	57.90	57.90	57.83	-20	58.25	58.32	58.25	-10	58.82	58.74	58.74	0	59.24	59.24	59.24	10	59.80	59.73	59.73	25	60.51	60.51	60.51	30	60.92	60.78	60.78	40	61.42	61.35	61.35	55	62.19	62.12	62.12	60	62.48	62.33	62.33	—	—	—	—
Ambient Temperature [°C]	Operating Point [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-30	57.90	57.90	57.83																																																			
-20	58.25	58.32	58.25																																																			
-10	58.82	58.74	58.74																																																			
0	59.24	59.24	59.24																																																			
10	59.80	59.73	59.73																																																			
25	60.51	60.51	60.51																																																			
30	60.92	60.78	60.78																																																			
40	61.42	61.35	61.35																																																			
55	62.19	62.12	62.12																																																			
60	62.48	62.33	62.33																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	LCA150S-48	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	_____		



Input Voltage 100 V


Frequency 60 Hz

Load 100 %


Inrush Current

① 13.57 [A]

② 12.77 [A]



COSEL



COSEL

Model	LCA150S-48																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																					
Object	+48.0V 3.2A																																																					
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>48.867</td><td>48.867</td><td>48.865</td></tr> <tr><td>-20</td><td>48.873</td><td>48.872</td><td>48.870</td></tr> <tr><td>-10</td><td>48.874</td><td>48.873</td><td>48.871</td></tr> <tr><td>0</td><td>48.871</td><td>48.871</td><td>48.868</td></tr> <tr><td>10</td><td>48.865</td><td>48.864</td><td>48.862</td></tr> <tr><td>25</td><td>48.849</td><td>48.848</td><td>48.846</td></tr> <tr><td>30</td><td>48.842</td><td>48.842</td><td>48.839</td></tr> <tr><td>40</td><td>48.826</td><td>48.825</td><td>48.822</td></tr> <tr><td>55</td><td>48.797</td><td>48.796</td><td>48.793</td></tr> <tr><td>60</td><td>48.787</td><td>48.786</td><td>48.782</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-30	48.867	48.867	48.865	-20	48.873	48.872	48.870	-10	48.874	48.873	48.871	0	48.871	48.871	48.868	10	48.865	48.864	48.862	25	48.849	48.848	48.846	30	48.842	48.842	48.839	40	48.826	48.825	48.822	55	48.797	48.796	48.793	60	48.787	48.786	48.782	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-30	48.867	48.867	48.865																																																			
-20	48.873	48.872	48.870																																																			
-10	48.874	48.873	48.871																																																			
0	48.871	48.871	48.868																																																			
10	48.865	48.864	48.862																																																			
25	48.849	48.848	48.846																																																			
30	48.842	48.842	48.839																																																			
40	48.826	48.825	48.822																																																			
55	48.797	48.796	48.793																																																			
60	48.787	48.786	48.782																																																			
—	—	—	—																																																			

COSEL

Model	LCA150S-48		
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧		
Object	+48.0V 3.2A		
1. Graph			
[V]			
Input Voltage [V]	Load 50% Load 100%		
Ambient Temperature [°C]	-40 0 40 80		
Note: Slanted line shows the range of the rated ambient temperature.			
(注)斜線は定格周囲温度範囲を示す。			

Testing Circuitry Figure A


2. Values

Ambient Temperature [°C]	Input Voltage [V]			
	Load	50%	Load	100%
-30		66		71
-20		66		71
-10		65		71
0		65		71
10		65		71
25		65		71
30		65		71
40		65		71
55		65		72
60		65		72
—		—		—

COSEL

Model	LCA150S-48
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+48V3.2A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	40	50
-10	35	50
0	30	35
10	20	30
20	20	30
25	20	30
30	20	25
40	15	25
50	15	25
--	--	--
--	--	--



Model	LCA150S-48		
Item	Output Voltage Accuracy 定電圧精度	Testing Circuitry	Figure A
Object	+48.0V 3.2A		

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~40 °C

Input Voltage : 85~132 V

Load Current : 0~3.2 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~40 °C

入力電圧 85~132 V

負荷電流 0~3.2 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	85	0.0	48.880		
Minimum Voltage	40	132	3.2	48.816	±33	±0.1




Figure A