



TEST DATA OF LCA15S-24

(100V INPUT)

Regulated DC Power Supply

Date : June 17. 1999

Approved by : H. Yamaguchi
Design Manager

Prepared by : S. Yamaguchi
Design Engineer

コーワセル株式会社
COSEL CO., LTD.



CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Inrush Current	12
突入電流	
13. Dynamic Load Response	13
動的負荷変動	
14. Rise and Fall Time	14
立上り、立下がり時間	
15. Ambient Temperature Drift	15
周囲温度変動	
16. Minimum Input Voltage for Regulated Output Voltage	16
最低レギュレーション電圧	
17. Ripple Voltage (by Ambient Temperature)	17
リップル電圧 (周囲温度特性)	
18. Time Lapse Drift	18
経時ドリフト	
19. Output Voltage Accuracy	19
定電圧精度	
20. Condensation	20
結露特性	
21. Leakage Current	21
漏洩電流	
22. Line Noise Tolerance	22
入力雑音耐量	
23. Conducted Emission	23
雑音端子電圧	
24. Figure of Testing Circuitry	24
測定回路図	

(Final Page 25)

COSEL

Model	LCA15S-24		Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																			
Object	+24.0V 0.7A																																			
1. Graph	<p style="text-align: center;">□ Load 50% △ Load 100%</p>																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>23.930</td><td>23.927</td></tr> <tr><td>80</td><td>23.929</td><td>23.926</td></tr> <tr><td>85</td><td>23.927</td><td>23.925</td></tr> <tr><td>90</td><td>23.926</td><td>23.924</td></tr> <tr><td>100</td><td>23.922</td><td>23.921</td></tr> <tr><td>110</td><td>23.918</td><td>23.917</td></tr> <tr><td>120</td><td>23.914</td><td>23.914</td></tr> <tr><td>132</td><td>23.908</td><td>23.909</td></tr> <tr><td>140</td><td>23.904</td><td>23.906</td></tr> </tbody> </table>				Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	23.930	23.927	80	23.929	23.926	85	23.927	23.925	90	23.926	23.924	100	23.922	23.921	110	23.918	23.917	120	23.914	23.914	132	23.908	23.909	140	23.904	23.906
Input Voltage [V]	Output Voltage [V]																																			
	Load 50%	Load 100%																																		
75	23.930	23.927																																		
80	23.929	23.926																																		
85	23.927	23.925																																		
90	23.926	23.924																																		
100	23.922	23.921																																		
110	23.918	23.917																																		
120	23.914	23.914																																		
132	23.908	23.909																																		
140	23.904	23.906																																		

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LCA15S-24																																																									
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Output	—																																																									
1. Graph	<p>—△— Input Volt. 85V —□— Input Volt. 100V —○— Input Volt. 132V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.050</td><td>0.052</td><td>0.057</td></tr> <tr><td>0.10</td><td>0.105</td><td>0.102</td><td>0.101</td></tr> <tr><td>0.20</td><td>0.156</td><td>0.146</td><td>0.136</td></tr> <tr><td>0.30</td><td>0.203</td><td>0.188</td><td>0.169</td></tr> <tr><td>0.40</td><td>0.252</td><td>0.229</td><td>0.201</td></tr> <tr><td>0.50</td><td>0.302</td><td>0.272</td><td>0.235</td></tr> <tr><td>0.60</td><td>0.350</td><td>0.313</td><td>0.266</td></tr> <tr><td>0.70</td><td>0.399</td><td>0.354</td><td>0.298</td></tr> <tr><td>0.77</td><td>0.433</td><td>0.384</td><td>0.320</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.050	0.052	0.057	0.10	0.105	0.102	0.101	0.20	0.156	0.146	0.136	0.30	0.203	0.188	0.169	0.40	0.252	0.229	0.201	0.50	0.302	0.272	0.235	0.60	0.350	0.313	0.266	0.70	0.399	0.354	0.298	0.77	0.433	0.384	0.320	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	0.050	0.052	0.057																																																							
0.10	0.105	0.102	0.101																																																							
0.20	0.156	0.146	0.136																																																							
0.30	0.203	0.188	0.169																																																							
0.40	0.252	0.229	0.201																																																							
0.50	0.302	0.272	0.235																																																							
0.60	0.350	0.313	0.266																																																							
0.70	0.399	0.354	0.298																																																							
0.77	0.433	0.384	0.320																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA15S-24																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	_____																																																									
1. Graph	<p style="text-align: center;">—△— Input Volt. 85V —□— Input Volt. 100V —○— Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85V [W]</th> <th>Input Volt. 100V [W]</th> <th>Input Volt. 132V [W]</th> </tr> </thead> <tbody> <tr><td>0.2</td><td>~5</td><td>~7</td><td>~6</td></tr> <tr><td>0.4</td><td>~13</td><td>~14</td><td>~12</td></tr> <tr><td>0.6</td><td>~20</td><td>~19</td><td>~17</td></tr> <tr><td>0.8</td><td>~24</td><td>~24</td><td>~23</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85V [W]	Input Volt. 100V [W]	Input Volt. 132V [W]	0.2	~5	~7	~6	0.4	~13	~14	~12	0.6	~20	~19	~17	0.8	~24	~24	~23																																			
Load Current [A]	Input Volt. 85V [W]	Input Volt. 100V [W]	Input Volt. 132V [W]																																																							
0.2	~5	~7	~6																																																							
0.4	~13	~14	~12																																																							
0.6	~20	~19	~17																																																							
0.8	~24	~24	~23																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1.93</td><td>2.32</td><td>3.21</td></tr> <tr><td>0.10</td><td>4.75</td><td>5.22</td><td>6.47</td></tr> <tr><td>0.20</td><td>7.52</td><td>7.96</td><td>9.11</td></tr> <tr><td>0.30</td><td>10.16</td><td>10.57</td><td>11.68</td></tr> <tr><td>0.40</td><td>12.93</td><td>13.27</td><td>14.31</td></tr> <tr><td>0.50</td><td>15.86</td><td>16.09</td><td>17.00</td></tr> <tr><td>0.60</td><td>18.73</td><td>18.84</td><td>19.60</td></tr> <tr><td>0.70</td><td>21.65</td><td>21.66</td><td>22.23</td></tr> <tr><td>0.77</td><td>23.73</td><td>23.66</td><td>24.11</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	1.93	2.32	3.21	0.10	4.75	5.22	6.47	0.20	7.52	7.96	9.11	0.30	10.16	10.57	11.68	0.40	12.93	13.27	14.31	0.50	15.86	16.09	17.00	0.60	18.73	18.84	19.60	0.70	21.65	21.66	22.23	0.77	23.73	23.66	24.11	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	1.93	2.32	3.21																																																							
0.10	4.75	5.22	6.47																																																							
0.20	7.52	7.96	9.11																																																							
0.30	10.16	10.57	11.68																																																							
0.40	12.93	13.27	14.31																																																							
0.50	15.86	16.09	17.00																																																							
0.60	18.73	18.84	19.60																																																							
0.70	21.65	21.66	22.23																																																							
0.77	23.73	23.66	24.11																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA15S-24		Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency 効率																																			
Object	_____																																			
1. Graph	<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Load 50% (Squares)</p> <p>Load 100% (Triangles)</p>																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>75.0</td><td>77.4</td></tr> <tr><td>80</td><td>74.3</td><td>78.0</td></tr> <tr><td>85</td><td>73.9</td><td>78.2</td></tr> <tr><td>90</td><td>73.0</td><td>78.3</td></tr> <tr><td>100</td><td>71.6</td><td>78.2</td></tr> <tr><td>110</td><td>69.7</td><td>77.8</td></tr> <tr><td>120</td><td>67.9</td><td>77.3</td></tr> <tr><td>132</td><td>65.3</td><td>76.2</td></tr> <tr><td>140</td><td>63.9</td><td>75.4</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	75.0	77.4	80	74.3	78.0	85	73.9	78.2	90	73.0	78.3	100	71.6	78.2	110	69.7	77.8	120	67.9	77.3	132	65.3	76.2	140	63.9	75.4
Input Voltage [V]	Efficiency [%]																																			
	Load 50%	Load 100%																																		
75	75.0	77.4																																		
80	74.3	78.0																																		
85	73.9	78.2																																		
90	73.0	78.3																																		
100	71.6	78.2																																		
110	69.7	77.8																																		
120	67.9	77.3																																		
132	65.3	76.2																																		
140	63.9	75.4																																		
Note:	Slanted line shows the range of the rated input voltage.																																			
(注)	斜線は定格入力電圧範囲を示す。																																			

COSEL

Model	LCA15S-24																																																									
Item	Efficiency (by Load Current) 効率 (負荷電流特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	——																																																									
1. Graph	<p>Legend: Input Volt. 85V (△), Input Volt. 100V (□), Input Volt. 132V (○)</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.10</td><td>53.8</td><td>48.8</td><td>39.6</td></tr> <tr><td>0.20</td><td>65.8</td><td>62.5</td><td>54.9</td></tr> <tr><td>0.30</td><td>72.0</td><td>69.2</td><td>62.9</td></tr> <tr><td>0.40</td><td>75.1</td><td>73.4</td><td>68.1</td></tr> <tr><td>0.50</td><td>77.0</td><td>76.0</td><td>71.8</td></tr> <tr><td>0.60</td><td>77.6</td><td>77.3</td><td>74.3</td></tr> <tr><td>0.70</td><td>78.1</td><td>78.1</td><td>76.2</td></tr> <tr><td>0.77</td><td>78.3</td><td>78.4</td><td>77.0</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.10	53.8	48.8	39.6	0.20	65.8	62.5	54.9	0.30	72.0	69.2	62.9	0.40	75.1	73.4	68.1	0.50	77.0	76.0	71.8	0.60	77.6	77.3	74.3	0.70	78.1	78.1	76.2	0.77	78.3	78.4	77.0	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.10	53.8	48.8	39.6																																																							
0.20	65.8	62.5	54.9																																																							
0.30	72.0	69.2	62.9																																																							
0.40	75.1	73.4	68.1																																																							
0.50	77.0	76.0	71.8																																																							
0.60	77.6	77.3	74.3																																																							
0.70	78.1	78.1	76.2																																																							
0.77	78.3	78.4	77.0																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.10</td><td>53.8</td><td>48.8</td><td>39.6</td></tr> <tr><td>0.20</td><td>65.8</td><td>62.5</td><td>54.9</td></tr> <tr><td>0.30</td><td>72.0</td><td>69.2</td><td>62.9</td></tr> <tr><td>0.40</td><td>75.1</td><td>73.4</td><td>68.1</td></tr> <tr><td>0.50</td><td>77.0</td><td>76.0</td><td>71.8</td></tr> <tr><td>0.60</td><td>77.6</td><td>77.3</td><td>74.3</td></tr> <tr><td>0.70</td><td>78.1</td><td>78.1</td><td>76.2</td></tr> <tr><td>0.77</td><td>78.3</td><td>78.4</td><td>77.0</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.10	53.8	48.8	39.6	0.20	65.8	62.5	54.9	0.30	72.0	69.2	62.9	0.40	75.1	73.4	68.1	0.50	77.0	76.0	71.8	0.60	77.6	77.3	74.3	0.70	78.1	78.1	76.2	0.77	78.3	78.4	77.0	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.10	53.8	48.8	39.6																																																							
0.20	65.8	62.5	54.9																																																							
0.30	72.0	69.2	62.9																																																							
0.40	75.1	73.4	68.1																																																							
0.50	77.0	76.0	71.8																																																							
0.60	77.6	77.3	74.3																																																							
0.70	78.1	78.1	76.2																																																							
0.77	78.3	78.4	77.0																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA15S-24		Temperature Testing Circuitry 25°C Figure A																															
Item	Hold-Up Time 出力保持時間																																	
Object	+24.0V 0.7A																																	
1. Graph																																		
			2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>40</td> <td>12</td> </tr> <tr> <td>80</td> <td>46</td> <td>14</td> </tr> <tr> <td>85</td> <td>52</td> <td>18</td> </tr> <tr> <td>90</td> <td>59</td> <td>21</td> </tr> <tr> <td>100</td> <td>73</td> <td>28</td> </tr> <tr> <td>110</td> <td>89</td> <td>36</td> </tr> <tr> <td>120</td> <td>105</td> <td>45</td> </tr> <tr> <td>132</td> <td>127</td> <td>56</td> </tr> <tr> <td>140</td> <td>142</td> <td>64</td> </tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	40	12	80	46	14	85	52	18	90	59	21	100	73	28	110	89	36	120	105	45	132	127	56	140	142	64
Input Voltage [V]	Hold-Up Time [mS]																																	
	Load 50%	Load 100%																																
75	40	12																																
80	46	14																																
85	52	18																																
90	59	21																																
100	73	28																																
110	89	36																																
120	105	45																																
132	127	56																																
140	142	64																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																		


COSEL

Model	LCA15S-24	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障	Testing Circuitry	Figure A																																																			
Object	+24.0V 0.7A																																																					
1. Graph		2. Values																																																				
<p>Graph showing Instantaneous Compensation Time [mS] vs Load Current [A]. The Y-axis is logarithmic from 1 to 1000. The X-axis is linear from 0 to 1.0 A. Three curves are shown for Input Volt. 85 V (triangles), Input Volt. 100 V (squares), and Input Volt. 132 V (circles). A slanted line indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.10</td><td>111</td><td>152</td><td>250</td></tr> <tr><td>0.20</td><td>80</td><td>111</td><td>189</td></tr> <tr><td>0.30</td><td>58</td><td>82</td><td>147</td></tr> <tr><td>0.40</td><td>39</td><td>56</td><td>106</td></tr> <tr><td>0.50</td><td>28</td><td>43</td><td>82</td></tr> <tr><td>0.60</td><td>20</td><td>31</td><td>67</td></tr> <tr><td>0.70</td><td>13</td><td>22</td><td>54</td></tr> <tr><td>0.77</td><td>5</td><td>20</td><td>47</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.10	111	152	250	0.20	80	111	189	0.30	58	82	147	0.40	39	56	106	0.50	28	43	82	0.60	20	31	67	0.70	13	22	54	0.77	5	20	47	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	—	—	—																																																			
0.10	111	152	250																																																			
0.20	80	111	189																																																			
0.30	58	82	147																																																			
0.40	39	56	106																																																			
0.50	28	43	82																																																			
0.60	20	31	67																																																			
0.70	13	22	54																																																			
0.77	5	20	47																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																						

Model	LCA15S-24
Item	Load Regulation 靜的負荷變動
Object	+24.0V 0.7A

1. Graph

—△— Input Volt. 85 V
 -□- Input Volt. 100 V
 -○- Input Volt. 132 V



Note: Slanted line shows the range of the rated load current.



(注)斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	23.937	23.935	23.935
0.10	23.931	23.925	23.911
0.20	23.929	23.923	23.909
0.30	23.928	23.923	23.909
0.40	23.927	23.922	23.909
0.50	23.927	23.922	23.909
0.60	23.926	23.921	23.909
0.70	23.926	23.921	23.909
0.77	23.925	23.921	23.909
—	—	—	—

COSEL

Model	LCA15S-24																																							
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)	Temperature Testing Circuitry 25°C Figure A																																						
Object	+24.0V 0.7A																																							
1. Graph																																								
Ripple Voltage [mV] Input Volt. 85V Input Volt. 132V		2. Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>5</td></tr> <tr><td>0.10</td><td>10</td><td>5</td></tr> <tr><td>0.20</td><td>10</td><td>5</td></tr> <tr><td>0.30</td><td>10</td><td>5</td></tr> <tr><td>0.35</td><td>15</td><td>10</td></tr> <tr><td>0.40</td><td>15</td><td>10</td></tr> <tr><td>0.50</td><td>15</td><td>15</td></tr> <tr><td>0.60</td><td>20</td><td>15</td></tr> <tr><td>0.70</td><td>25</td><td>15</td></tr> <tr><td>0.77</td><td>30</td><td>15</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	10	5	0.10	10	5	0.20	10	5	0.30	10	5	0.35	15	10	0.40	15	10	0.50	15	15	0.60	20	15	0.70	25	15	0.77	30	15	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																						
0.00	10	5																																						
0.10	10	5																																						
0.20	10	5																																						
0.30	10	5																																						
0.35	15	10																																						
0.40	15	10																																						
0.50	15	15																																						
0.60	20	15																																						
0.70	25	15																																						
0.77	30	15																																						
—	—	—																																						
Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.																																								
リップル電圧は、下図 p – p 値で示される。 (注)斜線は定格負荷電流範囲を示す。																																								
T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期																																								
																																								
Fig. Complex Ripple Wave Form 図 リップル波形詳細図																																								

COSEL

Model	LCA15S-24	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	+24.0V 0.7A																																								
1. Graph		2. Values																																							
<p>[mV]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>10</td></tr> <tr><td>0.10</td><td>15</td><td>10</td></tr> <tr><td>0.20</td><td>15</td><td>10</td></tr> <tr><td>0.30</td><td>15</td><td>15</td></tr> <tr><td>0.35</td><td>20</td><td>15</td></tr> <tr><td>0.40</td><td>20</td><td>15</td></tr> <tr><td>0.50</td><td>20</td><td>20</td></tr> <tr><td>0.60</td><td>25</td><td>20</td></tr> <tr><td>0.70</td><td>30</td><td>20</td></tr> <tr><td>0.77</td><td>35</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.00	15	10	0.10	15	10	0.20	15	10	0.30	15	15	0.35	20	15	0.40	20	15	0.50	20	20	0.60	25	20	0.70	30	20	0.77	35	20	—	—	—
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple-Noise [mV]	Ripple-Noise [mV]																																							
0.00	15	10																																							
0.10	15	10																																							
0.20	15	10																																							
0.30	15	15																																							
0.35	20	15																																							
0.40	20	15																																							
0.50	20	20																																							
0.60	25	20																																							
0.70	30	20																																							
0.77	35	20																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																									
<p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL


Model	LCA15S-24																																																									
Item	Overcurrent Protection 過電流保護																																																									
Object	+24.0V 0.7A																																																									
1. Graph	<p>Graph showing Output Voltage [V] vs Load Current [A]. Three curves are shown for Input Voltages 85V, 100V, and 132V. A slanted line indicates the rated load current range.</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>24.00</td><td>0.90</td><td>0.97</td><td>0.95</td></tr> <tr><td>22.80</td><td>0.91</td><td>0.97</td><td>0.95</td></tr> <tr><td>21.60</td><td>0.92</td><td>0.98</td><td>0.95</td></tr> <tr><td>19.20</td><td>0.93</td><td>0.98</td><td>0.95</td></tr> <tr><td>16.80</td><td>0.93</td><td>0.97</td><td>0.94</td></tr> <tr><td>14.40</td><td>0.93</td><td>0.95</td><td>0.92</td></tr> <tr><td>12.00</td><td>0.91</td><td>0.93</td><td>0.90</td></tr> <tr><td>9.60</td><td>0.88</td><td>0.89</td><td>0.87</td></tr> <tr><td>7.20</td><td>0.83</td><td>0.84</td><td>0.83</td></tr> <tr><td>4.80</td><td>0.76</td><td>0.76</td><td>0.77</td></tr> <tr><td>2.40</td><td>0.64</td><td>0.65</td><td>0.67</td></tr> <tr><td>0.00</td><td>0.75</td><td>0.86</td><td>0.99</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	24.00	0.90	0.97	0.95	22.80	0.91	0.97	0.95	21.60	0.92	0.98	0.95	19.20	0.93	0.98	0.95	16.80	0.93	0.97	0.94	14.40	0.93	0.95	0.92	12.00	0.91	0.93	0.90	9.60	0.88	0.89	0.87	7.20	0.83	0.84	0.83	4.80	0.76	0.76	0.77	2.40	0.64	0.65	0.67	0.00	0.75	0.86	0.99
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
24.00	0.90	0.97	0.95																																																							
22.80	0.91	0.97	0.95																																																							
21.60	0.92	0.98	0.95																																																							
19.20	0.93	0.98	0.95																																																							
16.80	0.93	0.97	0.94																																																							
14.40	0.93	0.95	0.92																																																							
12.00	0.91	0.93	0.90																																																							
9.60	0.88	0.89	0.87																																																							
7.20	0.83	0.84	0.83																																																							
4.80	0.76	0.76	0.77																																																							
2.40	0.64	0.65	0.67																																																							
0.00	0.75	0.86	0.99																																																							

Note: Slanted line shows the range of the rated load current.


(注)斜線は定格負荷電流範囲を示す。

COSSEL

Model	LCA15S-24	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current 突入電流		
Object	—		



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current
 ① 9.02 [A]
 ② 1.42 [A]



COSEL

Model	LCA15S-24	Temperature	25°C
Item	Dynamic Load Response 動的負荷変動	Testing Circuitry	Figure A
Object	+ 24.0 V 0.7A		



Input Volt. 100 V

Cycle 1000 mS





Load 0% ↔

Load 100 %



Load 0% ↔

Load 50 %



200 mV/div

10 mS/div

COSEL


Model LCA15S-24

Item Rise and Fall Time 立上り、立下り時間

Object +24.0V 0.7A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		4.8	11.3	16.0	42.6	51.3	
100 %		4.8	17.5	22.3	16.2	38.2	



COSEL


Model	LCA15S-24																																																				
Item	Ambient Temperature Drift 周囲温度変動																																																				
Object	+24.0V 0.7A																																																				
1. Graph	Input Volt. 85V Input Volt. 100V Input Volt. 132V	2. Values																																																			
<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>23.987</td><td>23.983</td><td>23.970</td></tr> <tr><td>-10</td><td>23.979</td><td>23.974</td><td>23.962</td></tr> <tr><td>0</td><td>23.967</td><td>23.963</td><td>23.950</td></tr> <tr><td>10</td><td>23.954</td><td>23.949</td><td>23.937</td></tr> <tr><td>20</td><td>23.938</td><td>23.934</td><td>23.922</td></tr> <tr><td>25</td><td>23.929</td><td>23.925</td><td>23.913</td></tr> <tr><td>30</td><td>23.923</td><td>23.918</td><td>23.906</td></tr> <tr><td>40</td><td>23.902</td><td>23.897</td><td>23.885</td></tr> <tr><td>50</td><td>23.881</td><td>23.876</td><td>23.864</td></tr> <tr><td>60</td><td>23.860</td><td>23.856</td><td>23.844</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	23.987	23.983	23.970	-10	23.979	23.974	23.962	0	23.967	23.963	23.950	10	23.954	23.949	23.937	20	23.938	23.934	23.922	25	23.929	23.925	23.913	30	23.923	23.918	23.906	40	23.902	23.897	23.885	50	23.881	23.876	23.864	60	23.860	23.856	23.844	—	—	—	—
Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																		
-20	23.987	23.983	23.970																																																		
-10	23.979	23.974	23.962																																																		
0	23.967	23.963	23.950																																																		
10	23.954	23.949	23.937																																																		
20	23.938	23.934	23.922																																																		
25	23.929	23.925	23.913																																																		
30	23.923	23.918	23.906																																																		
40	23.902	23.897	23.885																																																		
50	23.881	23.876	23.864																																																		
60	23.860	23.856	23.844																																																		
—	—	—	—																																																		

(注) 斜線は定格周囲温度範囲を示す。

COSCEL

Model	LCA15S-24
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+24.0V 0.7A

Testing Circuitry Figure A



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	38	67
-10	38	66
0	38	66
10	38	65
20	38	65
25	37	65
30	37	65
40	37	65
50	37	64
60	37	64
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSSEL

Model LCA15S-24

Item Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)


Object +24.0V 0.7A

1. Graph

-----□----- Load 50%

-----△----- Load 100%

[mV]



Input Volt. 100 V

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	35	90
-10	20	70
0	20	40
10	15	30
20	15	20
25	10	20
30	10	20
40	10	20
50	10	15
60	10	15
—	—	—

COSEL

Model	LCA15S-24	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift 経時ドリフト																							
Object	+24.0V 0.7A																							
1. Graph		2. Values																						
<p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>23.942</td></tr> <tr><td>0.5</td><td>23.927</td></tr> <tr><td>1.0</td><td>23.927</td></tr> <tr><td>2.0</td><td>23.927</td></tr> <tr><td>3.0</td><td>23.927</td></tr> <tr><td>4.0</td><td>23.926</td></tr> <tr><td>5.0</td><td>23.926</td></tr> <tr><td>6.0</td><td>23.926</td></tr> <tr><td>7.0</td><td>23.926</td></tr> <tr><td>8.0</td><td>23.927</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	23.942	0.5	23.927	1.0	23.927	2.0	23.927	3.0	23.927	4.0	23.926	5.0	23.926	6.0	23.926	7.0	23.926	8.0	23.927
Time since start [H]	Output Voltage [V]																							
0.0	23.942																							
0.5	23.927																							
1.0	23.927																							
2.0	23.927																							
3.0	23.927																							
4.0	23.926																							
5.0	23.926																							
6.0	23.926																							
7.0	23.926																							
8.0	23.927																							



Model	LCA15S-24	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+24.0V 0.7A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~0.7 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~0.7 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	85	0.0	23.988	±63	±0.3
Minimum Voltage	50	132	0.7	23.863		



Model	LCA15S-24		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+24.0V 0.7A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	23.91	Input Volt.:100V, Load Current:0.7A
Line Regulation [mV]	20	Input Volt.:85~132V, Load Current:0.7A
Load Regulation [mV]	28	Input Volt.:100V, Load Current:0~0.7A



Model	LCA15S-24	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.08	0.08	0.11
(B) IEC60950	0.08	0.09	0.11

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—

COSEL

Model	LCA15S-24	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure C
Object	+24.0V 0.7A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LCA15S-24	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	<hr/>		

1. Graph

Remarks


Input Volt. 100 V (VCCI Class B)

120 V (FCC Class B)


Load 100 %

規格1：[VCCI] Class B(平均値)

規格2：[VCCI] Class B(QP)



規格2：[FCC Part15] Class B






Figure A


Data Acquisition/Control Unit
データ集録システム

Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E