



TEST DATA OF LCA15S-5 (100V INPUT)

Regulated DC Power Supply

Date : June 17. 1999

Approved by : I. Yamaguchi
Design Manager

Prepared by : I. Yamaguchi
Design Engineer

コーワセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Inrush Current	12
突入電流	
13. Dynamic Load Response	13
動的負荷変動	
14. Rise and Fall Time	14
立ち上り、立下がり時間	
15. Ambient Temperature Drift	15
周囲温度変動	
16. Minimum Input Voltage for Regulated Output Voltage .	16
最低レギュレーション電圧	
17. Ripple Voltage (by Ambient Temperature)	17
リップル電圧 (周囲温度特性)	
18. Time Lapse Drift	18
経時ドリフト	
19. Output Voltage Accuracy	19
定電圧精度	
20. Condensation	20
結露特性	
21. Leakage Current	21
漏洩電流	
22. Line Noise Tolerance	22
入力雑音耐量	
23. Conducted Emission	23
雑音端子電圧	
24. Figure of Testing Circuitry	24
測定回路図	


(Final Page 25)

COSEL

Model	LCA15S-5		Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+5.0V 3A																																		
1. Graph																																			
			2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>5.096</td><td>5.089</td></tr> <tr><td>80</td><td>5.096</td><td>5.089</td></tr> <tr><td>85</td><td>5.096</td><td>5.089</td></tr> <tr><td>90</td><td>5.096</td><td>5.089</td></tr> <tr><td>100</td><td>5.096</td><td>5.090</td></tr> <tr><td>110</td><td>5.096</td><td>5.090</td></tr> <tr><td>120</td><td>5.096</td><td>5.090</td></tr> <tr><td>132</td><td>5.096</td><td>5.090</td></tr> <tr><td>140</td><td>5.096</td><td>5.090</td></tr> </tbody> </table>				Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	5.096	5.089	80	5.096	5.089	85	5.096	5.089	90	5.096	5.089	100	5.096	5.090	110	5.096	5.090	120	5.096	5.090	132	5.096	5.090	140	5.096	5.090
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	5.096	5.089																																	
80	5.096	5.089																																	
85	5.096	5.089																																	
90	5.096	5.089																																	
100	5.096	5.090																																	
110	5.096	5.090																																	
120	5.096	5.090																																	
132	5.096	5.090																																	
140	5.096	5.090																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	LCA15S-5
Item	Input Current (by Load Current) 入力電流（負荷特性）
Output	_____



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	0.032	0.029	0.026
0.6	0.110	0.104	0.097
1.2	0.178	0.162	0.144
1.8	0.248	0.222	0.190
2.4	0.321	0.284	0.237
3.0	0.395	0.347	0.285
3.3	0.433	0.380	0.310
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA15S-5																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	_____																																																									
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> △ Input Volt. 85V □ Input Volt. 100V ○ Input Volt. 132V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.13</td><td>1.15</td><td>1.24</td></tr> <tr><td>0.6</td><td>4.93</td><td>5.28</td><td>6.11</td></tr> <tr><td>1.2</td><td>8.65</td><td>8.90</td><td>9.70</td></tr> <tr><td>1.8</td><td>12.64</td><td>12.73</td><td>13.30</td></tr> <tr><td>2.4</td><td>16.83</td><td>16.77</td><td>17.08</td></tr> <tr><td>3.0</td><td>21.21</td><td>20.97</td><td>21.02</td></tr> <tr><td>3.3</td><td>23.54</td><td>23.19</td><td>23.11</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	1.13	1.15	1.24	0.6	4.93	5.28	6.11	1.2	8.65	8.90	9.70	1.8	12.64	12.73	13.30	2.4	16.83	16.77	17.08	3.0	21.21	20.97	21.02	3.3	23.54	23.19	23.11	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	1.13	1.15	1.24																																																							
0.6	4.93	5.28	6.11																																																							
1.2	8.65	8.90	9.70																																																							
1.8	12.64	12.73	13.30																																																							
2.4	16.83	16.77	17.08																																																							
3.0	21.21	20.97	21.02																																																							
3.3	23.54	23.19	23.11																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.13</td><td>1.15</td><td>1.24</td></tr> <tr><td>0.6</td><td>4.93</td><td>5.28</td><td>6.11</td></tr> <tr><td>1.2</td><td>8.65</td><td>8.90</td><td>9.70</td></tr> <tr><td>1.8</td><td>12.64</td><td>12.73</td><td>13.30</td></tr> <tr><td>2.4</td><td>16.83</td><td>16.77</td><td>17.08</td></tr> <tr><td>3.0</td><td>21.21</td><td>20.97</td><td>21.02</td></tr> <tr><td>3.3</td><td>23.54</td><td>23.19</td><td>23.11</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	1.13	1.15	1.24	0.6	4.93	5.28	6.11	1.2	8.65	8.90	9.70	1.8	12.64	12.73	13.30	2.4	16.83	16.77	17.08	3.0	21.21	20.97	21.02	3.3	23.54	23.19	23.11	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	1.13	1.15	1.24																																																							
0.6	4.93	5.28	6.11																																																							
1.2	8.65	8.90	9.70																																																							
1.8	12.64	12.73	13.30																																																							
2.4	16.83	16.77	17.08																																																							
3.0	21.21	20.97	21.02																																																							
3.3	23.54	23.19	23.11																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA15S-5																																	
Item	Efficiency 効率	Temperature 25°C Testing Circuitry Figure A																																
Object	_____																																	
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Load 50% (Squares)</p> <p>Load 100% (Triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>72.4</td><td>70.9</td></tr> <tr><td>80</td><td>72.6</td><td>71.6</td></tr> <tr><td>85</td><td>72.4</td><td>72.2</td></tr> <tr><td>90</td><td>72.0</td><td>72.6</td></tr> <tr><td>100</td><td>71.3</td><td>73.2</td></tr> <tr><td>110</td><td>70.2</td><td>73.2</td></tr> <tr><td>120</td><td>69.0</td><td>73.1</td></tr> <tr><td>132</td><td>67.1</td><td>73.0</td></tr> <tr><td>140</td><td>65.8</td><td>72.6</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	72.4	70.9	80	72.6	71.6	85	72.4	72.2	90	72.0	72.6	100	71.3	73.2	110	70.2	73.2	120	69.0	73.1	132	67.1	73.0	140	65.8	72.6
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	72.4	70.9																																
80	72.6	71.6																																
85	72.4	72.2																																
90	72.0	72.6																																
100	71.3	73.2																																
110	70.2	73.2																																
120	69.0	73.1																																
132	67.1	73.0																																
140	65.8	72.6																																

COSEL

Model	LCA15S-5																																																					
Item	Efficiency (by Load Current) 効率(負荷電流特性)	Temperature 25°C	Testing Circuitry Figure A																																																			
Output	——																																																					
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85V (△) Input Volt. 100V (□) Input Volt. 132V (○) <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [85V] [%]</th> <th>Efficiency [100V] [%]</th> <th>Efficiency [132V] [%]</th> </tr> </thead> <tbody> <tr><td>0.6</td><td>61.5</td><td>57.4</td><td>49.7</td></tr> <tr><td>1.2</td><td>70.8</td><td>69.0</td><td>63.1</td></tr> <tr><td>1.8</td><td>72.8</td><td>72.3</td><td>69.2</td></tr> <tr><td>2.4</td><td>72.9</td><td>73.0</td><td>71.8</td></tr> <tr><td>3.0</td><td>72.0</td><td>72.9</td><td>72.7</td></tr> <tr><td>3.3</td><td>71.5</td><td>72.6</td><td>72.8</td></tr> </tbody> </table>			Load Current [A]	Efficiency [85V] [%]	Efficiency [100V] [%]	Efficiency [132V] [%]	0.6	61.5	57.4	49.7	1.2	70.8	69.0	63.1	1.8	72.8	72.3	69.2	2.4	72.9	73.0	71.8	3.0	72.0	72.9	72.7	3.3	71.5	72.6	72.8																							
Load Current [A]	Efficiency [85V] [%]	Efficiency [100V] [%]	Efficiency [132V] [%]																																																			
0.6	61.5	57.4	49.7																																																			
1.2	70.8	69.0	63.1																																																			
1.8	72.8	72.3	69.2																																																			
2.4	72.9	73.0	71.8																																																			
3.0	72.0	72.9	72.7																																																			
3.3	71.5	72.6	72.8																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.6</td><td>61.5</td><td>57.4</td><td>49.7</td></tr> <tr><td>1.2</td><td>70.8</td><td>69.0</td><td>63.1</td></tr> <tr><td>1.8</td><td>72.8</td><td>72.3</td><td>69.2</td></tr> <tr><td>2.4</td><td>72.9</td><td>73.0</td><td>71.8</td></tr> <tr><td>3.0</td><td>72.0</td><td>72.9</td><td>72.7</td></tr> <tr><td>3.3</td><td>71.5</td><td>72.6</td><td>72.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.6	61.5	57.4	49.7	1.2	70.8	69.0	63.1	1.8	72.8	72.3	69.2	2.4	72.9	73.0	71.8	3.0	72.0	72.9	72.7	3.3	71.5	72.6	72.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.6	61.5	57.4	49.7																																																			
1.2	70.8	69.0	63.1																																																			
1.8	72.8	72.3	69.2																																																			
2.4	72.9	73.0	71.8																																																			
3.0	72.0	72.9	72.7																																																			
3.3	71.5	72.6	72.8																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA15S-5		Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+5.0V3A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>38</td><td>12</td></tr> <tr><td>80</td><td>44</td><td>15</td></tr> <tr><td>85</td><td>51</td><td>18</td></tr> <tr><td>90</td><td>58</td><td>22</td></tr> <tr><td>100</td><td>73</td><td>29</td></tr> <tr><td>110</td><td>89</td><td>38</td></tr> <tr><td>120</td><td>107</td><td>47</td></tr> <tr><td>132</td><td>131</td><td>59</td></tr> <tr><td>140</td><td>148</td><td>68</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	38	12	80	44	15	85	51	18	90	58	22	100	73	29	110	89	38	120	107	47	132	131	59	140	148	68
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	38	12																																	
80	44	15																																	
85	51	18																																	
90	58	22																																	
100	73	29																																	
110	89	38																																	
120	107	47																																	
132	131	59																																	
140	148	68																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																			



COSEL

Model	LCA15S-5																																																					
Item	Instantaneous Interruption Compensation 瞬時停電保障	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+5.0V 3A																																																					
1. Graph																																																						
<p>Legend:</p> <ul style="list-style-type: none"> △ Input Volt. 85 V □ Input Volt. 100 V ○ Input Volt. 132 V 																																																						
<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.6</td><td>123</td><td>169</td><td>285</td></tr> <tr><td>1.2</td><td>62</td><td>89</td><td>160</td></tr> <tr><td>1.8</td><td>35</td><td>53</td><td>102</td></tr> <tr><td>2.4</td><td>22</td><td>31</td><td>73</td></tr> <tr><td>3.0</td><td>12</td><td>22</td><td>51</td></tr> <tr><td>3.3</td><td>5</td><td>14</td><td>43</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	—	—	—	0.6	123	169	285	1.2	62	89	160	1.8	35	53	102	2.4	22	31	73	3.0	12	22	51	3.3	5	14	43	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	—	—	—																																																			
0.6	123	169	285																																																			
1.2	62	89	160																																																			
1.8	35	53	102																																																			
2.4	22	31	73																																																			
3.0	12	22	51																																																			
3.3	5	14	43																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																						

COSEL

Model	LCA15S-5	Temperature Testing Circuitry	25°C Figure A																																															
Item	Load Regulation 静的負荷変動																																																	
Object	+5.0V 3A																																																	
1. Graph		<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																
<p>—△— Input Volt. 85 V</p> <p>-□- Input Volt. 100 V</p> <p>-○- Input Volt. 132 V</p>			2. Values																																															
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.101</td><td>5.100</td><td>5.093</td></tr> <tr><td>0.6</td><td>5.099</td><td>5.099</td><td>5.099</td></tr> <tr><td>1.2</td><td>5.097</td><td>5.097</td><td>5.097</td></tr> <tr><td>1.8</td><td>5.094</td><td>5.095</td><td>5.095</td></tr> <tr><td>2.4</td><td>5.092</td><td>5.092</td><td>5.092</td></tr> <tr><td>3.0</td><td>5.089</td><td>5.090</td><td>5.090</td></tr> <tr><td>3.3</td><td>5.088</td><td>5.088</td><td>5.088</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	5.101	5.100	5.093	0.6	5.099	5.099	5.099	1.2	5.097	5.097	5.097	1.8	5.094	5.095	5.095	2.4	5.092	5.092	5.092	3.0	5.089	5.090	5.090	3.3	5.088	5.088	5.088	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.0	5.101	5.100	5.093																																															
0.6	5.099	5.099	5.099																																															
1.2	5.097	5.097	5.097																																															
1.8	5.094	5.095	5.095																																															
2.4	5.092	5.092	5.092																																															
3.0	5.089	5.090	5.090																																															
3.3	5.088	5.088	5.088																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																		

COSEL

Model	LCA15S-5																																									
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)	Temperature Testing Circuitry	25°C Figure A																																							
Object	+5.0V3A																																									
1. Graph	-----□----- Input Volt. 85V [mV] -----△----- Input Volt. 132V																																									
																																										
2. Values																																										
	<table border="1"><thead><tr><th rowspan="2">Load Current [A]</th><th>Input Volt. 85 [V]</th><th>Input Volt. 132 [V]</th></tr><tr><th>Ripple Output Volt. [mV]</th><th>Ripple Output Volt. [mV]</th></tr></thead><tbody><tr><td>0.00</td><td>10</td><td>5</td></tr><tr><td>0.40</td><td>10</td><td>5</td></tr><tr><td>0.80</td><td>10</td><td>10</td></tr><tr><td>1.20</td><td>10</td><td>10</td></tr><tr><td>1.60</td><td>15</td><td>10</td></tr><tr><td>2.00</td><td>15</td><td>15</td></tr><tr><td>2.40</td><td>15</td><td>15</td></tr><tr><td>2.80</td><td>25</td><td>15</td></tr><tr><td>3.00</td><td>30</td><td>20</td></tr><tr><td>3.30</td><td>40</td><td>25</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></tbody></table>			Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	10	5	0.40	10	5	0.80	10	10	1.20	10	10	1.60	15	10	2.00	15	15	2.40	15	15	2.80	25	15	3.00	30	20	3.30	40	25	—	—	—	
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																								
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																								
0.00	10	5																																								
0.40	10	5																																								
0.80	10	10																																								
1.20	10	10																																								
1.60	15	10																																								
2.00	15	15																																								
2.40	15	15																																								
2.80	25	15																																								
3.00	30	20																																								
3.30	40	25																																								
—	—	—																																								
Ripple Voltage is shown as p-p in the figure below.																																										
Note: Slanted line shows the range of the rated load current.																																										
リップル電圧は、下図 p – p 値で示される。 (注)斜線は定格負荷電流範囲を示す。																																										
T1: Due to AC Input Line T2: Due to Switching																																										
入力商用周期 スイッチング周期																																										
																																										
Fig. Complex Ripple Wave Form 図 リップル波形詳細図																																										

COSEL


Model LCA15S-5

Item Ripple-Noise リップルノイズ

Object +5.0V3A

1. Graph

-----□----- Input Volt. 85V
[mV]
-----△----- Input Volt. 132V



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.00	15	10
0.40	15	10
0.80	15	15
1.20	15	15
1.60	20	15
2.00	20	15
2.40	20	15
2.80	30	15
3.00	40	25
3.30	50	30
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期





Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL

Model	LCA15S-5
Item	Overcurrent Protection 過電流保護
Object	+5.0V 3A



Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。


Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
5.00	3.81	4.18	4.09
4.75	3.83	4.16	4.07
4.50	3.84	4.15	4.04
4.00	3.83	4.10	3.98
3.50	3.80	4.03	3.90
3.00	3.72	3.92	3.79
2.50	3.62	3.79	3.68
2.00	3.48	3.62	3.50
1.50	3.26	3.37	3.28
1.00	2.98	3.08	3.04
0.50	2.59	2.65	2.69
0.00	2.20	2.25	2.32

COSEL

Model	LCA15S-5	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current 突入電流		
Object	—		



Input Voltage 100 V


Frequency 60 Hz

Load 100 %


Inrush Current

① 9.18 [A]

② 1.18 [A]




COSEL



COSEL


Model	LCA15S-5	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+5.0V3A		


1. Graph



2. Values

Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		3.5	4.8	8.3	51.5	25.6	
100 %		3.8	6.0	9.8	19.3	23.0	



COSSEL

Testing Circuitry Figure A

2. Values

Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	5.087	5.088	5.089
-10	5.089	5.090	5.090
0	5.090	5.091	5.091
10	5.090	5.091	5.091
20	5.090	5.090	5.090
25	5.089	5.089	5.090
30	5.089	5.089	5.089
40	5.087	5.088	5.088
50	5.085	5.086	5.086
60	5.083	5.083	5.083
—	—	—	—

COSEL

Model	LCA15S-5			
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧			
Object	+5.0V3A			
1. Graph				
[V]				
Input Voltage [V]	Load 50% Load 100%			
Ambient Temperature [°C]				
Note: Slanted line shows the range of the rated ambient temperature.				
(注)斜線は定格周囲温度範囲を示す。				
Testing Circuitry Figure A				
2. Values				
Ambient Temperature [°C]	Input Voltage [V]			
	Load 50%	Load 100%		
-20	35	65		
-10	34	64		
0	34	64		
10	34	63		
20	34	63		
25	34	63		
30	34	63		
40	34	63		
50	34	63		
60	34	63		
—	—	—		

COSEL

Model LCA15S-5


Item Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)

Object +5.0V3A

1. Graph

-----□----- Load 50%

-----△----- Load 100%



Input Volt. 100 V

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	45	120
-10	25	80
0	15	45
10	15	40
20	15	30
25	15	25
30	10	20
40	10	20
50	10	20
60	10	20
—	—	—

COSEL

Model	LCA15S-5	Temperature	25°C																																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																																						
Object	+5.0V3A																																								
1. Graph			2. Values																																						
<p>[V]</p> <table border="1"> <tr> <td>Output Voltage [V]</td> <td>5.160</td> </tr> <tr> <td></td> <td>5.140</td> </tr> <tr> <td></td> <td>5.120</td> </tr> <tr> <td></td> <td>5.100</td> </tr> <tr> <td></td> <td>5.080</td> </tr> <tr> <td></td> <td>5.060</td> </tr> <tr> <td></td> <td>5.040</td> </tr> <tr> <td></td> <td>0</td> </tr> </table> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			Output Voltage [V]	5.160		5.140		5.120		5.100		5.080		5.060		5.040		0	<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.091</td></tr> <tr><td>0.5</td><td>5.090</td></tr> <tr><td>1.0</td><td>5.090</td></tr> <tr><td>2.0</td><td>5.090</td></tr> <tr><td>3.0</td><td>5.090</td></tr> <tr><td>4.0</td><td>5.090</td></tr> <tr><td>5.0</td><td>5.090</td></tr> <tr><td>6.0</td><td>5.090</td></tr> <tr><td>7.0</td><td>5.090</td></tr> <tr><td>8.0</td><td>5.090</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.091	0.5	5.090	1.0	5.090	2.0	5.090	3.0	5.090	4.0	5.090	5.0	5.090	6.0	5.090	7.0	5.090	8.0	5.090
Output Voltage [V]	5.160																																								
	5.140																																								
	5.120																																								
	5.100																																								
	5.080																																								
	5.060																																								
	5.040																																								
	0																																								
Time since start [H]	Output Voltage [V]																																								
0.0	5.091																																								
0.5	5.090																																								
1.0	5.090																																								
2.0	5.090																																								
3.0	5.090																																								
4.0	5.090																																								
5.0	5.090																																								
6.0	5.090																																								
7.0	5.090																																								
8.0	5.090																																								

COSEL

Model	LCA15S-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+5.0V3A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~3 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~3 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	85	0	5.102		
Minimum Voltage	50	132	3	5.085	±9	±0.2



Model	LCA15S-5	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+5.0V3A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.092	Input Volt.:100V, Load Current:3A
Line Regulation [mV]	7	Input Volt.:85~132V, Load Current:3A
Load Regulation [mV]	15	Input Volt.:100V, Load Current:0~3A



Model	LCA15S-5		
Item	Leakage Current 漏洩電流	Temperature	25°C
Object	<hr/>		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.08	0.08	0.11
(B) IEC60950	0.08	0.09	0.11

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	LCA15S-5	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+5.0V 3A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LCA15S-5	Temperature Testing Circuitry 25°C Figure D
Item	Conducted Emission 雜音端子電圧	
Object	_____	

1. Graph


Remarks

Input Volt. 100 V (VCCI Class B)
120 V (FCC Class B)


Load 100 %

規格 1: [VCCI] Class B(平均値)

規格 2: [VCCI] Class B(QP)



規格 2: [FCC Part15] Class B






Figure A


Data Acquisition/Control Unit
データ集録システム

Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E