



## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Input Power (by Load Current) . . . . .	2
3.Efficiency (by Input Voltage) . . . . .	3
4.Efficiency (by Load Current) . . . . .	4
5.Inrush Current . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	9
10.Ripple-Noise . . . . .	10
11.Ripple Voltage (by Ambient Temperature) . . . . .	11
12.Ambient Temperature Drift . . . . .	12
13.Output Voltage Accuracy . . . . .	13
14.Rise and Fall Time . . . . .	14
15.Hold-Up Time . . . . .	15
16.Instantaneous Interruption Compensation . . . . .	16
17.Minimum Input Voltage for Regulated Output Voltage . . . . .	17
18.Overcurrent Protection . . . . .	18
19.Figure of Testing Circuitry . . . . .	19

(Final Page 19)



Model		LCA30S-48		Temperature	25°C																																																			
Item		Input Current (by Load Current)		Testing Circuitry	Figure A																																																			
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 85V                  - - □ - - Input Volt. 100V                  - - ○ - - Input Volt. 132V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.102</td><td>0.114</td><td>0.116</td></tr> <tr><td>0.10</td><td>0.210</td><td>0.207</td><td>0.194</td></tr> <tr><td>0.20</td><td>0.314</td><td>0.295</td><td>0.263</td></tr> <tr><td>0.30</td><td>0.416</td><td>0.380</td><td>0.332</td></tr> <tr><td>0.40</td><td>0.520</td><td>0.468</td><td>0.401</td></tr> <tr><td>0.50</td><td>0.625</td><td>0.557</td><td>0.469</td></tr> <tr><td>0.60</td><td>0.729</td><td>0.647</td><td>0.540</td></tr> <tr><td>0.70</td><td>0.833</td><td>0.737</td><td>0.611</td></tr> <tr><td>0.77</td><td>0.906</td><td>0.801</td><td>0.662</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.102	0.114	0.116	0.10	0.210	0.207	0.194	0.20	0.314	0.295	0.263	0.30	0.416	0.380	0.332	0.40	0.520	0.468	0.401	0.50	0.625	0.557	0.469	0.60	0.729	0.647	0.540	0.70	0.833	0.737	0.611	0.77	0.906	0.801	0.662	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0.00	0.102	0.114	0.116																																																					
0.10	0.210	0.207	0.194																																																					
0.20	0.314	0.295	0.263																																																					
0.30	0.416	0.380	0.332																																																					
0.40	0.520	0.468	0.401																																																					
0.50	0.625	0.557	0.469																																																					
0.60	0.729	0.647	0.540																																																					
0.70	0.833	0.737	0.611																																																					
0.77	0.906	0.801	0.662																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		LCA30S-48		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 85V</p> <p>- - □ - - Input Volt. 100V</p> <p>- - ○ - - Input Volt. 132V</p>		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4.23</td><td>4.90</td><td>6.36</td></tr> <tr><td>0.10</td><td>9.60</td><td>10.20</td><td>11.94</td></tr> <tr><td>0.20</td><td>14.92</td><td>15.51</td><td>17.10</td></tr> <tr><td>0.30</td><td>20.30</td><td>20.73</td><td>22.33</td></tr> <tr><td>0.40</td><td>25.70</td><td>26.10</td><td>27.42</td></tr> <tr><td>0.50</td><td>31.20</td><td>31.50</td><td>32.60</td></tr> <tr><td>0.60</td><td>36.80</td><td>37.00</td><td>37.90</td></tr> <tr><td>0.70</td><td>42.50</td><td>42.50</td><td>43.20</td></tr> <tr><td>0.77</td><td>46.60</td><td>46.40</td><td>47.00</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	4.23	4.90	6.36	0.10	9.60	10.20	11.94	0.20	14.92	15.51	17.10	0.30	20.30	20.73	22.33	0.40	25.70	26.10	27.42	0.50	31.20	31.50	32.60	0.60	36.80	37.00	37.90	0.70	42.50	42.50	43.20	0.77	46.60	46.40	47.00	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0.00	4.23	4.90	6.36																																																					
0.10	9.60	10.20	11.94																																																					
0.20	14.92	15.51	17.10																																																					
0.30	20.30	20.73	22.33																																																					
0.40	25.70	26.10	27.42																																																					
0.50	31.20	31.50	32.60																																																					
0.60	36.80	37.00	37.90																																																					
0.70	42.50	42.50	43.20																																																					
0.77	46.60	46.40	47.00																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		LCA30S-48		Temperature 25°C																																	
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																	
Object																																					
1.Graph			2.Values																																		
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>74.0</td><td>78.7</td></tr> <tr><td>80</td><td>73.7</td><td>79.4</td></tr> <tr><td>85</td><td>73.8</td><td>79.6</td></tr> <tr><td>90</td><td>73.2</td><td>79.6</td></tr> <tr><td>100</td><td>72.1</td><td>79.6</td></tr> <tr><td>110</td><td>71.0</td><td>79.3</td></tr> <tr><td>120</td><td>69.6</td><td>78.8</td></tr> <tr><td>132</td><td>67.8</td><td>78.2</td></tr> <tr><td>140</td><td>66.7</td><td>77.6</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	74.0	78.7	80	73.7	79.4	85	73.8	79.6	90	73.2	79.6	100	72.1	79.6	110	71.0	79.3	120	69.6	78.8	132	67.8	78.2	140	66.7	77.6
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
75	74.0	78.7																																			
80	73.7	79.4																																			
85	73.8	79.6																																			
90	73.2	79.6																																			
100	72.1	79.6																																			
110	71.0	79.3																																			
120	69.6	78.8																																			
132	67.8	78.2																																			
140	66.7	77.6																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					



Model		LCA30S-48		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 85V - - □ - - Input Volt. 100V - - ○ - - Input Volt. 132V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.10</td><td>50.2</td><td>47.3</td><td>40.4</td></tr> <tr><td>0.20</td><td>64.7</td><td>62.2</td><td>56.3</td></tr> <tr><td>0.30</td><td>71.2</td><td>69.8</td><td>64.8</td></tr> <tr><td>0.40</td><td>75.0</td><td>73.9</td><td>70.3</td></tr> <tr><td>0.50</td><td>77.3</td><td>76.5</td><td>73.9</td></tr> <tr><td>0.60</td><td>78.6</td><td>78.2</td><td>76.3</td></tr> <tr><td>0.70</td><td>79.4</td><td>79.4</td><td>78.2</td></tr> <tr><td>0.77</td><td>79.7</td><td>80.0</td><td>79.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	-	-	-	0.10	50.2	47.3	40.4	0.20	64.7	62.2	56.3	0.30	71.2	69.8	64.8	0.40	75.0	73.9	70.3	0.50	77.3	76.5	73.9	0.60	78.6	78.2	76.3	0.70	79.4	79.4	78.2	0.77	79.7	80.0	79.0	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0.00	-	-	-																																																					
0.10	50.2	47.3	40.4																																																					
0.20	64.7	62.2	56.3																																																					
0.30	71.2	69.8	64.8																																																					
0.40	75.0	73.9	70.3																																																					
0.50	77.3	76.5	73.9																																																					
0.60	78.6	78.2	76.3																																																					
0.70	79.4	79.4	78.2																																																					
0.77	79.7	80.0	79.0																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		LCA30S-48	Temperature 25°C Testing Circuitry Figure A
Item		Inrush Current	
Object		_____	



Input Voltage 100 V  
 Frequency 60 Hz  
 Load 100 %

Primary inrush current 15.5 A  
 Secondary inrush current 2.3 A





Model		LCA30S-48	Temperature		25°C																																
Item		Line Regulation	Testing Circuitry		Figure A																																
Object		+48V0.7A	2.Values																																		
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>48.387</td><td>48.376</td></tr> <tr><td>80</td><td>48.380</td><td>48.376</td></tr> <tr><td>85</td><td>48.379</td><td>48.376</td></tr> <tr><td>90</td><td>48.378</td><td>48.375</td></tr> <tr><td>100</td><td>48.377</td><td>48.374</td></tr> <tr><td>110</td><td>48.376</td><td>48.374</td></tr> <tr><td>120</td><td>48.375</td><td>48.373</td></tr> <tr><td>132</td><td>48.374</td><td>48.371</td></tr> <tr><td>140</td><td>48.373</td><td>48.371</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	48.387	48.376	80	48.380	48.376	85	48.379	48.376	90	48.378	48.375	100	48.377	48.374	110	48.376	48.374	120	48.375	48.373	132	48.374	48.371	140	48.373	48.371
Input Voltage [V]	Output Voltage [V]																																				
	Load 50%	Load 100%																																			
75	48.387	48.376																																			
80	48.380	48.376																																			
85	48.379	48.376																																			
90	48.378	48.375																																			
100	48.377	48.374																																			
110	48.376	48.374																																			
120	48.375	48.373																																			
132	48.374	48.371																																			
140	48.373	48.371																																			






<p><b>Model</b> LCA30S-48</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																				
<p><b>Item</b> Load Regulation</p>																																																						
<p><b>Object</b> +48V0.7A</p>																																																						
<p>1. Graph</p> <p>                     —△— Input Volt. 85V                      - - - □ - - - Input Volt. 100V                      - · - ○ - · - - Input Volt. 132V                 </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>48.384</td><td>48.378</td><td>48.380</td></tr> <tr><td>0.10</td><td>48.380</td><td>48.375</td><td>48.371</td></tr> <tr><td>0.20</td><td>48.379</td><td>48.374</td><td>48.371</td></tr> <tr><td>0.30</td><td>48.378</td><td>48.374</td><td>48.371</td></tr> <tr><td>0.40</td><td>48.378</td><td>48.374</td><td>48.371</td></tr> <tr><td>0.50</td><td>48.377</td><td>48.374</td><td>48.371</td></tr> <tr><td>0.60</td><td>48.377</td><td>48.374</td><td>48.371</td></tr> <tr><td>0.70</td><td>48.377</td><td>48.374</td><td>48.371</td></tr> <tr><td>0.77</td><td>48.376</td><td>48.374</td><td>48.371</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	48.384	48.378	48.380	0.10	48.380	48.375	48.371	0.20	48.379	48.374	48.371	0.30	48.378	48.374	48.371	0.40	48.378	48.374	48.371	0.50	48.377	48.374	48.371	0.60	48.377	48.374	48.371	0.70	48.377	48.374	48.371	0.77	48.376	48.374	48.371	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	48.384	48.378	48.380																																																			
0.10	48.380	48.375	48.371																																																			
0.20	48.379	48.374	48.371																																																			
0.30	48.378	48.374	48.371																																																			
0.40	48.378	48.374	48.371																																																			
0.50	48.377	48.374	48.371																																																			
0.60	48.377	48.374	48.371																																																			
0.70	48.377	48.374	48.371																																																			
0.77	48.376	48.374	48.371																																																			
--	-	-	-																																																			
--	-	-	-																																																			





Model	LCA30S-48	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+48V0.7A		

Input Volt. 100 V  
 Cycle 1000 mS

Min. Load ( 0 A ) -- Load 100% ( 0.7 A )



Min. Load ( 0 A ) -- Load 50% ( 0.35 A )





<p>Model LCA30S-48</p> <p>Item Ripple Voltage (by Load Current)</p> <p>Object +48V0.7A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																						
<p>1.Graph</p> <p>—△— Input Volt. 85V - -○- - Input Volt. 132V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p> <p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.10</td><td>10</td><td>10</td></tr> <tr><td>0.20</td><td>10</td><td>10</td></tr> <tr><td>0.30</td><td>10</td><td>10</td></tr> <tr><td>0.40</td><td>10</td><td>10</td></tr> <tr><td>0.50</td><td>10</td><td>10</td></tr> <tr><td>0.60</td><td>10</td><td>10</td></tr> <tr><td>0.70</td><td>10</td><td>10</td></tr> <tr><td>0.77</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	5	5	0.10	10	10	0.20	10	10	0.30	10	10	0.40	10	10	0.50	10	10	0.60	10	10	0.70	10	10	0.77	10	10	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.00	5	5																																						
0.10	10	10																																						
0.20	10	10																																						
0.30	10	10																																						
0.40	10	10																																						
0.50	10	10																																						
0.60	10	10																																						
0.70	10	10																																						
0.77	10	10																																						
--	-	-																																						
--	-	-																																						
<p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p>																																								



Model		LCA30S-48		Temperature	25°C																																						
Item		Ripple-Noise		Testing Circuitry	Figure A																																						
Object		+48V0.7A																																									
1.Graph				2.Values																																							
<p>                     —△— Input Volt. 85V                      - - ○ - - Input Volt. 132V                 </p> <p>                     Measured by 20 MHz Oscilloscope.                      Ripple-Noise is shown as p-p in the figure below.                      Note: Slanted line shows the range of the rated load current.                 </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.10</td><td>20</td><td>20</td></tr> <tr><td>0.20</td><td>20</td><td>20</td></tr> <tr><td>0.30</td><td>20</td><td>20</td></tr> <tr><td>0.40</td><td>20</td><td>20</td></tr> <tr><td>0.50</td><td>20</td><td>20</td></tr> <tr><td>0.60</td><td>20</td><td>20</td></tr> <tr><td>0.70</td><td>20</td><td>20</td></tr> <tr><td>0.77</td><td>25</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	10	10	0.10	20	20	0.20	20	20	0.30	20	20	0.40	20	20	0.50	20	20	0.60	20	20	0.70	20	20	0.77	25	25	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																										
	Input Volt. 85 [V]	Input Volt. 132 [V]																																									
0.00	10	10																																									
0.10	20	20																																									
0.20	20	20																																									
0.30	20	20																																									
0.40	20	20																																									
0.50	20	20																																									
0.60	20	20																																									
0.70	20	20																																									
0.77	25	25																																									
--	-	-																																									
--	-	-																																									
<p>                     T1: Due to AC Input Line                      T2: Due to Switching                 </p>																																											
<p>Fig. Complex Ripple Wave Form</p>																																											



Model		LCA30S-48	Testing Circuitry Figure A																																						
Item		Ripple Voltage (by Ambient Temp.)																																							
Object		+48V0.7A																																							
1.Graph		<p>---□--- Load 50% —△— Load 100%</p> <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100V</p>	2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>40</td><td>50</td></tr> <tr><td>-10</td><td>30</td><td>40</td></tr> <tr><td>0</td><td>25</td><td>35</td></tr> <tr><td>10</td><td>20</td><td>25</td></tr> <tr><td>20</td><td>15</td><td>15</td></tr> <tr><td>25</td><td>10</td><td>10</td></tr> <tr><td>30</td><td>10</td><td>10</td></tr> <tr><td>40</td><td>10</td><td>10</td></tr> <tr><td>50</td><td>10</td><td>10</td></tr> <tr><td>60</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-20	40	50	-10	30	40	0	25	35	10	20	25	20	15	15	25	10	10	30	10	10	40	10	10	50	10	10	60	10	10	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																								
	Load 50%	Load 100%																																							
-20	40	50																																							
-10	30	40																																							
0	25	35																																							
10	20	25																																							
20	15	15																																							
25	10	10																																							
30	10	10																																							
40	10	10																																							
50	10	10																																							
60	10	10																																							
--	-	-																																							
Measured by 20 MHz Oscilloscope.																																									
Note: Slanted line shows the range of the rated ambient temperature.																																									



Model		LCA30S-48		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift																																																						
Object		+48V0.7A																																																						
1.Graph		<p>—△— Input Volt. 85V</p> <p>---□--- Input Volt. 100V</p> <p>-·-○-·- Input Volt. 132V</p>		2.Values																																																				
<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>48.446</td><td>48.445</td><td>48.444</td></tr> <tr><td>-10</td><td>48.440</td><td>48.439</td><td>48.437</td></tr> <tr><td>0</td><td>48.427</td><td>48.426</td><td>48.424</td></tr> <tr><td>10</td><td>48.408</td><td>48.407</td><td>48.405</td></tr> <tr><td>20</td><td>48.384</td><td>48.383</td><td>48.381</td></tr> <tr><td>25</td><td>48.369</td><td>48.368</td><td>48.366</td></tr> <tr><td>30</td><td>48.354</td><td>48.352</td><td>48.350</td></tr> <tr><td>40</td><td>48.321</td><td>48.319</td><td>48.316</td></tr> <tr><td>50</td><td>48.282</td><td>48.281</td><td>48.278</td></tr> <tr><td>60</td><td>48.241</td><td>48.240</td><td>48.238</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	48.446	48.445	48.444	-10	48.440	48.439	48.437	0	48.427	48.426	48.424	10	48.408	48.407	48.405	20	48.384	48.383	48.381	25	48.369	48.368	48.366	30	48.354	48.352	48.350	40	48.321	48.319	48.316	50	48.282	48.281	48.278	60	48.241	48.240	48.238	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
-20	48.446	48.445	48.444																																																					
-10	48.440	48.439	48.437																																																					
0	48.427	48.426	48.424																																																					
10	48.408	48.407	48.405																																																					
20	48.384	48.383	48.381																																																					
25	48.369	48.368	48.366																																																					
30	48.354	48.352	48.350																																																					
40	48.321	48.319	48.316																																																					
50	48.282	48.281	48.278																																																					
60	48.241	48.240	48.238																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																								



<b>COSEL</b>		
Model	LCA30S-48	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+48V0.7A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 132V

Load Current : 0 - 0.7A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	132	0	48.446	±85	±0.2
Minimum Voltage	50	132	0.7	48.276		



Model	LCA30S-48	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+48V0.7A		


1. Graph



2. Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	6.0	14.4	20.4	42.7	66.0
100 %	6.4	20.2	26.6	19.3	37.1

[mS]





Model		LCA30S-48																																	
Item		Hold-Up Time																																	
Object		+48V0.7A																																	
Temperature		25°C																																	
Testing Circuitry		Figure A																																	
1.Graph		2.Values																																	
<p>---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>28</td><td>9</td></tr> <tr><td>80</td><td>33</td><td>12</td></tr> <tr><td>85</td><td>38</td><td>14</td></tr> <tr><td>90</td><td>44</td><td>17</td></tr> <tr><td>100</td><td>55</td><td>23</td></tr> <tr><td>110</td><td>68</td><td>30</td></tr> <tr><td>120</td><td>81</td><td>38</td></tr> <tr><td>132</td><td>100</td><td>48</td></tr> <tr><td>140</td><td>113</td><td>56</td></tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	28	9	80	33	12	85	38	14	90	44	17	100	55	23	110	68	30	120	81	38	132	100	48	140	113	56
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	28	9																																	
80	33	12																																	
85	38	14																																	
90	44	17																																	
100	55	23																																	
110	68	30																																	
120	81	38																																	
132	100	48																																	
140	113	56																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.                  Note: Slanted line shows the range of the rated input voltage.</p>																																			




Model		LCA30S-48	Temperature	25°C																																																			
Item		Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object		+48V0.7A																																																					
1.Graph		<p>—△— Input Volt. 85V</p> <p>---□--- Input Volt. 100V</p> <p>-·-○-·- Input Volt. 132V</p>	2.Values																																																				
Instantaneous Compensation Time [mS]			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.10</td><td>112</td><td>155</td><td>251</td></tr> <tr><td>0.20</td><td>65</td><td>95</td><td>160</td></tr> <tr><td>0.30</td><td>45</td><td>65</td><td>115</td></tr> <tr><td>0.40</td><td>33</td><td>48</td><td>88</td></tr> <tr><td>0.50</td><td>25</td><td>38</td><td>70</td></tr> <tr><td>0.60</td><td>19</td><td>30</td><td>58</td></tr> <tr><td>0.70</td><td>15</td><td>24</td><td>50</td></tr> <tr><td>0.77</td><td>12</td><td>20</td><td>43</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	-	-	-	0.10	112	155	251	0.20	65	95	160	0.30	45	65	115	0.40	33	48	88	0.50	25	38	70	0.60	19	30	58	0.70	15	24	50	0.77	12	20	43	--	-	-	-	--	-	-	-
	Load Current [A]	Time [ms]																																																					
		Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
	0.00	-	-	-																																																			
	0.10	112	155	251																																																			
	0.20	65	95	160																																																			
	0.30	45	65	115																																																			
	0.40	33	48	88																																																			
	0.50	25	38	70																																																			
	0.60	19	30	58																																																			
	0.70	15	24	50																																																			
	0.77	12	20	43																																																			
	--	-	-	-																																																			
--	-	-	-																																																				
Note: Slanted line shows the range of the rated load current.																																																							



Model	LCA30S-48
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+48V0.7A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	37	60
-10	37	60
0	37	60
10	37	59
20	37	59
25	37	59
30	37	59
40	36	59
50	36	58
60	37	58
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model		LCA30S-48	Temperature		25°C																																																							
Item		Overcurrent Protection	Testing Circuitry		Figure A																																																							
Object		+48V0.7A																																																										
1. Graph			2. Values																																																									
<p>Legend:                  — Input Volt. 85V                  — Input Volt. 100V                  — Input Volt. 132V</p> <p>Note: Slanted line shows the range of the rated load current.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>48.0</td><td>0.73</td><td>0.73</td><td>0.73</td></tr> <tr><td>45.6</td><td>0.96</td><td>0.92</td><td>0.88</td></tr> <tr><td>43.2</td><td>0.97</td><td>0.93</td><td>0.88</td></tr> <tr><td>38.4</td><td>0.97</td><td>0.92</td><td>0.88</td></tr> <tr><td>33.6</td><td>0.96</td><td>0.91</td><td>0.87</td></tr> <tr><td>28.8</td><td>0.95</td><td>0.90</td><td>0.85</td></tr> <tr><td>24.0</td><td>0.91</td><td>0.87</td><td>0.82</td></tr> <tr><td>19.2</td><td>0.87</td><td>0.82</td><td>0.78</td></tr> <tr><td>14.4</td><td>0.80</td><td>0.76</td><td>0.73</td></tr> <tr><td>9.6</td><td>0.69</td><td>0.66</td><td>0.66</td></tr> <tr><td>4.8</td><td>0.54</td><td>0.53</td><td>0.54</td></tr> <tr><td>0.0</td><td>0.37</td><td>0.37</td><td>0.40</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	48.0	0.73	0.73	0.73	45.6	0.96	0.92	0.88	43.2	0.97	0.93	0.88	38.4	0.97	0.92	0.88	33.6	0.96	0.91	0.87	28.8	0.95	0.90	0.85	24.0	0.91	0.87	0.82	19.2	0.87	0.82	0.78	14.4	0.80	0.76	0.73	9.6	0.69	0.66	0.66	4.8	0.54	0.53	0.54	0.0	0.37	0.37	0.40
Output Voltage [V]	Load Current [A]																																																											
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																									
48.0	0.73	0.73	0.73																																																									
45.6	0.96	0.92	0.88																																																									
43.2	0.97	0.93	0.88																																																									
38.4	0.97	0.92	0.88																																																									
33.6	0.96	0.91	0.87																																																									
28.8	0.95	0.90	0.85																																																									
24.0	0.91	0.87	0.82																																																									
19.2	0.87	0.82	0.78																																																									
14.4	0.80	0.76	0.73																																																									
9.6	0.69	0.66	0.66																																																									
4.8	0.54	0.53	0.54																																																									
0.0	0.37	0.37	0.40																																																									




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950 )