




TEST DATA OF LCA75S-3

Regulated DC Power Supply

Approved by : 
k.Shibutani Design Manager

Prepared by : J. Asano J. Asano Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Inrush Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple Voltage (by Load Current)	8
9.Ripple-Noise	9
10.Ripple Voltage (by Ambient Temperature)	10
11.Ambient Temperature Drift	11
12.Output Voltage Accuracy	12
13.Time Lapse Drift	13
14.Rise and Fall Time	14
15.Hold-Up Time	15
16.Instantaneous Interruption Compensation	16
17.Minimum Input Voltage for Regulated Output Voltage	17
18.Overcurrent Protection	18
19.Ovvervoltage Protection	19
20.Figure of Testing Circuitry	20

(Final Page 20)

COSSEL

Model	LCA75S-3																																																						
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	_____																																																						
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85V (solid line with triangle markers) Input Volt. 100V (dashed line with square markers) Input Volt. 132V (dash-dot line with circle markers) <p>Note: Slanted line shows the range of the rated load current.</p>	2.Values																																																					
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.063</td><td>0.066</td><td>0.070</td></tr> <tr> <td>3.0</td><td>0.305</td><td>0.282</td><td>0.251</td></tr> <tr> <td>6.0</td><td>0.532</td><td>0.480</td><td>0.408</td></tr> <tr> <td>9.0</td><td>0.774</td><td>0.688</td><td>0.571</td></tr> <tr> <td>12.0</td><td>1.027</td><td>0.905</td><td>0.744</td></tr> <tr> <td>15.0</td><td>1.289</td><td>1.130</td><td>0.921</td></tr> <tr> <td>16.5</td><td>1.423</td><td>1.251</td><td>1.018</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.063	0.066	0.070	3.0	0.305	0.282	0.251	6.0	0.532	0.480	0.408	9.0	0.774	0.688	0.571	12.0	1.027	0.905	0.744	15.0	1.289	1.130	0.921	16.5	1.423	1.251	1.018	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Input Current [A]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0.0	0.063	0.066	0.070																																																				
3.0	0.305	0.282	0.251																																																				
6.0	0.532	0.480	0.408																																																				
9.0	0.774	0.688	0.571																																																				
12.0	1.027	0.905	0.744																																																				
15.0	1.289	1.130	0.921																																																				
16.5	1.423	1.251	1.018																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

COSSEL

Model	LCA75S-3																																																							
Item	Input Power (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																					
Object	—	—	—																																																					
1.Graph	—△— Input Volt. 85V ---□--- Input Volt. 100V ---○--- Input Volt. 132V	2.Values																																																						
<p>Input Power [W]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.10</td><td>2.46</td><td>3.27</td></tr> <tr><td>3.0</td><td>13.49</td><td>13.80</td><td>15.34</td></tr> <tr><td>6.0</td><td>25.00</td><td>25.40</td><td>26.70</td></tr> <tr><td>9.0</td><td>37.20</td><td>37.50</td><td>38.60</td></tr> <tr><td>12.0</td><td>49.90</td><td>50.00</td><td>50.90</td></tr> <tr><td>15.0</td><td>63.10</td><td>63.10</td><td>63.70</td></tr> <tr><td>16.5</td><td>69.80</td><td>69.80</td><td>70.30</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	2.10	2.46	3.27	3.0	13.49	13.80	15.34	6.0	25.00	25.40	26.70	9.0	37.20	37.50	38.60	12.0	49.90	50.00	50.90	15.0	63.10	63.10	63.70	16.5	69.80	69.80	70.30	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0.0	2.10	2.46	3.27																																																					
3.0	13.49	13.80	15.34																																																					
6.0	25.00	25.40	26.70																																																					
9.0	37.20	37.50	38.60																																																					
12.0	49.90	50.00	50.90																																																					
15.0	63.10	63.10	63.70																																																					
16.5	69.80	69.80	70.30																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								

COSSEL


Model	LCA75S-3																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	_____	_____																																
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>75.1</td><td>72.8</td> </tr> <tr> <td>80</td><td>74.9</td><td>73.1</td> </tr> <tr> <td>85</td><td>74.4</td><td>73.2</td> </tr> <tr> <td>90</td><td>74.4</td><td>73.3</td> </tr> <tr> <td>100</td><td>73.7</td><td>73.2</td> </tr> <tr> <td>110</td><td>72.7</td><td>73.1</td> </tr> <tr> <td>120</td><td>72.1</td><td>73.0</td> </tr> <tr> <td>132</td><td>71.0</td><td>72.4</td> </tr> <tr> <td>140</td><td>70.1</td><td>72.1</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	75.1	72.8	80	74.9	73.1	85	74.4	73.2	90	74.4	73.3	100	73.7	73.2	110	72.7	73.1	120	72.1	73.0	132	71.0	72.4	140	70.1	72.1
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	75.1	72.8																																
80	74.9	73.1																																
85	74.4	73.2																																
90	74.4	73.3																																
100	73.7	73.2																																
110	72.7	73.1																																
120	72.1	73.0																																
132	71.0	72.4																																
140	70.1	72.1																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSSEL

Model	LCA75S-3																																																					
Item	Efficiency (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____	_____	_____																																																			
1.Graph	Input Volt. 85V Input Volt. 100V Input Volt. 132V	2.Values																																																				
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>68.4</td><td>66.8</td><td>60.1</td></tr> <tr><td>6.0</td><td>73.8</td><td>72.6</td><td>69.1</td></tr> <tr><td>9.0</td><td>74.4</td><td>73.8</td><td>71.7</td></tr> <tr><td>12.0</td><td>74.0</td><td>73.8</td><td>72.5</td></tr> <tr><td>15.0</td><td>73.1</td><td>73.1</td><td>72.4</td></tr> <tr><td>16.5</td><td>72.7</td><td>72.7</td><td>72.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	-	-	-	3.0	68.4	66.8	60.1	6.0	73.8	72.6	69.1	9.0	74.4	73.8	71.7	12.0	74.0	73.8	72.5	15.0	73.1	73.1	72.4	16.5	72.7	72.7	72.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	-	-	-																																																			
3.0	68.4	66.8	60.1																																																			
6.0	73.8	72.6	69.1																																																			
9.0	74.4	73.8	71.7																																																			
12.0	74.0	73.8	72.5																																																			
15.0	73.1	73.1	72.4																																																			
16.5	72.7	72.7	72.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


COSEL

Model	LCA75S-3	Temperature Testing Circuitry Figure A
Item	Inrush Current	
Object	_____	



Input Voltage	100 V
Frequency	60 Hz
Load	100 %

Primary inrush current	27.1 A
Secondary inrush current	3.3 A



COSEL

Model	LCA75S-3																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+3V15A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>3.081</td><td>3.082</td></tr> <tr><td>80</td><td>3.081</td><td>3.083</td></tr> <tr><td>85</td><td>3.081</td><td>3.083</td></tr> <tr><td>90</td><td>3.081</td><td>3.083</td></tr> <tr><td>100</td><td>3.082</td><td>3.083</td></tr> <tr><td>110</td><td>3.082</td><td>3.083</td></tr> <tr><td>120</td><td>3.082</td><td>3.083</td></tr> <tr><td>132</td><td>3.082</td><td>3.083</td></tr> <tr><td>140</td><td>3.082</td><td>3.083</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	3.081	3.082	80	3.081	3.083	85	3.081	3.083	90	3.081	3.083	100	3.082	3.083	110	3.082	3.083	120	3.082	3.083	132	3.082	3.083	140	3.082	3.083
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	3.081	3.082																																
80	3.081	3.083																																
85	3.081	3.083																																
90	3.081	3.083																																
100	3.082	3.083																																
110	3.082	3.083																																
120	3.082	3.083																																
132	3.082	3.083																																
140	3.082	3.083																																

COSEL

Model	LCA75S-3																																																					
Item	Load Regulation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+3V15A																																																					
1.Graph	Input Volt. 85V 100V 132V	2.Values																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																						
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>3.082</td><td>3.082</td><td>3.082</td></tr> <tr> <td>3.0</td><td>3.082</td><td>3.082</td><td>3.083</td></tr> <tr> <td>6.0</td><td>3.083</td><td>3.083</td><td>3.083</td></tr> <tr> <td>9.0</td><td>3.083</td><td>3.083</td><td>3.083</td></tr> <tr> <td>12.0</td><td>3.083</td><td>3.083</td><td>3.084</td></tr> <tr> <td>15.0</td><td>3.084</td><td>3.084</td><td>3.084</td></tr> <tr> <td>16.5</td><td>3.084</td><td>3.084</td><td>3.084</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	3.082	3.082	3.082	3.0	3.082	3.082	3.083	6.0	3.083	3.083	3.083	9.0	3.083	3.083	3.083	12.0	3.083	3.083	3.084	15.0	3.084	3.084	3.084	16.5	3.084	3.084	3.084	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	3.082	3.082	3.082																																																			
3.0	3.082	3.082	3.083																																																			
6.0	3.083	3.083	3.083																																																			
9.0	3.083	3.083	3.083																																																			
12.0	3.083	3.083	3.084																																																			
15.0	3.084	3.084	3.084																																																			
16.5	3.084	3.084	3.084																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	LCA75S-3																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																						
Object	+3V15A																																							
1.Graph																																								
<p style="text-align: center;"> —△— Input Volt. 85V ---○--- Input Volt. 132V </p>																																								
2.Values																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>15</td> <td>15</td> </tr> <tr> <td>3.0</td> <td>30</td> <td>30</td> </tr> <tr> <td>6.0</td> <td>35</td> <td>35</td> </tr> <tr> <td>9.0</td> <td>35</td> <td>40</td> </tr> <tr> <td>12.0</td> <td>40</td> <td>45</td> </tr> <tr> <td>15.0</td> <td>40</td> <td>45</td> </tr> <tr> <td>16.5</td> <td>40</td> <td>45</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	15	15	3.0	30	30	6.0	35	35	9.0	35	40	12.0	40	45	15.0	40	45	16.5	40	45	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.0	15	15																																						
3.0	30	30																																						
6.0	35	35																																						
9.0	35	40																																						
12.0	40	45																																						
15.0	40	45																																						
16.5	40	45																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p style="text-align: center;"> T1: Due to AC Input Line T2: Due to Switching </p>																																								
<p style="text-align: center;">Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	LCA75S-3																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure A																																						
Object	+3V15A																																							
1.Graph																																								
<p>—△— Input Volt. 85V ---○--- Input Volt. 132V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (85V)</th> <th>Ripple-Noise [mV] (132V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>3.0</td><td>40</td><td>40</td></tr> <tr><td>6.0</td><td>40</td><td>45</td></tr> <tr><td>9.0</td><td>45</td><td>50</td></tr> <tr><td>12.0</td><td>50</td><td>55</td></tr> <tr><td>15.0</td><td>50</td><td>55</td></tr> <tr><td>16.5</td><td>50</td><td>55</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV] (85V)	Ripple-Noise [mV] (132V)	0.0	20	20	3.0	40	40	6.0	40	45	9.0	45	50	12.0	50	55	15.0	50	55	16.5	50	55															
Load Current [A]	Ripple-Noise [mV] (85V)	Ripple-Noise [mV] (132V)																																						
0.0	20	20																																						
3.0	40	40																																						
6.0	40	45																																						
9.0	45	50																																						
12.0	50	55																																						
15.0	50	55																																						
16.5	50	55																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>3.0</td><td>40</td><td>40</td></tr> <tr><td>6.0</td><td>40</td><td>45</td></tr> <tr><td>9.0</td><td>45</td><td>50</td></tr> <tr><td>12.0</td><td>50</td><td>55</td></tr> <tr><td>15.0</td><td>50</td><td>55</td></tr> <tr><td>16.5</td><td>50</td><td>55</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	20	20	3.0	40	40	6.0	40	45	9.0	45	50	12.0	50	55	15.0	50	55	16.5	50	55	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.0	20	20																																						
3.0	40	40																																						
6.0	40	45																																						
9.0	45	50																																						
12.0	50	55																																						
15.0	50	55																																						
16.5	50	55																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple-Noise [mVp-p]</p> <p>T1</p> <p>T2</p>																																								
Fig. Complex Ripple Wave Form																																								

COSEL

Model	LCA75S-3	Testing Circuitry Figure A																																			
Item	Ripple Voltage (by Ambient Temp.)																																				
Object	+3V15A																																				
1.Graph		2.Values																																			
<p>Graph showing Ripple Voltage [mV] vs Ambient Temperature [°C]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from -40 to 60 °C. Two data series are plotted: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general decrease in ripple voltage as ambient temperature increases. A slanted line indicates the rated ambient temperature range.</p> <table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV] (Load 50%)</th> <th>Ripple Voltage [mV] (Load 100%)</th> </tr> </thead> <tbody> <tr><td>-20</td><td>85</td><td>90</td></tr> <tr><td>-10</td><td>65</td><td>80</td></tr> <tr><td>0</td><td>55</td><td>70</td></tr> <tr><td>10</td><td>50</td><td>60</td></tr> <tr><td>20</td><td>45</td><td>55</td></tr> <tr><td>25</td><td>40</td><td>45</td></tr> <tr><td>30</td><td>40</td><td>40</td></tr> <tr><td>40</td><td>35</td><td>40</td></tr> <tr><td>50</td><td>35</td><td>35</td></tr> <tr><td>60</td><td>30</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV] (Load 50%)	Ripple Voltage [mV] (Load 100%)	-20	85	90	-10	65	80	0	55	70	10	50	60	20	45	55	25	40	45	30	40	40	40	35	40	50	35	35	60	30	35	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV] (Load 50%)	Ripple Voltage [mV] (Load 100%)																																			
-20	85	90																																			
-10	65	80																																			
0	55	70																																			
10	50	60																																			
20	45	55																																			
25	40	45																																			
30	40	40																																			
40	35	40																																			
50	35	35																																			
60	30	35																																			
--	-	-																																			
<p>Input Volt. 100V</p> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																					



		Testing Circuitry Figure A																																																					
Model	LCA75S-3																																																						
Item	Ambient Temperature Drift																																																						
Object	+3V15A																																																						
1.Graph	<p>—△— Input Volt. 85V - - -□- - Input Volt. 100V - - -○- - Input Volt. 132V</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>3.071</td><td>3.071</td><td>3.072</td></tr> <tr> <td>-10</td><td>3.074</td><td>3.074</td><td>3.074</td></tr> <tr> <td>0</td><td>3.076</td><td>3.077</td><td>3.077</td></tr> <tr> <td>10</td><td>3.079</td><td>3.079</td><td>3.079</td></tr> <tr> <td>20</td><td>3.081</td><td>3.081</td><td>3.081</td></tr> <tr> <td>25</td><td>3.082</td><td>3.082</td><td>3.083</td></tr> <tr> <td>30</td><td>3.083</td><td>3.083</td><td>3.083</td></tr> <tr> <td>40</td><td>3.084</td><td>3.085</td><td>3.085</td></tr> <tr> <td>50</td><td>3.086</td><td>3.086</td><td>3.086</td></tr> <tr> <td>60</td><td>3.087</td><td>3.087</td><td>3.087</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	3.071	3.071	3.072	-10	3.074	3.074	3.074	0	3.076	3.077	3.077	10	3.079	3.079	3.079	20	3.081	3.081	3.081	25	3.082	3.082	3.083	30	3.083	3.083	3.083	40	3.084	3.085	3.085	50	3.086	3.086	3.086	60	3.087	3.087	3.087	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
-20	3.071	3.071	3.072																																																				
-10	3.074	3.074	3.074																																																				
0	3.076	3.077	3.077																																																				
10	3.079	3.079	3.079																																																				
20	3.081	3.081	3.081																																																				
25	3.082	3.082	3.083																																																				
30	3.083	3.083	3.083																																																				
40	3.084	3.085	3.085																																																				
50	3.086	3.086	3.086																																																				
60	3.087	3.087	3.087																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							



Model	LCA75S-3	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+3V15A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 132V

Load Current : 0 - 15A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	50	132	15	3.087	±7	±0.2
Minimum Voltage	-10	85	0	3.074		

COSEL

Model	LCA75S-3	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+3V15A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.082</td></tr> <tr><td>0.5</td><td>3.084</td></tr> <tr><td>1.0</td><td>3.084</td></tr> <tr><td>2.0</td><td>3.084</td></tr> <tr><td>3.0</td><td>3.084</td></tr> <tr><td>4.0</td><td>3.084</td></tr> <tr><td>5.0</td><td>3.084</td></tr> <tr><td>6.0</td><td>3.084</td></tr> <tr><td>7.0</td><td>3.084</td></tr> <tr><td>8.0</td><td>3.084</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	3.082	0.5	3.084	1.0	3.084	2.0	3.084	3.0	3.084	4.0	3.084	5.0	3.084	6.0	3.084	7.0	3.084	8.0	3.084
Time since start [H]	Output Voltage [V]																								
0.0	3.082																								
0.5	3.084																								
1.0	3.084																								
2.0	3.084																								
3.0	3.084																								
4.0	3.084																								
5.0	3.084																								
6.0	3.084																								
7.0	3.084																								
8.0	3.084																								

COSEL



Model	LCA75S-3																																	
Item	Hold-Up Time	Temperature Testing Circuitry 25°C Figure A																																
Object	+3V15A																																	
1.Graph																																		
<p>Legend:</p> <ul style="list-style-type: none"> Load 50% (dashed line with squares) Load 100% (solid line with triangles) <p>Y-axis: Hold-Up Time [ms]</p> <p>X-axis: Input Voltage [V]</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>35</td> <td>13</td> </tr> <tr> <td>80</td> <td>46</td> <td>19</td> </tr> <tr> <td>85</td> <td>59</td> <td>25</td> </tr> <tr> <td>90</td> <td>71</td> <td>31</td> </tr> <tr> <td>100</td> <td>100</td> <td>45</td> </tr> <tr> <td>110</td> <td>132</td> <td>61</td> </tr> <tr> <td>120</td> <td>167</td> <td>78</td> </tr> <tr> <td>132</td> <td>212</td> <td>101</td> </tr> <tr> <td>140</td> <td>245</td> <td>118</td> </tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	35	13	80	46	19	85	59	25	90	71	31	100	100	45	110	132	61	120	167	78	132	212	101	140	245	118
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
75	35	13																																
80	46	19																																
85	59	25																																
90	71	31																																
100	100	45																																
110	132	61																																
120	167	78																																
132	212	101																																
140	245	118																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	LCA75S-3																																																						
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																				
Object	+3V15A																																																						
1.Graph	<p style="text-align: center;"> —△— Input Volt. 85V ---□--- Input Volt. 100V ---○--- Input Volt. 132V </p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>150</td><td>246</td><td>496</td></tr> <tr><td>6.0</td><td>76</td><td>129</td><td>267</td></tr> <tr><td>9.0</td><td>48</td><td>84</td><td>178</td></tr> <tr><td>12.0</td><td>35</td><td>60</td><td>131</td></tr> <tr><td>15.0</td><td>25</td><td>46</td><td>102</td></tr> <tr><td>16.5</td><td>21</td><td>41</td><td>92</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	-	-	-	3.0	150	246	496	6.0	76	129	267	9.0	48	84	178	12.0	35	60	131	15.0	25	46	102	16.5	21	41	92	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0.0	-	-	-																																																				
3.0	150	246	496																																																				
6.0	76	129	267																																																				
9.0	48	84	178																																																				
12.0	35	60	131																																																				
15.0	25	46	102																																																				
16.5	21	41	92																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				


Note: Slanted line shows the range of the rated load current.

COSEL

Model	LCA75S-3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3V15A

Testing Circuitry Figure A

1.Graph




Note: Slanted line shows the range of the rated ambient temperature.


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	58	63
-10	58	62
0	58	62
10	57	62
20	57	62
25	57	62
30	57	62
40	56	61
50	56	61
60	56	61
--	-	-

COSEL

Model	LCA75S-3		
Item	Overcurrent Protection		
Object	+3V15A		
1.Graph	Input Volt. 85V	Input Volt. 100V	Input Volt. 132V
			
Note:	Slanted line shows the range of the rated load current.		
Temperature	25°C	Testing Circuitry	Figure A
2.Values			
Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
3.00	15.33	15.24	15.24
2.85	18.83	18.83	18.93
2.70	18.89	18.90	18.98
2.40	19.03	19.04	19.07
2.10	19.17	19.15	19.27
1.80	19.26	19.33	19.25
1.50	19.40	19.35	19.33
1.20	19.47	19.45	19.43
0.90	19.58	19.56	19.50
0.60	19.68	19.64	19.53
0.30	19.74	19.65	19.46
0.00	19.68	19.53	19.16

COSEL

Model	LCA75S-3	Testing Circuitry Figure A			
Item	Overvoltage Protection				
Object	+3V15A				
1.Graph	<p>—△— Input Volt. 85V - - -□- - Input Volt. 100V - - -○- - Input Volt. 132V</p>  <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>	2.Values			
		Ambient Temperature [°C]	Operating Point [V]		
		[°C]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
	-20	4.93	4.93	4.93	
	-10	4.86	4.92	4.86	
	0	4.86	4.86	4.86	
	10	4.80	4.85	4.85	
	20	4.80	4.85	4.85	
	25	4.80	4.80	4.80	
	30	4.80	4.80	4.80	
	40	4.75	4.80	4.80	
	50	4.75	4.75	4.74	
	60	4.75	4.74	4.74	
	--	-	-	-	

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)