


## RADIATED EMISSION

Model Name :LDA100W-18  
 Model No. :  
 Serial No. :  
 Points :3  
 Detector :PEAK/QP  
 Polarization :Hori.&Vert.  
 Limit:[CISPR 22] Class B<3m>

Power Supply :230V(1 Phase) 50Hz  
 Temp. :25degC  
 Humi. :44%  
 Date :2001/5/16 15:14  
 Test Equip. :R3132,ESPC  
 Comment :




Frequency [MHz]	Meter Reading (QP) [dBuV]	Antena Factor [dBuV]	Cable & Preamp [dB]	Level (Qp) [dBuV]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]
969.529	23.3	25.3	-29.2	19.4	201	103	Hori.	47.0	27.6
31.319	37.7	17.6	-32.1	23.2	54	124	Vert.	40.0	16.8
61.164	49.0	4.7	-31.8	21.9	27	107	Vert.	40.0	18.1



## LINE CONDUCTION

Model Name : LDA100W-18  
 Model No. :  
 Serial No. :  
 Points : 3  
 Detector : PEAK/QP/Ave.  
 Line Mode : VA/VB  
 Limit1:[CISPR Pub22] Class B(QP)  
 Limit2:[CISPR Pub22] Class B(Ave.)

Power Supply : 230V(1 Phase) 50Hz  
 Temp. : 25degC  
 Humi. : 44%  
 Date : 2001/5/16 13:57  
 Test Equip. : R3132,ESPC  
 Comment :



Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level (Ave.) [dBuV]	Level (QP) [dBuV]	Line	Limit (Ave.) [dBuV]	Limit (QP) [dBuV]	Margin (Ave.) [dB]	Margin (QP) [dB]
0.2399	24.0	36.3	9.8	33.8	46.1	VA	52.1	62.1	18.3	16.0
13.2127	10.1	31.1	10.1	20.2	41.2	VA	50.0	60.0	29.8	18.8
8.9017	15.0	30.3	10.1	25.1	40.4	VB	50.0	60.0	24.9	19.6