


RADIATED EMISSION

Model Name :LDA100W-48
 Model No. :
 Serial No. :
 Points :3
 Detector :PEAK/QP
 Polarization :Hori.&Vert.
 Limit:[CISPR 22] Class B<3m>

Power Supply :230V(1 Phase) 50Hz
 Temp. :25degC
 Humi. :44%
 Date :2001/9/19 18:38
 Test Equip. :R3132,ESPC
 Comment :




Frequency [MHz]	Meter Reading (QP) [dBuV]	Antena Factor [dBuV]	Cable & Preamp [dB]	Level (Qp) [dBuV]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]
163.297	28.3	9.1	-24.1	13.3	266	132	Hori.	40.0	26.7
986.416	21.8	25.0	-23.8	23.0	50	147	Hori.	47.0	24.0
68.551	37.2	4.9	-23.4	18.7	330	101	Vert.	40.0	21.3



LINE CONDUCTION

Model Name :LDA100W-48
 Model No. :
 Serial No. :
 Points :4
 Detector :PEAK/QP/Ave.
 Line Mode :VA/VB
 Limit1:[CISPR Pub22] Class B(QP)
 Limit2:[CISPR Pub22] Class B(Ave.)

Power Supply :230V(1 Phase) 50Hz
 Temp. :25degC
 Humi. :44%
 Date :2001/9/19 18:12
 Test Equip. :R3132,ESPC
 Comment :



Frequency [MHz]	Meter Reading (QP) [dBuV]	Meter Reading (Ave.) [dBuV]	Factor [dB]	Level (QP) [dBuV]	Level (Ave.) [dBuV]	Line	Limit (QP) [dBuV]	Limit (Ave.) [dBuV]	Margin (QP) [dB]	Margin (Ave.) [dB]
12.9195	29.3	22.2	10.6	39.9	32.8	VA	60.0	50.0	20.1	17.2
0.2695	44.3	38.0	10.0	54.3	48.0	VB	61.1	51.1	6.8	3.1
0.6746	30.4	26.8	10.1	40.5	36.9	VB	56.0	46.0	15.5	9.1
4.8446	27.7	24.1	10.3	38.0	34.4	VB	56.0	46.0	18.0	11.6