

**COSEL**

TEST DATA OF LDA10F-5  
(200V INPUT)

Regulated DC Power Supply

Date : June 18. 1999

Approved by : K. Yamaguchi  
Design Manager

Prepared by : T. Ashihara  
Design Engineer

コーセル株式会社  
**COSEL CO., LTD.**



## C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Inrush Current	12
突入電流	
13. Dynamic Load Response	13
動的負荷変動	
14. Rise and Fall Time	14
立ち上り、立下がり時間	
15. Ambient Temperature Drift	15
周囲温度変動	
16. Minimum Input Voltage for Regulated Output Voltage	16
最低レギュレーション電圧	
17. Ripple Voltage (by Ambient Temperature)	17
リップル電圧 (周囲温度特性)	
18. Time Lapse Drift	18
経時ドリフト	
19. Output Voltage Accuracy	19
定電圧精度	
20. Condensation	20
結露特性	
21. Leakage Current	21
漏洩電流	
22. Line Noise Tolerance	22
入力雑音耐量	
23. Conducted Emission	23
雑音端子電圧	
24. Figure of Testing Circuitry	24
測定回路図	

(Final Page 25 )

**COSEL**

Model	LDA10F-5	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+5.0V2A																																		
1. Graph	<p>Load 50%      □</p> <p>Load 100%      △</p>	2. Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>150</td><td>5.150</td><td>5.146</td></tr> <tr> <td>160</td><td>5.150</td><td>5.146</td></tr> <tr> <td>170</td><td>5.150</td><td>5.146</td></tr> <tr> <td>180</td><td>5.150</td><td>5.147</td></tr> <tr> <td>200</td><td>5.150</td><td>5.147</td></tr> <tr> <td>220</td><td>5.150</td><td>5.147</td></tr> <tr> <td>240</td><td>5.151</td><td>5.147</td></tr> <tr> <td>264</td><td>5.151</td><td>5.148</td></tr> <tr> <td>280</td><td>5.151</td><td>5.148</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	150	5.150	5.146	160	5.150	5.146	170	5.150	5.146	180	5.150	5.147	200	5.150	5.147	220	5.150	5.147	240	5.151	5.147	264	5.151	5.148	280	5.151	5.148	
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
150	5.150	5.146																																	
160	5.150	5.146																																	
170	5.150	5.146																																	
180	5.150	5.147																																	
200	5.150	5.147																																	
220	5.150	5.147																																	
240	5.151	5.147																																	
264	5.151	5.148																																	
280	5.151	5.148																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

**COSEL**

Model	LDA10F-5																																																									
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	—																																																									
1. Graph	<p>—△— Input Volt. 170V        -□- Input Volt. 200V        -○- Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 264V [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.027</td><td>0.020</td><td>0.021</td></tr> <tr><td>0.4</td><td>0.059</td><td>0.057</td><td>0.057</td></tr> <tr><td>0.8</td><td>0.087</td><td>0.082</td><td>0.078</td></tr> <tr><td>1.2</td><td>0.113</td><td>0.105</td><td>0.096</td></tr> <tr><td>1.6</td><td>0.140</td><td>0.128</td><td>0.114</td></tr> <tr><td>2.0</td><td>0.169</td><td>0.153</td><td>0.133</td></tr> <tr><td>2.2</td><td>0.183</td><td>0.165</td><td>0.142</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170V [A]	Input Volt. 200V [A]	Input Volt. 264V [A]	0.0	0.027	0.020	0.021	0.4	0.059	0.057	0.057	0.8	0.087	0.082	0.078	1.2	0.113	0.105	0.096	1.6	0.140	0.128	0.114	2.0	0.169	0.153	0.133	2.2	0.183	0.165	0.142																							
Load Current [A]	Input Volt. 170V [A]	Input Volt. 200V [A]	Input Volt. 264V [A]																																																							
0.0	0.027	0.020	0.021																																																							
0.4	0.059	0.057	0.057																																																							
0.8	0.087	0.082	0.078																																																							
1.2	0.113	0.105	0.096																																																							
1.6	0.140	0.128	0.114																																																							
2.0	0.169	0.153	0.133																																																							
2.2	0.183	0.165	0.142																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.027</td><td>0.020</td><td>0.021</td></tr> <tr><td>0.4</td><td>0.059</td><td>0.057</td><td>0.057</td></tr> <tr><td>0.8</td><td>0.087</td><td>0.082</td><td>0.078</td></tr> <tr><td>1.2</td><td>0.113</td><td>0.105</td><td>0.096</td></tr> <tr><td>1.6</td><td>0.140</td><td>0.128</td><td>0.114</td></tr> <tr><td>2.0</td><td>0.169</td><td>0.153</td><td>0.133</td></tr> <tr><td>2.2</td><td>0.183</td><td>0.165</td><td>0.142</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	0.027	0.020	0.021	0.4	0.059	0.057	0.057	0.8	0.087	0.082	0.078	1.2	0.113	0.105	0.096	1.6	0.140	0.128	0.114	2.0	0.169	0.153	0.133	2.2	0.183	0.165	0.142	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.0	0.027	0.020	0.021																																																							
0.4	0.059	0.057	0.057																																																							
0.8	0.087	0.082	0.078																																																							
1.2	0.113	0.105	0.096																																																							
1.6	0.140	0.128	0.114																																																							
2.0	0.169	0.153	0.133																																																							
2.2	0.183	0.165	0.142																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current


(注)斜線は定格負荷電流範囲を示す。

**COSEL**

Model	LDA10F-5																																																									
Item	Input Power (by Load Current) 入力電力（負荷特性）	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	_____																																																									
1. Graph	<p>—△— Input Volt. 170V        -□- Input Volt. 200V        -○- Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power 170V [W]</th> <th>Input Power 200V [W]</th> <th>Input Power 264V [W]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.70</td><td>1.30</td><td>1.80</td></tr> <tr><td>0.5</td><td>4.30</td><td>4.80</td><td>6.00</td></tr> <tr><td>1.0</td><td>6.80</td><td>7.40</td><td>8.60</td></tr> <tr><td>1.5</td><td>9.30</td><td>9.70</td><td>11.00</td></tr> <tr><td>2.0</td><td>11.90</td><td>12.20</td><td>13.40</td></tr> <tr><td>2.2</td><td>14.70</td><td>14.90</td><td>15.90</td></tr> </tbody> </table>			Load Current [A]	Input Power 170V [W]	Input Power 200V [W]	Input Power 264V [W]	0.0	1.70	1.30	1.80	0.5	4.30	4.80	6.00	1.0	6.80	7.40	8.60	1.5	9.30	9.70	11.00	2.0	11.90	12.20	13.40	2.2	14.70	14.90	15.90																											
Load Current [A]	Input Power 170V [W]	Input Power 200V [W]	Input Power 264V [W]																																																							
0.0	1.70	1.30	1.80																																																							
0.5	4.30	4.80	6.00																																																							
1.0	6.80	7.40	8.60																																																							
1.5	9.30	9.70	11.00																																																							
2.0	11.90	12.20	13.40																																																							
2.2	14.70	14.90	15.90																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.70</td><td>1.30</td><td>1.80</td></tr> <tr><td>0.4</td><td>4.30</td><td>4.80</td><td>6.00</td></tr> <tr><td>0.8</td><td>6.80</td><td>7.40</td><td>8.60</td></tr> <tr><td>1.2</td><td>9.30</td><td>9.70</td><td>11.00</td></tr> <tr><td>1.6</td><td>11.90</td><td>12.20</td><td>13.40</td></tr> <tr><td>2.0</td><td>14.70</td><td>14.90</td><td>15.90</td></tr> <tr><td>2.2</td><td>16.00</td><td>16.20</td><td>17.10</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	1.70	1.30	1.80	0.4	4.30	4.80	6.00	0.8	6.80	7.40	8.60	1.2	9.30	9.70	11.00	1.6	11.90	12.20	13.40	2.0	14.70	14.90	15.90	2.2	16.00	16.20	17.10	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.0	1.70	1.30	1.80																																																							
0.4	4.30	4.80	6.00																																																							
0.8	6.80	7.40	8.60																																																							
1.2	9.30	9.70	11.00																																																							
1.6	11.90	12.20	13.40																																																							
2.0	14.70	14.90	15.90																																																							
2.2	16.00	16.20	17.10																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

**COSEL**

 Temperature 25°C  
 Testing Circuitry Figure A

## 2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
150	68.7	72.5
160	67.8	72.0
170	66.9	71.2
180	65.2	70.8
200	63.1	69.9
220	60.1	68.7
240	57.6	67.3
264	54.4	65.4
280	53.0	64.8

**COSEL**

Model	LDA10F-5																																																					
Item	Efficiency (by Load Current) 効率 (負荷電流特性)	Temperature 25°C	Testing Circuitry Figure A																																																			
Output	—																																																					
1. Graph	<p>Graph showing Efficiency (%) vs Load Current (A) for three input voltages: 170V, 200V, and 264V. The graph shows efficiency increasing with load current. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.4</td><td>48.7</td><td>44.0</td><td>35.0</td></tr> <tr><td>0.8</td><td>61.6</td><td>56.6</td><td>48.7</td></tr> <tr><td>1.2</td><td>67.1</td><td>64.4</td><td>56.8</td></tr> <tr><td>1.6</td><td>69.6</td><td>67.9</td><td>62.0</td></tr> <tr><td>2.0</td><td>70.7</td><td>69.6</td><td>65.5</td></tr> <tr><td>2.2</td><td>71.2</td><td>70.3</td><td>66.7</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.4	48.7	44.0	35.0	0.8	61.6	56.6	48.7	1.2	67.1	64.4	56.8	1.6	69.6	67.9	62.0	2.0	70.7	69.6	65.5	2.2	71.2	70.3	66.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Load Current [A]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0.4	48.7	44.0	35.0																																																			
0.8	61.6	56.6	48.7																																																			
1.2	67.1	64.4	56.8																																																			
1.6	69.6	67.9	62.0																																																			
2.0	70.7	69.6	65.5																																																			
2.2	71.2	70.3	66.7																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.4</td><td>48.7</td><td>44.0</td><td>35.0</td></tr> <tr><td>0.8</td><td>61.6</td><td>56.6</td><td>48.7</td></tr> <tr><td>1.2</td><td>67.1</td><td>64.4</td><td>56.8</td></tr> <tr><td>1.6</td><td>69.6</td><td>67.9</td><td>62.0</td></tr> <tr><td>2.0</td><td>70.7</td><td>69.6</td><td>65.5</td></tr> <tr><td>2.2</td><td>71.2</td><td>70.3</td><td>66.7</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.4	48.7	44.0	35.0	0.8	61.6	56.6	48.7	1.2	67.1	64.4	56.8	1.6	69.6	67.9	62.0	2.0	70.7	69.6	65.5	2.2	71.2	70.3	66.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0.4	48.7	44.0	35.0																																																			
0.8	61.6	56.6	48.7																																																			
1.2	67.1	64.4	56.8																																																			
1.6	69.6	67.9	62.0																																																			
2.0	70.7	69.6	65.5																																																			
2.2	71.2	70.3	66.7																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

**COSEL**

Model	LDA10F-5	Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																	
Object	+5.0V2A																																	
1. Graph	<p style="text-align: center;">□ Load 50% △ Load 100%</p>	2. Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>111</td><td>63</td></tr> <tr><td>160</td><td>127</td><td>73</td></tr> <tr><td>170</td><td>144</td><td>84</td></tr> <tr><td>180</td><td>162</td><td>96</td></tr> <tr><td>200</td><td>201</td><td>121</td></tr> <tr><td>220</td><td>242</td><td>148</td></tr> <tr><td>240</td><td>287</td><td>179</td></tr> <tr><td>264</td><td>345</td><td>218</td></tr> <tr><td>280</td><td>386</td><td>246</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	150	111	63	160	127	73	170	144	84	180	162	96	200	201	121	220	242	148	240	287	179	264	345	218	280	386	246
Input Voltage [V]	Hold-Up Time [mS]																																	
	Load 50%	Load 100%																																
150	111	63																																
160	127	73																																
170	144	84																																
180	162	96																																
200	201	121																																
220	242	148																																
240	287	179																																
264	345	218																																
280	386	246																																

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

**COSEL**


Model	LDA10F-5	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																						
Object	+5.0V2A																																																						
1. Graph	<p>Legend: Input Volt. 170 V (solid line with triangles), Input Volt. 200 V (dashed line with squares), Input Volt. 264 V (dotted line with circles).</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.4</td><td>393</td><td>525</td><td>841</td></tr> <tr><td>0.8</td><td>198</td><td>260</td><td>440</td></tr> <tr><td>1.2</td><td>123</td><td>169</td><td>248</td></tr> <tr><td>1.6</td><td>81</td><td>110</td><td>185</td></tr> <tr><td>2.0</td><td>60</td><td>80</td><td>139</td></tr> <tr><td>2.2</td><td>55</td><td>72</td><td>114</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	—	—	—	0.4	393	525	841	0.8	198	260	440	1.2	123	169	248	1.6	81	110	185	2.0	60	80	139	2.2	55	72	114	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—				
Load Current [A]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
0.0	—	—	—																																																				
0.4	393	525	841																																																				
0.8	198	260	440																																																				
1.2	123	169	248																																																				
1.6	81	110	185																																																				
2.0	60	80	139																																																				
2.2	55	72	114																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.4</td><td>393</td><td>525</td><td>841</td></tr> <tr><td>0.8</td><td>198</td><td>260</td><td>440</td></tr> <tr><td>1.2</td><td>123</td><td>169</td><td>248</td></tr> <tr><td>1.6</td><td>81</td><td>110</td><td>185</td></tr> <tr><td>2.0</td><td>60</td><td>80</td><td>139</td></tr> <tr><td>2.2</td><td>55</td><td>72</td><td>114</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Time [mS]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	—	—	—	0.4	393	525	841	0.8	198	260	440	1.2	123	169	248	1.6	81	110	185	2.0	60	80	139	2.2	55	72	114	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																						
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
0.0	—	—	—																																																				
0.4	393	525	841																																																				
0.8	198	260	440																																																				
1.2	123	169	248																																																				
1.6	81	110	185																																																				
2.0	60	80	139																																																				
2.2	55	72	114																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
	<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。 (注) 斜線は定格負荷電流範囲を示す。</p>																																																						

**COSEL**

Model	LDA10F-5
Item	Load Regulation 静的負荷変動
Object	+5.0V 2A

## 1. Graph

—△— Input Volt. 170 V  
 —□— Input Volt. 200 V  
 —○— Input Volt. 264 V



Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

Temperature 25°C  
 Testing Circuitry Figure A

## 2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
0.0	5.154	5.146	5.142
0.4	5.153	5.153	5.153
0.8	5.152	5.153	5.153
1.2	5.150	5.150	5.151
1.6	5.149	5.149	5.150
2.0	5.147	5.148	5.149
2.2	5.146	5.147	5.148
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	LDA10F-5	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																							
Object	+5.0V2A																																							
1. Graph	<p>□ Input Volt. 170V △ Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Volt. 170V [mV]</th> <th>Ripple Output Volt. 264V [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.40</td><td>10</td><td>10</td></tr> <tr><td>0.80</td><td>10</td><td>10</td></tr> <tr><td>1.20</td><td>10</td><td>15</td></tr> <tr><td>1.60</td><td>15</td><td>15</td></tr> <tr><td>2.00</td><td>15</td><td>15</td></tr> <tr><td>2.20</td><td>15</td><td>15</td></tr> </tbody> </table>	Load Current [A]	Ripple Output Volt. 170V [mV]	Ripple Output Volt. 264V [mV]	0.00	10	10	0.40	10	10	0.80	10	10	1.20	10	15	1.60	15	15	2.00	15	15	2.20	15	15															
Load Current [A]	Ripple Output Volt. 170V [mV]	Ripple Output Volt. 264V [mV]																																						
0.00	10	10																																						
0.40	10	10																																						
0.80	10	10																																						
1.20	10	15																																						
1.60	15	15																																						
2.00	15	15																																						
2.20	15	15																																						
2. Values																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 170 [V]</th> <th>Input Volt. 264 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.40</td><td>10</td><td>10</td></tr> <tr><td>0.80</td><td>10</td><td>10</td></tr> <tr><td>1.20</td><td>10</td><td>15</td></tr> <tr><td>1.60</td><td>15</td><td>15</td></tr> <tr><td>2.00</td><td>15</td><td>15</td></tr> <tr><td>2.20</td><td>15</td><td>15</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	10	10	0.40	10	10	0.80	10	10	1.20	10	15	1.60	15	15	2.00	15	15	2.20	15	15	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]																																						
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																						
0.00	10	10																																						
0.40	10	10																																						
0.80	10	10																																						
1.20	10	15																																						
1.60	15	15																																						
2.00	15	15																																						
2.20	15	15																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p – p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p>																																								
<p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL


Model	LDA10F-5	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	+ 5.0 V2A																																								
1. Graph		2. Values																																							
<p style="text-align: center;">□ Input Volt. 170V [mV]      △ Input Volt. 264V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 170 [V]</th> <th>Input Volt. 264 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>0.40</td><td>15</td><td>20</td></tr> <tr><td>0.80</td><td>15</td><td>20</td></tr> <tr><td>1.20</td><td>25</td><td>30</td></tr> <tr><td>1.60</td><td>30</td><td>30</td></tr> <tr><td>2.00</td><td>40</td><td>30</td></tr> <tr><td>2.20</td><td>40</td><td>30</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.00	15	15	0.40	15	20	0.80	15	20	1.20	25	30	1.60	30	30	2.00	40	30	2.20	40	30	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]																																							
	Ripple-Noise [mV]	Ripple-Noise [mV]																																							
0.00	15	15																																							
0.40	15	20																																							
0.80	15	20																																							
1.20	25	30																																							
1.60	30	30																																							
2.00	40	30																																							
2.20	40	30																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>			BC-4035																																						

**COSEL**

Model	LDA10F-5																																																									
Item	Overcurrent Protection 過電流保護																																																									
Object	+5.0V2A																																																									
1. Graph	<p>[V]</p> <p>Output Voltage</p> <p>Load Current [A]</p> <p>Input Volt. 170 V</p> <p>Input Volt. 200 V</p> <p>Input Volt. 264 V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>2.80</td><td>2.84</td><td>2.97</td></tr> <tr><td>4.75</td><td>2.81</td><td>2.85</td><td>2.98</td></tr> <tr><td>4.50</td><td>2.83</td><td>2.86</td><td>2.99</td></tr> <tr><td>4.00</td><td>2.85</td><td>2.88</td><td>2.99</td></tr> <tr><td>3.50</td><td>2.86</td><td>2.88</td><td>2.98</td></tr> <tr><td>3.00</td><td>2.84</td><td>2.86</td><td>2.97</td></tr> <tr><td>2.50</td><td>2.82</td><td>2.83</td><td>2.93</td></tr> <tr><td>2.00</td><td>2.76</td><td>2.77</td><td>2.87</td></tr> <tr><td>1.50</td><td>2.67</td><td>2.69</td><td>2.78</td></tr> <tr><td>1.00</td><td>2.53</td><td>2.55</td><td>2.65</td></tr> <tr><td>0.50</td><td>2.31</td><td>2.32</td><td>2.41</td></tr> <tr><td>0.00</td><td>2.09</td><td>2.10</td><td>2.30</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	5.00	2.80	2.84	2.97	4.75	2.81	2.85	2.98	4.50	2.83	2.86	2.99	4.00	2.85	2.88	2.99	3.50	2.86	2.88	2.98	3.00	2.84	2.86	2.97	2.50	2.82	2.83	2.93	2.00	2.76	2.77	2.87	1.50	2.67	2.69	2.78	1.00	2.53	2.55	2.65	0.50	2.31	2.32	2.41	0.00	2.09	2.10	2.30
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
5.00	2.80	2.84	2.97																																																							
4.75	2.81	2.85	2.98																																																							
4.50	2.83	2.86	2.99																																																							
4.00	2.85	2.88	2.99																																																							
3.50	2.86	2.88	2.98																																																							
3.00	2.84	2.86	2.97																																																							
2.50	2.82	2.83	2.93																																																							
2.00	2.76	2.77	2.87																																																							
1.50	2.67	2.69	2.78																																																							
1.00	2.53	2.55	2.65																																																							
0.50	2.31	2.32	2.41																																																							
0.00	2.09	2.10	2.30																																																							
Note:	Slanted line shows the range of the rated load current.																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

**COSEL**

Model	LDA10F-5	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current 突入電流		
Object	—		



Input Voltage 200 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 16.81 [A]

② 0.79 [A]



**COSEL**

Model	LDA10F-5	Temperature Testing Circuitry Figure A	25°C
Item	Dynamic Load Response 動的負荷變動		
Object	+5.0V2A		



Input Volt. 200 V

Cycle 1000 mS





Load 0% ↔

Load 100 %



Load 0% ↔

Load 50 %




200 mV/div

10 mS/div

**COSEL**


Model	LDA10F-5	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time 立上り、立下り時間		
Object	+5.0V2A		

## 1. Graph



## 2. Values

Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		2.3	6.3	8.5	157.0	36.5	
100 %		2.3	7.3	9.5	87.0	30.0	




**COSEL**

Model	LDA10F-5	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+5.0V2A																																																						
1. Graph	<p style="text-align: center;">—△— Input Volt. 170V —□— Input Volt. 200V —○— Input Volt. 264V</p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>	2. Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>5.144</td><td>5.145</td><td>5.146</td></tr> <tr> <td>-10</td><td>5.145</td><td>5.146</td><td>5.146</td></tr> <tr> <td>0</td><td>5.145</td><td>5.146</td><td>5.147</td></tr> <tr> <td>10</td><td>5.145</td><td>5.146</td><td>5.147</td></tr> <tr> <td>20</td><td>5.145</td><td>5.146</td><td>5.147</td></tr> <tr> <td>25</td><td>5.146</td><td>5.146</td><td>5.147</td></tr> <tr> <td>30</td><td>5.147</td><td>5.147</td><td>5.148</td></tr> <tr> <td>40</td><td>5.147</td><td>5.147</td><td>5.148</td></tr> <tr> <td>50</td><td>5.146</td><td>5.147</td><td>5.148</td></tr> <tr> <td>60</td><td>5.145</td><td>5.145</td><td>5.146</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Temperature [°C]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	-20	5.144	5.145	5.146	-10	5.145	5.146	5.146	0	5.145	5.146	5.147	10	5.145	5.146	5.147	20	5.145	5.146	5.147	25	5.146	5.146	5.147	30	5.147	5.147	5.148	40	5.147	5.147	5.148	50	5.146	5.147	5.148	60	5.145	5.145	5.146	—	—	—	—
Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
-20	5.144	5.145	5.146																																																				
-10	5.145	5.146	5.146																																																				
0	5.145	5.146	5.147																																																				
10	5.145	5.146	5.147																																																				
20	5.145	5.146	5.147																																																				
25	5.146	5.146	5.147																																																				
30	5.147	5.147	5.148																																																				
40	5.147	5.147	5.148																																																				
50	5.146	5.147	5.148																																																				
60	5.145	5.145	5.146																																																				
—	—	—	—																																																				

(注) 斜線は定格周囲温度範囲を示す。

**COSEL**

Model	LDA10F-5			
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧			
Object	+5.0V2A			
1. Graph				
[V]	<p>Load 50%      Load 100%</p>			
Input Voltage [V]	<p>Ambient Temperature [°C]</p>			
Note: Slanted line shows the range of the rated ambient temperature.				
(注)斜線は定格周囲温度範囲を示す。				
Testing Circuitry Figure A				
2. Values				
Ambient Temperature [°C]	Input Voltage [V]			
Load 50%	Load 100%			
-20	42	67		
-10	42	67		
0	41	68		
10	42	69		
20	42	69		
25	42	70		
30	42	70		
40	43	71		
50	43	72		
60	44	74		
—	—	—		

**COSEL**

**COSEL**

Model	LDA10F-5	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+5.0V2A																								
1. Graph			2. Values																						
<p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 200V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.152</td></tr> <tr><td>0.5</td><td>5.149</td></tr> <tr><td>1.0</td><td>5.150</td></tr> <tr><td>2.0</td><td>5.150</td></tr> <tr><td>3.0</td><td>5.149</td></tr> <tr><td>4.0</td><td>5.150</td></tr> <tr><td>5.0</td><td>5.150</td></tr> <tr><td>6.0</td><td>5.150</td></tr> <tr><td>7.0</td><td>5.150</td></tr> <tr><td>8.0</td><td>5.149</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.152	0.5	5.149	1.0	5.150	2.0	5.150	3.0	5.149	4.0	5.150	5.0	5.150	6.0	5.150	7.0	5.150	8.0	5.149
Time since start [H]	Output Voltage [V]																								
0.0	5.152																								
0.5	5.149																								
1.0	5.150																								
2.0	5.150																								
3.0	5.149																								
4.0	5.150																								
5.0	5.150																								
6.0	5.150																								
7.0	5.150																								
8.0	5.149																								

**COSEL**

Model	LDA10F-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+5.0V2A	

#### Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 170~264 V

Load Current : 0~2 A

\* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

#### 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 170~264 V

負荷電流 0~2 A

\* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$\text{* 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	50	170	0	5.154		
Minimum Voltage	-10	264	0	5.140	±8	±0.2



Model	LDA10F-5		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+5.0V2A		

### 1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

### 1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

### 2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.14	Input Volt.: 200V, Load Current:2A
Line Regulation [mV]	5	Input Volt.: 170~264V, Load Current:2A
Load Regulation [mV]	12	Input Volt.: 200V, Load Current:0~2A



Model	LDA10F-5	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	_____		

### 1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	--	--	--
(B) IEC60950	--	--	--

### 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	0.23	0.26	0.28



Model	LDA10F-5	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+5.0V2A		

### 1. Results

Pulse Width [ nS ]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

### 2. Conditions

Input Voltage : 200 V  
 Pulse Voltage : 2000 V  
 Pulse Cycle : 10 mS  
 Pulse Input Duration : 1 min. or more  
 Load : 100 %

**COSSEL**

Model	LDA10F-5	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	_____		


## 1. Graph

Remarks

Input Volt. 230 V

Load 100 %

規格 1 : [EN 55022] Class B(平均値)  
 規格 2 : [EN 55022] Class B(QP)







Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E