


## RADIATED EMISSION

Model Name :LDA150W-18  
 Model No. :  
 Serial No. :  
 Points :2  
 Detector :PEAK/QP  
 Polarization :Hori.&Vert.  
 Limit:[CISPR 22] Class B<3m>

Power Supply :230V(1 Phase) 50Hz  
 Temp. :25degC  
 Humi. :44%  
 Date :2001/8/8  
 Test Equip. :R3132,ESPC  
 Comment :




Frequency [MHz]	Meter Reading (QP) [dBuV]	Antena Factor [dBuV]	Cable & Preamp [dB]	Level (Qp) [dBuV]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]
129.256	54.2	11.2	-31.5	33.9	134	156	Hori.	40.0	6.1
60.591	61.3	4.7	-31.9	34.1	39	117	Vert.	40.0	5.9



# LINE CONDUCTION

Model Name : LDA150W-18  
 Model No. :  
 Serial No. :  
 Points : 12  
 Detector : PEAK/QP/Ave.  
 Line Mode : VA/VB  
 Limit1:[CISPR Pub22] Class B(QP)  
 Limit2:[CISPR Pub22] Class B(Ave.)

Power Supply : 230V(1 Phase) 50Hz  
 Temp. : 25degC  
 Humi. : 44%  
 Date : 2001/8/7  
 Test Equip. : R3132,ESPC  
 Comment :



Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level (Ave.) [dBuV]	Level (QP) [dBuV]	Line	Limit (Ave.) [dBuV]	Limit (QP) [dBuV]	Margin (Ave.) [dB]	Margin (QP) [dB]
1.5301	20.7	34.0	9.9	30.6	43.9	VA	46.0	56.0	15.4	12.1
1.9464	17.8	28.4	9.9	27.7	38.3	VA	46.0	56.0	18.3	17.7
0.1547	19.6	39.2	9.8	29.4	49.0	VB	55.8	65.8	26.4	16.8
0.2781	36.0	47.8	9.8	45.8	57.6	VB	50.9	60.9	5.1	3.3
0.5588	19.2	31.3	9.8	29.0	41.1	VB	46.0	56.0	17.0	14.9
0.6971	17.7	29.5	9.8	27.5	39.3	VB	46.0	56.0	18.5	16.7
1.1130	18.9	33.1	9.9	28.8	43.0	VB	46.0	56.0	17.2	13.0
1.3911	21.3	37.4	9.9	31.2	47.3	VB	46.0	56.0	14.8	8.7
1.5295	23.0	37.6	9.9	32.9	47.5	VB	46.0	56.0	13.1	8.5
1.6681	15.6	31.1	9.9	25.5	41.0	VB	46.0	56.0	20.5	15.0
1.8075	17.5	31.7	9.9	27.4	41.6	VB	46.0	56.0	18.6	14.4
1.9466	19.3	31.5	9.9	29.2	41.4	VB	46.0	56.0	16.8	14.6