

# TEST DATA OF LDA150W-24-H

(100V INPUT)

Regulated DC Power Supply  
Apr. 25. 2002

Approved by : Tooru Tsukurimichi  
Tooru Tsukurimichi Design Manager

Prepared by : Youji Kawagishi  
Youji Kawagishi Design Engineer

**コーセル株式会社**  
**COSEL CO.,LTD.**

## CONTENTS

1.	Line Regulation . . . . .	1
	静的入力変動	
2.	Input Current (by Load Current) . . . . .	2
	入力電流 (負荷特性)	
3.	Input Power (by Load Current) . . . . .	3
	入力電力 (負荷特性)	
4.	Efficiency (by Input Voltage) . . . . .	4
	効率 (入力電圧特性)	
5.	Efficiency (by Load Current) . . . . .	5
	効率 (負荷特性)	
6.	Hold-Up Time . . . . .	6
	出力保持時間	
7.	Load Regulation . . . . .	7
	静的負荷変動	
8.	Ripple Voltage (by Load Current) . . . . .	8
	リップル電圧 (負荷特性)	
9.	Ripple-Noise . . . . .	9
	リップルノイズ	
10.	Overcurrent Protection . . . . .	10
	過電流保護	
11.	Overvoltage Protection . . . . .	11
	過電圧保護	
12.	Inrush Current . . . . .	12
	突入電流	
13.	Rise and Fall Time . . . . .	13
	立上り、立下り時間	
14.	Ambient Temperature Drift . . . . .	14
	周囲温度変動	
15.	Minimum Input Voltage for Regulated Output Voltage . . . . .	15
	最低レギュレーション電圧	
16.	Ripple Voltage (by Ambient Temperature) . . . . .	16
	リップル電圧 (周囲温度特性)	
17.	Output Voltage Accuracy . . . . .	17
	定電圧精度	
18.	Figure of Testing Circuitry . . . . .	18
	測定回路図	

(Final Page 19)



<p>Model LDA150W-24-H</p> <p>Item Line Regulation 静的入力変動</p> <p>Object +24V6.3A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																
<p>1. Graph</p> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>24.247</td><td>24.245</td></tr> <tr><td>80</td><td>24.247</td><td>24.246</td></tr> <tr><td>85</td><td>24.247</td><td>24.246</td></tr> <tr><td>90</td><td>24.247</td><td>24.246</td></tr> <tr><td>100</td><td>24.247</td><td>24.246</td></tr> <tr><td>110</td><td>24.247</td><td>24.246</td></tr> <tr><td>120</td><td>24.247</td><td>24.246</td></tr> <tr><td>132</td><td>24.247</td><td>24.246</td></tr> <tr><td>140</td><td>24.247</td><td>24.246</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	24.247	24.245	80	24.247	24.246	85	24.247	24.246	90	24.247	24.246	100	24.247	24.246	110	24.247	24.246	120	24.247	24.246	132	24.247	24.246	140	24.247	24.246
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	24.247	24.245																																
80	24.247	24.246																																
85	24.247	24.246																																
90	24.247	24.246																																
100	24.247	24.246																																
110	24.247	24.246																																
120	24.247	24.246																																
132	24.247	24.246																																
140	24.247	24.246																																



Model		LDA150W-24-H	Temperature		25°C																																																			
Item		Input Current (by Load Current) 入力電流 (負荷特性)	Testing Circuitry		Figure A																																																			
Object																																																								
1. Graph		—△— Input Volt. 85V ---□--- Input Volt. 100V -·-○-·- Input Volt. 132V		2. Values																																																				
<p>Input Current [A]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.161</td><td>0.164</td><td>0.178</td></tr> <tr><td>1.00</td><td>0.806</td><td>0.733</td><td>0.642</td></tr> <tr><td>2.00</td><td>1.326</td><td>1.202</td><td>1.028</td></tr> <tr><td>3.00</td><td>1.843</td><td>1.656</td><td>1.399</td></tr> <tr><td>4.00</td><td>2.356</td><td>2.106</td><td>1.758</td></tr> <tr><td>5.00</td><td>2.855</td><td>2.552</td><td>2.124</td></tr> <tr><td>6.00</td><td>3.378</td><td>2.988</td><td>2.480</td></tr> <tr><td>6.30</td><td>3.522</td><td>3.123</td><td>2.586</td></tr> <tr><td>6.93</td><td>3.840</td><td>3.396</td><td>2.810</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.161	0.164	0.178	1.00	0.806	0.733	0.642	2.00	1.326	1.202	1.028	3.00	1.843	1.656	1.399	4.00	2.356	2.106	1.758	5.00	2.855	2.552	2.124	6.00	3.378	2.988	2.480	6.30	3.522	3.123	2.586	6.93	3.840	3.396	2.810	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0.00	0.161	0.164	0.178																																																					
1.00	0.806	0.733	0.642																																																					
2.00	1.326	1.202	1.028																																																					
3.00	1.843	1.656	1.399																																																					
4.00	2.356	2.106	1.758																																																					
5.00	2.855	2.552	2.124																																																					
6.00	3.378	2.988	2.480																																																					
6.30	3.522	3.123	2.586																																																					
6.93	3.840	3.396	2.810																																																					
—	—	—	—																																																					
—	—	—	—																																																					
Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。																																																								



Model		LDA150W-24-H	Temperature		25°C																																																			
Item		Input Power (by Load Current) 入力電力 (負荷特性)	Testing Circuitry		Figure A																																																			
Object																																																								
1. Graph		<p>—△— Input Volt. 85V</p> <p>---□--- Input Volt. 100V</p> <p>-·-○-·- Input Volt. 132V</p>	2. Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3.8</td><td>4.5</td><td>6.4</td></tr> <tr><td>1.00</td><td>32.6</td><td>33.5</td><td>35.9</td></tr> <tr><td>2.00</td><td>59.3</td><td>60.4</td><td>63.5</td></tr> <tr><td>3.00</td><td>87.0</td><td>87.7</td><td>89.8</td></tr> <tr><td>4.00</td><td>114.3</td><td>114.6</td><td>117.0</td></tr> <tr><td>5.00</td><td>141.9</td><td>141.9</td><td>143.7</td></tr> <tr><td>6.00</td><td>170.1</td><td>169.5</td><td>170.7</td></tr> <tr><td>6.30</td><td>178.5</td><td>177.9</td><td>178.8</td></tr> <tr><td>6.93</td><td>197.0</td><td>195.6</td><td>196.2</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	3.8	4.5	6.4	1.00	32.6	33.5	35.9	2.00	59.3	60.4	63.5	3.00	87.0	87.7	89.8	4.00	114.3	114.6	117.0	5.00	141.9	141.9	143.7	6.00	170.1	169.5	170.7	6.30	178.5	177.9	178.8	6.93	197.0	195.6	196.2	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0.00	3.8	4.5	6.4																																																					
1.00	32.6	33.5	35.9																																																					
2.00	59.3	60.4	63.5																																																					
3.00	87.0	87.7	89.8																																																					
4.00	114.3	114.6	117.0																																																					
5.00	141.9	141.9	143.7																																																					
6.00	170.1	169.5	170.7																																																					
6.30	178.5	177.9	178.8																																																					
6.93	197.0	195.6	196.2																																																					
—	—	—	—																																																					
—	—	—	—																																																					
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																								



Model		LDA150W-24-H	Temperature		25°C																																
Item		Efficiency (by Input Voltage) 効率 (入力電圧特性)	Testing Circuitry		Figure A																																
Object																																					
1. Graph			2. Values																																		
<p>---□--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>84.0</td><td>83.9</td></tr> <tr><td>80</td><td>84.1</td><td>84.3</td></tr> <tr><td>85</td><td>84.0</td><td>85.2</td></tr> <tr><td>90</td><td>83.8</td><td>85.4</td></tr> <tr><td>100</td><td>83.2</td><td>85.7</td></tr> <tr><td>110</td><td>82.7</td><td>85.7</td></tr> <tr><td>120</td><td>81.9</td><td>85.5</td></tr> <tr><td>132</td><td>81.1</td><td>85.2</td></tr> <tr><td>140</td><td>80.8</td><td>84.9</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	84.0	83.9	80	84.1	84.3	85	84.0	85.2	90	83.8	85.4	100	83.2	85.7	110	82.7	85.7	120	81.9	85.5	132	81.1	85.2	140	80.8	84.9
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
75	84.0	83.9																																			
80	84.1	84.3																																			
85	84.0	85.2																																			
90	83.8	85.4																																			
100	83.2	85.7																																			
110	82.7	85.7																																			
120	81.9	85.5																																			
132	81.1	85.2																																			
140	80.8	84.9																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																					




Model		LDA150W-24-H		Temperature		25°C																																																				
Item		Efficiency (by Load Current) 効率 (負荷特性)		Testing Circuitry		Figure A																																																				
Object		_____		2. Values																																																						
1. Graph				—△— Input Volt. 85V ---□--- Input Volt. 100V -·-○-·- Input Volt. 132V																																																						
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>1.00</td><td>74.3</td><td>72.3</td><td>67.6</td></tr> <tr><td>2.00</td><td>81.6</td><td>80.2</td><td>76.3</td></tr> <tr><td>3.00</td><td>83.5</td><td>82.9</td><td>80.9</td></tr> <tr><td>4.00</td><td>84.7</td><td>84.5</td><td>82.8</td></tr> <tr><td>5.00</td><td>85.3</td><td>85.3</td><td>84.2</td></tr> <tr><td>6.00</td><td>85.4</td><td>85.7</td><td>85.1</td></tr> <tr><td>6.30</td><td>85.5</td><td>85.8</td><td>85.3</td></tr> <tr><td>6.93</td><td>85.1</td><td>85.7</td><td>85.5</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	1.00	74.3	72.3	67.6	2.00	81.6	80.2	76.3	3.00	83.5	82.9	80.9	4.00	84.7	84.5	82.8	5.00	85.3	85.3	84.2	6.00	85.4	85.7	85.1	6.30	85.5	85.8	85.3	6.93	85.1	85.7	85.5	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	—	—	—																																																							
1.00	74.3	72.3	67.6																																																							
2.00	81.6	80.2	76.3																																																							
3.00	83.5	82.9	80.9																																																							
4.00	84.7	84.5	82.8																																																							
5.00	85.3	85.3	84.2																																																							
6.00	85.4	85.7	85.1																																																							
6.30	85.5	85.8	85.3																																																							
6.93	85.1	85.7	85.5																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。																																																										



Model	LDA150W-24-H
Item	Hold-Up Time 出力保持時間
Object	+24V6.3A

Temperature 25°C  
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
75	29	10
80	36	14
85	44	18
90	52	22
100	69	31
110	88	41
120	108	51
132	135	66
140	27	12

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
Note: Slanted line shows the range of the rated input voltage.


出力保持時間とは、入力電圧断から出力電圧が定電圧精度の範囲を保持しているところまでの時間。  
(注) 斜線は定格入力電圧範囲を示す。



Model	LDA150W-24-H
Item	Load Regulation 静的負荷変動
Object	+24V6.3A

Temperature 25°C  
Testing Circuitry Figure A

1. Graph  
 —△— Input Volt. 85V  
 ---□--- Input Volt. 100V  
 -·-○-·- Input Volt. 132V



2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	24.247	24.247	24.247
1.00	24.246	24.246	24.246
2.00	24.246	24.246	24.246
3.00	24.246	24.246	24.246
4.00	24.246	24.246	24.246
5.00	24.246	24.246	24.246
6.00	24.246	24.246	24.246
6.30	24.246	24.246	24.246
6.93	24.245	24.246	24.246
--	--	--	--

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。




<p>Model LDA150W-24-H</p> <p>Item Ripple Voltage (by Load Current) リップル電圧 (負荷特性)</p> <p>Object +24V6.3A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																						
<p>1. Graph</p> <p>—△— Input Volt. 85V - - ○ - - Input Volt. 132V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>1.26</td><td>15</td><td>15</td></tr> <tr><td>2.52</td><td>15</td><td>15</td></tr> <tr><td>3.78</td><td>15</td><td>20</td></tr> <tr><td>5.04</td><td>20</td><td>20</td></tr> <tr><td>6.30</td><td>20</td><td>25</td></tr> <tr><td>6.93</td><td>20</td><td>25</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	10	10	1.26	15	15	2.52	15	15	3.78	15	20	5.04	20	20	6.30	20	25	6.93	20	25	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.00	10	10																																						
1.26	15	15																																						
2.52	15	15																																						
3.78	15	20																																						
5.04	20	20																																						
6.30	20	25																																						
6.93	20	25																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p-p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p>																																								
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								



Model	LDA150W-24-H	Temperature	25°C
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A
Object	+24V6.3A		

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.00	15	20
1.26	25	35
2.52	30	40
3.78	40	45
5.04	50	55
6.30	50	65
6.93	55	65
---	---	---
---	---	---
---	---	---
---	---	---

Ripple-Noise is shown as p-p in the figure below.  
Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p-p 値で示される。  
(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line  
入力商用周期  
T2: Due to Switching  
スイッチング周期




Fig. Complex Ripple Wave Form  
図 リップル波形詳細図



<p>Model LDA150W-24-H</p> <p>Item Overcurrent Protection 過電流保護</p> <p>Object +24V6.3A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																							
<p>1. Graph</p> <p>— Input Volt. 85V</p> <p>--- Input Volt. 100V</p> <p>..... Input Volt. 132V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>24.0</td><td>11.97</td><td>11.88</td><td>11.92</td></tr> <tr><td>22.8</td><td>12.00</td><td>11.91</td><td>12.02</td></tr> <tr><td>21.6</td><td>12.01</td><td>11.95</td><td>12.06</td></tr> <tr><td>19.2</td><td>12.05</td><td>12.07</td><td>12.17</td></tr> <tr><td>16.8</td><td>12.11</td><td>12.12</td><td>12.26</td></tr> <tr><td>14.4</td><td>12.18</td><td>12.22</td><td>12.30</td></tr> <tr><td>12.0</td><td>12.25</td><td>12.25</td><td>12.32</td></tr> <tr><td>9.6</td><td>12.26</td><td>12.33</td><td>12.46</td></tr> <tr><td>7.2</td><td>12.35</td><td>12.32</td><td>12.53</td></tr> <tr><td>4.8</td><td>12.29</td><td>12.26</td><td>12.22</td></tr> <tr><td>2.4</td><td>11.65</td><td>11.56</td><td>11.43</td></tr> <tr><td>0.0</td><td>12.93</td><td>13.04</td><td>13.15</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	24.0	11.97	11.88	11.92	22.8	12.00	11.91	12.02	21.6	12.01	11.95	12.06	19.2	12.05	12.07	12.17	16.8	12.11	12.12	12.26	14.4	12.18	12.22	12.30	12.0	12.25	12.25	12.32	9.6	12.26	12.33	12.46	7.2	12.35	12.32	12.53	4.8	12.29	12.26	12.22	2.4	11.65	11.56	11.43	0.0	12.93	13.04	13.15
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																						
24.0	11.97	11.88	11.92																																																						
22.8	12.00	11.91	12.02																																																						
21.6	12.01	11.95	12.06																																																						
19.2	12.05	12.07	12.17																																																						
16.8	12.11	12.12	12.26																																																						
14.4	12.18	12.22	12.30																																																						
12.0	12.25	12.25	12.32																																																						
9.6	12.26	12.33	12.46																																																						
7.2	12.35	12.32	12.53																																																						
4.8	12.29	12.26	12.22																																																						
2.4	11.65	11.56	11.43																																																						
0.0	12.93	13.04	13.15																																																						




Model	LDA150W-24-H
Item	Overvoltage Protection 過電圧保護
Object	+24V6.3A

Testing Circuitry Figure A

1. Graph

—△— Input Volt. 85V  
 ---□--- Input Volt. 100V  
 -·-○-·- Input Volt. 132V



2. Values


Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	29.23	29.23	29.23
-10	29.41	29.41	29.41
0	29.65	29.65	29.65
10	29.82	29.82	29.82
20	30.06	30.06	30.06
25	30.18	30.18	30.18
30	30.30	30.30	30.30
40	30.48	30.48	30.48
50	30.71	30.71	30.71
60	30.89	30.89	30.89
—	—	—	—

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。



Model	LDA150W-24-H	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	_____		



Input Voltage 100 V  
 Frequency 60 Hz  
 Load 100 %  
 Inrush Current  
 ① 21.2 [A]  
 ② 8.0 [A]






Model	LDA150W-24-H	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+24V6.3A		


1. Graph

Input Volt. 85 V



2. Values

Load	Time	[mS]				
		T d	T r	T s	T h	T f
50 %		136.8	25.8	162.5	42.6	47.5
100 %		135.0	25.3	160.3	17.6	29.0






Model	LDA150W-24-H
Item	Ambient Temperature Drift 周囲温度変動
Object	+24V6.3A

Testing Circuitry Figure A

1. Graph

—△— Input Volt. 85V  
 ---□--- Input Volt. 100V  
 -·-○-·- Input Volt. 132V



2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	24.235	24.236	24.235
-10	24.239	24.240	24.240
0	24.242	24.243	24.243
10	24.245	24.245	24.246
20	24.248	24.249	24.249
25	24.253	24.253	24.254
30	24.256	24.256	24.256
40	24.254	24.254	24.254
50	24.249	24.249	24.249
60	24.239	24.240	24.239
--	--	--	--

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。



Model	LDA150W-24-H
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+24V6.3A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	54	63
-10	54	62
0	54	62
10	53	62
20	53	62
25	53	62
30	53	62
40	53	62
50	53	62
60	53	62
--	--	--

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。



Model	LDA150W-24-H
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+24V6.3A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	30	50
-10	20	35
0	15	30
10	15	25
20	15	20
25	15	20
30	15	20
40	15	20
50	10	20
60	10	20
--	--	--

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。



Model		LDA150W-24-H	Testing Circuitry Figure A
Item		Output Voltage Accuracy 定電圧精度	
Object		+24V6.3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 ~ 40°C

Input Voltage : 85 ~ 132V

Load Current : 0 ~ 6.3A

\* Output Voltage Accuracy =  $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage}}{\text{Rated Output Voltage}} \times 100$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -10 ~ 40°C

入力電圧 : 85 ~ 132V

負荷電流 : 0 ~ 6.3A

\* 定電圧精度(変動値) =  $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

\* 定電圧精度(変動率) =  $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	132	0	24.256	±8	±0.1
Minimum Voltage	-10	85	6.3	24.240		




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950 )




Figure C




Figure D




Figure E