


RADIATED EMISSION

Model Name :LDA150W-48
 Model No. :
 Serial No. :
 Points :4
 Detector :PEAK/QP
 Polarization :Hori.&Vert.
 Limit:[CISPR 22] Class B<3m>

Power Supply :230V(1 Phase) 50Hz
 Temp. :25degC
 Humi. :44%
 Date :2001/10/19
 Test Equip. :R3132,ESPC
 Comment :




Frequency [MHz]	Meter Reading (QP) [dBuV]	Antena Factor [dBuV]	Cable & Preamp [dB]	Level (Qp) [dBuV]	Angle [$^{\circ}$]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]
958.998	22.6	25.1	-23.7	24.0	5	138	Hori.	47.0	23.0
52.253	45.7	6.2	-23.5	28.4	223	104	Vert.	40.0	11.6
52.708	43.4	6.1	-23.4	26.1	203	110	Vert.	40.0	13.9
79.685	33.3	6.6	-24.0	15.9	56	113	Vert.	40.0	24.1



LINE CONDUCTION

Model Name :LDA150W-48
 Model No. :
 Serial No. :
 Points :2
 Detector :PEAK/QP/Ave.
 Line Mode :VA/VB
 Limit1:[CISPR Pub22] Class B(QP)
 Limit2:[CISPR Pub22] Class B(Ave.)

Power Supply :230V(1 Phase) 50Hz
 Temp. :25degC
 Humi. :44%
 Date :2001/10/19
 Test Equip. :R3132,ESPC
 Comment :



Frequency [MHz]	Meter Reading (QP) [dBuV]	Meter Reading (Ave.) [dBuV]	Factor [dB]	Level (QP) [dBuV]	Level (Ave.) [dBuV]	Line	Limit (QP) [dBuV]	Limit (Ave.) [dBuV]	Margin (QP) [dB]	Margin (Ave.) [dB]
0.2780	46.1	40.3	10.0	56.1	50.3	VB	60.9	50.9	4.8	0.6
4.1678	36.8	34.1	10.3	47.1	44.4	VB	56.0	46.0	8.9	1.6