



TEST DATA OF LDA150W-48 (100V INPUT)

Regulated DC Power Supply
Nov. 5. 2001

Approved by : M. Miyamoto
Design Manager

Prepared by : D. Ishibashi
Design Engineer

コーワセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的の入力変動	
2. Efficiency (by Input Voltage)	2
効率 (入力電圧特性)	
3. Efficiency (by Load Current)	3
効率 (負荷特性)	
4. Hold-Up Time	4
出力保持時間	
5. Instantaneous Interruption Compensation	5
瞬時停電保障	
6. Load Regulation	6
静的の負荷変動	
7. Ripple Voltage (by Load Current)	7
リップル電圧 (負荷特性)	
8. Ripple-Noise	8
リップルノイズ	
9. Overcurrent Protection	9
過電流保護	
10. Overvoltage Protection	10
過電圧保護	
11. Inrush Current	11
突入電流	
12. Rise and Fall Time	12
立ち上り、立下り時間	
13. Ambient Temperature Drift	13
周囲温度変動	
14. Minimum Input Voltage for Regulated Output Voltage	14
最低レギュレーション電圧	
15. Ripple Voltage (by Ambient Temperature)	15
リップル電圧 (周囲温度特性)	
16. Output Voltage Accuracy	16
定電圧精度	
17. Figure of Testing Circuitry	17
測定回路図	

(Final Page 17)


COSEL

Model	LDA150W-48																																	
Item	Line Regulation 静的入力変動	Temperature Testing Circuitry 25°C Figure A																																
Object	+48V3A																																	
1. Graph																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>48.626</td> <td>48.625</td> </tr> <tr> <td>80</td> <td>48.627</td> <td>48.625</td> </tr> <tr> <td>85</td> <td>48.627</td> <td>48.625</td> </tr> <tr> <td>90</td> <td>48.626</td> <td>48.625</td> </tr> <tr> <td>100</td> <td>48.626</td> <td>48.624</td> </tr> <tr> <td>110</td> <td>48.625</td> <td>48.623</td> </tr> <tr> <td>120</td> <td>48.625</td> <td>48.622</td> </tr> <tr> <td>132</td> <td>48.624</td> <td>48.621</td> </tr> <tr> <td>140</td> <td>48.623</td> <td>48.620</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	48.626	48.625	80	48.627	48.625	85	48.627	48.625	90	48.626	48.625	100	48.626	48.624	110	48.625	48.623	120	48.625	48.622	132	48.624	48.621	140	48.623	48.620
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	48.626	48.625																																
80	48.627	48.625																																
85	48.627	48.625																																
90	48.626	48.625																																
100	48.626	48.624																																
110	48.625	48.623																																
120	48.625	48.622																																
132	48.624	48.621																																
140	48.623	48.620																																

COSEL

Model	LDA150W-48																																	
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Temperature Testing Circuitry 25°C Figure A																																
Object	<hr/>																																	
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (Dashed line with squares) Load 100% (Solid line with triangles) 																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>83.2</td><td>84.5</td></tr> <tr><td>80</td><td>83.8</td><td>85.4</td></tr> <tr><td>85</td><td>83.9</td><td>86.0</td></tr> <tr><td>90</td><td>84.2</td><td>86.4</td></tr> <tr><td>100</td><td>84.1</td><td>86.6</td></tr> <tr><td>110</td><td>83.5</td><td>86.6</td></tr> <tr><td>120</td><td>82.9</td><td>86.3</td></tr> <tr><td>132</td><td>81.3</td><td>86.0</td></tr> <tr><td>140</td><td>80.5</td><td>85.7</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	83.2	84.5	80	83.8	85.4	85	83.9	86.0	90	84.2	86.4	100	84.1	86.6	110	83.5	86.6	120	82.9	86.3	132	81.3	86.0	140	80.5	85.7
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	83.2	84.5																																
80	83.8	85.4																																
85	83.9	86.0																																
90	84.2	86.4																																
100	84.1	86.6																																
110	83.5	86.6																																
120	82.9	86.3																																
132	81.3	86.0																																
140	80.5	85.7																																

COSEL


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	—	—	—
0.6	76.0	74.9	69.9
1.2	82.9	82.6	79.3
1.8	85.1	85.3	83.1
2.4	86.2	86.8	85.4
3.0	86.5	86.9	86.1
3.3	86.2	86.6	86.2
---	—	—	—
---	—	—	—
---	—	—	—
---	—	—	—

COSEL


Model	LDA150W-48																																	
Item	Hold-Up Time 出力保持時間	Temperature Testing Circuitry 25°C Figure A																																
Object	+48V3A																																	
1. Graph																																		
<p>Legend: - - - □ - - - Load 50% —△— Load 100% </p>																																		
<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>26</td> <td>9</td> </tr> <tr> <td>80</td> <td>33</td> <td>13</td> </tr> <tr> <td>85</td> <td>41</td> <td>17</td> </tr> <tr> <td>90</td> <td>49</td> <td>22</td> </tr> <tr> <td>100</td> <td>66</td> <td>31</td> </tr> <tr> <td>110</td> <td>85</td> <td>41</td> </tr> <tr> <td>120</td> <td>106</td> <td>52</td> </tr> <tr> <td>132</td> <td>133</td> <td>67</td> </tr> <tr> <td>140</td> <td>153</td> <td>77</td> </tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	26	9	80	33	13	85	41	17	90	49	22	100	66	31	110	85	41	120	106	52	132	133	67	140	153	77
Input Voltage [V]	Hold-Up Time [mS]																																	
	Load 50%	Load 100%																																
75	26	9																																
80	33	13																																
85	41	17																																
90	49	22																																
100	66	31																																
110	85	41																																
120	106	52																																
132	133	67																																
140	153	77																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が定電圧精度の範囲を保持しているところまでの時間。 (注) 斜線は定格入力電圧範囲を示す。</p>																																		

COSEL

Model	LDA150W-48																																																				
Item	Instantaneous Interruption Compensation 瞬時停電保障	Temperature Testing Circuitry	25°C Figure A																																																		
Object	+48V3A																																																				
1. Graph	<p>—△— Input Volt. 85V - - -□--- Input Volt. 100V - - ○--- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>85V [mS]</th> <th>100V [mS]</th> <th>132V [mS]</th> </tr> </thead> <tbody> <tr><td>0.6</td><td>47</td><td>70</td><td>131</td></tr> <tr><td>1.2</td><td>47</td><td>70</td><td>131</td></tr> <tr><td>1.8</td><td>47</td><td>70</td><td>131</td></tr> <tr><td>2.4</td><td>30</td><td>47</td><td>97</td></tr> <tr><td>3.0</td><td>19</td><td>37</td><td>78</td></tr> </tbody> </table>		Load Current [A]	85V [mS]	100V [mS]	132V [mS]	0.6	47	70	131	1.2	47	70	131	1.8	47	70	131	2.4	30	47	97	3.0	19	37	78																											
Load Current [A]	85V [mS]	100V [mS]	132V [mS]																																																		
0.6	47	70	131																																																		
1.2	47	70	131																																																		
1.8	47	70	131																																																		
2.4	30	47	97																																																		
3.0	19	37	78																																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.6</td><td>47</td><td>70</td><td>131</td></tr> <tr><td>1.2</td><td>47</td><td>70</td><td>131</td></tr> <tr><td>1.8</td><td>47</td><td>70</td><td>131</td></tr> <tr><td>2.4</td><td>30</td><td>47</td><td>97</td></tr> <tr><td>3.0</td><td>19</td><td>37</td><td>78</td></tr> <tr><td>3.3</td><td>16</td><td>30</td><td>71</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	—	—	—	0.6	47	70	131	1.2	47	70	131	1.8	47	70	131	2.4	30	47	97	3.0	19	37	78	3.3	16	30	71	---	—	—	—	---	—	—	—	---	—	—	—	---	—	—	—
Load Current [A]	Time [mS]																																																				
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																		
0.0	—	—	—																																																		
0.6	47	70	131																																																		
1.2	47	70	131																																																		
1.8	47	70	131																																																		
2.4	30	47	97																																																		
3.0	19	37	78																																																		
3.3	16	30	71																																																		
---	—	—	—																																																		
---	—	—	—																																																		
---	—	—	—																																																		
---	—	—	—																																																		

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	48.629	48.630	48.629
0.6	48.625	48.626	48.621
1.2	48.626	48.625	48.623
1.8	48.625	48.624	48.622
2.4	48.624	48.623	48.621
3.0	48.624	48.623	48.620
3.3	48.624	48.623	48.620
---	—	—	—
---	—	—	—
---	—	—	—

COSEL


Model	LDA150W-48																																						
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	Temperature Testing Circuitry 25°C Figure A																																					
Object	+48V3A																																						
1. Graph																																							
<p>—△— Input Volt. 85V ---○--- Input Volt. 132V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 85V)</th> <th>Ripple Voltage [mV] (Input Volt. 132V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.6</td><td>25</td><td>30</td></tr> <tr><td>1.2</td><td>30</td><td>30</td></tr> <tr><td>1.8</td><td>30</td><td>30</td></tr> <tr><td>2.4</td><td>35</td><td>30</td></tr> <tr><td>3.0</td><td>40</td><td>35</td></tr> <tr><td>3.3</td><td>45</td><td>35</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)	0.0	10	10	0.6	25	30	1.2	30	30	1.8	30	30	2.4	35	30	3.0	40	35	3.3	45	35														
Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)																																					
0.0	10	10																																					
0.6	25	30																																					
1.2	30	30																																					
1.8	30	30																																					
2.4	35	30																																					
3.0	40	35																																					
3.3	45	35																																					
2. Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.6</td><td>25</td><td>30</td></tr> <tr><td>1.2</td><td>30</td><td>30</td></tr> <tr><td>1.8</td><td>30</td><td>30</td></tr> <tr><td>2.4</td><td>35</td><td>30</td></tr> <tr><td>3.0</td><td>40</td><td>35</td></tr> <tr><td>3.3</td><td>45</td><td>35</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	10	10	0.6	25	30	1.2	30	30	1.8	30	30	2.4	35	30	3.0	40	35	3.3	45	35	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 85 [V]	Input Volt. 132 [V]																																					
0.0	10	10																																					
0.6	25	30																																					
1.2	30	30																																					
1.8	30	30																																					
2.4	35	30																																					
3.0	40	35																																					
3.3	45	35																																					
--	--	--																																					
--	--	--																																					
--	--	--																																					
--	--	--																																					
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p – p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																							

COSEL

Model	LDA150W-48
Item	Ripple-Noise リップルノイズ
Object	+48V3A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	15	15
0.6	35	35
1.2	40	40
1.8	50	50
2.4	65	55
3.0	70	60
3.3	75	65
--	--	--
--	--	--
--	--	--
--	--	--

Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。
(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期





Fig. Complex Ripple Wave Form
図 リップル波形詳細図

COSEL

Model	LDA150W-48
Item	Overcurrent Protection 過電流保護
Object	+48V3A



Note: Slanted line shows the range of the rated load current.


(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
48.0	4.09	4.08	4.16
45.6	4.10	4.10	4.16
43.2	4.11	4.12	4.17
38.4	4.14	4.14	4.21
33.6	4.15	4.17	4.24
28.8	4.19	4.20	4.24
24.0	4.18	4.21	4.29
19.2	4.21	4.24	4.31
14.4	4.22	4.26	4.30
9.6	4.16	4.14	4.11
4.8	3.94	3.96	3.99
0.0	4.29	4.36	4.73

COSEL

Model	LDA150W-48																																																					
Item	Overvoltage Protection 過電圧保護																																																					
Object	+48V3A																																																					
1. Graph	<p>—△— Input Volt. 85V - - -□- - Input Volt. 100V - - ○- - Input Volt. 132V</p>  <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>59.03</td> <td>59.15</td> <td>59.15</td> </tr> <tr> <td>-10</td> <td>59.61</td> <td>59.61</td> <td>59.61</td> </tr> <tr> <td>0</td> <td>60.15</td> <td>60.21</td> <td>60.20</td> </tr> <tr> <td>10</td> <td>60.62</td> <td>60.62</td> <td>60.74</td> </tr> <tr> <td>20</td> <td>61.21</td> <td>61.21</td> <td>61.21</td> </tr> <tr> <td>25</td> <td>61.45</td> <td>61.45</td> <td>61.45</td> </tr> <tr> <td>30</td> <td>61.74</td> <td>61.74</td> <td>61.74</td> </tr> <tr> <td>40</td> <td>62.21</td> <td>62.21</td> <td>62.21</td> </tr> <tr> <td>50</td> <td>62.74</td> <td>62.74</td> <td>62.74</td> </tr> <tr> <td>60</td> <td>63.26</td> <td>63.26</td> <td>63.26</td> </tr> <tr> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	59.03	59.15	59.15	-10	59.61	59.61	59.61	0	60.15	60.21	60.20	10	60.62	60.62	60.74	20	61.21	61.21	61.21	25	61.45	61.45	61.45	30	61.74	61.74	61.74	40	62.21	62.21	62.21	50	62.74	62.74	62.74	60	63.26	63.26	63.26	--	--	--	--
Ambient Temperature [°C]	Operating Point [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	59.03	59.15	59.15																																																			
-10	59.61	59.61	59.61																																																			
0	60.15	60.21	60.20																																																			
10	60.62	60.62	60.74																																																			
20	61.21	61.21	61.21																																																			
25	61.45	61.45	61.45																																																			
30	61.74	61.74	61.74																																																			
40	62.21	62.21	62.21																																																			
50	62.74	62.74	62.74																																																			
60	63.26	63.26	63.26																																																			
--	--	--	--																																																			

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model LDA150W-48

Item Inrush Current
突入電流


Object _____

Temperature 25°C
Testing Circuitry Figure AInput
Current
[20A/div]

Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current

(1) 12.8 [A]

(2) 13.6 [A]




COSSEL

Model	LDA150W-48
Item	Rise and Fall Time 立上り、立下り時間
Object	+48V3A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values


Load \ Time	T d	T r	T s	T h	T f
50 %	176.3	40.3	216.5	43.9	56.3
100 %	176.3	42.8	219.0	16.8	27.2

[mS]



COSEL

Model	LDA150W-48
Item	Ambient Temperature Drift 周囲温度変動
Object	+48V3A



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values


Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-30	48.653	48.653	48.651
-20	48.652	48.652	48.649
-10	48.652	48.652	48.649
0	48.654	48.654	48.651
10	48.658	48.657	48.655
25	48.661	48.661	48.658
30	48.656	48.656	48.653
40	48.645	48.645	48.641
55	48.614	48.613	48.609
60	48.595	48.594	48.590
--	—	—	—

COSEL

Model	LDA150W-48
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+48V3A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	55	62
-20	54	62
-10	54	62
0	54	62
10	54	62
25	54	62
30	54	62
40	54	62
55	54	62
60	54	62
--	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model	LDA150W-48																																								
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A																																							
Object	+48V3A																																								
1. Graph																																									
		2. Values																																							
<p>Ambient Temperature [°C]</p> <p>Input Volt. 100V</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>65</td> <td>70</td> </tr> <tr> <td>-10</td> <td>55</td> <td>60</td> </tr> <tr> <td>0</td> <td>50</td> <td>55</td> </tr> <tr> <td>10</td> <td>40</td> <td>45</td> </tr> <tr> <td>20</td> <td>35</td> <td>40</td> </tr> <tr> <td>25</td> <td>35</td> <td>40</td> </tr> <tr> <td>30</td> <td>30</td> <td>35</td> </tr> <tr> <td>40</td> <td>25</td> <td>30</td> </tr> <tr> <td>50</td> <td>25</td> <td>30</td> </tr> <tr> <td>60</td> <td>25</td> <td>30</td> </tr> <tr> <td>--</td> <td>—</td> <td>—</td> </tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-20	65	70	-10	55	60	0	50	55	10	40	45	20	35	40	25	35	40	30	30	35	40	25	30	50	25	30	60	25	30	--	—	—
Ambient Temperature [°C]	Ripple Voltage [mV]																																								
	Load 50%	Load 100%																																							
-20	65	70																																							
-10	55	60																																							
0	50	55																																							
10	40	45																																							
20	35	40																																							
25	35	40																																							
30	30	35																																							
40	25	30																																							
50	25	30																																							
60	25	30																																							
--	—	—																																							



Model	LDA150W-48
Item	Output Voltage Accuracy 定電圧精度
Object	+48V3A

Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 ~ 40°C

Input Voltage : 85 ~ 132V

Load Current : 0 ~ 3A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -10 ~ 40°C

入力電圧 : 85 ~ 132V

負荷電流 : 0 ~ 3A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	100	0	48. 667		
Minimum Voltage	40	132	3	48. 638	±15	±0. 1




Figure A