

COSEL

TEST DATA OF LDA150W-5
(200V INPUT)

Regulated DC Power Supply

Dec. 1, 1999

Approved by : K. Yamaguchi
Design Manager

Prepared by : T. Ashihara
Design Engineer

コーワセル株式会社

COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Overvoltage Protection	12
過電圧保護	
13. Inrush Current	13
突入電流	
14. Dynamic Load Response	14
動的負荷変動	
15. Rise and Fall Time	15
立ち上り、立ち下り時間	
16. Ambient Temperature Drift	16
周囲温度変動	
17. Minimum Input Voltage for Regulated Output Voltage	17
最低レギュレーション電圧	
18. Ripple Voltage (by Ambient Temperature)	18
リップル電圧 (周囲温度特性)	
19. Time Lapse Drift	19
経時ドリフト	
20. Output Voltage Accuracy	20
定電圧精度	
21. Condensation	21
結露特性	
22. Leakage Current	22
漏洩電流	
23. Line Noise Tolerance	23
入力雑音耐量	
24. Conducted Emission	24
雑音端子電圧	
25. Figure of Testing Circuitry	25
測定回路図	

(Final Page 26)

COSEL

Model	LDA150W-5	Temperature Testing Circuitry	25°C Figure A																															
Item	Line Regulation 静的入力変動																																	
Object	+5.0V30A																																	
1. Graph																																		
			2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>5.145</td><td>5.143</td></tr> <tr><td>160</td><td>5.145</td><td>5.143</td></tr> <tr><td>170</td><td>5.145</td><td>5.143</td></tr> <tr><td>180</td><td>5.145</td><td>5.143</td></tr> <tr><td>200</td><td>5.145</td><td>5.143</td></tr> <tr><td>220</td><td>5.145</td><td>5.143</td></tr> <tr><td>240</td><td>5.145</td><td>5.143</td></tr> <tr><td>264</td><td>5.145</td><td>5.143</td></tr> <tr><td>280</td><td>5.145</td><td>5.143</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	150	5.145	5.143	160	5.145	5.143	170	5.145	5.143	180	5.145	5.143	200	5.145	5.143	220	5.145	5.143	240	5.145	5.143	264	5.145	5.143	280	5.145	5.143
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
150	5.145	5.143																																
160	5.145	5.143																																
170	5.145	5.143																																
180	5.145	5.143																																
200	5.145	5.143																																
220	5.145	5.143																																
240	5.145	5.143																																
264	5.145	5.143																																
280	5.145	5.143																																
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																		

COSEL

Model	LDA150W-5																																																									
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Output	——																																																									
1. Graph	<p>Input Volt. 170V Input Volt. 200V Input Volt. 264V</p> <p>[A]</p> <p>Load Current [A]</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>170[V]</th> <th>200[V]</th> <th>264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.072</td><td>0.082</td><td>0.100</td></tr> <tr><td>6</td><td>0.454</td><td>0.413</td><td>0.359</td></tr> <tr><td>12</td><td>0.822</td><td>0.732</td><td>0.609</td></tr> <tr><td>18</td><td>1.212</td><td>1.071</td><td>0.877</td></tr> <tr><td>24</td><td>1.607</td><td>1.418</td><td>1.154</td></tr> <tr><td>30</td><td>1.996</td><td>1.761</td><td>1.430</td></tr> <tr><td>33</td><td>2.197</td><td>1.940</td><td>1.575</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			170[V]	200[V]	264[V]	0	0.072	0.082	0.100	6	0.454	0.413	0.359	12	0.822	0.732	0.609	18	1.212	1.071	0.877	24	1.607	1.418	1.154	30	1.996	1.761	1.430	33	2.197	1.940	1.575	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	170[V]	200[V]	264[V]																																																							
0	0.072	0.082	0.100																																																							
6	0.454	0.413	0.359																																																							
12	0.822	0.732	0.609																																																							
18	1.212	1.071	0.877																																																							
24	1.607	1.418	1.154																																																							
30	1.996	1.761	1.430																																																							
33	2.197	1.940	1.575																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

COSEL

Model	LDA150W-5	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Input Power (by Load Current) 入力電力（負荷特性）																																																									
Output	—																																																									
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> △ Input Volt. 170V □ Input Volt. 200V ○ Input Volt. 264V <p>Note: Slanted line shows the range of the rated load current</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.10</td><td>4.00</td><td>6.10</td></tr> <tr><td>6</td><td>40.30</td><td>41.30</td><td>43.90</td></tr> <tr><td>12</td><td>76.50</td><td>77.20</td><td>79.50</td></tr> <tr><td>18</td><td>113.50</td><td>113.90</td><td>115.70</td></tr> <tr><td>24</td><td>151.80</td><td>151.80</td><td>153.10</td></tr> <tr><td>30</td><td>190.70</td><td>190.20</td><td>190.90</td></tr> <tr><td>33</td><td>211.10</td><td>210.20</td><td>210.40</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	3.10	4.00	6.10	6	40.30	41.30	43.90	12	76.50	77.20	79.50	18	113.50	113.90	115.70	24	151.80	151.80	153.10	30	190.70	190.20	190.90	33	211.10	210.20	210.40	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0	3.10	4.00	6.10																																																							
6	40.30	41.30	43.90																																																							
12	76.50	77.20	79.50																																																							
18	113.50	113.90	115.70																																																							
24	151.80	151.80	153.10																																																							
30	190.70	190.20	190.90																																																							
33	211.10	210.20	210.40																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

COSEL

Model	LDA150W-5		Temperature Testing Circuitry 25°C Figure A																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)																																		
Object	—																																		
1. Graph																																			
<p>The graph plots Efficiency [%] from 0 to 86 against Input Voltage [V] from 0 to 300. Two sets of data points are shown: Load 50% (squares) and Load 100% (triangles). Both series show efficiency remaining relatively constant around 80-82% across the input voltage range. A slanted line on the graph indicates the rated input voltage range.</p>																																			
2. Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>82.1</td><td>81.0</td></tr> <tr><td>160</td><td>82.1</td><td>81.5</td></tr> <tr><td>170</td><td>82.1</td><td>81.8</td></tr> <tr><td>180</td><td>81.7</td><td>81.9</td></tr> <tr><td>200</td><td>81.5</td><td>82.1</td></tr> <tr><td>220</td><td>81.1</td><td>82.1</td></tr> <tr><td>240</td><td>80.6</td><td>82.0</td></tr> <tr><td>264</td><td>80.0</td><td>81.9</td></tr> <tr><td>280</td><td>79.5</td><td>81.6</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	150	82.1	81.0	160	82.1	81.5	170	82.1	81.8	180	81.7	81.9	200	81.5	82.1	220	81.1	82.1	240	80.6	82.0	264	80.0	81.9	280	79.5	81.6
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
150	82.1	81.0																																	
160	82.1	81.5																																	
170	82.1	81.8																																	
180	81.7	81.9																																	
200	81.5	82.1																																	
220	81.1	82.1																																	
240	80.6	82.0																																	
264	80.0	81.9																																	
280	79.5	81.6																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA150W-5	Temperature	25°C																																																							
Item	Efficiency (by Load Current) 効率(負荷特性)	Testing Circuitry	Figure A																																																							
Output	_____																																																									
1. Graph																																																										
<p>The graph plots Efficiency [%] on the y-axis (0 to 90) against Load Current [A] on the x-axis (0 to 40). Three data series are shown for Input Volt. 170V (triangles), Input Volt. 200V (squares), and Input Volt. 264V (circles). All series show efficiency starting around 75% at 10A, rising to about 80% at 20A, and remaining relatively flat up to 30A. A slanted line from the origin marks the rated load current range.</p>			2. Values																																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>6</td><td>76.7</td><td>75.5</td><td>71.1</td></tr> <tr><td>12</td><td>81.1</td><td>80.6</td><td>78.3</td></tr> <tr><td>18</td><td>82.0</td><td>82.0</td><td>80.8</td></tr> <tr><td>24</td><td>82.1</td><td>82.1</td><td>81.5</td></tr> <tr><td>30</td><td>81.6</td><td>82.0</td><td>81.6</td></tr> <tr><td>33</td><td>81.3</td><td>81.6</td><td>81.6</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	6	76.7	75.5	71.1	12	81.1	80.6	78.3	18	82.0	82.0	80.8	24	82.1	82.1	81.5	30	81.6	82.0	81.6	33	81.3	81.6	81.6	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
6	76.7	75.5	71.1																																																							
12	81.1	80.6	78.3																																																							
18	82.0	82.0	80.8																																																							
24	82.1	82.1	81.5																																																							
30	81.6	82.0	81.6																																																							
33	81.3	81.6	81.6																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA150W-5		Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																			
Object	+5.0V 30A																																			
1. Graph																																				
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>28</td><td>12</td></tr> <tr><td>160</td><td>35</td><td>16</td></tr> <tr><td>170</td><td>42</td><td>19</td></tr> <tr><td>180</td><td>50</td><td>23</td></tr> <tr><td>200</td><td>66</td><td>32</td></tr> <tr><td>220</td><td>85</td><td>41</td></tr> <tr><td>240</td><td>105</td><td>51</td></tr> <tr><td>264</td><td>131</td><td>65</td></tr> <tr><td>280</td><td>150</td><td>75</td></tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	150	28	12	160	35	16	170	42	19	180	50	23	200	66	32	220	85	41	240	105	51	264	131	65	280	150	75
Input Voltage [V]	Hold-Up Time [ms]																																			
	Load 50%	Load 100%																																		
150	28	12																																		
160	35	16																																		
170	42	19																																		
180	50	23																																		
200	66	32																																		
220	85	41																																		
240	105	51																																		
264	131	65																																		
280	150	75																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。 (注)斜線は定格入力電圧範囲を示す。</p>																																				

COSEL

Model	LDA150W-5	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																				
Object	+5.0V 30A																																																				
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 170 V (△) Input Volt. 200 V (□) Input Volt. 264 V (○) <p>Y-axis: Instantaneous Compensation Time [mS]</p> <p>X-axis: Load Current [A]</p>	2. Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>170 [V]</th> <th>200 [V]</th> <th>264 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>6</td><td>96</td><td>139</td><td>256</td></tr> <tr><td>12</td><td>47</td><td>73</td><td>139</td></tr> <tr><td>18</td><td>29</td><td>48</td><td>97</td></tr> <tr><td>24</td><td>19</td><td>31</td><td>73</td></tr> <tr><td>30</td><td>14</td><td>22</td><td>56</td></tr> <tr><td>33</td><td>12</td><td>21</td><td>48</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Time [mS]			170 [V]	200 [V]	264 [V]	0	—	—	—	6	96	139	256	12	47	73	139	18	29	48	97	24	19	31	73	30	14	22	56	33	12	21	48	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																				
	170 [V]	200 [V]	264 [V]																																																		
0	—	—	—																																																		
6	96	139	256																																																		
12	47	73	139																																																		
18	29	48	97																																																		
24	19	31	73																																																		
30	14	22	56																																																		
33	12	21	48																																																		
—	—	—	—																																																		
—	—	—	—																																																		
—	—	—	—																																																		
—	—	—	—																																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																					
<p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																					

COSEL


Model	LDA150W-5	Temperature	25°C																																															
Item	Load Regulation 靜的負荷変動	Testing Circuitry	Figure A																																															
Object	+5.0V30A																																																	
1. Graph		2. Values																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>5.148</td><td>5.148</td><td>5.148</td></tr> <tr><td>6</td><td>5.147</td><td>5.147</td><td>5.147</td></tr> <tr><td>12</td><td>5.146</td><td>5.146</td><td>5.146</td></tr> <tr><td>18</td><td>5.145</td><td>5.145</td><td>5.145</td></tr> <tr><td>24</td><td>5.144</td><td>5.144</td><td>5.144</td></tr> <tr><td>30</td><td>5.143</td><td>5.143</td><td>5.143</td></tr> <tr><td>33</td><td>5.143</td><td>5.143</td><td>5.143</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	5.148	5.148	5.148	6	5.147	5.147	5.147	12	5.146	5.146	5.146	18	5.145	5.145	5.145	24	5.144	5.144	5.144	30	5.143	5.143	5.143	33	5.143	5.143	5.143	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																															
0	5.148	5.148	5.148																																															
6	5.147	5.147	5.147																																															
12	5.146	5.146	5.146																																															
18	5.145	5.145	5.145																																															
24	5.144	5.144	5.144																																															
30	5.143	5.143	5.143																																															
33	5.143	5.143	5.143																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															
Note: Slanted line shows the range of the rated load current.																																																		
(注)斜線は定格負荷電流範囲を示す。																																																		

COSEL

Model	LDA150W-5	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																							
Object	+5.0V 30A																																							
1. Graph	<p style="text-align: center;">□ Input Volt. 170V [mV] ▲ Input Volt. 264V</p>	2. Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 170 [V]</th> <th>Input Volt. 264 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>4.00</td><td>20</td><td>25</td></tr> <tr><td>8.00</td><td>25</td><td>30</td></tr> <tr><td>12.00</td><td>30</td><td>35</td></tr> <tr><td>16.00</td><td>35</td><td>40</td></tr> <tr><td>20.00</td><td>35</td><td>40</td></tr> <tr><td>24.00</td><td>40</td><td>40</td></tr> <tr><td>28.00</td><td>40</td><td>45</td></tr> <tr><td>30.00</td><td>45</td><td>50</td></tr> <tr><td>33.00</td><td>50</td><td>50</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	10	10	4.00	20	25	8.00	25	30	12.00	30	35	16.00	35	40	20.00	35	40	24.00	40	40	28.00	40	45	30.00	45	50	33.00	50	50	—	—	—
Load Current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]																																						
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																						
0.00	10	10																																						
4.00	20	25																																						
8.00	25	30																																						
12.00	30	35																																						
16.00	35	40																																						
20.00	35	40																																						
24.00	40	40																																						
28.00	40	45																																						
30.00	45	50																																						
33.00	50	50																																						
—	—	—																																						
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図p-p値で示される。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>		<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p>																																						
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL

Model	LDA150W-5	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	+5.0V 30A																																								
1. Graph	<p style="text-align: center;">□ Input Volt. 170V [mV] ▲ Input Volt. 264V</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 170 [V]</th> <th>Input Volt. 264 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>25</td></tr> <tr><td>4.00</td><td>40</td><td>45</td></tr> <tr><td>8.00</td><td>45</td><td>50</td></tr> <tr><td>12.00</td><td>50</td><td>60</td></tr> <tr><td>16.00</td><td>55</td><td>65</td></tr> <tr><td>20.00</td><td>55</td><td>70</td></tr> <tr><td>24.00</td><td>55</td><td>75</td></tr> <tr><td>28.00</td><td>60</td><td>80</td></tr> <tr><td>30.00</td><td>70</td><td>80</td></tr> <tr><td>33.00</td><td>75</td><td>80</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.00	20	25	4.00	40	45	8.00	45	50	12.00	50	60	16.00	55	65	20.00	55	70	24.00	55	75	28.00	60	80	30.00	70	80	33.00	75	80	—	—	—
Load current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]																																							
	Ripple-Noise [mV]	Ripple-Noise [mV]																																							
0.00	20	25																																							
4.00	40	45																																							
8.00	45	50																																							
12.00	50	60																																							
16.00	55	65																																							
20.00	55	70																																							
24.00	55	75																																							
28.00	60	80																																							
30.00	70	80																																							
33.00	75	80																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									



COSEL

Model	LDA150W-5	Temperature	25°C																																																							
Item	Overcurrent Protection 過電流保護	Testing Circuitry	Figure A																																																							
Object	+5.0V30A																																																									
1. Graph	<p>[V] Input Volt. 170 V Input Volt. 200 V Input Volt. 264 V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 170 [V]</th> <th>Input Volt. 200 [V]</th> <th>Input Volt. 264 [V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>37.66</td><td>37.53</td><td>37.66</td></tr> <tr><td>4.75</td><td>37.78</td><td>37.72</td><td>37.85</td></tr> <tr><td>4.50</td><td>37.92</td><td>37.88</td><td>38.00</td></tr> <tr><td>4.00</td><td>38.23</td><td>38.17</td><td>38.28</td></tr> <tr><td>3.50</td><td>38.56</td><td>38.52</td><td>38.60</td></tr> <tr><td>3.00</td><td>38.87</td><td>38.83</td><td>38.90</td></tr> <tr><td>2.50</td><td>39.07</td><td>39.11</td><td>39.26</td></tr> <tr><td>2.00</td><td>39.36</td><td>39.39</td><td>39.59</td></tr> <tr><td>1.50</td><td>39.70</td><td>39.68</td><td>39.91</td></tr> <tr><td>1.00</td><td>39.91</td><td>39.99</td><td>40.07</td></tr> <tr><td>0.50</td><td>39.87</td><td>39.69</td><td>38.78</td></tr> <tr><td>0.00</td><td>38.71</td><td>38.36</td><td>37.67</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 170 [V]	Input Volt. 200 [V]	Input Volt. 264 [V]	5.00	37.66	37.53	37.66	4.75	37.78	37.72	37.85	4.50	37.92	37.88	38.00	4.00	38.23	38.17	38.28	3.50	38.56	38.52	38.60	3.00	38.87	38.83	38.90	2.50	39.07	39.11	39.26	2.00	39.36	39.39	39.59	1.50	39.70	39.68	39.91	1.00	39.91	39.99	40.07	0.50	39.87	39.69	38.78	0.00	38.71	38.36	37.67
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 170 [V]	Input Volt. 200 [V]	Input Volt. 264 [V]																																																							
5.00	37.66	37.53	37.66																																																							
4.75	37.78	37.72	37.85																																																							
4.50	37.92	37.88	38.00																																																							
4.00	38.23	38.17	38.28																																																							
3.50	38.56	38.52	38.60																																																							
3.00	38.87	38.83	38.90																																																							
2.50	39.07	39.11	39.26																																																							
2.00	39.36	39.39	39.59																																																							
1.50	39.70	39.68	39.91																																																							
1.00	39.91	39.99	40.07																																																							
0.50	39.87	39.69	38.78																																																							
0.00	38.71	38.36	37.67																																																							

Note: Slanted line shows the range of the rated load current.


(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA150W-5	Testing Circuitry Figure A																																																					
Item	Overvoltage Protection 過電圧保護																																																						
Object	+5V 30.0A																																																						
1. Graph	<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> <tr> <th colspan="3">Operating Point [V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>6.57</td><td>6.57</td><td>6.57</td></tr> <tr> <td>-10</td><td>6.57</td><td>6.56</td><td>6.57</td></tr> <tr> <td>0</td><td>6.56</td><td>6.56</td><td>6.56</td></tr> <tr> <td>10</td><td>6.56</td><td>6.56</td><td>6.56</td></tr> <tr> <td>20</td><td>6.56</td><td>6.56</td><td>6.57</td></tr> <tr> <td>25</td><td>6.56</td><td>6.56</td><td>6.55</td></tr> <tr> <td>30</td><td>6.56</td><td>6.55</td><td>6.55</td></tr> <tr> <td>40</td><td>6.50</td><td>6.51</td><td>6.52</td></tr> <tr> <td>50</td><td>6.51</td><td>6.50</td><td>6.51</td></tr> <tr> <td>60</td><td>6.50</td><td>6.50</td><td>6.50</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temp. [°C]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	Operating Point [V]			-20	6.57	6.57	6.57	-10	6.57	6.56	6.57	0	6.56	6.56	6.56	10	6.56	6.56	6.56	20	6.56	6.56	6.57	25	6.56	6.56	6.55	30	6.56	6.55	6.55	40	6.50	6.51	6.52	50	6.51	6.50	6.51	60	6.50	6.50	6.50	—	—	—	—
Ambient Temp. [°C]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
	Operating Point [V]																																																						
-20	6.57	6.57	6.57																																																				
-10	6.57	6.56	6.57																																																				
0	6.56	6.56	6.56																																																				
10	6.56	6.56	6.56																																																				
20	6.56	6.56	6.57																																																				
25	6.56	6.56	6.55																																																				
30	6.56	6.55	6.55																																																				
40	6.50	6.51	6.52																																																				
50	6.51	6.50	6.51																																																				
60	6.50	6.50	6.50																																																				
—	—	—	—																																																				

COSEL

Model	LDA150W-5	Temperature Testing Circuitry 25°C Figure A
Item	Inrush Current 突入電流	
Object	—	



Input Voltage 200 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 29.12 [A]

② 4.08 [A]



COSEL

Model	LDA150W-5	Temperature	25°C
Item	Dynamic Load Response 動的負荷変動	Testing Circuitry	Figure A
Object	+5.0V30A		



Input Volt. 200 V

Cycle 1000 mS




Load 0% ↔

Load 100 %




Load 0% ↔

Load 50 %



100 mV/div




10 mS/div

COSEL

Model	LDA150W-5	Temperature	25°C		
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A		
Object	+5.0V 30A				
1. Graph					
Output Voltage [1V/div]	Load 50%	Input Volt. 170 V			
Output Voltage [1V/div]	Load 100%				
Input Voltage [100V/DIV]					
	Time [50mS/div]	Time [20mS/div]			
2. Values	[mS]				
Load \ Time	T d	T r	T s	T h	T f
50 %	127.8	1.5	129.3	42.3	18.4
100 %	127.8	2.0	129.8	19.6	10.6

COSEL

Model	LDA150W-5																																																					
Item	Ambient Temperature Drift 周囲温度変動	Testing Circuitry Figure A																																																				
Object	+5.0V 30A																																																					
1. Graph																																																						
—△— Input Volt. 170V -□- Input Volt. 200V -○- Input Volt. 264V		2. Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>5.139</td> <td>5.140</td> <td>5.140</td> </tr> <tr> <td>-10</td> <td>5.140</td> <td>5.140</td> <td>5.140</td> </tr> <tr> <td>0</td> <td>5.139</td> <td>5.139</td> <td>5.139</td> </tr> <tr> <td>10</td> <td>5.139</td> <td>5.139</td> <td>5.139</td> </tr> <tr> <td>20</td> <td>5.141</td> <td>5.141</td> <td>5.142</td> </tr> <tr> <td>25</td> <td>5.142</td> <td>5.142</td> <td>5.143</td> </tr> <tr> <td>30</td> <td>5.144</td> <td>5.145</td> <td>5.145</td> </tr> <tr> <td>40</td> <td>5.147</td> <td>5.147</td> <td>5.147</td> </tr> <tr> <td>50</td> <td>5.147</td> <td>5.147</td> <td>5.148</td> </tr> <tr> <td>60</td> <td>5.145</td> <td>5.145</td> <td>5.146</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	-20	5.139	5.140	5.140	-10	5.140	5.140	5.140	0	5.139	5.139	5.139	10	5.139	5.139	5.139	20	5.141	5.141	5.142	25	5.142	5.142	5.143	30	5.144	5.145	5.145	40	5.147	5.147	5.147	50	5.147	5.147	5.148	60	5.145	5.145	5.146	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
-20	5.139	5.140	5.140																																																			
-10	5.140	5.140	5.140																																																			
0	5.139	5.139	5.139																																																			
10	5.139	5.139	5.139																																																			
20	5.141	5.141	5.142																																																			
25	5.142	5.142	5.143																																																			
30	5.144	5.145	5.145																																																			
40	5.147	5.147	5.147																																																			
50	5.147	5.147	5.148																																																			
60	5.145	5.145	5.146																																																			
—	—	—	—																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						
(注)斜線は定格周囲温度範囲を示す。																																																						

COSEL

Model	LDA150W-5																																						
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧																																						
Object	+5.0V 30A																																						
1. Graph	[V]	Load 50% Load 100%																																					
		2. Values																																					
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>57</td><td>65</td></tr> <tr><td>-10</td><td>57</td><td>65</td></tr> <tr><td>0</td><td>57</td><td>65</td></tr> <tr><td>10</td><td>56</td><td>65</td></tr> <tr><td>20</td><td>56</td><td>65</td></tr> <tr><td>25</td><td>56</td><td>65</td></tr> <tr><td>30</td><td>56</td><td>65</td></tr> <tr><td>40</td><td>56</td><td>65</td></tr> <tr><td>50</td><td>56</td><td>65</td></tr> <tr><td>60</td><td>56</td><td>65</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	57	65	-10	57	65	0	57	65	10	56	65	20	56	65	25	56	65	30	56	65	40	56	65	50	56	65	60	56	65	—	—	—
Ambient Temperature [°C]	Input Voltage [V]																																						
	Load 50%	Load 100%																																					
-20	57	65																																					
-10	57	65																																					
0	57	65																																					
10	56	65																																					
20	56	65																																					
25	56	65																																					
30	56	65																																					
40	56	65																																					
50	56	65																																					
60	56	65																																					
—	—	—																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																							

COSEL

Model	LDA150W-5																																								
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A																																							
Object	+5.0V 30A																																								
1. Graph																																									
		Load 50%	Load 100%																																						
<p>[mV]</p> <p>150</p> <p>125</p> <p>100</p> <p>75</p> <p>50</p> <p>25</p> <p>0</p> <p>Ambient Temperature [°C]</p> <p>-30 -10 10 30 50 70</p> <p>Input Volt. 200 V</p>																																									
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																									
		2. Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>60</td><td>85</td></tr> <tr><td>-10</td><td>50</td><td>75</td></tr> <tr><td>0</td><td>45</td><td>65</td></tr> <tr><td>10</td><td>45</td><td>60</td></tr> <tr><td>20</td><td>40</td><td>55</td></tr> <tr><td>25</td><td>40</td><td>50</td></tr> <tr><td>30</td><td>40</td><td>50</td></tr> <tr><td>40</td><td>40</td><td>50</td></tr> <tr><td>50</td><td>35</td><td>45</td></tr> <tr><td>60</td><td>35</td><td>45</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temp. [°C]	Load 50%	Load 100%	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	-20	60	85	-10	50	75	0	45	65	10	45	60	20	40	55	25	40	50	30	40	50	40	40	50	50	35	45	60	35	45	—	—	—
Ambient Temp. [°C]	Load 50%	Load 100%																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
-20	60	85																																							
-10	50	75																																							
0	45	65																																							
10	45	60																																							
20	40	55																																							
25	40	50																																							
30	40	50																																							
40	40	50																																							
50	35	45																																							
60	35	45																																							
—	—	—																																							

COSEL

Model	LDA150W-5	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift 経時ドリフト																								
Object	+5.0V 30A																								
1. Graph			2. Values																						
<p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 200V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.146</td></tr> <tr><td>0.5</td><td>5.145</td></tr> <tr><td>1.0</td><td>5.145</td></tr> <tr><td>2.0</td><td>5.145</td></tr> <tr><td>3.0</td><td>5.145</td></tr> <tr><td>4.0</td><td>5.145</td></tr> <tr><td>5.0</td><td>5.145</td></tr> <tr><td>6.0</td><td>5.145</td></tr> <tr><td>7.0</td><td>5.145</td></tr> <tr><td>8.0</td><td>5.145</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.146	0.5	5.145	1.0	5.145	2.0	5.145	3.0	5.145	4.0	5.145	5.0	5.145	6.0	5.145	7.0	5.145	8.0	5.145
Time since start [H]	Output Voltage [V]																								
0.0	5.146																								
0.5	5.145																								
1.0	5.145																								
2.0	5.145																								
3.0	5.145																								
4.0	5.145																								
5.0	5.145																								
6.0	5.145																								
7.0	5.145																								
8.0	5.145																								

COSSEL

Model	LDA150W-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+5.0V 30A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 170~264 V

Load Current : 0~30 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 170~264 V

負荷電流 0~30 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	50	170	0	5.153		
Minimum Voltage	-10	170	30	5.140	±7	±0.2



Model	LDA150W-5		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+5.0V30A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.143	Input Volt.: 200V, Load Current:30A
Line Regulation [mV]	2	Input Volt.: 170~264V, Load Current:30A
Load Regulation [mV]	4	Input Volt.: 200V, Load Current:0~30A

COSEL

Model	LDA150W-5	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 200 [V]	Input Volt. 264 [V]
(A) DENTORI	—	—	—
(B) IEC60950	—	—	—

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	0.32	0.44	0.51



Model	LDA150F-5	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure C
Object	+5.0V 30A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 200 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LDA150W-5	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	<hr/>		

1. Graph


Remarks

Input Volt. 230 V

Load 100 %

規格 1 : [EN 55022] Class B(平均値)

規格 2 : [EN 55022] Class B(QP)



COSEL





Figure B (DENTORI)




Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E