



# TEST DATA OF LDA15F-15 (100V INPUT)

Regulated DC Power Supply

Date : June 23. 1999

Approved by : H. Yamaguchi  
Design Manager

Prepared by : T. Ashihara  
Design Engineer

**コーセル株式会社**  
**COSEL CO., LTD.**


## CONTENTS

1. Line Regulation . . . . .	1
静的入力変動	
2. Input Current (by Load Current) . . . . .	2
入力電流 (負荷特性)	
3. Input Power (by Load Current) . . . . .	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage) . . . . .	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current) . . . . .	5
効率 (負荷特性)	
6. Hold-Up Time . . . . .	6
出力保持時間	
7. Instantaneous Interruption Compensation . . . . .	7
瞬時停電保障	
8. Load Regulation . . . . .	8
静的負荷変動	
9. Ripple Voltage (by Load Current) . . . . .	9
リップル電圧 (負荷特性)	
10. Ripple-Noise . . . . .	10
リップルノイズ	
11. Overcurrent Protection . . . . .	11
過電流保護	
12. Inrush Current . . . . .	12
突入電流	
13. Dynamic Load Response . . . . .	13
動的負荷変動	
14. Rise and Fall Time . . . . .	14
立上り、立下がり時間	
15. Ambient Temperature Drift . . . . .	15
周囲温度変動	
16. Minimum Input Voltage for Regulated Output Voltage . . . . .	16
最低レギュレーション電圧	
17. Ripple Voltage (by Ambient Temperature) . . . . .	17
リップル電圧 (周囲温度特性)	
18. Time Lapse Drift . . . . .	18
経時ドリフト	
19. Output Voltage Accuracy . . . . .	19
定電圧精度	
20. Condensation . . . . .	20
結露特性	
21. Leakage Current . . . . .	21
漏洩電流	
22. Line Noise Tolerance . . . . .	22
入力雑音耐量	
23. Conducted Emission . . . . .	23
雑音端子電圧	
24. Figure of Testing Circuitry . . . . .	24
測定回路図	

(Final Page 25 )

# COSEL

Model		LDA15F-15		Temperature Testing Circuitry	25℃ Figure A																																
Item		Line Regulation  静的入力変動																																			
Object		+15.0V1A																																			
1. Graph				2. Values																																	
<div><div><div>□</div><div>Load 50%</div></div><div><div>△</div><div>Load 100%</div></div></div> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>				<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>75</td><td>15.071</td><td>15.065</td></tr><tr><td>80</td><td>15.071</td><td>15.066</td></tr><tr><td>85</td><td>15.071</td><td>15.066</td></tr><tr><td>90</td><td>15.070</td><td>15.066</td></tr><tr><td>100</td><td>15.070</td><td>15.066</td></tr><tr><td>110</td><td>15.070</td><td>15.065</td></tr><tr><td>120</td><td>15.069</td><td>15.065</td></tr><tr><td>132</td><td>15.069</td><td>15.064</td></tr><tr><td>140</td><td>15.069</td><td>15.064</td></tr></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	15.071	15.065	80	15.071	15.066	85	15.071	15.066	90	15.070	15.066	100	15.070	15.066	110	15.070	15.065	120	15.069	15.065	132	15.069	15.064	140	15.069	15.064
Input Voltage [V]	Output Voltage [V]																																				
	Load 50%	Load 100%																																			
75	15.071	15.065																																			
80	15.071	15.066																																			
85	15.071	15.066																																			
90	15.070	15.066																																			
100	15.070	15.066																																			
110	15.070	15.065																																			
120	15.069	15.065																																			
132	15.069	15.064																																			
140	15.069	15.064																																			

**COSEL**

# COSEL

Model		LDA15F-15		Temperature		25℃																																																								
Item		Input Power (by Load Current) 入力電力 (負荷特性)		Testing Circuitry		Figure A																																																								
Output		_____																																																												
1. Graph				2. Values																																																										
<div><div>—△—</div>Input Volt. 85V</div> <div><div>---□---</div>Input Volt. 100V</div> <div><div>---○---</div>Input Volt. 132V</div> <p>Input Power [W]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.0</td><td>1.43</td><td>1.56</td><td>1.87</td></tr><tr><td>0.2</td><td>4.94</td><td>5.08</td><td>5.39</td></tr><tr><td>0.4</td><td>8.51</td><td>8.59</td><td>8.92</td></tr><tr><td>0.6</td><td>12.36</td><td>12.31</td><td>12.49</td></tr><tr><td>0.8</td><td>16.27</td><td>16.09</td><td>16.09</td></tr><tr><td>1.0</td><td>20.31</td><td>19.96</td><td>19.75</td></tr><tr><td>1.1</td><td>22.42</td><td>21.98</td><td>21.67</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	1.43	1.56	1.87	0.2	4.94	5.08	5.39	0.4	8.51	8.59	8.92	0.6	12.36	12.31	12.49	0.8	16.27	16.09	16.09	1.0	20.31	19.96	19.75	1.1	22.42	21.98	21.67	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																													
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																											
0.0	1.43	1.56	1.87																																																											
0.2	4.94	5.08	5.39																																																											
0.4	8.51	8.59	8.92																																																											
0.6	12.36	12.31	12.49																																																											
0.8	16.27	16.09	16.09																																																											
1.0	20.31	19.96	19.75																																																											
1.1	22.42	21.98	21.67																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											

**COSEL**

Model		LDA15F-15	
Item	Efficiency 効率		
Object			

1. Graph

□

Load 50%

△

Load 100%

Efficiency [%]

86

82

78

74

70

66

62

0

0

80

90

100

110

120

130

140

150

Input Voltage [V]

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	73.0	73.0
80	73.2	74.1
85	73.3	74.9
90	73.4	75.4
100	73.2	76.3
110	72.8	76.7
120	72.2	76.9
132	71.4	77.0
140	70.7	76.9

**COSEL**

Model		LDA15F-15		Temperature		25℃																																																								
Item		Efficiency (by Load Current) 効率 (負荷電流特性)		Testing Circuitry		Figure A																																																								
Output		—————																																																												
1. Graph				2. Values																																																										
<div><div>—△— Input Volt. 85V - - -□- - Input Volt. 100V - - -○- - Input Volt. 132V</div><p>Efficiency [%]</p><p>Load Current [A]</p></div> <p>Note: Slanted line shows the range of the rated load current</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.2</td><td>62.0</td><td>60.5</td><td>57.2</td></tr><tr><td>0.4</td><td>71.3</td><td>70.8</td><td>68.2</td></tr><tr><td>0.6</td><td>74.0</td><td>74.4</td><td>73.4</td></tr><tr><td>0.8</td><td>74.8</td><td>75.7</td><td>75.7</td></tr><tr><td>1.0</td><td>74.7</td><td>76.0</td><td>76.8</td></tr><tr><td>1.1</td><td>74.5</td><td>76.1</td><td>77.2</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.2	62.0	60.5	57.2	0.4	71.3	70.8	68.2	0.6	74.0	74.4	73.4	0.8	74.8	75.7	75.7	1.0	74.7	76.0	76.8	1.1	74.5	76.1	77.2	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																													
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																											
0.2	62.0	60.5	57.2																																																											
0.4	71.3	70.8	68.2																																																											
0.6	74.0	74.4	73.4																																																											
0.8	74.8	75.7	75.7																																																											
1.0	74.7	76.0	76.8																																																											
1.1	74.5	76.1	77.2																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											

# COSEL

Model		LDA15F-15		Temperature		25℃																																	
Item		Hold-Up Time 出力保持時間		Testing Circuitry		Figure A																																	
Object		+15.0V1A																																					
1. Graph				2. Values																																			
<div><div><div>□</div><div>Load 50%</div></div><div><div>△</div><div>Load 100%</div></div></div> <p>Hold-Up Time [mS]</p> <p>Input Voltage [V]</p>				<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [mS]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>75</td><td>31</td><td>11</td></tr><tr><td>80</td><td>36</td><td>13</td></tr><tr><td>85</td><td>42</td><td>16</td></tr><tr><td>90</td><td>47</td><td>19</td></tr><tr><td>100</td><td>59</td><td>25</td></tr><tr><td>110</td><td>72</td><td>32</td></tr><tr><td>120</td><td>87</td><td>40</td></tr><tr><td>132</td><td>106</td><td>50</td></tr><tr><td>140</td><td>120</td><td>58</td></tr></table>				Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	31	11	80	36	13	85	42	16	90	47	19	100	59	25	110	72	32	120	87	40	132	106	50	140	120	58
Input Voltage [V]	Hold-Up Time [mS]																																						
	Load 50%	Load 100%																																					
75	31	11																																					
80	36	13																																					
85	42	16																																					
90	47	19																																					
100	59	25																																					
110	72	32																																					
120	87	40																																					
132	106	50																																					
140	120	58																																					
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																							



# COSEL

Model		LDA15F-15		Temperature		25℃																																																				
Item		Instantaneous Interruption Compensation 瞬時停電保障		Testing Circuitry		Figure A																																																				
Object		+15.0V1A																																																								
1. Graph				2. Values																																																						
<div><div><div>—△—</div><div>Input Volt. 85 V</div></div><div><div>—□—</div><div>Input Volt. 100 V</div></div><div><div>—○—</div><div>Input Volt. 132 V</div></div></div> <div><div><div>[mS]</div><div>1000</div><div>100</div><div>10</div><div>1</div></div><div><div>Instantaneous Compensation Time</div><div>Load Current</div><div>[A]</div></div></div> <div><div>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</div><div>Note:Slanted line shows the range of the rated load current.</div></div> <div><div>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</div><div>(注)斜線は定格負荷電流範囲を示す。</div></div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [mS]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr><tr><td>0.2</td><td>90</td><td>128</td><td>226</td></tr><tr><td>0.4</td><td>45</td><td>65</td><td>123</td></tr><tr><td>0.6</td><td>26</td><td>40</td><td>82</td></tr><tr><td>0.8</td><td>14</td><td>27</td><td>56</td></tr><tr><td>1.0</td><td>5</td><td>14</td><td>43</td></tr><tr><td>1.1</td><td>4</td><td>13</td><td>36</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	—	—	—	0.2	90	128	226	0.4	45	65	123	0.6	26	40	82	0.8	14	27	56	1.0	5	14	43	1.1	4	13	36	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	—	—	—																																																							
0.2	90	128	226																																																							
0.4	45	65	123																																																							
0.6	26	40	82																																																							
0.8	14	27	56																																																							
1.0	5	14	43																																																							
1.1	4	13	36																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

**COSEL**

Model		LDA15F-15		Temperature		25℃																																																
Item		Load Regulation 静的負荷変動		Testing Circuitry		Figure A																																																
Object		+15.0V1A																																																				
1. Graph				2. Values																																																		
<div><div><div>△</div><div>Input Volt. 85 V</div></div><div><div>□</div><div>Input Volt. 100 V</div></div><div><div>○</div><div>Input Volt. 132 V</div></div></div> <div><div><div>Output Voltage [V]</div><div><div><div>15.21</div><div>15.17</div><div>15.13</div><div>15.09</div><div>15.05</div><div>15.01</div><div>14.97</div><div>0</div></div><div><div>0</div><div>0.2</div><div>0.4</div><div>0.6</div><div>0.8</div><div>1</div><div>1.2</div></div></div><div><div>Load Current [A]</div><div><div><div>15.071</div><div>15.068</div><div>15.067</div><div>15.065</div><div>15.064</div><div>15.063</div><div>15.062</div><div>—</div><div>—</div><div>—</div></div><div><div>15.070</div><div>15.068</div><div>15.066</div><div>15.065</div><div>15.064</div><div>15.062</div><div>15.062</div><div>—</div><div>—</div><div>—</div></div><div><div>15.070</div><div>15.068</div><div>15.066</div><div>15.065</div><div>15.063</div><div>15.062</div><div>15.061</div><div>—</div><div>—</div><div>—</div></div></div></div></div><div><div>Note: Slanted line shows the range of the rated load current.</div><div><div>(注)斜線は定格負荷電流範囲を示す。</div></div></div></div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.0</td><td>15.071</td><td>15.070</td><td>15.070</td></tr><tr><td>0.2</td><td>15.068</td><td>15.068</td><td>15.068</td></tr><tr><td>0.4</td><td>15.067</td><td>15.066</td><td>15.066</td></tr><tr><td>0.6</td><td>15.065</td><td>15.065</td><td>15.065</td></tr><tr><td>0.8</td><td>15.064</td><td>15.064</td><td>15.063</td></tr><tr><td>1.0</td><td>15.063</td><td>15.062</td><td>15.062</td></tr><tr><td>1.1</td><td>15.062</td><td>15.062</td><td>15.061</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	15.071	15.070	15.070	0.2	15.068	15.068	15.068	0.4	15.067	15.066	15.066	0.6	15.065	15.065	15.065	0.8	15.064	15.064	15.063	1.0	15.063	15.062	15.062	1.1	15.062	15.062	15.061	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	15.071	15.070	15.070																																																			
0.2	15.068	15.068	15.068																																																			
0.4	15.067	15.066	15.066																																																			
0.6	15.065	15.065	15.065																																																			
0.8	15.064	15.064	15.063																																																			
1.0	15.063	15.062	15.062																																																			
1.1	15.062	15.062	15.061																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

# COSEL

Model		LDA15F-15	
Item		Ripple Voltage (by Load Current) リップル電圧 (負荷電流特性)	
Object		+15.0V1A	

1. Graph

□----- Input Volt. 85V

—△— Input Volt. 132V

150

125

100

75

50

25

0

Ripple Voltage [mV]

00.20.40.60.811.2

Load Current [A]

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line  
入力商用周期

T2: Due to Switching  
スイッチング周期

Ripple [mVp-p]

T1

T2

Fig. Complex Ripple Wave Form

図 リップル波形詳細図


Temperature		25℃	
Testing Circuitry		Figure A	

2.Values

Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.00	10	10
0.10	10	10
0.20	10	10
0.40	10	10
0.50	10	10
0.60	10	10
0.80	10	10
0.90	10	10
1.00	20	10
1.10	30	10
—	—	—


BC-4046

**COSEL**


Model		LDA15F-15	Temperature25℃ Testing CircuitryFigure A
Item		Overcurrent Protection 過電流保護	
Object		+15.0V1A	
1. Graph			
		<div><div></div>Input Volt. 85 V</div> <div><div></div>Input Volt. 100 V</div> <div><div></div>Input Volt. 132 V</div>	2. Values
[V]			
			
Note: Slanted line shows the range of the rated load current.			
(注) 斜線は定格負荷電流範囲を示す。			

**COSEL**

Model	LDA15F-15	Temperature 25°C Testing Circuitry Figure A
Item	Inrush Current 突入電流	
Object		



Input Voltage 100 V  
Frequency 60 Hz  
Load 100 %  
Inrush Current  
① 8.01 [A]  
② 1.21 [A]



**COSEL**

Model	LDA15F-15	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Responce 動的負荷変動	
Object	+15.0V1A	



Input Volt. 100 V

Cycle 1000 mS

Load Current



Load 0% ←→

Load 100 %



Load 0% ←→

Load 50 %



200 mV/div


10 mS/div

**COSEL**

Model	LDA15F-15	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+15.0V1A		

## 1. Graph


Input Volt. 85 V



## 2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	4.3	10.8	15.0	42.5	84.0
100 %	4.3	16.3	20.5	16.0	48.3







# COSEL

Model		LDA15F-15
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	
Object	+15.0V1A	

1. Graph

□

Load 50%

△

Load 100%

[V]

100

80

60

40

20

0

Input Voltage

-30

-10

10

30

50

70

Ambient Temperature

[°C]

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	46	72
-10	46	71
0	45	71
10	45	71
20	45	71
25	45	71
30	45	71
40	45	71
50	46	71
60	46	72
—	—	—

# COSEL

Model

LDA15F-15

Item

Ripple Voltage (by Ambient Temp.)  
リップル電圧 (周囲温度特性)


Object

+15.0V1A

Testing Circuitry

Figure A

## 1. Graph




Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

## 2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	10	25
-10	10	15
0	10	10
10	10	10
20	10	10
25	10	10
30	10	10
40	10	10
50	10	10
60	10	10
—	—	—

**COSEL**

COSEL																									
Model	LDA15F-15	Temperature	25℃																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+15.0V1A																								
1. Graph		2.Values																							
<div>[V]</div> <div></div> <div>Input Volt. 100V</div> <div>Load 100%</div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>15.075</td></tr><tr><td>0.5</td><td>15.053</td></tr><tr><td>1.0</td><td>15.053</td></tr><tr><td>2.0</td><td>15.053</td></tr><tr><td>3.0</td><td>15.053</td></tr><tr><td>4.0</td><td>15.053</td></tr><tr><td>5.0</td><td>15.053</td></tr><tr><td>6.0</td><td>15.054</td></tr><tr><td>7.0</td><td>15.053</td></tr><tr><td>8.0</td><td>15.054</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	15.075	0.5	15.053	1.0	15.053	2.0	15.053	3.0	15.053	4.0	15.053	5.0	15.053	6.0	15.054	7.0	15.053	8.0	15.054
Time since start [H]	Output Voltage [V]																								
0.0	15.075																								
0.5	15.053																								
1.0	15.053																								
2.0	15.053																								
3.0	15.053																								
4.0	15.053																								
5.0	15.053																								
6.0	15.054																								
7.0	15.053																								
8.0	15.054																								

# COSEL

Model	LDA15F-15	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+15.0V1A	

## Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~1 A

\* Output Voltage Accuracy =  $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

## 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~1 A

\* 定電圧精度(変動値) =  $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

\* 定電圧精度(変動率) =  $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	-10	132	0	15.101	±34	±0.3
Minimum Voltage	50	132	1	15.035		



**COSEL**

Model	LDA15F-15	Temperature	25℃
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	_____		

## 1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.12	0.16	0.24
(B) IEC60950	0.12	0.16	0.25

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—

## 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力 of 両相について測定し、その大きい方を漏洩電流測定値とする。

**COSEL**

Model	LDA15F-15	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure C
Object	+15.0V1A		

## 1. Results

Pulse Width [ nS ]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

## 2. Conditions

Input Voltage : 100 V  
 Pulse Voltage : 2000 V  
 Pulse Cycle : 10 mS  
 Pulse Input Duration : 1 min. or more  
 Load : 100 %



# COSEL

Model	LDA15F-15	Temperature	25°C
Item	Conducted Emission 雑音端子電圧	Testing Circuitry	Figure D
Object	_____		

## 1. Graph

Remarks


Input Volt. 100 V (VCCI Class B)

120 V (FCC Class B)


Load 100 %

規格 1 : [VCCI] Class B(平均値)

規格 2 : [VCCI] Class B(QP)



規格 2 : [FCC Part15] Class B







Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E