



TEST DATA OF LDA15F-15
(200V INPUT)

Regulated DC Power Supply

Date : June 23. 1999

Approved by : N. Yamaguchi
Design Manager

Prepared by : T. Ashihara
Design Engineer

コーワセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Inrush Current	12
突入電流	
13. Dynamic Load Responce	13
動的負荷変動	
14. Rise and Fall Time	14
立ち上り、立下がり時間	
15. Ambient Temperature Drift	15
周囲温度変動	
16. Minimum Input Voltage for Regulated Output Voltage .	16
最低レギュレーション電圧	
17. Ripple Voltage (by Ambient Temperature)	17
リップル電圧 (周囲温度特性)	
18. Time Lapse Drift	18
経時ドリフト	
19. Output Voltage Accuracy	19
定電圧精度	
20. Condensation	20
結露特性	
21. Leakage Current	21
漏洩電流	
22. Line Noise Tolerance	22
入力雜音耐量	
23. Conducted Emission	23
雜音端子電圧	
24. Figure of Testing Circuitry	24
測定回路図	

(Final Page 25)

COSEL

Model	LDA15F-15		Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+15.0V 1A																																		
1. Graph																																			
		Load 50% □ Load 100% △	2. Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>15.066</td><td>15.062</td></tr> <tr><td>160</td><td>15.066</td><td>15.062</td></tr> <tr><td>170</td><td>15.066</td><td>15.062</td></tr> <tr><td>180</td><td>15.065</td><td>15.061</td></tr> <tr><td>200</td><td>15.065</td><td>15.061</td></tr> <tr><td>220</td><td>15.065</td><td>15.061</td></tr> <tr><td>240</td><td>15.065</td><td>15.061</td></tr> <tr><td>264</td><td>15.064</td><td>15.060</td></tr> <tr><td>280</td><td>15.064</td><td>15.060</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	150	15.066	15.062	160	15.066	15.062	170	15.066	15.062	180	15.065	15.061	200	15.065	15.061	220	15.065	15.061	240	15.065	15.061	264	15.064	15.060	280	15.064	15.060
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
150	15.066	15.062																																	
160	15.066	15.062																																	
170	15.066	15.062																																	
180	15.065	15.061																																	
200	15.065	15.061																																	
220	15.065	15.061																																	
240	15.065	15.061																																	
264	15.064	15.060																																	
280	15.064	15.060																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL


Model	LDA15F-15	Temperature	25°C																																																							
Item	Input Current (by Load Current) 入力電流（負荷特性）	Testing Circuitry	Figure A																																																							
Output	——																																																									
1. Graph	<p>—△— Input Volt. 170V —□— Input Volt. 200V —○— Input Volt. 264V</p> <table border="1"> <caption>Data points from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170[V] [A]</th> <th>Input Volt. 200[V] [A]</th> <th>Input Volt. 264[V] [A]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>0.036</td> <td>0.037</td> <td>0.040</td> </tr> <tr> <td>0.2</td> <td>0.078</td> <td>0.074</td> <td>0.072</td> </tr> <tr> <td>0.6</td> <td>0.117</td> <td>0.109</td> <td>0.099</td> </tr> <tr> <td>0.8</td> <td>0.154</td> <td>0.142</td> <td>0.126</td> </tr> <tr> <td>1.0</td> <td>0.190</td> <td>0.173</td> <td>0.152</td> </tr> <tr> <td>1.1</td> <td>0.227</td> <td>0.205</td> <td>0.177</td> </tr> </tbody> </table>			Load Current [A]	Input Volt. 170[V] [A]	Input Volt. 200[V] [A]	Input Volt. 264[V] [A]	0.0	0.036	0.037	0.040	0.2	0.078	0.074	0.072	0.6	0.117	0.109	0.099	0.8	0.154	0.142	0.126	1.0	0.190	0.173	0.152	1.1	0.227	0.205	0.177																											
Load Current [A]	Input Volt. 170[V] [A]	Input Volt. 200[V] [A]	Input Volt. 264[V] [A]																																																							
0.0	0.036	0.037	0.040																																																							
0.2	0.078	0.074	0.072																																																							
0.6	0.117	0.109	0.099																																																							
0.8	0.154	0.142	0.126																																																							
1.0	0.190	0.173	0.152																																																							
1.1	0.227	0.205	0.177																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>0.036</td> <td>0.037</td> <td>0.040</td> </tr> <tr> <td>0.2</td> <td>0.078</td> <td>0.074</td> <td>0.072</td> </tr> <tr> <td>0.4</td> <td>0.117</td> <td>0.109</td> <td>0.099</td> </tr> <tr> <td>0.6</td> <td>0.154</td> <td>0.142</td> <td>0.126</td> </tr> <tr> <td>0.8</td> <td>0.190</td> <td>0.173</td> <td>0.152</td> </tr> <tr> <td>1.0</td> <td>0.227</td> <td>0.205</td> <td>0.177</td> </tr> <tr> <td>1.1</td> <td>0.246</td> <td>0.222</td> <td>0.190</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	0.036	0.037	0.040	0.2	0.078	0.074	0.072	0.4	0.117	0.109	0.099	0.6	0.154	0.142	0.126	0.8	0.190	0.173	0.152	1.0	0.227	0.205	0.177	1.1	0.246	0.222	0.190	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.0	0.036	0.037	0.040																																																							
0.2	0.078	0.074	0.072																																																							
0.4	0.117	0.109	0.099																																																							
0.6	0.154	0.142	0.126																																																							
0.8	0.190	0.173	0.152																																																							
1.0	0.227	0.205	0.177																																																							
1.1	0.246	0.222	0.190																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSSEL

Model	LDA15F-15
Item	Input Power (by Load Current) 入力電力 (負荷特性)
Output	—

Temperature 25°C
Testing Circuitry Figure A

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
0.0	2.30	2.70	3.80
0.2	5.90	6.40	7.70
0.4	9.50	9.90	11.20
0.6	13.00	13.50	14.80
0.8	16.40	16.90	18.20
1.0	20.00	20.30	21.60
1.1	21.80	22.10	23.30
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	LDA15F-15																																	
Item	Efficiency 効率	Temperature 25°C Testing Circuitry Figure A																																
Object	_____																																	
1. Graph																																		
<p>[%]</p>		Load 50% Load 100%																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>150</td> <td>70.2</td> <td>77.4</td> </tr> <tr> <td>160</td> <td>68.7</td> <td>76.9</td> </tr> <tr> <td>170</td> <td>67.8</td> <td>76.6</td> </tr> <tr> <td>180</td> <td>66.6</td> <td>76.1</td> </tr> <tr> <td>200</td> <td>64.4</td> <td>75.1</td> </tr> <tr> <td>220</td> <td>62.3</td> <td>73.5</td> </tr> <tr> <td>240</td> <td>60.3</td> <td>72.1</td> </tr> <tr> <td>264</td> <td>58.0</td> <td>70.2</td> </tr> <tr> <td>280</td> <td>57.0</td> <td>69.4</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	150	70.2	77.4	160	68.7	76.9	170	67.8	76.6	180	66.6	76.1	200	64.4	75.1	220	62.3	73.5	240	60.3	72.1	264	58.0	70.2	280	57.0	69.4
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
150	70.2	77.4																																
160	68.7	76.9																																
170	67.8	76.6																																
180	66.6	76.1																																
200	64.4	75.1																																
220	62.3	73.5																																
240	60.3	72.1																																
264	58.0	70.2																																
280	57.0	69.4																																

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA15F-15																																																									
Item	Efficiency (by Load Current) 効率(負荷電流特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	_____																																																									
1. Graph	<p>The graph plots Efficiency [%] on the y-axis (40 to 90) against Load Current [A] on the x-axis (0 to 1.2). Three data series are shown for Input Volt. 170V (triangles), Input Volt. 200V (squares), and Input Volt. 264V (circles). All series show an upward trend. A slanted line is drawn through the data points, representing the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.2</td><td>52.3</td><td>48.1</td><td>40.0</td></tr> <tr><td>0.4</td><td>64.1</td><td>61.5</td><td>54.4</td></tr> <tr><td>0.6</td><td>70.5</td><td>67.8</td><td>61.9</td></tr> <tr><td>0.8</td><td>74.3</td><td>72.0</td><td>67.0</td></tr> <tr><td>1.0</td><td>75.9</td><td>74.8</td><td>70.3</td></tr> <tr><td>1.1</td><td>76.7</td><td>75.6</td><td>71.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.2	52.3	48.1	40.0	0.4	64.1	61.5	54.4	0.6	70.5	67.8	61.9	0.8	74.3	72.0	67.0	1.0	75.9	74.8	70.3	1.1	76.7	75.6	71.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Load Current [A]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.2	52.3	48.1	40.0																																																							
0.4	64.1	61.5	54.4																																																							
0.6	70.5	67.8	61.9																																																							
0.8	74.3	72.0	67.0																																																							
1.0	75.9	74.8	70.3																																																							
1.1	76.7	75.6	71.8																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.2</td><td>52.3</td><td>48.1</td><td>40.0</td></tr> <tr><td>0.4</td><td>64.1</td><td>61.5</td><td>54.4</td></tr> <tr><td>0.6</td><td>70.5</td><td>67.8</td><td>61.9</td></tr> <tr><td>0.8</td><td>74.3</td><td>72.0</td><td>67.0</td></tr> <tr><td>1.0</td><td>75.9</td><td>74.8</td><td>70.3</td></tr> <tr><td>1.1</td><td>76.7</td><td>75.6</td><td>71.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.2	52.3	48.1	40.0	0.4	64.1	61.5	54.4	0.6	70.5	67.8	61.9	0.8	74.3	72.0	67.0	1.0	75.9	74.8	70.3	1.1	76.7	75.6	71.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.2	52.3	48.1	40.0																																																							
0.4	64.1	61.5	54.4																																																							
0.6	70.5	67.8	61.9																																																							
0.8	74.3	72.0	67.0																																																							
1.0	75.9	74.8	70.3																																																							
1.1	76.7	75.6	71.8																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current


(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA15F-15		Temperature Testing Circuitry 25°C Figure A																													
Item	Hold-Up Time 出力保持時間																															
Object	+15.0V1A																															
1. Graph			2. Values																													
<table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% [mS]</th> <th>Load 100% [mS]</th> </tr> </thead> <tbody> <tr><td>150</td><td>140</td><td>66</td></tr> <tr><td>160</td><td>160</td><td>77</td></tr> <tr><td>170</td><td>180</td><td>88</td></tr> <tr><td>180</td><td>202</td><td>100</td></tr> <tr><td>200</td><td>249</td><td>125</td></tr> <tr><td>220</td><td>299</td><td>154</td></tr> <tr><td>240</td><td>353</td><td>185</td></tr> <tr><td>264</td><td>424</td><td>225</td></tr> <tr><td>280</td><td>475</td><td>255</td></tr> </tbody> </table>	Input Voltage [V]	Load 50% [mS]	Load 100% [mS]	150	140	66	160	160	77	170	180	88	180	202	100	200	249	125	220	299	154	240	353	185	264	424	225	280	475	255		
Input Voltage [V]	Load 50% [mS]	Load 100% [mS]																														
150	140	66																														
160	160	77																														
170	180	88																														
180	202	100																														
200	249	125																														
220	299	154																														
240	353	185																														
264	424	225																														
280	475	255																														
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。 (注)斜線は定格入力電圧範囲を示す。</p>																																

COSSEL

Model	LDA15F-15
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	+15.0V 1A



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。
(注)斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Time [mS]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
0.0	—	—	—
0.2	371	504	827
0.4	212	292	502
0.6	146	205	361
0.8	107	154	277
1.0	82	122	224
1.1	73	107	204
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	LDA15F-15	Temperature	25°C																																															
Item	Load Regulation 靜的負荷変動	Testing Circuitry	Figure A																																															
Object	+15.0V1A																																																	
1. Graph	<p>—△— Input Volt. 170 V —□— Input Volt. 200 V —○— Input Volt. 264 V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Volt. 170[V]</th> <th>Output Volt. 200[V]</th> <th>Output Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.071</td><td>15.070</td><td>15.070</td></tr> <tr><td>0.2</td><td>15.068</td><td>15.068</td><td>15.067</td></tr> <tr><td>0.4</td><td>15.067</td><td>15.066</td><td>15.065</td></tr> <tr><td>0.6</td><td>15.065</td><td>15.065</td><td>15.064</td></tr> <tr><td>0.8</td><td>15.064</td><td>15.063</td><td>15.062</td></tr> <tr><td>1.0</td><td>15.062</td><td>15.062</td><td>15.061</td></tr> <tr><td>1.1</td><td>15.062</td><td>15.061</td><td>15.060</td></tr> </tbody> </table>			Load Current [A]	Output Volt. 170[V]	Output Volt. 200[V]	Output Volt. 264[V]	0.0	15.071	15.070	15.070	0.2	15.068	15.068	15.067	0.4	15.067	15.066	15.065	0.6	15.065	15.065	15.064	0.8	15.064	15.063	15.062	1.0	15.062	15.062	15.061	1.1	15.062	15.061	15.060															
Load Current [A]	Output Volt. 170[V]	Output Volt. 200[V]	Output Volt. 264[V]																																															
0.0	15.071	15.070	15.070																																															
0.2	15.068	15.068	15.067																																															
0.4	15.067	15.066	15.065																																															
0.6	15.065	15.065	15.064																																															
0.8	15.064	15.063	15.062																																															
1.0	15.062	15.062	15.061																																															
1.1	15.062	15.061	15.060																																															
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.071</td><td>15.070</td><td>15.070</td></tr> <tr><td>0.2</td><td>15.068</td><td>15.068</td><td>15.067</td></tr> <tr><td>0.4</td><td>15.067</td><td>15.066</td><td>15.065</td></tr> <tr><td>0.6</td><td>15.065</td><td>15.065</td><td>15.064</td></tr> <tr><td>0.8</td><td>15.064</td><td>15.063</td><td>15.062</td></tr> <tr><td>1.0</td><td>15.062</td><td>15.062</td><td>15.061</td></tr> <tr><td>1.1</td><td>15.062</td><td>15.061</td><td>15.060</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	15.071	15.070	15.070	0.2	15.068	15.068	15.067	0.4	15.067	15.066	15.065	0.6	15.065	15.065	15.064	0.8	15.064	15.063	15.062	1.0	15.062	15.062	15.061	1.1	15.062	15.061	15.060	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																															
0.0	15.071	15.070	15.070																																															
0.2	15.068	15.068	15.067																																															
0.4	15.067	15.066	15.065																																															
0.6	15.065	15.065	15.064																																															
0.8	15.064	15.063	15.062																																															
1.0	15.062	15.062	15.061																																															
1.1	15.062	15.061	15.060																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA15F-15	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																								
Object	+15.0V1A																																								
1. Graph		2. Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 170 [V]</th> <th>Input Volt. 264 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.10</td><td>10</td><td>10</td></tr> <tr><td>0.20</td><td>10</td><td>10</td></tr> <tr><td>0.40</td><td>10</td><td>10</td></tr> <tr><td>0.50</td><td>10</td><td>10</td></tr> <tr><td>0.60</td><td>10</td><td>10</td></tr> <tr><td>0.80</td><td>10</td><td>10</td></tr> <tr><td>0.90</td><td>10</td><td>10</td></tr> <tr><td>1.00</td><td>10</td><td>10</td></tr> <tr><td>1.10</td><td>10</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	10	10	0.10	10	10	0.20	10	10	0.40	10	10	0.50	10	10	0.60	10	10	0.80	10	10	0.90	10	10	1.00	10	10	1.10	10	10	—	—	—
Load Current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.00	10	10																																							
0.10	10	10																																							
0.20	10	10																																							
0.40	10	10																																							
0.50	10	10																																							
0.60	10	10																																							
0.80	10	10																																							
0.90	10	10																																							
1.00	10	10																																							
1.10	10	10																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL


Model	LDA15F-15	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																							
Object	+15.0V1A																																							
1. Graph	<p style="text-align: center;">□ Input Volt. 170V △ Input Volt. 264V</p>	2. Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 170 [V]</th> <th>Input Volt. 264 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>0.10</td><td>15</td><td>15</td></tr> <tr><td>0.20</td><td>15</td><td>15</td></tr> <tr><td>0.40</td><td>15</td><td>15</td></tr> <tr><td>0.50</td><td>15</td><td>15</td></tr> <tr><td>0.60</td><td>20</td><td>15</td></tr> <tr><td>0.80</td><td>20</td><td>20</td></tr> <tr><td>0.90</td><td>20</td><td>20</td></tr> <tr><td>1.00</td><td>20</td><td>20</td></tr> <tr><td>1.10</td><td>20</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.00	15	15	0.10	15	15	0.20	15	15	0.40	15	15	0.50	15	15	0.60	20	15	0.80	20	20	0.90	20	20	1.00	20	20	1.10	20	20	—	—	—
Load current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]																																						
	Ripple-Noise [mV]	Ripple-Noise [mV]																																						
0.00	15	15																																						
0.10	15	15																																						
0.20	15	15																																						
0.40	15	15																																						
0.50	15	15																																						
0.60	20	15																																						
0.80	20	20																																						
0.90	20	20																																						
1.00	20	20																																						
1.10	20	20																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																								
<p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																								
<p>T1: Due to AC Input Line T2: Due to Switching</p>																																								
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								


COSEL

Model	LDA15F-15																																																									
Item	Overcurrent Protection 過電流保護	Temperature 25°C	Testing Circuitry Figure A																																																							
Object	+15.0V1A																																																									
1. Graph	<p>Input Volt. 170 V Input Volt. 200 V Input Volt. 264 V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>15.00</td><td>1.33</td><td>1.33</td><td>1.33</td></tr> <tr><td>14.25</td><td>1.38</td><td>1.37</td><td>1.36</td></tr> <tr><td>13.50</td><td>1.40</td><td>1.38</td><td>1.38</td></tr> <tr><td>12.00</td><td>1.44</td><td>1.43</td><td>1.42</td></tr> <tr><td>10.50</td><td>1.49</td><td>1.46</td><td>1.45</td></tr> <tr><td>9.00</td><td>1.52</td><td>1.49</td><td>1.48</td></tr> <tr><td>7.50</td><td>1.54</td><td>1.51</td><td>1.50</td></tr> <tr><td>6.00</td><td>1.55</td><td>1.51</td><td>1.51</td></tr> <tr><td>4.50</td><td>1.53</td><td>1.50</td><td>1.51</td></tr> <tr><td>3.00</td><td>1.46</td><td>1.44</td><td>1.48</td></tr> <tr><td>1.50</td><td>1.32</td><td>1.31</td><td>1.37</td></tr> <tr><td>0.00</td><td>1.04</td><td>1.06</td><td>1.15</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	15.00	1.33	1.33	1.33	14.25	1.38	1.37	1.36	13.50	1.40	1.38	1.38	12.00	1.44	1.43	1.42	10.50	1.49	1.46	1.45	9.00	1.52	1.49	1.48	7.50	1.54	1.51	1.50	6.00	1.55	1.51	1.51	4.50	1.53	1.50	1.51	3.00	1.46	1.44	1.48	1.50	1.32	1.31	1.37	0.00	1.04	1.06	1.15
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
15.00	1.33	1.33	1.33																																																							
14.25	1.38	1.37	1.36																																																							
13.50	1.40	1.38	1.38																																																							
12.00	1.44	1.43	1.42																																																							
10.50	1.49	1.46	1.45																																																							
9.00	1.52	1.49	1.48																																																							
7.50	1.54	1.51	1.50																																																							
6.00	1.55	1.51	1.51																																																							
4.50	1.53	1.50	1.51																																																							
3.00	1.46	1.44	1.48																																																							
1.50	1.32	1.31	1.37																																																							
0.00	1.04	1.06	1.15																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。


COSEL

COSEL

COSEL


Model	LDA15F-15	Temperature Testing Circuitry 25°C Figure A
Item	Rise and Fall Time 立上り、立下り時間	
Object	+15.0V1A	

1. Graph



2. Values

Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		3.0	10.5	13.5	180.5	84.3	
100 %		3.0	14.5	17.5	88.3	49.0	



COSSEL

Model	LDA15F-15																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																					
Object	+15.0V1A																																																					
Testing Circuitry Figure A																																																						
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>15.097</td><td>15.097</td><td>15.096</td></tr> <tr><td>-10</td><td>15.089</td><td>15.088</td><td>15.088</td></tr> <tr><td>0</td><td>15.081</td><td>15.080</td><td>15.080</td></tr> <tr><td>10</td><td>15.073</td><td>15.073</td><td>15.072</td></tr> <tr><td>20</td><td>15.065</td><td>15.065</td><td>15.064</td></tr> <tr><td>25</td><td>15.062</td><td>15.061</td><td>15.060</td></tr> <tr><td>30</td><td>15.057</td><td>15.057</td><td>15.056</td></tr> <tr><td>40</td><td>15.047</td><td>15.047</td><td>15.046</td></tr> <tr><td>50</td><td>15.037</td><td>15.036</td><td>15.036</td></tr> <tr><td>60</td><td>15.023</td><td>15.023</td><td>15.022</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Temperature [°C]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	-20	15.097	15.097	15.096	-10	15.089	15.088	15.088	0	15.081	15.080	15.080	10	15.073	15.073	15.072	20	15.065	15.065	15.064	25	15.062	15.061	15.060	30	15.057	15.057	15.056	40	15.047	15.047	15.046	50	15.037	15.036	15.036	60	15.023	15.023	15.022	—	—	—	—
Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
-20	15.097	15.097	15.096																																																			
-10	15.089	15.088	15.088																																																			
0	15.081	15.080	15.080																																																			
10	15.073	15.073	15.072																																																			
20	15.065	15.065	15.064																																																			
25	15.062	15.061	15.060																																																			
30	15.057	15.057	15.056																																																			
40	15.047	15.047	15.046																																																			
50	15.037	15.036	15.036																																																			
60	15.023	15.023	15.022																																																			
—	—	—	—																																																			

COSEL

Model	LDA15F-15	
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	
Object	+15.0V 1A	
1. Graph		
<p>[V]</p>		Load 50%
		Load 100%
2. Values		
Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	46	71
-10	45	71
0	45	71
10	45	71
20	45	71
25	45	71
30	45	71
40	45	71
50	46	71
60	46	72
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSSEL

Model	LDA15F-15				
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A			
Object	+15.0V 1A				
1. Graph					
<p>Graph showing Ripple Voltage [mV] vs Ambient Temperature [°C]. The Y-axis ranges from 0 to 150 mV, and the X-axis ranges from -30 to 70 °C. Two sets of data points are shown: Load 50% (open squares) and Load 100% (open triangles). A slanted line connects the points for Load 50% between approximately -10°C and 50°C.</p>					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>		2. Values			
Ambient Temp. [°C]	Load 50%	Load 100%			
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]			
-20	10	15			
-10	10	10			
0	10	10			
10	10	10			
20	10	10			
25	10	10			
30	10	10			
40	10	10			
50	10	10			
60	10	10			
—	—	—			

COSEL

Model	LDA15F-15	Temperature Testing Circuitry	25°C Figure A																					
Item	Time Lapse Drift 経時ドリフト																							
Object	+15.0V1A																							
1. Graph			2. Values																					
<p>[V]</p> <table> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.073</td></tr> <tr><td>0.5</td><td>15.052</td></tr> <tr><td>1.0</td><td>15.052</td></tr> <tr><td>2.0</td><td>15.052</td></tr> <tr><td>3.0</td><td>15.052</td></tr> <tr><td>4.0</td><td>15.052</td></tr> <tr><td>5.0</td><td>15.052</td></tr> <tr><td>6.0</td><td>15.052</td></tr> <tr><td>7.0</td><td>15.052</td></tr> <tr><td>8.0</td><td>15.053</td></tr> </tbody> </table>			Time since start [H]	Output Voltage [V]	0.0	15.073	0.5	15.052	1.0	15.052	2.0	15.052	3.0	15.052	4.0	15.052	5.0	15.052	6.0	15.052	7.0	15.052	8.0	15.053
Time since start [H]	Output Voltage [V]																							
0.0	15.073																							
0.5	15.052																							
1.0	15.052																							
2.0	15.052																							
3.0	15.052																							
4.0	15.052																							
5.0	15.052																							
6.0	15.052																							
7.0	15.052																							
8.0	15.053																							
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 200V</p> <p>Load 100%</p>																								



Model	LDA15F-15	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+15.0V1A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 170~264 V

Load Current : 0~1 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 170~264 V

負荷電流 0~1 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	264	0	15.098		
Minimum Voltage	50	264	1	15.032	±34	±0.3



Model	LDA15F-15		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+15.0V1A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	15.06	Input Volt.: 200V, Load Current:1A
Line Regulation [mV]	6	Input Volt.: 170~264V, Load Current:1A
Load Regulation [mV]	13	Input Volt.: 200V, Load Current:0~1A



Model	LDA15F-15	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	—	—	—
(B) IEC60950	—	—	—

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	0.25	0.35	0.43



Model	LDA15F-15	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+15.0V1A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 200 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LDA15F-15	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	_____		


1. Graph

Remarks

Input Volt. 230 V

Load 100 %

規格 1 : [EN 55022] Class B(QP)
 規格 2 : [EN 55022] Class B(平均値)






Figure A


Data Acquisition/Control Unit
データ集録システム

Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E