

COSEL

TEST DATA OF LDA15F-24
(100V INPUT)

Regulated DC Power Supply

Date : June 23. 1999

Approved by : H. Yamaguchi
Design Manager

Prepared by : T. Ashikawa
Design Engineer

コーセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Inrush Current	12
突入電流	
13. Dynamic Load Response	13
動的負荷変動	
14. Rise and Fall Time	14
立上り、立下がり時間	
15. Ambient Temperature Drift	15
周囲温度変動	
16. Minimum Input Voltage for Regulated Output Voltage .	16
最低レギュレーション電圧	
17. Ripple Voltage (by Ambient Temperature)	17
リップル電圧 (周囲温度特性)	
18. Time Lapse Drift	18
経時ドリフト	
19. Output Voltage Accuracy	19
定電圧精度	
20. Condensation	20
結露特性	
21. Leakage Current	21
漏洩電流	
22. Line Noise Tolerance	22
入力雑音耐量	
23. Conducted Emission	23
雑音端子電圧	
24. Figure of Testing Circuitry	24
測定回路図	

(Final Page 25)

COSEL

Model	LDA15F-24	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+24V 0.7A																																		
1. Graph	<p>Load 50% □</p> <p>Load 100% ▲</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>24.005</td><td>23.987</td></tr> <tr><td>80</td><td>24.005</td><td>23.999</td></tr> <tr><td>85</td><td>24.005</td><td>24.003</td></tr> <tr><td>90</td><td>24.005</td><td>24.003</td></tr> <tr><td>100</td><td>24.004</td><td>24.001</td></tr> <tr><td>110</td><td>24.003</td><td>24.001</td></tr> <tr><td>120</td><td>24.003</td><td>24.000</td></tr> <tr><td>132</td><td>24.003</td><td>24.000</td></tr> <tr><td>140</td><td>24.003</td><td>24.000</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	24.005	23.987	80	24.005	23.999	85	24.005	24.003	90	24.005	24.003	100	24.004	24.001	110	24.003	24.001	120	24.003	24.000	132	24.003	24.000	140	24.003	24.000
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	24.005	23.987																																	
80	24.005	23.999																																	
85	24.005	24.003																																	
90	24.005	24.003																																	
100	24.004	24.001																																	
110	24.003	24.001																																	
120	24.003	24.000																																	
132	24.003	24.000																																	
140	24.003	24.000																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA15F-24
Item	Input Current (by Load Current) 入力電流（負荷特性）
Output	—
1. Graph	
<p>The graph plots Input Current [A] on the y-axis (0 to 0.5) against Load Current [A] on the x-axis (0 to 1.0). Three sets of curves are shown for Input Volt. 85V (triangles), Input Volt. 100V (squares), and Input Volt. 132V (circles). Each set consists of three curves corresponding to Load Current values of 0.00, 0.10, and 0.20 A. A slanted line is drawn through the data points at approximately 0.55 A load current.</p>	

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	0.037	0.036	0.034
0.10	0.095	0.087	0.075
0.20	0.145	0.131	0.111
0.30	0.198	0.176	0.148
0.40	0.252	0.224	0.184
0.50	0.308	0.270	0.222
0.60	0.367	0.322	0.257
0.70	0.418	0.368	0.293
0.77	0.465	0.400	0.319
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current


(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA15F-24																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Output	_____																																																									
1. Graph	<p>Graph showing Input Power (W) vs Load Current (A) for three input voltages: 85V (triangles), 100V (squares), and 132V (circles). The power increases linearly with load current. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85V [W]</th> <th>Input Volt. 100V [W]</th> <th>Input Volt. 132V [W]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1.32</td><td>1.46</td><td>1.72</td></tr> <tr><td>0.10</td><td>4.17</td><td>4.28</td><td>4.53</td></tr> <tr><td>0.20</td><td>6.89</td><td>6.98</td><td>7.28</td></tr> <tr><td>0.30</td><td>9.80</td><td>9.80</td><td>10.05</td></tr> <tr><td>0.40</td><td>12.82</td><td>12.80</td><td>12.88</td></tr> <tr><td>0.50</td><td>15.96</td><td>15.77</td><td>15.83</td></tr> <tr><td>0.60</td><td>19.34</td><td>19.07</td><td>18.69</td></tr> <tr><td>0.70</td><td>22.28</td><td>22.14</td><td>21.49</td></tr> <tr><td>0.77</td><td>25.06</td><td>24.23</td><td>23.65</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85V [W]	Input Volt. 100V [W]	Input Volt. 132V [W]	0.00	1.32	1.46	1.72	0.10	4.17	4.28	4.53	0.20	6.89	6.98	7.28	0.30	9.80	9.80	10.05	0.40	12.82	12.80	12.88	0.50	15.96	15.77	15.83	0.60	19.34	19.07	18.69	0.70	22.28	22.14	21.49	0.77	25.06	24.23	23.65	—	—	—	—	—	—	—	—	—	—	—	—			
Load Current [A]	Input Volt. 85V [W]	Input Volt. 100V [W]	Input Volt. 132V [W]																																																							
0.00	1.32	1.46	1.72																																																							
0.10	4.17	4.28	4.53																																																							
0.20	6.89	6.98	7.28																																																							
0.30	9.80	9.80	10.05																																																							
0.40	12.82	12.80	12.88																																																							
0.50	15.96	15.77	15.83																																																							
0.60	19.34	19.07	18.69																																																							
0.70	22.28	22.14	21.49																																																							
0.77	25.06	24.23	23.65																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1.32</td><td>1.46</td><td>1.72</td></tr> <tr><td>0.10</td><td>4.17</td><td>4.28</td><td>4.53</td></tr> <tr><td>0.20</td><td>6.89</td><td>6.98</td><td>7.28</td></tr> <tr><td>0.30</td><td>9.80</td><td>9.80</td><td>10.05</td></tr> <tr><td>0.40</td><td>12.82</td><td>12.80</td><td>12.88</td></tr> <tr><td>0.50</td><td>15.96</td><td>15.77</td><td>15.83</td></tr> <tr><td>0.60</td><td>19.34</td><td>19.07</td><td>18.69</td></tr> <tr><td>0.70</td><td>22.28</td><td>22.14</td><td>21.49</td></tr> <tr><td>0.77</td><td>25.06</td><td>24.23</td><td>23.65</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	1.32	1.46	1.72	0.10	4.17	4.28	4.53	0.20	6.89	6.98	7.28	0.30	9.80	9.80	10.05	0.40	12.82	12.80	12.88	0.50	15.96	15.77	15.83	0.60	19.34	19.07	18.69	0.70	22.28	22.14	21.49	0.77	25.06	24.23	23.65	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	1.32	1.46	1.72																																																							
0.10	4.17	4.28	4.53																																																							
0.20	6.89	6.98	7.28																																																							
0.30	9.80	9.80	10.05																																																							
0.40	12.82	12.80	12.88																																																							
0.50	15.96	15.77	15.83																																																							
0.60	19.34	19.07	18.69																																																							
0.70	22.28	22.14	21.49																																																							
0.77	25.06	24.23	23.65																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	77.2	76.6
80	77.6	78.1
85	77.7	78.8
90	78.0	79.5
100	78.2	80.5
110	78.3	81.1
120	77.7	81.4
132	77.6	81.4
140	77.1	80.9

COSEL

Model	LDA15F-24																																																										
Item	Efficiency (by Load Current) 効率(負荷電流特性)	Temperature Testing Circuitry	25°C Figure A																																																								
Output	——																																																										
1. Graph	<p>Efficiency [%] vs Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 85V (△) Input Volt. 100V (□) Input Volt. 132V (○) <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [85V] (%)</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [132V] (%)</th> </tr> </thead> <tbody> <tr><td>0.10</td><td>63.1</td><td>62.0</td><td>58.6</td></tr> <tr><td>0.20</td><td>73.5</td><td>72.8</td><td>69.8</td></tr> <tr><td>0.30</td><td>77.0</td><td>77.1</td><td>75.6</td></tr> <tr><td>0.40</td><td>78.7</td><td>79.0</td><td>77.9</td></tr> <tr><td>0.50</td><td>78.3</td><td>80.6</td><td>79.4</td></tr> <tr><td>0.60</td><td>78.4</td><td>78.7</td><td>81.5</td></tr> <tr><td>0.70</td><td>77.8</td><td>79.6</td><td>80.7</td></tr> <tr><td>0.77</td><td>77.5</td><td>79.9</td><td>81.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Efficiency [85V] (%)	Efficiency [100V] (%)	Efficiency [132V] (%)	0.10	63.1	62.0	58.6	0.20	73.5	72.8	69.8	0.30	77.0	77.1	75.6	0.40	78.7	79.0	77.9	0.50	78.3	80.6	79.4	0.60	78.4	78.7	81.5	0.70	77.8	79.6	80.7	0.77	77.5	79.9	81.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—						
Load Current [A]	Efficiency [85V] (%)	Efficiency [100V] (%)	Efficiency [132V] (%)																																																								
0.10	63.1	62.0	58.6																																																								
0.20	73.5	72.8	69.8																																																								
0.30	77.0	77.1	75.6																																																								
0.40	78.7	79.0	77.9																																																								
0.50	78.3	80.6	79.4																																																								
0.60	78.4	78.7	81.5																																																								
0.70	77.8	79.6	80.7																																																								
0.77	77.5	79.9	81.8																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.10</td><td>63.1</td><td>62.0</td><td>58.6</td></tr> <tr><td>0.20</td><td>73.5</td><td>72.8</td><td>69.8</td></tr> <tr><td>0.30</td><td>77.0</td><td>77.1</td><td>75.6</td></tr> <tr><td>0.40</td><td>78.7</td><td>79.0</td><td>77.9</td></tr> <tr><td>0.50</td><td>78.3</td><td>80.6</td><td>79.4</td></tr> <tr><td>0.60</td><td>78.4</td><td>78.7</td><td>81.5</td></tr> <tr><td>0.70</td><td>77.8</td><td>79.6</td><td>80.7</td></tr> <tr><td>0.77</td><td>77.5</td><td>79.9</td><td>81.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.10	63.1	62.0	58.6	0.20	73.5	72.8	69.8	0.30	77.0	77.1	75.6	0.40	78.7	79.0	77.9	0.50	78.3	80.6	79.4	0.60	78.4	78.7	81.5	0.70	77.8	79.6	80.7	0.77	77.5	79.9	81.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Load Current [A]	Efficiency [%]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
0.10	63.1	62.0	58.6																																																								
0.20	73.5	72.8	69.8																																																								
0.30	77.0	77.1	75.6																																																								
0.40	78.7	79.0	77.9																																																								
0.50	78.3	80.6	79.4																																																								
0.60	78.4	78.7	81.5																																																								
0.70	77.8	79.6	80.7																																																								
0.77	77.5	79.9	81.8																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA15F-24	Temperature	25°C																																
Item	Hold-Up Time 出力保持時間	Testing Circuitry	Figure A																																
Object	+24.0V 0.7A																																		
1. Graph		2. Values																																	
<p style="text-align: center;">Load 50% Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>27</td><td>9</td></tr> <tr><td>80</td><td>32</td><td>12</td></tr> <tr><td>85</td><td>37</td><td>14</td></tr> <tr><td>90</td><td>42</td><td>17</td></tr> <tr><td>100</td><td>53</td><td>23</td></tr> <tr><td>110</td><td>66</td><td>29</td></tr> <tr><td>120</td><td>79</td><td>37</td></tr> <tr><td>132</td><td>97</td><td>46</td></tr> <tr><td>140</td><td>110</td><td>53</td></tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	27	9	80	32	12	85	37	14	90	42	17	100	53	23	110	66	29	120	79	37	132	97	46	140	110	53
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	27	9																																	
80	32	12																																	
85	37	14																																	
90	42	17																																	
100	53	23																																	
110	66	29																																	
120	79	37																																	
132	97	46																																	
140	110	53																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	LDA15F-24	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障	Testing Circuitry	Figure A																																																			
Object	+24.0V 0.7A																																																					
1. Graph		2. Values																																																				
<p>Graph showing Instantaneous Compensation Time [mS] vs Load Current [A]. The Y-axis is logarithmic from 1 to 1000 ms. The X-axis ranges from 0 to 1 A. Three curves are shown for Input Volt. 85V (solid line with triangles), Input Volt. 100V (dashed line with squares), and Input Volt. 132V (dotted line with circles). A slanted line indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.10</td><td>118</td><td>165</td><td>288</td></tr> <tr><td>0.20</td><td>64</td><td>93</td><td>168</td></tr> <tr><td>0.30</td><td>39</td><td>57</td><td>111</td></tr> <tr><td>0.40</td><td>27</td><td>40</td><td>82</td></tr> <tr><td>0.50</td><td>18</td><td>30</td><td>64</td></tr> <tr><td>0.60</td><td>12</td><td>22</td><td>48</td></tr> <tr><td>0.70</td><td>5</td><td>14</td><td>39</td></tr> <tr><td>0.77</td><td>4</td><td>13</td><td>35</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.10	118	165	288	0.20	64	93	168	0.30	39	57	111	0.40	27	40	82	0.50	18	30	64	0.60	12	22	48	0.70	5	14	39	0.77	4	13	35	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	—	—	—																																																			
0.10	118	165	288																																																			
0.20	64	93	168																																																			
0.30	39	57	111																																																			
0.40	27	40	82																																																			
0.50	18	30	64																																																			
0.60	12	22	48																																																			
0.70	5	14	39																																																			
0.77	4	13	35																																																			
—	—	—	—																																																			
—	—	—	—																																																			


This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA15F-24	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+24.0V 0.7A																																																	
1. Graph																																																		
—△— Input Volt. 85 V —□— Input Volt. 100 V —○— Input Volt. 132 V																																																		
																																																		
2. Values																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>24.013</td><td>24.012</td><td>24.012</td></tr> <tr> <td>0.10</td><td>24.010</td><td>24.010</td><td>24.009</td></tr> <tr> <td>0.20</td><td>24.009</td><td>24.008</td><td>24.007</td></tr> <tr> <td>0.30</td><td>24.008</td><td>24.007</td><td>24.006</td></tr> <tr> <td>0.40</td><td>24.006</td><td>24.006</td><td>24.004</td></tr> <tr> <td>0.50</td><td>24.005</td><td>24.005</td><td>24.004</td></tr> <tr> <td>0.60</td><td>24.005</td><td>24.004</td><td>24.002</td></tr> <tr> <td>0.70</td><td>24.002</td><td>24.002</td><td>24.001</td></tr> <tr> <td>0.77</td><td>23.999</td><td>24.001</td><td>24.000</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	24.013	24.012	24.012	0.10	24.010	24.010	24.009	0.20	24.009	24.008	24.007	0.30	24.008	24.007	24.006	0.40	24.006	24.006	24.004	0.50	24.005	24.005	24.004	0.60	24.005	24.004	24.002	0.70	24.002	24.002	24.001	0.77	23.999	24.001	24.000	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.00	24.013	24.012	24.012																																															
0.10	24.010	24.010	24.009																																															
0.20	24.009	24.008	24.007																																															
0.30	24.008	24.007	24.006																																															
0.40	24.006	24.006	24.004																																															
0.50	24.005	24.005	24.004																																															
0.60	24.005	24.004	24.002																																															
0.70	24.002	24.002	24.001																																															
0.77	23.999	24.001	24.000																																															
—	—	—	—																																															
Note: Slanted line shows the range of the rated load current.																																																		
(注)斜線は定格負荷電流範囲を示す。																																																		

COSEL

Model	LDA15F-24	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																							
Object	+24.0V 0.7A																																							
1. Graph	<p style="text-align: center;">□ Input Volt. 85V △ Input Volt. 132V</p>	2. Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.10</td><td>10</td><td>10</td></tr> <tr><td>0.20</td><td>10</td><td>10</td></tr> <tr><td>0.40</td><td>10</td><td>10</td></tr> <tr><td>0.50</td><td>10</td><td>10</td></tr> <tr><td>0.60</td><td>10</td><td>10</td></tr> <tr><td>0.65</td><td>10</td><td>10</td></tr> <tr><td>0.70</td><td>20</td><td>10</td></tr> <tr><td>0.77</td><td>40</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	10	10	0.10	10	10	0.20	10	10	0.40	10	10	0.50	10	10	0.60	10	10	0.65	10	10	0.70	20	10	0.77	40	10	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																						
0.00	10	10																																						
0.10	10	10																																						
0.20	10	10																																						
0.40	10	10																																						
0.50	10	10																																						
0.60	10	10																																						
0.65	10	10																																						
0.70	20	10																																						
0.77	40	10																																						
—	—	—																																						
—	—	—																																						
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p>		<p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p>																																						
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL


Model	LDA15F-24																																							
Item	Ripple-Noise リップルノイズ	Temperature Testing Circuitry 25°C Figure A																																						
Object	+24.0V 0.7A																																							
1. Graph																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>0.10</td><td>15</td><td>15</td></tr> <tr><td>0.20</td><td>15</td><td>15</td></tr> <tr><td>0.30</td><td>15</td><td>15</td></tr> <tr><td>0.40</td><td>15</td><td>15</td></tr> <tr><td>0.50</td><td>20</td><td>15</td></tr> <tr><td>0.60</td><td>30</td><td>20</td></tr> <tr><td>0.70</td><td>40</td><td>20</td></tr> <tr><td>0.77</td><td>55</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.00	15	15	0.10	15	15	0.20	15	15	0.30	15	15	0.40	15	15	0.50	20	15	0.60	30	20	0.70	40	20	0.77	55	20	—	—	—	—	—	—
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
	Ripple-Noise [mV]	Ripple-Noise [mV]																																						
0.00	15	15																																						
0.10	15	15																																						
0.20	15	15																																						
0.30	15	15																																						
0.40	15	15																																						
0.50	20	15																																						
0.60	30	20																																						
0.70	40	20																																						
0.77	55	20																																						
—	—	—																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																								
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL

Model LDA15F-24

Item Overcurrent Protection
過電流保護

Object +24.0V 0.7A

Temperature 25°C
Testing Circuitry Figure A

2. Values


Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
24.00	0.81	0.88	0.89
22.80	0.83	0.89	0.90
21.60	0.86	0.92	0.92
19.20	0.92	0.97	0.96
16.80	0.99	1.02	1.00
14.40	1.05	1.08	1.04
12.00	1.11	1.12	1.06
9.60	1.17	1.15	1.08
7.20	1.20	1.16	1.07
4.80	1.18	1.12	1.02
2.40	1.05	0.99	0.91
0.00	0.75	0.75	0.71

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。


COSEL

Model	LDA15F-24	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current 突入電流		
Object	—		



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current

- ① 8.81 [A]
- ② 1.21 [A]




COSEL

Model	LDA15F-24	Temperature Testing Circuitry 25°C Figure A
Item	Dynamic Load Response 動的負荷變動	
Object	+24.0 V 0.7 A	



Input Volt. 100 V

Cycle 1000 mS





Load 0% ↔

Load 100 %



Load 0% ↔

Load 50 %




200 mV/div

10 mS/div

COSEL


Model	LDA15F-24	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+24.0V 0.7A		

1. Graph



2. Values

Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		4.8	11.5	16.3	37.0	133.5	
100 %		4.8	17.3	22.0	14.3	57.8	




COSEL

Model	LDA15F-24																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																					
Object	+24.0V 0.7A																																																					
1. Graph	—△— Input Volt. 85V —□— Input Volt. 100V —○— Input Volt. 132V	[V]	2. Values																																																			
<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>24.009</td><td>24.010</td><td>24.008</td></tr> <tr><td>-10</td><td>24.011</td><td>24.009</td><td>24.008</td></tr> <tr><td>0</td><td>24.007</td><td>24.006</td><td>24.005</td></tr> <tr><td>10</td><td>24.005</td><td>24.002</td><td>24.002</td></tr> <tr><td>20</td><td>24.002</td><td>24.002</td><td>24.000</td></tr> <tr><td>25</td><td>24.001</td><td>24.000</td><td>23.999</td></tr> <tr><td>30</td><td>23.998</td><td>24.001</td><td>23.997</td></tr> <tr><td>40</td><td>23.989</td><td>23.988</td><td>23.985</td></tr> <tr><td>50</td><td>23.974</td><td>23.973</td><td>23.971</td></tr> <tr><td>60</td><td>23.953</td><td>23.952</td><td>23.950</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	24.009	24.010	24.008	-10	24.011	24.009	24.008	0	24.007	24.006	24.005	10	24.005	24.002	24.002	20	24.002	24.002	24.000	25	24.001	24.000	23.999	30	23.998	24.001	23.997	40	23.989	23.988	23.985	50	23.974	23.973	23.971	60	23.953	23.952	23.950	—	—	—	—
Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	24.009	24.010	24.008																																																			
-10	24.011	24.009	24.008																																																			
0	24.007	24.006	24.005																																																			
10	24.005	24.002	24.002																																																			
20	24.002	24.002	24.000																																																			
25	24.001	24.000	23.999																																																			
30	23.998	24.001	23.997																																																			
40	23.989	23.988	23.985																																																			
50	23.974	23.973	23.971																																																			
60	23.953	23.952	23.950																																																			
—	—	—	—																																																			

COSEL

Model	LDA15F-24
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+24.0V 0.7A



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A


2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	47	75
-10	47	75
0	46	73
10	46	72
20	46	73
25	46	73
30	46	73
40	46	73
50	46	73
60	47	73
—	—	—

COSEL

Model	LDA15F-24
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+24.0V 0.7A

1. Graph



Input Volt. 100 V

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	15	40
-10	10	25
0	10	20
10	10	15
20	10	15
25	10	10
30	10	10
40	10	10
50	10	10
60	10	10
—	—	—

COSEL

Model	LDA15F-24	Temperature Testing Circuitry	25°C																					
Item	Time Lapse Drift 経時ドリフト		Figure A																					
Object	+24.0V 0.7A	2. Values																						
1. Graph																								
<p>[V]</p> <table border="1"> <caption>Data points from Figure A graph</caption> <thead> <tr> <th>Time [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>23.985</td></tr> <tr><td>0.5</td><td>23.985</td></tr> <tr><td>1.0</td><td>23.985</td></tr> <tr><td>2.0</td><td>23.985</td></tr> <tr><td>3.0</td><td>23.985</td></tr> <tr><td>4.0</td><td>23.985</td></tr> <tr><td>5.0</td><td>23.985</td></tr> <tr><td>6.0</td><td>23.985</td></tr> <tr><td>7.0</td><td>23.985</td></tr> <tr><td>8.0</td><td>23.985</td></tr> </tbody> </table> <p>Input Volt. 100V Load 100%</p>			Time [H]	Output Voltage [V]	0.0	23.985	0.5	23.985	1.0	23.985	2.0	23.985	3.0	23.985	4.0	23.985	5.0	23.985	6.0	23.985	7.0	23.985	8.0	23.985
Time [H]	Output Voltage [V]																							
0.0	23.985																							
0.5	23.985																							
1.0	23.985																							
2.0	23.985																							
3.0	23.985																							
4.0	23.985																							
5.0	23.985																							
6.0	23.985																							
7.0	23.985																							
8.0	23.985																							



Model	LDA15F-24	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+24.0V 0.7A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~0.7 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~0.7 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	85	0.0	24.020	±29	±0.2
Minimum Voltage	50	132	0.7	23.964		

COSEL

Model	LDA15F-24	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+24.0V 0.7A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	24.002	Input Volt.: 100V, Load Current: 0.7A
Line Regulation [mV]	8	Input Volt.: 85~132V, Load Current: 0.7A
Load Regulation [mV]	15	Input Volt.: 100V, Load Current: 0~0.7A



Model	LDA15F-24	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.12	0.16	0.24
(B) IEC60950	0.12	0.16	0.25

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	LDA15F-24	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+24.0V 0.7A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LDA15F-24	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	<hr/>		

1. Graph

Remarks


Input Volt. 100 V (VCCI Class B)

120 V (FCC Class B)


Load 100 %

規格1：[VCCI] Class B(平均値)

規格2：[VCCI] Class B(QP)



規格2：[FCC Part15] Class B







Figure B (DENTORI)




Figure B (IEC 60950)

