

COSEL

TEST DATA OF LDA300W-12

(100V INPUT)

Regulated DC Power Supply

Date : Feb. 22. 1997

Approved by : K. Nagahara
Design Manager

Prepared by : T. Mano
Design Engineer

コーワセル株式会社

COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Hold-Up Time	3
出力保持時間	
4. Instantaneous Interruption Compensation	4
瞬時停電保障	
5. Load Regulation	5
静的負荷変動	
6. Ripple Voltage (by Load Current)	6
リップル電圧(負荷電流特性)	
7. Ripple-Noise	7
リップルノイズ	
8. Overcurrent Protection	8
過電流保護	
9. Overvoltage Protection	9
過電圧保護	
10. Inrush Current	10
突入電流	
11. Dynamic Load Responce	11
動的負荷変動	
12. Rise and Fall Time	12
立ち上り、立下り時間	
13. Ambient Temperature Drift	13
周囲温度変動	
14. Minimum Input Voltage for Regulated Output Voltage	14
最低レギュレーション電圧	
15. Ripple Voltage (by Ambient Temperature)	15
リップル電圧(周囲温度特性)	
16. Time Lapse Drift	16
経時ドリフト	
17. Voltage Accuracy	17
定電圧精度	
18. Condensation	18
結露特性	
19. Leakage Current	19
漏洩電流	
20. Line Noise Tolerance	20
入力雑音耐量	
21. Conducted Emission	21
雑音端子電圧	
22. Figure of Testing Circuitry	22
測定回路図	

(Final Page 23)

COSEL

Model	LDA300W-12																															
Item	Line Regulation 静的入力変動	Temperature 25°C Testing Circuitry Figure A																														
Object	+12V27A																															
1. Graph																																
		2. Values																														
<table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% Output Volt. [V]</th> <th>Load 100% Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>75</td><td>12.027</td><td>12.027</td></tr> <tr><td>80</td><td>12.028</td><td>12.028</td></tr> <tr><td>85</td><td>12.028</td><td>12.028</td></tr> <tr><td>90</td><td>12.028</td><td>12.028</td></tr> <tr><td>100</td><td>12.028</td><td>12.028</td></tr> <tr><td>110</td><td>12.028</td><td>12.028</td></tr> <tr><td>120</td><td>12.028</td><td>12.028</td></tr> <tr><td>132</td><td>12.028</td><td>12.028</td></tr> <tr><td>140</td><td>12.028</td><td>12.028</td></tr> </tbody> </table>			Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	75	12.027	12.027	80	12.028	12.028	85	12.028	12.028	90	12.028	12.028	100	12.028	12.028	110	12.028	12.028	120	12.028	12.028	132	12.028	12.028	140	12.028	12.028
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																														
75	12.027	12.027																														
80	12.028	12.028																														
85	12.028	12.028																														
90	12.028	12.028																														
100	12.028	12.028																														
110	12.028	12.028																														
120	12.028	12.028																														
132	12.028	12.028																														
140	12.028	12.028																														
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																

COSEL

Model	LDA300W-12																															
Item	Efficiency 効率	Temperature 25°C Testing Circuitry Figure A																														
Object	<hr/>																															
1. Graph																																
[%]		2. Values																														
		<table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% Efficiency [%]</th> <th>Load 100% Efficiency [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>79.72</td><td>77.35</td></tr> <tr><td>80</td><td>80.33</td><td>78.09</td></tr> <tr><td>85</td><td>80.56</td><td>78.85</td></tr> <tr><td>90</td><td>80.73</td><td>79.23</td></tr> <tr><td>100</td><td>80.85</td><td>80.00</td></tr> <tr><td>110</td><td>80.77</td><td>80.59</td></tr> <tr><td>120</td><td>80.53</td><td>81.00</td></tr> <tr><td>132</td><td>80.33</td><td>81.20</td></tr> <tr><td>140</td><td>79.97</td><td>81.20</td></tr> </tbody> </table>	Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]	75	79.72	77.35	80	80.33	78.09	85	80.56	78.85	90	80.73	79.23	100	80.85	80.00	110	80.77	80.59	120	80.53	81.00	132	80.33	81.20	140	79.97	81.20
Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]																														
75	79.72	77.35																														
80	80.33	78.09																														
85	80.56	78.85																														
90	80.73	79.23																														
100	80.85	80.00																														
110	80.77	80.59																														
120	80.53	81.00																														
132	80.33	81.20																														
140	79.97	81.20																														
Note: Slanted line shows the range of the rated input voltage.																																
(注)斜線は定格入力電圧範囲を示す。																																


COSEL

Model	LDA300W-12																																	
Item	Hold-Up Time 出力保持時間	Temperature 25°C Testing Circuitry Figure A																																
Object	+12V27A																																	
1. Graph																																		
		2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Hold-Up Time [ms]</th> <th>Hold-Up Time [ms]</th> </tr> </thead> <tbody> <tr><td>75</td><td>25</td><td>5</td></tr> <tr><td>80</td><td>33</td><td>9</td></tr> <tr><td>85</td><td>41</td><td>13</td></tr> <tr><td>90</td><td>50</td><td>18</td></tr> <tr><td>100</td><td>69</td><td>28</td></tr> <tr><td>110</td><td>90</td><td>38</td></tr> <tr><td>120</td><td>114</td><td>50</td></tr> <tr><td>132</td><td>144</td><td>66</td></tr> <tr><td>140</td><td>167</td><td>77</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Hold-Up Time [ms]	Hold-Up Time [ms]	75	25	5	80	33	9	85	41	13	90	50	18	100	69	28	110	90	38	120	114	50	132	144	66	140	167	77
Input Voltage [V]	Load 50%	Load 100%																																
	Hold-Up Time [ms]	Hold-Up Time [ms]																																
75	25	5																																
80	33	9																																
85	41	13																																
90	50	18																																
100	69	28																																
110	90	38																																
120	114	50																																
132	144	66																																
140	167	77																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、AC入力断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。 (注)斜線は定格入力電圧範囲を示す。</p>																																		

COSEL

Model	LDA300W-12
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	+12V 27A

Testing Circuitry Figure A 25°C



2. Values

Load Current [A]	Input Volt.	Input Volt.	Input Volt.
	85[V]	100[V]	132[V]
Time [mS]			
0.0	—	—	—
5.0	91	162	346
10.0	43	74	177
15.0	26	50	113
20.0	16	34	82
25.0	10	26	63
27.0	8	22	56
30.0	6	18	52
—	—	—	—
—	—	—	—
—	—	—	—

This duration covers from Shut-off of AC-IN to the moment when output voltage descends to its 95% of the rated.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定格値の 95 % になる時の瞬時停電時間をいう。

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA300W-12																																																	
Item	Load Regulation 靜的負荷変動	Temperature 25°C	Testing Circuitry Figure A																																															
Object	+12V 27A																																																	
1. Graph																																																		
			2. Values																																															
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>12.036</td><td>12.036</td><td>12.036</td></tr> <tr> <td>4.0</td><td>12.034</td><td>12.034</td><td>12.034</td></tr> <tr> <td>8.0</td><td>12.033</td><td>12.033</td><td>12.033</td></tr> <tr> <td>12.0</td><td>12.031</td><td>12.032</td><td>12.032</td></tr> <tr> <td>16.0</td><td>12.030</td><td>12.030</td><td>12.031</td></tr> <tr> <td>20.0</td><td>12.029</td><td>12.029</td><td>12.030</td></tr> <tr> <td>24.0</td><td>12.028</td><td>12.028</td><td>12.029</td></tr> <tr> <td>27.0</td><td>12.027</td><td>12.027</td><td>12.028</td></tr> <tr> <td>29.7</td><td>12.026</td><td>12.027</td><td>12.027</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100[V]	Input Volt. 100[V]	Input Volt. 132[V]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.0	12.036	12.036	12.036	4.0	12.034	12.034	12.034	8.0	12.033	12.033	12.033	12.0	12.031	12.032	12.032	16.0	12.030	12.030	12.031	20.0	12.029	12.029	12.030	24.0	12.028	12.028	12.029	27.0	12.027	12.027	12.028	29.7	12.026	12.027	12.027	—	—	—	—			
Load Current [A]		Input Volt. 100[V]	Input Volt. 100[V]	Input Volt. 132[V]																																														
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																															
0.0	12.036	12.036	12.036																																															
4.0	12.034	12.034	12.034																																															
8.0	12.033	12.033	12.033																																															
12.0	12.031	12.032	12.032																																															
16.0	12.030	12.030	12.031																																															
20.0	12.029	12.029	12.030																																															
24.0	12.028	12.028	12.029																																															
27.0	12.027	12.027	12.028																																															
29.7	12.026	12.027	12.027																																															
—	—	—	—																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																		

COSEL

Model	LDA300W-12																																					
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)	Temperature Testing Circuitry 25°C Figure A																																				
Object	+12V27A																																					
1. Graph																																						
[mV]																																						
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85 [V] Ripple Output Volt. [mV]</th> <th>Input Volt. 132 [V] Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>5.0</td><td>20</td><td>20</td></tr> <tr><td>10.0</td><td>25</td><td>25</td></tr> <tr><td>15.0</td><td>30</td><td>25</td></tr> <tr><td>20.0</td><td>35</td><td>30</td></tr> <tr><td>25.0</td><td>40</td><td>30</td></tr> <tr><td>27.0</td><td>45</td><td>35</td></tr> <tr><td>30.0</td><td>50</td><td>40</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 85 [V] Ripple Output Volt. [mV]	Input Volt. 132 [V] Ripple Output Volt. [mV]	0.0	10	10	5.0	20	20	10.0	25	25	15.0	30	25	20.0	35	30	25.0	40	30	27.0	45	35	30.0	50	40	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V] Ripple Output Volt. [mV]	Input Volt. 132 [V] Ripple Output Volt. [mV]																																				
0.0	10	10																																				
5.0	20	20																																				
10.0	25	25																																				
15.0	30	25																																				
20.0	35	30																																				
25.0	40	30																																				
27.0	45	35																																				
30.0	50	40																																				
—	—	—																																				
—	—	—																																				
—	—	—																																				
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																						
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																						

COSEL

Model	LDA300W-12																																							
Item	Ripple-Noise リップルノイズ	Temperature Testing Circuitry 25°C Figure A																																						
Object	+12V27A																																							
1. Graph																																								
<p>[mV]</p>		Input Volt. 85V																																						
		Input Volt. 132V																																						
		2. Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>5.0</td><td>25</td><td>30</td></tr> <tr><td>10.0</td><td>30</td><td>40</td></tr> <tr><td>15.0</td><td>35</td><td>45</td></tr> <tr><td>20.0</td><td>45</td><td>50</td></tr> <tr><td>25.0</td><td>55</td><td>55</td></tr> <tr><td>27.0</td><td>60</td><td>60</td></tr> <tr><td>30.0</td><td>70</td><td>70</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.0	20	20	5.0	25	30	10.0	30	40	15.0	35	45	20.0	45	50	25.0	55	55	27.0	60	60	30.0	70	70	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
	Ripple-Noise [mV]	Ripple-Noise [mV]																																						
0.0	20	20																																						
5.0	25	30																																						
10.0	30	40																																						
15.0	35	45																																						
20.0	45	50																																						
25.0	55	55																																						
27.0	60	60																																						
30.0	70	70																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																								
<p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																								
<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p>																																								
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL

Model	LDA300W-12		
Item	Overcurrent Protection 過電流保護	Temperature Testing Circuitry Figure A	25°C
Object	+12V27A		
1. Graph	<p>[V] Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V</p>		
2. Values			
Output Voltage [V]	Input Volt. 85[V] Load Current [A]	Input Volt. 100[V] Load Current [A]	Input Volt. 132[V] Load Current [A]
12.00	33.58	33.36	33.21
11.40	33.58	33.40	33.29
10.80	33.61	33.45	33.35
9.60	33.69	33.56	33.49
8.40	33.79	33.68	33.62
7.20	—	—	—
6.00	—	—	—
4.80	—	—	—
3.60	—	—	—
2.40	—	—	—
1.20	—	—	—
0.00	—	—	—

Note: Slanted line shows the range of the rated load current.


Hiccup operation occurs when the output voltage is under 8V.

(注) 斜線は定格負荷電流範囲を示す。

8V以下は間欠動作となる。

COSEL

Model	LDA300W-12
Item	Overvoltage Protection 過電圧保護
Object	+12V27A



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
	Operating Point [V]		
-20	15.27	15.27	15.27
-10	15.40	15.40	15.40
0	15.48	15.48	15.48
10	15.55	15.55	15.55
20	15.65	15.65	15.65
25	15.69	15.69	15.69
30	15.74	15.74	15.74
40	15.83	15.83	15.83
50	15.92	15.92	15.92
60	16.00	16.00	16.00
—	—	—	—


COSEL

Model LDA300W-12

Item Inrush Current 突入電流

Temperature 25°C
Testing Circuitry Figure A

Object



Input Voltage 100 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 15.00 [A]

② 29.40 [A]



COSEL

Model	LDA300W-12	Temperature Testing Circuitry 25°C Figure A
Item	Dynamic Load Response 動的負荷變動	
Object	+12V 27A	



Input Volt. 100 V

Cycle 1000 mS

Load Current



Min. Load ↔

Load 100 %



Min. Load ↔


Load 50 %



COSEL


Model	LDA300W-12	Temperature Testing Circuitry	25°C
Item	Rise and Fall Time 立上り、立下り時間		Figure A
Object	+12V27A		

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		142.8	15.3	158.0	71.8	20.7	
100 %		143.3	15.3	158.5	31.3	11.8	




COSEL

Model	LDA300W-12
Item	Ambient Temperature Drift 周囲温度変動
Object	+12V 27A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

2. Values

Temperature [°C]	Input Volt. 100[V]	Input Volt. 100[V]	Input Volt. 132[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
-20	12.051	12.052	12.052
-10	12.046	12.046	12.047
0	12.040	12.040	12.041
10	12.035	12.035	12.035
20	12.031	12.031	12.031
25	12.028	12.029	12.029
30	12.025	12.025	12.026
40	12.019	12.019	12.020
50	12.013	12.013	12.014
60	12.005	12.005	12.005
—	—	—	—


COSEL

Model LDA300W-12

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +12V 27A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%		Load 100%	
	Input Volt. [V]	Input Volt. [V]	Input Volt. [V]	Input Volt. [V]
-20	58	66	58	66
-10	57	66	57	66
0	57	66	57	66
10	57	66	57	66
20	56	66	56	66
25	56	66	56	66
30	56	66	56	66
40	56	66	56	66
50	56	66	56	66
60	56	66	56	66
—	—	—	—	—

COSEL

Model	LDA300W-12	Testing Circuitry	Figure A																																																																							
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)																																																																									
Object	+12V 27A																																																																									
1. Graph		2. Values																																																																								
<p>Graph showing Ripple Voltage (mV) vs Ambient Temperature (°C) for LDA300W-12 at Input Volt. 85 V. The graph shows two sets of curves for Load 50% (squares) and Load 100% (triangles). The ambient temperature range is indicated by slanted lines between -10°C and 50°C.</p> <table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50% Ripple Output Volt. [mV]</th> <th>Load 100% Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>55</td><td>80</td></tr> <tr><td>-10</td><td>50</td><td>70</td></tr> <tr><td>0</td><td>40</td><td>60</td></tr> <tr><td>10</td><td>35</td><td>50</td></tr> <tr><td>20</td><td>30</td><td>45</td></tr> <tr><td>25</td><td>30</td><td>45</td></tr> <tr><td>30</td><td>25</td><td>40</td></tr> <tr><td>40</td><td>25</td><td>35</td></tr> <tr><td>50</td><td>20</td><td>35</td></tr> <tr><td>60</td><td>20</td><td>30</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-20	55	80	-10	50	70	0	40	60	10	35	50	20	30	45	25	30	45	30	25	40	40	25	35	50	20	35	60	20	30	—	—	—	<table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50% Ripple Output Volt. [mV]</th> <th>Load 100% Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>55</td><td>80</td></tr> <tr><td>-10</td><td>50</td><td>70</td></tr> <tr><td>0</td><td>40</td><td>60</td></tr> <tr><td>10</td><td>35</td><td>50</td></tr> <tr><td>20</td><td>30</td><td>45</td></tr> <tr><td>25</td><td>30</td><td>45</td></tr> <tr><td>30</td><td>25</td><td>40</td></tr> <tr><td>40</td><td>25</td><td>35</td></tr> <tr><td>50</td><td>20</td><td>35</td></tr> <tr><td>60</td><td>20</td><td>30</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-20	55	80	-10	50	70	0	40	60	10	35	50	20	30	45	25	30	45	30	25	40	40	25	35	50	20	35	60	20	30	—	—	—
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																																																								
-20	55	80																																																																								
-10	50	70																																																																								
0	40	60																																																																								
10	35	50																																																																								
20	30	45																																																																								
25	30	45																																																																								
30	25	40																																																																								
40	25	35																																																																								
50	20	35																																																																								
60	20	30																																																																								
—	—	—																																																																								
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																																																								
-20	55	80																																																																								
-10	50	70																																																																								
0	40	60																																																																								
10	35	50																																																																								
20	30	45																																																																								
25	30	45																																																																								
30	25	40																																																																								
40	25	35																																																																								
50	20	35																																																																								
60	20	30																																																																								
—	—	—																																																																								
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																																																										

COSSEL

Model	LDA300W-12	Temperature	25 °C																					
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																					
Object	+12V27A																							
1. Graph			2. Values																					
<p>[V]</p> <table border="1"> <caption>Data points from Figure A graph</caption> <thead> <tr> <th>Time [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.034</td></tr> <tr><td>0.5</td><td>12.030</td></tr> <tr><td>1.0</td><td>12.030</td></tr> <tr><td>2.0</td><td>12.030</td></tr> <tr><td>3.0</td><td>12.030</td></tr> <tr><td>4.0</td><td>12.030</td></tr> <tr><td>5.0</td><td>12.030</td></tr> <tr><td>6.0</td><td>12.030</td></tr> <tr><td>7.0</td><td>12.030</td></tr> <tr><td>8.0</td><td>12.030</td></tr> </tbody> </table>			Time [H]	Output Voltage [V]	0.0	12.034	0.5	12.030	1.0	12.030	2.0	12.030	3.0	12.030	4.0	12.030	5.0	12.030	6.0	12.030	7.0	12.030	8.0	12.030
Time [H]	Output Voltage [V]																							
0.0	12.034																							
0.5	12.030																							
1.0	12.030																							
2.0	12.030																							
3.0	12.030																							
4.0	12.030																							
5.0	12.030																							
6.0	12.030																							
7.0	12.030																							
8.0	12.030																							
<p>Output Voltage [V]</p> <p>Input Volt. 100V Load 100%</p>																								



Model	LDA300W-12	
Item	Output Voltage Accuracy 定電圧精度	Testing Circuitry Figure A
Object	+12V27A	

Output Voltage Accuracy

This is defined as the maximum value of the output voltage regulation load, temperature and input voltage vary at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 100~132 V

Load Current : 0~27 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage})/2$

Voltage Accuracy

* Output Voltage Accuracy (Ration) = $\frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

定電圧精度

温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 100~132 V

負過電流 0~27 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値})/2$

変動値

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	132	0	12.046		
Minimum Voltage	50	100	27	12.012	±17	±0.142



Model	LDA300W-12		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+12V27A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 45%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度45%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	12.03	40	60
	2	12.03	40	60
	3	12.03	40	60
Load 100 %	1	12.03	40	60
	2	12.03	40	60
	3	12.03	40	60

Input Volt. 100 V



Model	LDA300W-12		
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	+12V27A		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.20	0.23	0.31
(B) UL	0.20	0.23	0.31
(C) CSA	0.20	0.23	0.31

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 220 [V]	Input Volt. 264 [V]
(D) VDE	—	—	—

Load 100 %



Model	LDA300W-12	Testing Circuitry Figure C
Item	Line Noise Tolerance 入力雑音耐量	
Object	+12V27A	

1. Results

Pulse Width [nS]	MODE	Operating Point of Overvoltage Protection [V] 過電圧保護動作値	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	15.64	no regulation
	NORMAL	15.64	no regulation
1000	COMMON	15.64	no regulation
	NORMAL	15.64	no regulation

Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration: 1 min. or more
 Load : 100 %

COSEL

Model	LDA300W-12	Testing Circuitry Figure D
Item	Conducted Emission 雜音端子電圧	
Object	+12V27A	

1. Graph

Remarks



Input Volt. 120 V

Load 100 %

Note: Slanted line shows the range of Tolerance.

(注)斜線は許容値を示す。

No	Standards	Standards Complied	Frequency [MHz]	Tolerance [dB/μV]
1	FCC Class A		0.45~1.6	60
			1.6~30	69.5
2	FCC Class B	○	0.45~30	48
3	VCCI -1		0.15~0.5	79
			0.5~30	73
4	VCCI -2	○	0.15~0.5	66~56
			0.5~5	56
			5~30	60
5	CISPR 22 Class A (EN55022)		0.15~0.5	79
			0.5~30	73
6	CISPR 22 Class B (EN55022)		0.15~0.5	66~56
			0.5~5	56
			5~30	60






Figure A


Data Acquisition/Control Unit
データ集録システム

Figure B (DENTORI)




Figure B (UL, CSA, VDE)




Figure C




Figure D




Figure E