



RADIATED EMISSION

Model Name : LDA300W-3

Model No. :

Serial No. :

Points : 3

Detector : PEAK/QP

Polarization : Hori. & Vert.

Limit: [CISPR 22] Class B<3m>

Power Supply : 230V(1 Phase) 50Hz


Temp. : 25degC

Humi. : 44%

Date : 2003/4/9 15:52

Test Equip. : R3132,ESPC

Comment : Io=100%



Frequency [MHz]	Meter Reading (QP) [dBμV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level (QP) [dBμV/m]	Angle[°]	Height [cm]	Polar.	Limit [dBμV/m]	Margin [dB]
54.284	43.3	BL	-28.4	10.9	25.8	223	134	Vert.	40.0	14.2
89.422	36.2	BL	-28.0	11.5	19.7	75	122	Vert.	40.0	20.3
942.839	21.1	BL	-25.6	27.3	22.8	183	134	Hori.	47.0	24.2

BL: Biconi-Log



LINE CONDUCTION

Model Name : LDA300W-3

Model No. :

Serial No. :

Points : 11

Detector : PEAK/QP/Ave.

Line Mode : VA/VB

Limit1: [CISPR Pub22] Class B(QP)

Limit2: [CISPR Pub22] Class B(Ave.)

Power Supply : 230V(1 Phase) 50Hz


Temp. : 25degC

Humi. : 44%

Date : 2003/4/9 6:59

Test Equip. : R3132,ESPC

Comment :



Frequency [MHz]	Meter Reading (QP) [dBμV]	Meter Reading (Ave.) [dBμV]	Factor [dB]	Level (QP) [dBμV]	Level (Ave.) [dBμV]	Line	Limit (QP) [dBμV]	Limit (Ave.) [dBμV]	Margin (QP)[dB]	Margin (Ave.) [dB]
0.7909	34.3	34.7	9.9	44.2	44.6	VA	56.0	46.0	11.8	1.4
0.9242	34.1	34.5	9.9	44.0	44.4	VA	56.0	46.0	12.0	1.6
1.3201	33.4	33.5	9.9	43.3	43.4	VA	56.0	46.0	12.7	2.6
1.4523	33.9	34.4	9.9	43.8	44.3	VA	56.0	46.0	12.2	1.7
1.9800	34.6	34.9	9.9	44.5	44.8	VA	56.0	46.0	11.5	1.2
2.1123	33.3	33.6	9.9	43.2	43.5	VA	56.0	46.0	12.8	2.5
2.5081	32.8	32.5	9.9	42.7	42.4	VA	56.0	46.0	13.3	3.6
2.6407	33.5	34.1	9.9	43.4	44.0	VA	56.0	46.0	12.6	2.0
3.1686	32.9	33.2	10.0	42.9	43.2	VA	56.0	46.0	13.1	2.8
0.2639	36.4	36.1	9.8	46.2	45.9	VB	61.3	51.3	15.1	5.4
1.5842	33.8	33.8	9.9	43.7	43.7	VB	56.0	46.0	12.3	2.3