

COSEL

TEST DATA OF LDA30F-24
(100V INPUT)

Regulated DC Power Supply

Date : Aug. 17. 1999

Approved by : H. Yamaguchi
Design Manager

Prepared by : T. Ashihara
Design Engineer

コーセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保護	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Overvoltage Protection	12
過電圧保護	
13. Inrush Current	13
突入電流	
14. Dynamic Load Responce	14
動的負荷変動	
15. Rise and Fall Time	15
立ち上り、立下がり時間	
16. Ambient Temperature Drift	16
周囲温度変動	
17. Minimum Input Voltage for Regulated Output Voltage	17
最低レギュレーション電圧	
18. Ripple Voltage (by Ambient Temperature)	18
リップル電圧 (周囲温度特性)	
19. Time Lapse Drift	19
経時ドリフト	
20. Output Voltage Accuracy	20
定電圧精度	
21. Condensation	21
結露特性	
22. Leakage Current	22
漏洩電流	
23. Line Noise Tolerance	23
入力雑音耐量	
24. Conducted Emission	24
雑音端子電圧	
25. Figure of Testing Circuitry	25
測定回路図	

(Final Page 26)

COSEL


Model	LDA30F-24	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+24.0V 1.3A																																		
1. Graph	<p style="text-align: center;">□ Load 50% —△— Load 100%</p>	2. Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>23.979</td><td>23.979</td></tr> <tr><td>80</td><td>23.979</td><td>23.979</td></tr> <tr><td>85</td><td>23.980</td><td>23.979</td></tr> <tr><td>90</td><td>23.979</td><td>23.979</td></tr> <tr><td>100</td><td>23.979</td><td>23.979</td></tr> <tr><td>110</td><td>23.980</td><td>23.979</td></tr> <tr><td>120</td><td>23.980</td><td>23.979</td></tr> <tr><td>132</td><td>23.980</td><td>23.979</td></tr> <tr><td>140</td><td>23.980</td><td>23.979</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	23.979	23.979	80	23.979	23.979	85	23.980	23.979	90	23.979	23.979	100	23.979	23.979	110	23.980	23.979	120	23.980	23.979	132	23.980	23.979	140	23.980	23.979	
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	23.979	23.979																																	
80	23.979	23.979																																	
85	23.980	23.979																																	
90	23.979	23.979																																	
100	23.979	23.979																																	
110	23.980	23.979																																	
120	23.980	23.979																																	
132	23.980	23.979																																	
140	23.980	23.979																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA30F-24
Item	Input Current (by Load Current) 入力電流（負荷特性）
Output	_____

Temperature 25°C
Testing Circuitry Figure A

2. Values


Load Current [A]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	0.041	0.043	0.047
0.20	0.156	0.145	0.128
0.40	0.254	0.230	0.198
0.60	0.354	0.317	0.267
0.80	0.457	0.407	0.337
1.00	0.559	0.494	0.406
1.20	0.661	0.584	0.478
1.30	0.711	0.628	0.513
1.43	0.779	0.687	0.560
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-24
Item	Input Power (by Load Current) 入力電力 (負荷特性)
Output	_____

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	1.38	1.63	2.21
0.20	7.21	7.49	8.13
0.40	12.62	12.91	13.63
0.60	18.11	18.30	19.03
0.80	23.70	23.82	24.40
1.00	29.31	29.31	29.77
1.20	35.09	35.01	35.31
1.30	37.87	37.74	38.00
1.43	41.83	41.61	41.74
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-24	Temperature Testing Circuitry	25°C Figure A																													
Item	Efficiency 効率																															
Object	—																															
1. Graph		2. Values																														
<p style="text-align: center;">□ Load 50% △ Load 100%</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>80.5</td><td>81.4</td></tr> <tr><td>80</td><td>80.5</td><td>82.1</td></tr> <tr><td>85</td><td>80.3</td><td>82.4</td></tr> <tr><td>90</td><td>80.3</td><td>82.7</td></tr> <tr><td>100</td><td>79.8</td><td>82.6</td></tr> <tr><td>110</td><td>79.2</td><td>82.6</td></tr> <tr><td>120</td><td>78.6</td><td>82.5</td></tr> <tr><td>132</td><td>77.1</td><td>82.2</td></tr> <tr><td>140</td><td>76.7</td><td>81.9</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	75	80.5	81.4	80	80.5	82.1	85	80.3	82.4	90	80.3	82.7	100	79.8	82.6	110	79.2	82.6	120	78.6	82.5	132	77.1	82.2	140	76.7	81.9		
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																														
75	80.5	81.4																														
80	80.5	82.1																														
85	80.3	82.4																														
90	80.3	82.7																														
100	79.8	82.6																														
110	79.2	82.6																														
120	78.6	82.5																														
132	77.1	82.2																														
140	76.7	81.9																														
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																

COSEL

Model	LDA30F-24																																																									
Item	Efficiency (by Load Current) 効率 (負荷電流特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	_____																																																									
1. Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Input Volt. 85V Input Volt. 100V Input Volt. 132V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.20</td><td>67.6</td><td>64.6</td><td>60.1</td></tr> <tr><td>0.40</td><td>76.8</td><td>74.9</td><td>71.0</td></tr> <tr><td>0.60</td><td>79.7</td><td>79.1</td><td>76.1</td></tr> <tr><td>0.80</td><td>81.3</td><td>81.1</td><td>79.2</td></tr> <tr><td>1.00</td><td>82.1</td><td>82.1</td><td>80.6</td></tr> <tr><td>1.20</td><td>82.2</td><td>82.6</td><td>81.9</td></tr> <tr><td>1.30</td><td>82.3</td><td>82.6</td><td>82.4</td></tr> <tr><td>1.43</td><td>82.2</td><td>82.6</td><td>82.5</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.20	67.6	64.6	60.1	0.40	76.8	74.9	71.0	0.60	79.7	79.1	76.1	0.80	81.3	81.1	79.2	1.00	82.1	82.1	80.6	1.20	82.2	82.6	81.9	1.30	82.3	82.6	82.4	1.43	82.2	82.6	82.5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.20	67.6	64.6	60.1																																																							
0.40	76.8	74.9	71.0																																																							
0.60	79.7	79.1	76.1																																																							
0.80	81.3	81.1	79.2																																																							
1.00	82.1	82.1	80.6																																																							
1.20	82.2	82.6	81.9																																																							
1.30	82.3	82.6	82.4																																																							
1.43	82.2	82.6	82.5																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

COSEL


Model LDA30F-24

Item Hold-Up Time 出力保持時間

Object +24.0V 1.3A

1. Graph

□	Load 50%
△	Load 100%



Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
75	23	10
80	28	13
85	34	16
90	40	19
100	53	26
110	68	34
120	84	42
132	105	53
140	120	61

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.


Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSSEL

Model	LDA30F-24
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	+24.0V 1.3A

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Time [mS]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	—	—	—
0.20	96	148	290
0.40	52	81	163
0.60	35	56	113
0.80	23	40	86
1.00	20	31	70
1.20	14	27	56
1.30	14	23	53
1.43	13	22	47
—	—	—	—
—	—	—	—

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注)斜線は定格負荷電流範囲を示す。

COSSEL

Model	LDA30F-24																																																	
Item	Load Regulation 靜的負荷変動	Temperature 25°C	Testing Circuitry Figure A																																															
Object	+24.0V 1.3A																																																	
1. Graph	<p>—△— Input Volt. 85 V □ Input Volt. 100 V ○ Input Volt. 132 V</p>																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>23.981</td><td>23.982</td><td>23.981</td></tr> <tr><td>0.20</td><td>23.980</td><td>23.980</td><td>23.981</td></tr> <tr><td>0.40</td><td>23.980</td><td>23.980</td><td>23.981</td></tr> <tr><td>0.60</td><td>23.980</td><td>23.980</td><td>23.981</td></tr> <tr><td>0.80</td><td>23.980</td><td>23.980</td><td>23.980</td></tr> <tr><td>1.00</td><td>23.979</td><td>23.979</td><td>23.980</td></tr> <tr><td>1.20</td><td>23.979</td><td>23.979</td><td>23.980</td></tr> <tr><td>1.30</td><td>23.979</td><td>23.979</td><td>23.979</td></tr> <tr><td>1.43</td><td>23.979</td><td>23.979</td><td>23.979</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	23.981	23.982	23.981	0.20	23.980	23.980	23.981	0.40	23.980	23.980	23.981	0.60	23.980	23.980	23.981	0.80	23.980	23.980	23.980	1.00	23.979	23.979	23.980	1.20	23.979	23.979	23.980	1.30	23.979	23.979	23.979	1.43	23.979	23.979	23.979	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.00	23.981	23.982	23.981																																															
0.20	23.980	23.980	23.981																																															
0.40	23.980	23.980	23.981																																															
0.60	23.980	23.980	23.981																																															
0.80	23.980	23.980	23.980																																															
1.00	23.979	23.979	23.980																																															
1.20	23.979	23.979	23.980																																															
1.30	23.979	23.979	23.979																																															
1.43	23.979	23.979	23.979																																															
—	—	—	—																																															

Note: Slanted line shows the range of the rated load current.


(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-24	Temperature Testing Circuitry	25°C Figure A																																							
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																									
Object	+24.0V 1.3A																																									
1. Graph		2. Values																																								
<p>[mV]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.20</td><td>20</td><td>20</td></tr> <tr><td>0.40</td><td>20</td><td>20</td></tr> <tr><td>0.60</td><td>20</td><td>20</td></tr> <tr><td>0.80</td><td>20</td><td>20</td></tr> <tr><td>1.00</td><td>25</td><td>25</td></tr> <tr><td>1.20</td><td>25</td><td>25</td></tr> <tr><td>1.30</td><td>25</td><td>25</td></tr> <tr><td>1.43</td><td>25</td><td>25</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	10	10	0.20	20	20	0.40	20	20	0.60	20	20	0.80	20	20	1.00	25	25	1.20	25	25	1.30	25	25	1.43	25	25	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																								
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																								
0.00	10	10																																								
0.20	20	20																																								
0.40	20	20																																								
0.60	20	20																																								
0.80	20	20																																								
1.00	25	25																																								
1.20	25	25																																								
1.30	25	25																																								
1.43	25	25																																								
—	—	—																																								
—	—	—																																								
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																										
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>			<p>BC-4072</p>																																							

COSEL

Model	LDA30F-24
Item	Ripple-Noise リップルノイズ
Object	+24.0V 1.3A



Temperature
Testing Circuitry 25°C
Figure A

2. Values

Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.00	15	15
0.20	25	30
0.40	25	30
0.60	30	30
0.80	30	30
1.00	35	30
1.20	35	30
1.30	40	30
1.43	40	30
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。

- T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期




Fig. Complex Ripple Wave Form


図 リップル波形詳細図

COSEL

Model LDA30F-24

Item Overcurrent Protection
過電流保護

Object +24.0V 1.3A

Temperature 25°C
Testing Circuitry Figure A

2. Values


Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
24.00	1.66	1.64	1.64
22.80	1.67	1.65	1.65
21.60	1.67	1.66	1.66
19.20	1.68	1.67	1.68
16.80	1.70	1.69	1.70
14.40	1.72	1.72	1.72
12.00	1.74	1.73	1.74
9.60	1.75	1.75	1.76
7.20	1.76	1.76	1.77
4.80	1.77	1.77	1.76
2.40	1.75	1.72	1.67
0.00	1.50	1.42	1.30

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-24
Item	Overvoltage Protection 過電圧保護
Object	+24.0V 1.3A



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
-20	29.49	29.49	29.49
-10	29.72	29.67	29.67
0	29.90	29.91	29.91
10	30.15	30.09	30.09
20	30.33	30.33	30.33
25	30.50	30.44	30.44
30	30.56	30.56	30.56
40	30.79	30.74	30.74
50	30.97	30.98	30.98
60	31.21	31.16	31.16
—	—	—	—

COSEL

Model	LDA30F-24	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	<hr/>		



Input Voltage 100 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 9.80 [A]

② 1.40 [A]




COSEL

Model	LDA30F-24	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response 動的負荷變動	
Object	+24.0 V 1.3A	


Input Volt. 100 V

Cycle 1000 mS




Load 0% ↔

Load 100 %



Load 0% ↔

Load 50 %



100 mV/div

10 mS/div

COSEL


Model LDA30F-24

Item Rise and Fall Time 立上り、立下り時間

Object +24.0V 1.3A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load \ Time	T d	T r	T s	T h	T f
50 %	134.0	28.3	162.3	33.7	51.0
100 %	134.0	28.5	162.5	15.8	23.3



COSEL

Model

LDA30F-24

Item


Ambient Temperature Drift
周囲温度変動

Object

+24.0V 1.3A

1. Graph

—△— Input Volt. 85V
 □ Input Volt. 100V
 ○ Input Volt. 132V



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


Testing Circuitry Figure A

2. Values

Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	23.938	23.938	23.938
-10	23.945	23.946	23.946
0	23.954	23.954	23.955
10	23.965	23.965	23.965
20	23.974	23.974	23.974
25	23.979	23.979	23.979
30	23.978	23.978	23.978
40	23.978	23.978	23.978
50	23.972	23.972	23.972
60	23.962	23.962	23.962
—	—	—	—

COSEL

Model	LDA30F-24
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+24.0V 1.3A



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	52	59
-10	52	58
0	51	58
10	51	58
20	50	58
25	50	58
30	51	58
40	50	59
50	50	59
60	50	59
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


COSEL

Model LDA30F-24

Item Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)

Object +24.0V 1.3A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	45	45
-10	35	40
0	30	35
10	30	30
20	25	30
25	25	25
30	20	20
40	20	20
50	20	20
60	15	20
—	—	—

COSSEL

Model	LDA30F-24	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift 経時ドリフト																								
Object	+24.0V 1.3A																								
1. Graph																									
<p>[V]</p> <table border="1"> <caption>Data points from Figure A graph</caption> <thead> <tr> <th>Time [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>23.956</td></tr> <tr><td>0.5</td><td>23.955</td></tr> <tr><td>1.0</td><td>23.955</td></tr> <tr><td>2.0</td><td>23.955</td></tr> <tr><td>3.0</td><td>23.956</td></tr> <tr><td>4.0</td><td>23.956</td></tr> <tr><td>5.0</td><td>23.956</td></tr> <tr><td>6.0</td><td>23.956</td></tr> <tr><td>7.0</td><td>23.956</td></tr> <tr><td>8.0</td><td>23.957</td></tr> </tbody> </table> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>				Time [H]	Output Voltage [V]	0.0	23.956	0.5	23.955	1.0	23.955	2.0	23.955	3.0	23.956	4.0	23.956	5.0	23.956	6.0	23.956	7.0	23.956	8.0	23.957
Time [H]	Output Voltage [V]																								
0.0	23.956																								
0.5	23.955																								
1.0	23.955																								
2.0	23.955																								
3.0	23.956																								
4.0	23.956																								
5.0	23.956																								
6.0	23.956																								
7.0	23.956																								
8.0	23.957																								
2. Values																									
<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>23.956</td></tr> <tr><td>0.5</td><td>23.955</td></tr> <tr><td>1.0</td><td>23.955</td></tr> <tr><td>2.0</td><td>23.955</td></tr> <tr><td>3.0</td><td>23.956</td></tr> <tr><td>4.0</td><td>23.956</td></tr> <tr><td>5.0</td><td>23.956</td></tr> <tr><td>6.0</td><td>23.956</td></tr> <tr><td>7.0</td><td>23.956</td></tr> <tr><td>8.0</td><td>23.957</td></tr> </tbody> </table>				Time since start [H]	Output Voltage [V]	0.0	23.956	0.5	23.955	1.0	23.955	2.0	23.955	3.0	23.956	4.0	23.956	5.0	23.956	6.0	23.956	7.0	23.956	8.0	23.957
Time since start [H]	Output Voltage [V]																								
0.0	23.956																								
0.5	23.955																								
1.0	23.955																								
2.0	23.955																								
3.0	23.956																								
4.0	23.956																								
5.0	23.956																								
6.0	23.956																								
7.0	23.956																								
8.0	23.957																								



Model	LDA30F-24	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+24.0V 1.3A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~1.3 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~1.3 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	25	132	0.0	23.982	±18	±0.1
Minimum Voltage	-10	85	1.3	23.947		



Model	LDA30F-24	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+24.0V 1.3A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	23.977	Input Volt.: 100V, Load Current: 1.3A
Line Regulation [mV]	2	Input Volt.: 85~132V, Load Current: 1.3A
Load Regulation [mV]	5	Input Volt.: 100V, Load Current: 0.0~1.3A



Model	LDA30F-24	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.16	0.20	0.26
(B) IEC60950	0.16	0.21	0.26

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	LDA30F-24	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+24.0V 1.3A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LDA30F-24	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	<hr/>		

1. Graph

Remarks


Input Volt. 100 V (VCCI Class B)

120 V (FCC Class B)


Load 100 %




規格 1: [VCCI] Class B(平均値)

規格 2: [VCCI] Class B(QP)



規格 1: [FCC Part15] Class B








Figure C




Figure D




Figure E