



TEST DATA OF LDA50F-5 (200V INPUT)

Regulated DC Power Supply

Aug. 23, 1999

Approved by : N. Yamaguchi
Design Manager

Prepared by : T. Ashihara
Design Engineer

コーワセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流(負荷特性)	
3. Input Power (by Load Current)	3
入力電力(負荷特性)	
4. Efficiency (by Input Voltage)	4
効率(入力電圧特性)	
5. Efficiency (by Load Current)	5
効率(負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電障害	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧(負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Overvoltage Protection	12
過電圧保護	
13. Inrush Current	13
突入電流	
14. Dynamic Load Response	14
動的負荷変動	
15. Rise and Fall Time	15
立ち上り、立下り時間	
16. Ambient Temperature Drift	16
周囲温度変動	
17. Minimum Input Voltage for Regulated Output Voltage	17
最低レギュレーション電圧	
18. Ripple Voltage (by Ambient Temperature)	18
リップル電圧(周囲温度特性)	
19. Time Lapse Drift	19
経時ドリフト	
20. Output Voltage Accuracy	20
定電圧精度	
21. Condensation	21
結露特性	
22. Leakage Current	22
漏洩電流	
23. Line Noise Tolerance	23
入力雑音耐量	
24. Conducted Emission	24
雑音端子電圧	
25. Figure of Testing Circuitry	25
測定回路図	

(Final Page 26)

COSEL

Model	LDA50F-5	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+5.0V 10A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>5.114</td><td>5.107</td></tr> <tr><td>160</td><td>5.114</td><td>5.107</td></tr> <tr><td>170</td><td>5.114</td><td>5.107</td></tr> <tr><td>180</td><td>5.114</td><td>5.107</td></tr> <tr><td>200</td><td>5.114</td><td>5.107</td></tr> <tr><td>220</td><td>5.114</td><td>5.107</td></tr> <tr><td>240</td><td>5.114</td><td>5.107</td></tr> <tr><td>264</td><td>5.114</td><td>5.107</td></tr> <tr><td>280</td><td>5.114</td><td>5.106</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	150	5.114	5.107	160	5.114	5.107	170	5.114	5.107	180	5.114	5.107	200	5.114	5.107	220	5.114	5.107	240	5.114	5.107	264	5.114	5.107	280	5.114	5.106
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
150	5.114	5.107																																	
160	5.114	5.107																																	
170	5.114	5.107																																	
180	5.114	5.107																																	
200	5.114	5.107																																	
220	5.114	5.107																																	
240	5.114	5.107																																	
264	5.114	5.107																																	
280	5.114	5.106																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA50F-5																																																									
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	—																																																									
1. Graph	<p>—△— Input Volt. 170V - - -□- Input Volt. 200V - - -○- Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 264V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.053</td><td>0.057</td><td>0.063</td></tr> <tr><td>2</td><td>0.196</td><td>0.185</td><td>0.173</td></tr> <tr><td>4</td><td>0.323</td><td>0.296</td><td>0.261</td></tr> <tr><td>6</td><td>0.456</td><td>0.411</td><td>0.352</td></tr> <tr><td>8</td><td>0.592</td><td>0.529</td><td>0.446</td></tr> <tr><td>10</td><td>0.735</td><td>0.654</td><td>0.545</td></tr> <tr><td>11</td><td>0.809</td><td>0.719</td><td>0.595</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170V [A]	Input Volt. 200V [A]	Input Volt. 264V [A]	0	0.053	0.057	0.063	2	0.196	0.185	0.173	4	0.323	0.296	0.261	6	0.456	0.411	0.352	8	0.592	0.529	0.446	10	0.735	0.654	0.545	11	0.809	0.719	0.595																							
Load Current [A]	Input Volt. 170V [A]	Input Volt. 200V [A]	Input Volt. 264V [A]																																																							
0	0.053	0.057	0.063																																																							
2	0.196	0.185	0.173																																																							
4	0.323	0.296	0.261																																																							
6	0.456	0.411	0.352																																																							
8	0.592	0.529	0.446																																																							
10	0.735	0.654	0.545																																																							
11	0.809	0.719	0.595																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.053</td><td>0.057</td><td>0.063</td></tr> <tr><td>2</td><td>0.196</td><td>0.185</td><td>0.173</td></tr> <tr><td>4</td><td>0.323</td><td>0.296</td><td>0.261</td></tr> <tr><td>6</td><td>0.456</td><td>0.411</td><td>0.352</td></tr> <tr><td>8</td><td>0.592</td><td>0.529</td><td>0.446</td></tr> <tr><td>10</td><td>0.735</td><td>0.654</td><td>0.545</td></tr> <tr><td>11</td><td>0.809</td><td>0.719</td><td>0.595</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	0.053	0.057	0.063	2	0.196	0.185	0.173	4	0.323	0.296	0.261	6	0.456	0.411	0.352	8	0.592	0.529	0.446	10	0.735	0.654	0.545	11	0.809	0.719	0.595	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0	0.053	0.057	0.063																																																							
2	0.196	0.185	0.173																																																							
4	0.323	0.296	0.261																																																							
6	0.456	0.411	0.352																																																							
8	0.592	0.529	0.446																																																							
10	0.735	0.654	0.545																																																							
11	0.809	0.719	0.595																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA50F-5																																																					
Item	Input Power (by Load Current) 入力電力（負荷特性）	Temperature 25°C	Testing Circuitry Figure A																																																			
Output	_____																																																					
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 170V (△) Input Volt. 200V (□) Input Volt. 264V (○) <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (170V)</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (264V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.10</td><td>3.80</td><td>5.30</td></tr> <tr><td>2</td><td>15.90</td><td>17.00</td><td>19.60</td></tr> <tr><td>4</td><td>28.00</td><td>28.90</td><td>31.50</td></tr> <tr><td>6</td><td>40.30</td><td>41.10</td><td>43.70</td></tr> <tr><td>8</td><td>52.70</td><td>53.50</td><td>55.80</td></tr> <tr><td>10</td><td>66.00</td><td>66.60</td><td>68.70</td></tr> <tr><td>11</td><td>72.50</td><td>73.10</td><td>75.10</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (170V)	Input Power [W] (200V)	Input Power [W] (264V)	0	3.10	3.80	5.30	2	15.90	17.00	19.60	4	28.00	28.90	31.50	6	40.30	41.10	43.70	8	52.70	53.50	55.80	10	66.00	66.60	68.70	11	72.50	73.10	75.10																			
Load Current [A]	Input Power [W] (170V)	Input Power [W] (200V)	Input Power [W] (264V)																																																			
0	3.10	3.80	5.30																																																			
2	15.90	17.00	19.60																																																			
4	28.00	28.90	31.50																																																			
6	40.30	41.10	43.70																																																			
8	52.70	53.50	55.80																																																			
10	66.00	66.60	68.70																																																			
11	72.50	73.10	75.10																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.10</td><td>3.80</td><td>5.30</td></tr> <tr><td>2</td><td>15.90</td><td>17.00</td><td>19.60</td></tr> <tr><td>4</td><td>28.00</td><td>28.90</td><td>31.50</td></tr> <tr><td>6</td><td>40.30</td><td>41.10</td><td>43.70</td></tr> <tr><td>8</td><td>52.70</td><td>53.50</td><td>55.80</td></tr> <tr><td>10</td><td>66.00</td><td>66.60</td><td>68.70</td></tr> <tr><td>11</td><td>72.50</td><td>73.10</td><td>75.10</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	3.10	3.80	5.30	2	15.90	17.00	19.60	4	28.00	28.90	31.50	6	40.30	41.10	43.70	8	52.70	53.50	55.80	10	66.00	66.60	68.70	11	72.50	73.10	75.10	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0	3.10	3.80	5.30																																																			
2	15.90	17.00	19.60																																																			
4	28.00	28.90	31.50																																																			
6	40.30	41.10	43.70																																																			
8	52.70	53.50	55.80																																																			
10	66.00	66.60	68.70																																																			
11	72.50	73.10	75.10																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。


COSEL

Model	LDA50F-5																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Temperature Testing Circuitry 25°C Figure A																															
Object																																	
1. Graph	<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Load 50% (Squares)</p> <p>Load 100% (Triangles)</p>																																
<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>150</td> <td>76.9</td> <td>78.4</td> </tr> <tr> <td>160</td> <td>76.1</td> <td>78.4</td> </tr> <tr> <td>170</td> <td>75.8</td> <td>78.2</td> </tr> <tr> <td>180</td> <td>74.6</td> <td>78.1</td> </tr> <tr> <td>200</td> <td>73.8</td> <td>77.6</td> </tr> <tr> <td>220</td> <td>72.2</td> <td>76.8</td> </tr> <tr> <td>240</td> <td>70.6</td> <td>76.1</td> </tr> <tr> <td>264</td> <td>69.0</td> <td>75.2</td> </tr> <tr> <td>280</td> <td>67.6</td> <td>74.2</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	150	76.9	78.4	160	76.1	78.4	170	75.8	78.2	180	74.6	78.1	200	73.8	77.6	220	72.2	76.8	240	70.6	76.1	264	69.0	75.2	280	67.6	74.2
Input Voltage [V]	Efficiency [%]																																
	Load 50%	Load 100%																															
150	76.9	78.4																															
160	76.1	78.4																															
170	75.8	78.2																															
180	74.6	78.1																															
200	73.8	77.6																															
220	72.2	76.8																															
240	70.6	76.1																															
264	69.0	75.2																															
280	67.6	74.2																															

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA50F-5																																																									
Item	Efficiency (by Load Current) 効率(負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Output	—																																																									
1. Graph																																																										
—△— Input Volt. 170V -□--- Input Volt. 200V -○--- Input Volt. 264V			2. Values																																																							
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>2</td><td>64.5</td><td>60.3</td><td>52.4</td></tr> <tr><td>4</td><td>73.5</td><td>71.3</td><td>65.4</td></tr> <tr><td>6</td><td>76.5</td><td>75.0</td><td>70.6</td></tr> <tr><td>8</td><td>77.7</td><td>76.6</td><td>73.4</td></tr> <tr><td>10</td><td>77.9</td><td>77.2</td><td>74.8</td></tr> <tr><td>11</td><td>78.0</td><td>77.4</td><td>75.3</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	2	64.5	60.3	52.4	4	73.5	71.3	65.4	6	76.5	75.0	70.6	8	77.7	76.6	73.4	10	77.9	77.2	74.8	11	78.0	77.4	75.3	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
2	64.5	60.3	52.4																																																							
4	73.5	71.3	65.4																																																							
6	76.5	75.0	70.6																																																							
8	77.7	76.6	73.4																																																							
10	77.9	77.2	74.8																																																							
11	78.0	77.4	75.3																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA50F-5	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+5.0V 10A																																		
1. Graph	<p>Graph showing Hold-Up Time [mS] vs Input Voltage [V] for LDA50F-5 at 25°C. The Y-axis is logarithmic from 1 to 1000. The X-axis ranges from 0 to 300 V. Two curves are shown: Load 50% (dotted line with squares) and Load 100% (solid line with triangles). Both curves show an increase in hold-up time as input voltage increases, with a sharp drop-off near 260V. A slanted line indicates the rated input voltage range.</p>	2. Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>150</td> <td>146</td> <td>69</td> </tr> <tr> <td>160</td> <td>168</td> <td>80</td> </tr> <tr> <td>170</td> <td>192</td> <td>92</td> </tr> <tr> <td>180</td> <td>217</td> <td>105</td> </tr> <tr> <td>200</td> <td>272</td> <td>133</td> </tr> <tr> <td>220</td> <td>331</td> <td>164</td> </tr> <tr> <td>240</td> <td>396</td> <td>198</td> </tr> <tr> <td>264</td> <td>480</td> <td>243</td> </tr> <tr> <td>280</td> <td>540</td> <td>275</td> </tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	150	146	69	160	168	80	170	192	92	180	217	105	200	272	133	220	331	164	240	396	198	264	480	243	280	540	275	
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
150	146	69																																	
160	168	80																																	
170	192	92																																	
180	217	105																																	
200	272	133																																	
220	331	164																																	
240	396	198																																	
264	480	243																																	
280	540	275																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA50F-5	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																						
Object	+5.0V10A																																																						
1. Graph	<p>—△— Input Volt. 170 V —□— Input Volt. 200 V —○— Input Volt. 264 V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>170[V] [ms]</th> <th>200[V] [ms]</th> <th>264[V] [ms]</th> </tr> </thead> <tbody> <tr><td>2</td><td>~350</td><td>~350</td><td>~450</td></tr> <tr><td>4</td><td>~250</td><td>~250</td><td>~350</td></tr> <tr><td>6</td><td>~180</td><td>~180</td><td>~250</td></tr> <tr><td>8</td><td>~120</td><td>~120</td><td>~180</td></tr> <tr><td>10</td><td>~80</td><td>~80</td><td>~120</td></tr> <tr><td>11</td><td>~65</td><td>~65</td><td>~100</td></tr> </tbody> </table>	Load Current [A]	170[V] [ms]	200[V] [ms]	264[V] [ms]	2	~350	~350	~450	4	~250	~250	~350	6	~180	~180	~250	8	~120	~120	~180	10	~80	~80	~120	11	~65	~65	~100																										
Load Current [A]	170[V] [ms]	200[V] [ms]	264[V] [ms]																																																				
2	~350	~350	~450																																																				
4	~250	~250	~350																																																				
6	~180	~180	~250																																																				
8	~120	~120	~180																																																				
10	~80	~80	~120																																																				
11	~65	~65	~100																																																				
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>2</td><td>371</td><td>555</td><td>800</td></tr> <tr><td>4</td><td>198</td><td>280</td><td>482</td></tr> <tr><td>6</td><td>135</td><td>190</td><td>342</td></tr> <tr><td>8</td><td>98</td><td>144</td><td>257</td></tr> <tr><td>10</td><td>81</td><td>111</td><td>222</td></tr> <tr><td>11</td><td>72</td><td>102</td><td>169</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Time [mS]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	—	—	—	2	371	555	800	4	198	280	482	6	135	190	342	8	98	144	257	10	81	111	222	11	72	102	169	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																						
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
0	—	—	—																																																				
2	371	555	800																																																				
4	198	280	482																																																				
6	135	190	342																																																				
8	98	144	257																																																				
10	81	111	222																																																				
11	72	102	169																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.																																																							
Note: Slanted line shows the range of the rated load current.																																																							
瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。 (注)斜線は定格負荷電流範囲を示す。																																																							

COSEL

Model	LDA50F-5	Temperature Testing Circuitry	25°C Figure A																																															
Item	Load Regulation 靜的負荷変動																																																	
Object	+5.0V10A																																																	
1. Graph	<p>—△— Input Volt. 170 V —□— Input Volt. 200 V —○— Input Volt. 264 V</p>																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>5.122</td> <td>5.122</td> <td>5.122</td> </tr> <tr> <td>2</td> <td>5.119</td> <td>5.119</td> <td>5.119</td> </tr> <tr> <td>4</td> <td>5.116</td> <td>5.116</td> <td>5.116</td> </tr> <tr> <td>6</td> <td>5.113</td> <td>5.113</td> <td>5.113</td> </tr> <tr> <td>8</td> <td>5.110</td> <td>5.110</td> <td>5.110</td> </tr> <tr> <td>10</td> <td>5.107</td> <td>5.107</td> <td>5.107</td> </tr> <tr> <td>11</td> <td>5.105</td> <td>5.105</td> <td>5.105</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	5.122	5.122	5.122	2	5.119	5.119	5.119	4	5.116	5.116	5.116	6	5.113	5.113	5.113	8	5.110	5.110	5.110	10	5.107	5.107	5.107	11	5.105	5.105	5.105	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																															
0	5.122	5.122	5.122																																															
2	5.119	5.119	5.119																																															
4	5.116	5.116	5.116																																															
6	5.113	5.113	5.113																																															
8	5.110	5.110	5.110																																															
10	5.107	5.107	5.107																																															
11	5.105	5.105	5.105																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA50F-5	Temperature Testing Circuitry 25°C Figure A																																			
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																				
Object	+5.0V10A																																				
1. Graph		2. Values																																			
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 150 mV, and the X-axis ranges from 0 to 12 A. Two sets of data points are shown for Input Volt. 170V (squares) and Input Volt. 264V (triangles). A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170 [V] [mV]</th> <th>Input Volt. 264 [V] [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>2.00</td><td>20</td><td>25</td></tr> <tr><td>4.00</td><td>20</td><td>25</td></tr> <tr><td>6.00</td><td>25</td><td>25</td></tr> <tr><td>8.00</td><td>25</td><td>25</td></tr> <tr><td>10.00</td><td>25</td><td>25</td></tr> <tr><td>11.00</td><td>25</td><td>25</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 170 [V] [mV]	Input Volt. 264 [V] [mV]	0.00	10	10	2.00	20	25	4.00	20	25	6.00	25	25	8.00	25	25	10.00	25	25	11.00	25	25	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 170 [V] [mV]	Input Volt. 264 [V] [mV]																																			
0.00	10	10																																			
2.00	20	25																																			
4.00	20	25																																			
6.00	25	25																																			
8.00	25	25																																			
10.00	25	25																																			
11.00	25	25																																			
—	—	—																																			
—	—	—																																			
—	—	—																																			
—	—	—																																			
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																					

COSEL

Model	LDA50F-5	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																							
Object	+5.0V10A																																							
1. Graph	<p>Input Volt. 170V □ Input Volt. 264V</p> <p>[mV]</p> <p>Load Current [A]</p>																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 170 [V]</th> <th>Input Volt. 264 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>25</td></tr> <tr><td>2.00</td><td>35</td><td>40</td></tr> <tr><td>4.00</td><td>40</td><td>45</td></tr> <tr><td>6.00</td><td>45</td><td>50</td></tr> <tr><td>8.00</td><td>50</td><td>50</td></tr> <tr><td>10.00</td><td>55</td><td>55</td></tr> <tr><td>11.00</td><td>60</td><td>60</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.00	20	25	2.00	35	40	4.00	40	45	6.00	45	50	8.00	50	50	10.00	55	55	11.00	60	60	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 170 [V]	Input Volt. 264 [V]																																						
	Ripple-Noise [mV]	Ripple-Noise [mV]																																						
0.00	20	25																																						
2.00	35	40																																						
4.00	40	45																																						
6.00	45	50																																						
8.00	50	50																																						
10.00	55	55																																						
11.00	60	60																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																								
<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p> <p>T2 Ripple-Noise [mVp-p]</p> <p>T1</p>																																								
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL


Model	LDA50F-5	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection 過電流保護																																																								
Object	+5.0V10A																																																								
1. Graph	<p>Input Volt. 170 V Input Volt. 200 V Input Volt. 264 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2. Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>12.30</td><td>12.30</td><td>12.36</td></tr> <tr><td>4.75</td><td>12.34</td><td>12.34</td><td>12.39</td></tr> <tr><td>4.50</td><td>12.37</td><td>12.37</td><td>12.51</td></tr> <tr><td>4.00</td><td>12.47</td><td>12.46</td><td>12.53</td></tr> <tr><td>3.50</td><td>12.55</td><td>12.57</td><td>12.65</td></tr> <tr><td>3.00</td><td>12.65</td><td>12.62</td><td>12.78</td></tr> <tr><td>2.50</td><td>12.72</td><td>12.73</td><td>12.91</td></tr> <tr><td>2.00</td><td>12.83</td><td>12.83</td><td>13.04</td></tr> <tr><td>1.50</td><td>12.91</td><td>12.94</td><td>13.15</td></tr> <tr><td>1.00</td><td>13.00</td><td>13.01</td><td>13.14</td></tr> <tr><td>0.50</td><td>12.92</td><td>12.82</td><td>12.62</td></tr> <tr><td>0.00</td><td>12.17</td><td>11.72</td><td>11.08</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	5.00	12.30	12.30	12.36	4.75	12.34	12.34	12.39	4.50	12.37	12.37	12.51	4.00	12.47	12.46	12.53	3.50	12.55	12.57	12.65	3.00	12.65	12.62	12.78	2.50	12.72	12.73	12.91	2.00	12.83	12.83	13.04	1.50	12.91	12.94	13.15	1.00	13.00	13.01	13.14	0.50	12.92	12.82	12.62	0.00	12.17	11.72	11.08
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																						
5.00	12.30	12.30	12.36																																																						
4.75	12.34	12.34	12.39																																																						
4.50	12.37	12.37	12.51																																																						
4.00	12.47	12.46	12.53																																																						
3.50	12.55	12.57	12.65																																																						
3.00	12.65	12.62	12.78																																																						
2.50	12.72	12.73	12.91																																																						
2.00	12.83	12.83	13.04																																																						
1.50	12.91	12.94	13.15																																																						
1.00	13.00	13.01	13.14																																																						
0.50	12.92	12.82	12.62																																																						
0.00	12.17	11.72	11.08																																																						
	<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																								

COSEL

Model	LDA50F-5																																																						
Item	Overvoltage Protection 過電圧保護	Testing Circuitry																																																					
Object	+5.0V 10A	Figure A																																																					
1. Graph	<p style="text-align: center;">△ Input Volt. 170 V □ Input Volt. 200 V ○ Input Volt. 264 V</p> <p style="text-align: center;">Operating Point [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 0%</p>	2. Values																																																					
			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> <tr> <th colspan="3">Operating Point [V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>6.49</td> <td>6.50</td> <td>6.52</td> </tr> <tr> <td>-10</td> <td>6.49</td> <td>6.49</td> <td>6.49</td> </tr> <tr> <td>0</td> <td>6.49</td> <td>6.49</td> <td>6.49</td> </tr> <tr> <td>10</td> <td>6.49</td> <td>6.49</td> <td>6.49</td> </tr> <tr> <td>20</td> <td>6.49</td> <td>6.49</td> <td>6.47</td> </tr> <tr> <td>25</td> <td>6.48</td> <td>6.48</td> <td>6.48</td> </tr> <tr> <td>30</td> <td>6.48</td> <td>6.48</td> <td>6.48</td> </tr> <tr> <td>40</td> <td>6.48</td> <td>6.48</td> <td>6.48</td> </tr> <tr> <td>50</td> <td>6.47</td> <td>6.47</td> <td>6.45</td> </tr> <tr> <td>60</td> <td>6.47</td> <td>6.42</td> <td>6.42</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>		Ambient Temp. [°C]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	Operating Point [V]			-20	6.49	6.50	6.52	-10	6.49	6.49	6.49	0	6.49	6.49	6.49	10	6.49	6.49	6.49	20	6.49	6.49	6.47	25	6.48	6.48	6.48	30	6.48	6.48	6.48	40	6.48	6.48	6.48	50	6.47	6.47	6.45	60	6.47	6.42	6.42	—	—	—	—
Ambient Temp. [°C]	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
	Operating Point [V]																																																						
-20	6.49	6.50	6.52																																																				
-10	6.49	6.49	6.49																																																				
0	6.49	6.49	6.49																																																				
10	6.49	6.49	6.49																																																				
20	6.49	6.49	6.47																																																				
25	6.48	6.48	6.48																																																				
30	6.48	6.48	6.48																																																				
40	6.48	6.48	6.48																																																				
50	6.47	6.47	6.45																																																				
60	6.47	6.42	6.42																																																				
—	—	—	—																																																				

COSEL

Model	LDA50F-5	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	_____		



Input Voltage 200 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 29.31 [A]

② 2.11 [A]




COSEL

Model	LDA50F-5	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response 動的負荷変動	
Object	+5.0V 10A	



Input Volt. 200 V

Cycle 1000 mS





Load 0% ↔

Load 100 %



Load 0% ↔

Load 50 %



100 mV/div



10 mS/div

COSEL

Model	LDA50F-5
Item	Rise and Fall Time 立ち上り、立下り時間
Object	+5.0V 10A


Temperature
Testing Circuitry 25°C
Figure A

1. Graph




2. Values

Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		40.8	7.5	48.3	185.0	12.8	
100 %		41.0	7.8	48.8	92.0	7.0	




COSEL

Model	LDA50F-5	Testing Circuitry Figure A		
Item	Ambient Temperature Drift 周囲温度変動			
Object	+5.0V 10A			
1. Graph	<p style="text-align: center;"> Input Volt. 170V Input Volt. 200V Input Volt. 264V </p> <p style="text-align: center;">[V]</p>  <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>	2. Values		
Note:	Slanted line shows the range of the rated ambient temperature.			
(注)	斜線は定格周囲温度範囲を示す。			


COSEL

		Testing Circuitry Figure A	
Model	LDA50F-5		
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧		
Object	+5.0V10A		
1. Graph		2. Values	
[V]		Ambient Temperature [°C]	Input Voltage [V]
			Load 50% Load 100%
160		-20	54 60
140		-10	53 60
120		0	52 59
100		10	52 59
80		20	52 59
60		25	52 59
40		30	52 59
20		40	52 60
0		50	51 60
		60	51 60
		—	— —



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


COSEL


COSEL

Model	LDA50F-5
Item	Time Lapse Drift 経時ドリフト
Object	+5.0V10A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Time since start [H]	Output Voltage [V]
0.0	5.122
0.5	5.119
1.0	5.119
2.0	5.119
3.0	5.120
4.0	5.120
5.0	5.120
6.0	5.120
7.0	5.120
8.0	5.120



Model	LDA50F-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+5.0V10A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 170~264 V

Load Current : 0~10 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 170~264 V

負荷電流 0~10 A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	25	264	0	5.122	±9	±0.2
Minimum Voltage	50	264	10	5.105		



Model	LDA50F-5	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+5.0V 10A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.107	Input Volt.: 200V, Load Current:10A
Line Regulation [mV]	2	Input Volt.: 170~264V, Load Current:10A
Load Regulation [mV]	16	Input Volt.: 200V, Load Current:0~10A



Model	LDA50F-5	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	---	---	---
(B) IEC60950	---	---	---

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	0.18	0.21	0.26

COSSEL

Model	LDA50F-5	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+5.0V 10A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 200 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LDA50F-5	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	_____		

1. Graph


Remarks

Input Volt. 230 V

Load 100 %

規格 1 : [EN 55022] Class B(平均値)

規格 2 : [EN 55022] Class B(QP)



COSEL





Figure B (DENTORI)




Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E