



TEST DATA OF LDA50F-9

Regulated DC Power Supply
Oct.13. 2004

Approved by :

K.Shiho

Design Manager

Prepared by :

A.Kawai

Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Inrush Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Hold-Up Time	16
17.Instantaneous Interruption Compensation	17
18.Minimum Input Voltage for Regulated Output Voltage	18
19.Overcurrent Protection	19
20.Overvoltage Protection	20
21.Figure of Testing Circuitry	21

(Final Page 21)

COSSEL

Model	LDA50F-9
Item	Input Current (by Load Current)
Object	_____


Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	0.044	0.057	0.060
0.80	0.209	0.161	0.155
1.60	0.351	0.241	0.226
2.40	0.496	0.321	0.300
3.20	0.645	0.403	0.373
4.00	0.795	0.487	0.447
4.80	0.947	0.572	0.523
5.60	1.099	0.656	0.600
6.16	1.207	0.716	0.655
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL


Model	LDA50F-9																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	—	—	—																																																			
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○- - Input Volt. 230V</p> 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>1.68</td><td>3.80</td><td>4.60</td></tr> <tr> <td>0.80</td><td>10.53</td><td>13.50</td><td>14.70</td></tr> <tr> <td>1.60</td><td>19.07</td><td>21.80</td><td>23.00</td></tr> <tr> <td>2.40</td><td>27.80</td><td>30.20</td><td>31.40</td></tr> <tr> <td>3.20</td><td>36.70</td><td>38.90</td><td>39.90</td></tr> <tr> <td>4.00</td><td>45.70</td><td>47.50</td><td>48.50</td></tr> <tr> <td>4.80</td><td>54.70</td><td>56.20</td><td>57.20</td></tr> <tr> <td>5.60</td><td>64.00</td><td>65.00</td><td>65.90</td></tr> <tr> <td>6.16</td><td>70.60</td><td>71.30</td><td>72.10</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	1.68	3.80	4.60	0.80	10.53	13.50	14.70	1.60	19.07	21.80	23.00	2.40	27.80	30.20	31.40	3.20	36.70	38.90	39.90	4.00	45.70	47.50	48.50	4.80	54.70	56.20	57.20	5.60	64.00	65.00	65.90	6.16	70.60	71.30	72.10	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	1.68	3.80	4.60																																																			
0.80	10.53	13.50	14.70																																																			
1.60	19.07	21.80	23.00																																																			
2.40	27.80	30.20	31.40																																																			
3.20	36.70	38.90	39.90																																																			
4.00	45.70	47.50	48.50																																																			
4.80	54.70	56.20	57.20																																																			
5.60	64.00	65.00	65.90																																																			
6.16	70.60	71.30	72.10																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LDA50F-9																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	<hr/>																																	
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>79.0</td><td>78.4</td></tr> <tr> <td>100</td><td>79.0</td><td>79.2</td></tr> <tr> <td>120</td><td>78.7</td><td>79.7</td></tr> <tr> <td>200</td><td>73.7</td><td>78.1</td></tr> <tr> <td>230</td><td>71.4</td><td>76.9</td></tr> <tr> <td>264</td><td>68.6</td><td>75.4</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	79.0	78.4	100	79.0	79.2	120	78.7	79.7	200	73.7	78.1	230	71.4	76.9	264	68.6	75.4	--	-	-	--	-	-	--	-	-	
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
85	79.0	78.4																																
100	79.0	79.2																																
120	78.7	79.7																																
200	73.7	78.1																																
230	71.4	76.9																																
264	68.6	75.4																																
--	-	-																																
--	-	-																																
--	-	-																																

COSEL

Model	LDA50F-9
Item	Efficiency (by Load Current)
Object	—

 Temperature 25°C
 Testing Circuitry Figure A


2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
0.80	69.2	54.0	49.6
1.60	76.3	66.8	63.3
2.40	78.5	72.2	69.5
3.20	79.2	74.7	72.8
4.00	79.4	76.4	74.8
4.80	79.6	77.5	76.1
5.60	79.3	78.1	77.0
6.16	79.0	78.2	77.3
--	-	-	-
--	-	-	-



Note: Slanted line shows the range of the rated load current.

COSEL

Model LDA50F-9

Item Inrush Current

Object _____

Temperature 25°C
Testing Circuitry Figure AInput
Current
[20A/div]Input
Current
[20A/div]

Primary inrush current


Secondary inrush current

COSEL

Model	LDA50F-9
Item	Line Regulation
Object	+9V5.6A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	9.087	9.079
100	9.085	9.079
120	9.085	9.078
200	9.085	9.078
230	9.085	9.077
264	9.085	9.076
--	-	-
--	-	-
--	-	-

COSEL


Model	LDA50F-9																																								
Item	Load Regulation																																								
Object	+9V5.6A																																								
1. Graph																																									
<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - ·○- · Input Volt. 230V</p>  <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Volt. 100V [V]</th> <th>Output Volt. 200V [V]</th> <th>Output Volt. 230V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>9.115</td><td>9.115</td><td>9.115</td></tr> <tr><td>0.80</td><td>9.109</td><td>9.110</td><td>9.109</td></tr> <tr><td>1.60</td><td>9.104</td><td>9.105</td><td>9.104</td></tr> <tr><td>2.40</td><td>9.099</td><td>9.100</td><td>9.099</td></tr> <tr><td>3.20</td><td>9.094</td><td>9.094</td><td>9.094</td></tr> <tr><td>4.00</td><td>9.089</td><td>9.089</td><td>9.088</td></tr> <tr><td>4.80</td><td>9.084</td><td>9.084</td><td>9.083</td></tr> <tr><td>5.60</td><td>9.078</td><td>9.078</td><td>9.077</td></tr> <tr><td>6.16</td><td>9.075</td><td>9.074</td><td>9.073</td></tr> </tbody> </table>		Load Current [A]	Output Volt. 100V [V]	Output Volt. 200V [V]	Output Volt. 230V [V]	0.00	9.115	9.115	9.115	0.80	9.109	9.110	9.109	1.60	9.104	9.105	9.104	2.40	9.099	9.100	9.099	3.20	9.094	9.094	9.094	4.00	9.089	9.089	9.088	4.80	9.084	9.084	9.083	5.60	9.078	9.078	9.077	6.16	9.075	9.074	9.073
Load Current [A]	Output Volt. 100V [V]	Output Volt. 200V [V]	Output Volt. 230V [V]																																						
0.00	9.115	9.115	9.115																																						
0.80	9.109	9.110	9.109																																						
1.60	9.104	9.105	9.104																																						
2.40	9.099	9.100	9.099																																						
3.20	9.094	9.094	9.094																																						
4.00	9.089	9.089	9.088																																						
4.80	9.084	9.084	9.083																																						
5.60	9.078	9.078	9.077																																						
6.16	9.075	9.074	9.073																																						

Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	9.115	9.115	9.115
0.80	9.109	9.110	9.109
1.60	9.104	9.105	9.104
2.40	9.099	9.100	9.099
3.20	9.094	9.094	9.094
4.00	9.089	9.089	9.088
4.80	9.084	9.084	9.083
5.60	9.078	9.078	9.077
6.16	9.075	9.074	9.073
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

COSEL


Model	LDA50F-9																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																						
Object	+9V5.6A																																							
1. Graph																																								
<p style="text-align: center;"> —△— Input Volt. 100V —○— Input Volt. 200V </p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.80</td><td>20</td><td>20</td></tr> <tr><td>1.60</td><td>20</td><td>20</td></tr> <tr><td>2.40</td><td>20</td><td>20</td></tr> <tr><td>3.20</td><td>30</td><td>30</td></tr> <tr><td>4.00</td><td>30</td><td>30</td></tr> <tr><td>4.80</td><td>30</td><td>30</td></tr> <tr><td>5.60</td><td>40</td><td>30</td></tr> <tr><td>6.16</td><td>50</td><td>50</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	0.00	10	10	0.80	20	20	1.60	20	20	2.40	20	20	3.20	30	30	4.00	30	30	4.80	30	30	5.60	40	30	6.16	50	50									
Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																						
0.00	10	10																																						
0.80	20	20																																						
1.60	20	20																																						
2.40	20	20																																						
3.20	30	30																																						
4.00	30	30																																						
4.80	30	30																																						
5.60	40	30																																						
6.16	50	50																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.80</td><td>20</td><td>20</td></tr> <tr><td>1.60</td><td>20</td><td>20</td></tr> <tr><td>2.40</td><td>20</td><td>20</td></tr> <tr><td>3.20</td><td>30</td><td>30</td></tr> <tr><td>4.00</td><td>30</td><td>30</td></tr> <tr><td>4.80</td><td>30</td><td>30</td></tr> <tr><td>5.60</td><td>40</td><td>30</td></tr> <tr><td>6.16</td><td>50</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.00	10	10	0.80	20	20	1.60	20	20	2.40	20	20	3.20	30	30	4.00	30	30	4.80	30	30	5.60	40	30	6.16	50	50	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0.00	10	10																																						
0.80	20	20																																						
1.60	20	20																																						
2.40	20	20																																						
3.20	30	30																																						
4.00	30	30																																						
4.80	30	30																																						
5.60	40	30																																						
6.16	50	50																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p style="text-align: center;"> T1: Due to AC Input Line T2: Due to Switching </p>																																								
<p style="text-align: center;">Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	LDA50F-9																																								
Item	Temperature Testing Circuitry	25°C Figure A																																							
Object	+9V5.6A																																								
1. Graph																																									
<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from 0 to 6 A. Two curves are plotted: one for Input Volt. 100V (solid line with open circles) and one for Input Volt. 200V (dashed line with open triangles). Both curves show an increase in noise as load current increases. A slanted line indicates the rated load current range.</p>		2. Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>20</td><td>25</td></tr> <tr> <td>0.80</td><td>35</td><td>40</td></tr> <tr> <td>1.60</td><td>40</td><td>45</td></tr> <tr> <td>2.40</td><td>45</td><td>50</td></tr> <tr> <td>3.20</td><td>50</td><td>55</td></tr> <tr> <td>4.00</td><td>60</td><td>60</td></tr> <tr> <td>4.80</td><td>65</td><td>65</td></tr> <tr> <td>5.60</td><td>75</td><td>70</td></tr> <tr> <td>6.16</td><td>75</td><td>70</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.00	20	25	0.80	35	40	1.60	40	45	2.40	45	50	3.20	50	55	4.00	60	60	4.80	65	65	5.60	75	70	6.16	75	70	--	-	-	--	-	-		
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 100 [V]	Input Volt. 200 [V]																																							
0.00	20	25																																							
0.80	35	40																																							
1.60	40	45																																							
2.40	45	50																																							
3.20	50	55																																							
4.00	60	60																																							
4.80	65	65																																							
5.60	75	70																																							
6.16	75	70																																							
--	-	-																																							
--	-	-																																							
Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.																																									
<p>Diagram illustrating a Complex Ripple Wave Form. The diagram shows a waveform with two distinct components: T1, which is a high-frequency noise component, and T2, which is a low-frequency switching component. The total amplitude of the ripple noise is indicated as Ripple-Noise [mVp-p].</p>																																									
Fig. Complex Ripple Wave Form																																									

COSEL

Model	LDA50F-9																																							
Item	Ripple Voltage (by Ambient Temp.)																																							
Object	+9V5.6A																																							
1.Graph																																								
<p>Legend:</p> <ul style="list-style-type: none"> ---□--- Input Volt. 100V —△— Input Volt. 200V <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Load 100 %</p>																																								
<p>Measured by 20 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								
Testing Circuitry Figure A																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>60</td> <td>55</td> </tr> <tr> <td>-10</td> <td>60</td> <td>55</td> </tr> <tr> <td>0</td> <td>55</td> <td>50</td> </tr> <tr> <td>10</td> <td>50</td> <td>40</td> </tr> <tr> <td>20</td> <td>45</td> <td>35</td> </tr> <tr> <td>25</td> <td>40</td> <td>30</td> </tr> <tr> <td>40</td> <td>40</td> <td>25</td> </tr> <tr> <td>50</td> <td>35</td> <td>25</td> </tr> <tr> <td>60</td> <td>30</td> <td>20</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	-20	60	55	-10	60	55	0	55	50	10	50	40	20	45	35	25	40	30	40	40	25	50	35	25	60	30	20	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
-20	60	55																																						
-10	60	55																																						
0	55	50																																						
10	50	40																																						
20	45	35																																						
25	40	30																																						
40	40	25																																						
50	35	25																																						
60	30	20																																						
--	-	-																																						
--	-	-																																						

Model	LDA50F-9																																																					
Item	Ambient Temperature Drift																																																					
Object	+9V5.6A																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - · -○- · Input Volt. 230V</p>  <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																					
Testing Circuitry	Figure A																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>9.074</td><td>9.073</td><td>9.073</td></tr> <tr> <td>-10</td><td>9.069</td><td>9.068</td><td>9.068</td></tr> <tr> <td>0</td><td>9.069</td><td>9.069</td><td>9.069</td></tr> <tr> <td>10</td><td>9.066</td><td>9.066</td><td>9.065</td></tr> <tr> <td>25</td><td>9.060</td><td>9.060</td><td>9.059</td></tr> <tr> <td>40</td><td>9.049</td><td>9.049</td><td>9.047</td></tr> <tr> <td>50</td><td>9.040</td><td>9.038</td><td>9.035</td></tr> <tr> <td>60</td><td>9.015</td><td>9.012</td><td>9.012</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	9.074	9.073	9.073	-10	9.069	9.068	9.068	0	9.069	9.069	9.069	10	9.066	9.066	9.065	25	9.060	9.060	9.059	40	9.049	9.049	9.047	50	9.040	9.038	9.035	60	9.015	9.012	9.012	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
-20	9.074	9.073	9.073																																																			
-10	9.069	9.068	9.068																																																			
0	9.069	9.069	9.069																																																			
10	9.066	9.066	9.065																																																			
25	9.060	9.060	9.059																																																			
40	9.049	9.049	9.047																																																			
50	9.040	9.038	9.035																																																			
60	9.015	9.012	9.012																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated ambient temperature.																																																					



Model	LDA50F-9	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+9V5.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 5.6A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	264	0	9.143	± 59	± 0.7
Minimum Voltage	50	264	5.6	9.025		

COSEL


Model	LDA50F-9	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift																								
Object	+9V5.6A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>9.091</td></tr> <tr><td>0.5</td><td>9.078</td></tr> <tr><td>1.0</td><td>9.077</td></tr> <tr><td>2.0</td><td>9.077</td></tr> <tr><td>3.0</td><td>9.077</td></tr> <tr><td>4.0</td><td>9.077</td></tr> <tr><td>5.0</td><td>9.077</td></tr> <tr><td>6.0</td><td>9.077</td></tr> <tr><td>7.0</td><td>9.077</td></tr> <tr><td>8.0</td><td>9.077</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	9.091	0.5	9.078	1.0	9.077	2.0	9.077	3.0	9.077	4.0	9.077	5.0	9.077	6.0	9.077	7.0	9.077	8.0	9.077
Time since start [H]	Output Voltage [V]																								
0.0	9.091																								
0.5	9.078																								
1.0	9.077																								
2.0	9.077																								
3.0	9.077																								
4.0	9.077																								
5.0	9.077																								
6.0	9.077																								
7.0	9.077																								
8.0	9.077																								

* The characteristic of AC200V is equal.

COSEL


Model	LDA50F-9	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+9V5.6A		

1. Graph



2. Values

Input Volt.		Time	Td	Tr	Ts	Th	Tf	[mS]
100 V			85.8	35.3	121.1	23.1	7.8	
200 V			34.0	34.5	68.5	127.0	7.8	




COSEL

Model	LDA50F-9																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+9V5.6A																																	
1. Graph																																		
		2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>29</td><td>13</td></tr> <tr> <td>100</td><td>48</td><td>22</td></tr> <tr> <td>120</td><td>78</td><td>38</td></tr> <tr> <td>200</td><td>253</td><td>128</td></tr> <tr> <td>230</td><td>339</td><td>174</td></tr> <tr> <td>264</td><td>453</td><td>235</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	29	13	100	48	22	120	78	38	200	253	128	230	339	174	264	453	235	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
85	29	13																																
100	48	22																																
120	78	38																																
200	253	128																																
230	339	174																																
264	453	235																																
--	-	-																																
--	-	-																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	LDA50F-9
Item	Instantaneous Interruption Compensation
Object	+9V5.6A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
0.80	159	739	960
1.60	86	423	563
2.40	58	297	395
3.20	43	225	305
4.00	32	182	247
4.80	28	153	206
5.60	23	130	177
6.16	20	118	161
--	-	-	-
--	-	-	-


Model	LDA50F-9																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+9V5.6A																																							
1.Graph																																								
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Legend:</p> <ul style="list-style-type: none"> --□-- Load 50% —△— Load 100% 																																								
Note: Slanted line shows the range of the rated ambient temperature.																																								
Testing Circuitry Figure A																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>55</td><td>62</td> </tr> <tr> <td>-10</td><td>54</td><td>61</td> </tr> <tr> <td>0</td><td>54</td><td>61</td> </tr> <tr> <td>10</td><td>54</td><td>61</td> </tr> <tr> <td>25</td><td>54</td><td>61</td> </tr> <tr> <td>40</td><td>54</td><td>61</td> </tr> <tr> <td>50</td><td>53</td><td>61</td> </tr> <tr> <td>60</td><td>53</td><td>61</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	55	62	-10	54	61	0	54	61	10	54	61	25	54	61	40	54	61	50	53	61	60	53	61	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-20	55	62																																						
-10	54	61																																						
0	54	61																																						
10	54	61																																						
25	54	61																																						
40	54	61																																						
50	53	61																																						
60	53	61																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						

COSEL

Model	LDA50F-9
Item	Overcurrent Protection
Object	+9V5.6A

Temperature 25°C
 Testing Circuitry Figure A

1. Graph




Note: Slanted line shows the range of the rated load current.

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 200[V]
9.00	7.08	6.98
8.55	7.55	7.57
8.10	7.57	7.60
7.20	7.62	7.65
6.30	7.66	7.67
5.40	7.71	7.70
4.50	7.75	7.75
3.60	7.81	7.79
2.70	7.85	7.83
1.80	7.89	7.82
0.90	7.91	7.68
0.00	7.86	7.34

Model	LDA50F-9
Item	Overvoltage Protection
Object	+9V5.6A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-20	11.68	11.74
-10	11.80	11.80
0	11.86	11.86
10	11.92	11.91
25	12.03	11.97
40	12.03	12.03
50	12.15	12.15
60	12.20	12.20
--	-	-
--	-	-
--	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)