



TEST DATA OF LEA100F-48

(100V INPUT)

Regulated DC Power Supply
Apr. 25. 2002

Approved by : M. Miyama
Design Manager

Prepared by : T. Miyahara
Design Engineer

コーセル株式会社
COSEL CO.,LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Current)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	9
瞬時停電保障	
10. Load Regulation	10
静的負荷変動	
11. Ripple Voltage (by Load Current)	11
リップル電圧 (負荷特性)	
12. Ripple-Noise	12
リップルノイズ	
13. Overcurrent Protection	13
過電流保護	
14. Overvoltage Protection	14
過電圧保護	
15. Inrush Current	15
突入電流	
16. Dynamic Load Response	16
動的負荷変動	
17. Rise and Fall Time	17
立上り、立下り時間	
18. Ambient Temperature Drift	18
周囲温度変動	
19. Minimum Input Voltage for Regulated Output Voltage	19
最低レギュレーション電圧	
20. Ripple Voltage (by Ambient Temperature)	20
リップル電圧 (周囲温度特性)	
21. Output Voltage Accuracy	21
定電圧精度	
22. Harmonic Current	22
高調波電流	
23. Leakage Current	24
漏洩電流	
24. Line Noise Tolerance	25
入力雑音耐量	
25. Conducted Emission	26
雑音端子電圧	
26. Figure of Testing Circuitry	27
測定回路図	

(Final Page 28)

COSEL

Model		LEA100F-48	Temperature25℃ Testing CircuitryFigure A																																	
Item		Line Regulation 静の入力変動																																		
Object		+48V2.2A																																		
1. Graph			2. Values																																	
<div><div><div>-----□----- Load 50%</div><div>-----△----- Load 100%</div></div><div><div><div>Output Voltage [V]</div><div><div>48.30</div><div>48.20</div><div>48.10</div><div>48.00</div><div>47.90</div><div>47.80</div><div>47.70</div><div>47.60</div></div><div><div>70</div><div>90</div><div>110</div><div>130</div><div>150</div></div><div>Input Voltage [V]</div></div><div></div></div><div><div>Note: Slanted line shows the range of the rated input voltage.</div><div>(注) 斜線は定格入力電圧範囲を示す。</div></div></div>			<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>75</td><td>48.058</td><td>48.054</td></tr><tr><td>80</td><td>48.058</td><td>48.053</td></tr><tr><td>85</td><td>48.058</td><td>48.053</td></tr><tr><td>90</td><td>48.057</td><td>48.052</td></tr><tr><td>100</td><td>48.057</td><td>48.052</td></tr><tr><td>110</td><td>48.057</td><td>48.052</td></tr><tr><td>120</td><td>48.057</td><td>48.052</td></tr><tr><td>132</td><td>48.057</td><td>48.051</td></tr><tr><td>140</td><td>48.056</td><td>48.051</td></tr></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	48.058	48.054	80	48.058	48.053	85	48.058	48.053	90	48.057	48.052	100	48.057	48.052	110	48.057	48.052	120	48.057	48.052	132	48.057	48.051	140	48.056	48.051
Input Voltage [V]	Output Voltage [V]																																			
	Load 50%	Load 100%																																		
75	48.058	48.054																																		
80	48.058	48.053																																		
85	48.058	48.053																																		
90	48.057	48.052																																		
100	48.057	48.052																																		
110	48.057	48.052																																		
120	48.057	48.052																																		
132	48.057	48.051																																		
140	48.056	48.051																																		
			BC-0820																																	

COSEL

Model		LEA100F-48	
Item		Input Current (by Load Current) 入力電流 (負荷特性)	
Object			

1. Graph

—△—

Input Volt. 85V

---□---

Input Volt. 100V

-●-

Input Volt. 132V

Input Current [A]

Load Current [A]	Input Current 85V [A]	Input Current 100V [A]	Input Current 132V [A]
0.00	0.098	0.089	0.079
0.40	0.388	0.333	0.261
0.80	0.640	0.545	0.419
1.20	0.895	0.760	0.580
1.60	1.150	0.974	0.739
2.00	1.414	1.195	0.904
2.20	1.546	1.305	0.983
2.42	1.696	1.431	1.076
--	--	--	--
--	--	--	--
--	--	--	--

Load Current [A]

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	0.098	0.089	0.079
0.40	0.388	0.333	0.261
0.80	0.640	0.545	0.419
1.20	0.895	0.760	0.580
1.60	1.150	0.974	0.739
2.00	1.414	1.195	0.904
2.20	1.546	1.305	0.983
2.42	1.696	1.431	1.076
--	--	--	--
--	--	--	--
--	--	--	--


COSEL

Model		LEA100F-48		Temperature		25℃																																																				
Item		Input Power (by Load Current) 入力電力（負荷特性）		Testing Circuitry		Figure A																																																				
Object																																																										
1. Graph				2. Values																																																						
<div><div><div>—△—</div><div>---□---</div><div>---○---</div></div><div><div>Input Volt. 85V</div><div>Input Volt. 100V</div><div>Input Volt. 132V</div></div></div> <div><div><div>200</div><div>150</div><div>100</div><div>50</div><div>0</div></div><div><div>0.0</div><div>1.0</div><div>2.0</div></div><div>Load Current [A]</div></div> <div>Note: Slanted line shows the range of the rated load current.</div> <div>(注) 斜線は定格負荷電流範囲を示す。</div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.00</td><td>6.5</td><td>6.6</td><td>6.7</td></tr><tr><td>0.40</td><td>30.7</td><td>30.5</td><td>30.2</td></tr><tr><td>0.80</td><td>52.2</td><td>51.8</td><td>51.2</td></tr><tr><td>1.20</td><td>73.9</td><td>73.5</td><td>72.6</td></tr><tr><td>1.60</td><td>95.8</td><td>95.0</td><td>93.9</td></tr><tr><td>2.00</td><td>118.2</td><td>117.2</td><td>115.8</td></tr><tr><td>2.20</td><td>129.3</td><td>128.3</td><td>126.4</td></tr><tr><td>2.42</td><td>142.0</td><td>140.9</td><td>138.6</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>				Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	6.5	6.6	6.7	0.40	30.7	30.5	30.2	0.80	52.2	51.8	51.2	1.20	73.9	73.5	72.6	1.60	95.8	95.0	93.9	2.00	118.2	117.2	115.8	2.20	129.3	128.3	126.4	2.42	142.0	140.9	138.6	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	6.5	6.6	6.7																																																							
0.40	30.7	30.5	30.2																																																							
0.80	52.2	51.8	51.2																																																							
1.20	73.9	73.5	72.6																																																							
1.60	95.8	95.0	93.9																																																							
2.00	118.2	117.2	115.8																																																							
2.20	129.3	128.3	126.4																																																							
2.42	142.0	140.9	138.6																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							

COSEL

Model		LEA100F-48																																																															
Item		Efficiency (by Input Voltage) 効率 (入力電圧特性)																																																															
Object																																																																	
1. Graph		2. Values																																																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Load 50% Efficiency [%]</th><th>Load 100% Efficiency [%]</th></tr></thead><tbody><tr><td>75</td><td>77.6</td><td>81.0</td></tr><tr><td>80</td><td>77.7</td><td>81.9</td></tr><tr><td>85</td><td>78.1</td><td>82.4</td></tr><tr><td>90</td><td>78.4</td><td>82.7</td></tr><tr><td>100</td><td>78.7</td><td>83.2</td></tr><tr><td>110</td><td>78.8</td><td>83.8</td></tr><tr><td>120</td><td>79.2</td><td>84.2</td></tr><tr><td>132</td><td>79.7</td><td>84.5</td></tr><tr><td>140</td><td>79.7</td><td>84.8</td></tr></tbody></table>		Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]	75	77.6	81.0	80	77.7	81.9	85	78.1	82.4	90	78.4	82.7	100	78.7	83.2	110	78.8	83.8	120	79.2	84.2	132	79.7	84.5	140	79.7	84.8	<table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>75</td><td>77.6</td><td>81.0</td></tr><tr><td>80</td><td>77.7</td><td>81.9</td></tr><tr><td>85</td><td>78.1</td><td>82.4</td></tr><tr><td>90</td><td>78.4</td><td>82.7</td></tr><tr><td>100</td><td>78.7</td><td>83.2</td></tr><tr><td>110</td><td>78.8</td><td>83.8</td></tr><tr><td>120</td><td>79.2</td><td>84.2</td></tr><tr><td>132</td><td>79.7</td><td>84.5</td></tr><tr><td>140</td><td>79.7</td><td>84.8</td></tr></tbody></table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	77.6	81.0	80	77.7	81.9	85	78.1	82.4	90	78.4	82.7	100	78.7	83.2	110	78.8	83.8	120	79.2	84.2	132	79.7	84.5	140	79.7	84.8
Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]																																																															
75	77.6	81.0																																																															
80	77.7	81.9																																																															
85	78.1	82.4																																																															
90	78.4	82.7																																																															
100	78.7	83.2																																																															
110	78.8	83.8																																																															
120	79.2	84.2																																																															
132	79.7	84.5																																																															
140	79.7	84.8																																																															
Input Voltage [V]	Efficiency [%]																																																																
	Load 50%	Load 100%																																																															
75	77.6	81.0																																																															
80	77.7	81.9																																																															
85	78.1	82.4																																																															
90	78.4	82.7																																																															
100	78.7	83.2																																																															
110	78.8	83.8																																																															
120	79.2	84.2																																																															
132	79.7	84.5																																																															
140	79.7	84.8																																																															
Note: Slanted line shows the range of the rated input voltage.																																																																	
(注) 斜線は定格入力電圧範囲を示す。																																																																	

COSEL

Model		LEA100F-48		Temperature		25℃																																																				
Item		Efficiency (by Load Current) 効率 (負荷特性)		Testing Circuitry		Figure A																																																				
Object																																																										
1. Graph		<div>—△— Input Volt. 85V</div> <div>---□--- Input Volt. 100V</div> <div>-·○-·- Input Volt. 132V</div>		2. Values																																																						
<div>Efficiency [%]</div>  <div>Load Current [A]</div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr><tr><td>0.40</td><td>65.2</td><td>65.6</td><td>66.2</td></tr><tr><td>0.80</td><td>75.3</td><td>75.7</td><td>76.6</td></tr><tr><td>1.20</td><td>79.2</td><td>79.6</td><td>80.7</td></tr><tr><td>1.60</td><td>81.2</td><td>81.9</td><td>82.8</td></tr><tr><td>2.00</td><td>82.3</td><td>83.0</td><td>84.0</td></tr><tr><td>2.20</td><td>82.6</td><td>83.3</td><td>84.5</td></tr><tr><td>2.42</td><td>82.7</td><td>83.3</td><td>84.7</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>				Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.40	65.2	65.6	66.2	0.80	75.3	75.7	76.6	1.20	79.2	79.6	80.7	1.60	81.2	81.9	82.8	2.00	82.3	83.0	84.0	2.20	82.6	83.3	84.5	2.42	82.7	83.3	84.7	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	—	—	—																																																							
0.40	65.2	65.6	66.2																																																							
0.80	75.3	75.7	76.6																																																							
1.20	79.2	79.6	80.7																																																							
1.60	81.2	81.9	82.8																																																							
2.00	82.3	83.0	84.0																																																							
2.20	82.6	83.3	84.5																																																							
2.42	82.7	83.3	84.7																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
Note: Slanted line shows the range of the rated load current.																																																										
(注) 斜線は定格負荷電流範囲を示す。																																																										

COSEL

Model		LEA100F-48		Temperature		25℃																																																																	
Item		Power Factor (by Input Voltage) 力率 (入力電圧特性)		Testing Circuitry		Figure A																																																																	
Object																																																																							
1. Graph				2. Values																																																																			
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>---△---</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Power Factor</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>75</td><td>0.976</td><td>0.993</td></tr><tr><td>80</td><td>0.973</td><td>0.989</td></tr><tr><td>85</td><td>0.972</td><td>0.989</td></tr><tr><td>90</td><td>0.967</td><td>0.988</td></tr><tr><td>100</td><td>0.965</td><td>0.985</td></tr><tr><td>110</td><td>0.959</td><td>0.982</td></tr><tr><td>120</td><td>0.952</td><td>0.978</td></tr><tr><td>132</td><td>0.943</td><td>0.974</td></tr><tr><td>140</td><td>0.937</td><td>0.970</td></tr></tbody></table>				Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.976	0.993	80	0.973	0.989	85	0.972	0.989	90	0.967	0.988	100	0.965	0.985	110	0.959	0.982	120	0.952	0.978	132	0.943	0.974	140	0.937	0.970	<table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Power Factor</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>75</td><td>0.976</td><td>0.993</td></tr><tr><td>80</td><td>0.973</td><td>0.989</td></tr><tr><td>85</td><td>0.972</td><td>0.989</td></tr><tr><td>90</td><td>0.967</td><td>0.988</td></tr><tr><td>100</td><td>0.965</td><td>0.985</td></tr><tr><td>110</td><td>0.959</td><td>0.982</td></tr><tr><td>120</td><td>0.952</td><td>0.978</td></tr><tr><td>132</td><td>0.943</td><td>0.974</td></tr><tr><td>140</td><td>0.937</td><td>0.970</td></tr></tbody></table>				Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.976	0.993	80	0.973	0.989	85	0.972	0.989	90	0.967	0.988	100	0.965	0.985	110	0.959	0.982	120	0.952	0.978	132	0.943	0.974	140	0.937	0.970
Input Voltage [V]	Power Factor																																																																						
	Load 50%	Load 100%																																																																					
75	0.976	0.993																																																																					
80	0.973	0.989																																																																					
85	0.972	0.989																																																																					
90	0.967	0.988																																																																					
100	0.965	0.985																																																																					
110	0.959	0.982																																																																					
120	0.952	0.978																																																																					
132	0.943	0.974																																																																					
140	0.937	0.970																																																																					
Input Voltage [V]	Power Factor																																																																						
	Load 50%	Load 100%																																																																					
75	0.976	0.993																																																																					
80	0.973	0.989																																																																					
85	0.972	0.989																																																																					
90	0.967	0.988																																																																					
100	0.965	0.985																																																																					
110	0.959	0.982																																																																					
120	0.952	0.978																																																																					
132	0.943	0.974																																																																					
140	0.937	0.970																																																																					
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																																																							

COSEL

Model		LEA100F-48	
Item		Hold-Up Time 出力保持時間	
Object		+48V2.2A	

1. Graph

---□--- Load 50%

—△— Load 100%

Hold-Up Time [mS]

Input Voltage [V]

2. Values

Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
75	—	—
80	64	23
85	65	25
90	67	26
100	69	27
110	71	29
120	71	30
132	72	31
140	73	31

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が定電圧精度の範囲を保持しているところまでの時間。
(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	LEA100F-48																																																						
Item	Instantaneous Interruption Compensation 瞬時停電保障	Temperature	25℃																																																				
Object	+48V2.2A	Testing Circuitry	Figure A																																																				
1. Graph		2. Values																																																					
<div><div>—△—</div>Input Volt. 85V</div> <div><div>---□---</div>Input Volt. 100V</div> <div><div>-·-○-·-</div>Input Volt. 132V</div> <p>Instantaneous Compensation Time [mS]</p> <p>Load Current [A]</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [mS]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr><tr><td>0.40</td><td>253</td><td>262</td><td>272</td></tr><tr><td>0.80</td><td>145</td><td>154</td><td>163</td></tr><tr><td>1.20</td><td>103</td><td>104</td><td>113</td></tr><tr><td>1.60</td><td>69</td><td>74</td><td>88</td></tr><tr><td>2.00</td><td>48</td><td>56</td><td>71</td></tr><tr><td>2.20</td><td>44</td><td>49</td><td>63</td></tr><tr><td>2.42</td><td>38</td><td>42</td><td>55</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr></table>			Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.40	253	262	272	0.80	145	154	163	1.20	103	104	113	1.60	69	74	88	2.00	48	56	71	2.20	44	49	63	2.42	38	42	55	--	—	—	—	--	—	—	—	--	—	—	—
Load Current [A]	Time [mS]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0.00	—	—	—																																																				
0.40	253	262	272																																																				
0.80	145	154	163																																																				
1.20	103	104	113																																																				
1.60	69	74	88																																																				
2.00	48	56	71																																																				
2.20	44	49	63																																																				
2.42	38	42	55																																																				
--	—	—	—																																																				
--	—	—	—																																																				
--	—	—	—																																																				
Note: Slanted line shows the range of the rated load current.																																																							
(注) 斜線は定格負荷電流範囲を示す。																																																							

COSEL

Model		LEA100F-48		Temperature		25℃																																																
Item		Load Regulation 静的負荷変動		Testing Circuitry		Figure A																																																
Object		+48V2. 2A																																																				
1. Graph				2. Values																																																		
<div><div><div>—△—</div><div>---□---</div><div>-·-○-·-</div></div><div>Input Volt. 85V</div><div>Input Volt. 100V</div><div>Input Volt. 132V</div></div> <p>Output Voltage [V]</p> <p>Load Current [A]</p>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.00</td><td>48.079</td><td>48.079</td><td>48.080</td></tr><tr><td>0.40</td><td>48.066</td><td>48.066</td><td>48.066</td></tr><tr><td>0.80</td><td>48.060</td><td>48.060</td><td>48.060</td></tr><tr><td>1.20</td><td>48.058</td><td>48.058</td><td>48.057</td></tr><tr><td>1.60</td><td>48.057</td><td>48.056</td><td>48.056</td></tr><tr><td>2.00</td><td>48.055</td><td>48.054</td><td>48.054</td></tr><tr><td>2.20</td><td>48.054</td><td>48.054</td><td>48.053</td></tr><tr><td>2.42</td><td>48.054</td><td>48.053</td><td>48.052</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>				Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	48.079	48.079	48.080	0.40	48.066	48.066	48.066	0.80	48.060	48.060	48.060	1.20	48.058	48.058	48.057	1.60	48.057	48.056	48.056	2.00	48.055	48.054	48.054	2.20	48.054	48.054	48.053	2.42	48.054	48.053	48.052	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	48.079	48.079	48.080																																																			
0.40	48.066	48.066	48.066																																																			
0.80	48.060	48.060	48.060																																																			
1.20	48.058	48.058	48.057																																																			
1.60	48.057	48.056	48.056																																																			
2.00	48.055	48.054	48.054																																																			
2.20	48.054	48.054	48.053																																																			
2.42	48.054	48.053	48.052																																																			
--	--	--	--																																																			
--	--	--	--																																																			
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																						

COSEL

Model		LEA100F-48	
Item		Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	
Object		+48V2.2A	
1. Graph		2. Values	

—△— Input Volt. 85V
- - ○ - - Input Volt. 132V

Ripple Voltage [mV]

Load Current [A]

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。
(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期

Ripple [mVp-p]


T1

T2

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	15	15
0.4	30	30
0.8	35	35
1.3	35	35
1.7	40	40
2.2	45	45
2.4	50	50
--	--	--
--	--	--
--	--	--
--	--	--




Fig. Complex Ripple Wave Form
図 リップル波形詳細図


COSEL



COSEL

Model	LEA100F-48																																																									
Item	Overcurrent Protection 過電流保護	Temperature	25℃																																																							
Object	+48V2.2A	Testing Circuitry	Figure A																																																							
1. Graph		2. Values																																																								
<div><div><div></div><div></div><div></div></div><div>Input Volt. 85V Input Volt. 100V Input Volt. 132V</div></div> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。</p> <p>Intermittent operation occurs when the output voltage is from 28V to 0V. 28V~0V間は、間欠モードとなる。</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>48.0</td><td>2.67</td><td>2.68</td><td>2.68</td></tr><tr><td>45.6</td><td>2.69</td><td>2.69</td><td>2.69</td></tr><tr><td>43.2</td><td>2.72</td><td>2.72</td><td>2.72</td></tr><tr><td>38.4</td><td>2.72</td><td>2.71</td><td>2.72</td></tr><tr><td>33.6</td><td>2.70</td><td>2.70</td><td>2.69</td></tr><tr><td>28.8</td><td>2.68</td><td>2.69</td><td>2.69</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	48.0	2.67	2.68	2.68	45.6	2.69	2.69	2.69	43.2	2.72	2.72	2.72	38.4	2.72	2.71	2.72	33.6	2.70	2.70	2.69	28.8	2.68	2.69	2.69	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
48.0	2.67	2.68	2.68																																																							
45.6	2.69	2.69	2.69																																																							
43.2	2.72	2.72	2.72																																																							
38.4	2.72	2.71	2.72																																																							
33.6	2.70	2.70	2.69																																																							
28.8	2.68	2.69	2.69																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							

1. Graph		Input Volt. 85V
		Input Volt. 100V
		Input Volt. 132V




2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	59.30	59.30	59.30
-10	59.87	59.87	59.87
0	60.43	60.36	60.36
10	60.93	60.93	60.93
20	61.49	61.49	61.49
25	61.78	61.78	61.78
30	62.06	62.06	62.06
40	62.55	62.55	62.55
50	63.12	63.12	63.12
60	63.61	63.61	63.61
--	--	--	--


COSEL

Model	LEA100F-48	Temperature 25°C Testing Circuitry Figure A
Item	Inrush Current 突入電流	
Object	_____	



Input Voltage 100 V
Frequency 60 Hz
Load 100 %
Inrush Current

- ① 13.6 [A]
② 1.2 [A]



COSEL


Model	LEA100F-48	Temperature	25°C
Item	Dynamic Load Response 動的負荷変動	Testing Circuitry	Figure A
Object	+48V2.2A		

Input Volt. 100 V
Cycle 1000 ms


Load Current

Min. Load (0A) ←→
Load 100% (2.2A)

200 mV/div




20 ms/div




20 ms/div

Min. Load (0A) ←→
Load 50% (1.1A)

200 mV/div



20 ms/div




20 ms/div

COSEL

Model	LEA100F-48	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+48V2.2A		

1. Graph


Input Volt. 85 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	367.0	10.0	377.0	55.5	83.8
100 %	367.0	11.0	378.0	24.0	46.8



COSEL

Model

LEA100F-48

Item

Ambient Temperature Drift
周囲温度変動

Object

+48V2.2A

1. Graph

—△—

Input Volt. 85V

---□---

Input Volt. 100V

---○---

Input Volt. 132V

Output Voltage [V]

</

COSEL

Model		LEA100F-48	
Item		Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	
Object		+48V2.2A	
1. Graph			
<div><div>---□--- Load 50%</div><div>—△— Load 100%</div></div> <p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p>			
Note: Slanted line shows the range of the rated ambient temperature.			
(注) 斜線は定格周囲温度範囲を示す。			

Testing Circuitry		Figure A	
2. Values			
Ambient Temperature [°C]	Input Voltage [V]		
	Load 50%	Load 100%	
-20	73	74	
-10	73	74	
0	73	74	
10	73	74	
20	73	74	
25	73	74	
30	73	74	
40	73	74	
50	73	74	
60	73	74	
--	—	—	

COSEL

LOREL

Model	LEA100F-48
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+48V2.2A

1. Graph

□

Load 50%

—

△

—

Load 100%

Ripple Voltage [mV]

Ambient Temperature [°C]

Input Volt. 100V

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	190	210
-10	130	150
0	80	90
10	55	60
20	40	45
25	35	45
30	35	40
40	30	40
50	30	35
60	25	35
--	—	—

COSEL

		Testing Circuitry Figure A
Model	LEA100F-48	
Item	Output Voltage Accuracy 定電圧精度	
Object	+48V2.2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 ~ 50°C

Input Voltage : 85 ~ 132V

Load Current : 0 ~ 2.2A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage}}{\text{Rated Output Voltage}} \times 100$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -10 ~ 50°C

入力電圧 : 85 ~ 132V

負荷電流 : 0 ~ 2.2A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	132	0	12.071	±17	±0.1
Minimum Voltage	55	85	0.9	12.037		


COSEL

Model	LEA100F-48	Temperature	25°C
Item	Harmonic Current 高調波電流	Testing Circuitry	Figure E
Object	_____		


1. Input Current Waveform

— Input Current
— Envelope of the input current to classify equipment as Class D
クラスDの機器を決定するための入力電流包絡線

1 A/div



2. Harmonic Current



— Harmonic Current
高調波電流
— Limits for Class A equipment
クラスAの機器に対する限度値

Conditions	Values
Input Voltage [V]	99.9
Input Current [A]	1.279
Active Power [W]	126.3
Apparent Power [VA]	127.8
Frequency [Hz]	60
Power Factor	0.988
Output Power [W]	105.6

Harmonics order 高調波次数	Limits 限度値 [A]	Values 測定値 [A]
1	—	1.26500
2	—	0.00050
3	5.29530	0.15460
4	—	0.00030
5	2.62462	0.08980
6	—	0.00010
7	1.77277	0.04740
8	—	0.00000
9	0.92092	0.01980
10	—	0.00010
11	0.75976	0.00540
12	—	0.00010
13	0.48348	0.00490
14	—	0.00010
15	0.34535	0.00950
16	—	0.00000
17	0.30472	0.01030
18	—	0.00000
19	0.27264	0.00720
20	—	0.00000
21	0.24668	0.00510
22	—	0.00010
23	0.22523	0.00350
24	—	0.00010
25	0.20721	0.00280
26	—	0.00000
27	0.19186	0.00540
28	—	0.00000
29	0.17863	0.00590
30	—	0.00000
31	0.16710	0.00350
32	—	0.00000
33	0.15698	0.00260
34	—	0.00000
35	0.14801	0.00310
36	—	0.00010
37	0.14000	0.00230
38	—	0.00000
39	0.13283	0.00240
40	—	0.00000


COSEL

Model	LEA100F-48	Temperature	25℃
Item	Harmonic Current	Testing Circuitry	Figure E
Object			


1. Input Current Waveform

— Input Current
 — Envelope of the input current to classify equipment as Class D
 クラスDの機器を決定するための入力電流包絡線

1 A/div



2. Harmonic Current



Conditions	Values
Input Voltage [V]	100.1
Input Current [A]	0.681
Active Power [W]	66
Apparent Power [VA]	68.2
Frequency [Hz]	60
Power Factor	0.968
Output Power [W]	52.8

Harmonics order 高調波次数	Limits 限度値 [A]	Values 測定値 [A]
1	—	0.66030
2	—	0.00050
3	5.28472	0.15270
4	—	0.00010
5	2.61938	0.06000
6	—	0.00010
7	1.76923	0.01030
8	—	0.00010
9	0.91908	0.01000
10	—	0.00010
11	0.75824	0.01190
12	—	0.00000
13	0.48252	0.00600
14	—	0.00000
15	0.34466	0.00640
16	—	0.00000
17	0.30411	0.00960
18	—	0.00010
19	0.27210	0.00690
20	—	0.00010
21	0.24618	0.00370
22	—	0.00000
23	0.22478	0.00420
24	—	0.00000
25	0.20679	0.00490
26	—	0.00000
27	0.19148	0.00330
28	—	0.00010
29	0.17827	0.00090
30	—	0.00010
31	0.16677	0.00060
32	—	0.00000
33	0.15666	0.00080
34	—	0.00000
35	0.14771	0.00210
36	—	0.00000
37	0.13973	0.00190
38	—	0.00010
39	0.13256	0.00090
40	—	0.00010

COSEL

Model		LEA100F-48	
Item		Leakage Current 漏洩電流	Temperature 25℃ Testing Circuitry Figure B
Object			

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DEN-AN	0.15	0.18	0.24
(B) IEC60950	0.15	0.18	0.24

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の一相について測定し、その大きい方を漏洩電流測定値とする。

COSEL

Model	LEA100F-48		
Item	Line Noise Tolerance 入力雑音耐量	Temperature	25°C
Object	+48V2.2A	Testing Circuitry	Figure C

1. Conditions

- Input Voltage : 100 V
- Pulse Voltage : 2000 V
- Pulse Cycle : 10 mS
- Pulse Input Duration : 1 min. or more
- Load : 100 %

2. Results

Pulse Width [nS]	MODE		No protection failure should occur	DC-like Regulation of Output Voltage
		POLARITY	保護回路の誤動作がない	出力電圧の直流的変動
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

COSEL

Model	LEA100F-48	Temperature	25°C
Item	Conducted Emission 雑音端子電圧	Testing Circuitry	Figure D
Object			

1. Graph

Remarks


Input Volt. 100V (VCCI Class B)

120V (FCC Class B)

Load 100%


規格 1: [VCCI] Class B(QP)

規格 2: [VCCI] Class B(平均値)



規格 1: [FCC Part15] Class B

規格 2: [FCC Part15] Class B(-6dB)



COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)




Figure C




Figure D




Figure E