

COSEL

TEST DATA OF LEB150F-0524
(100V INPUT)

Regulated DC Power Supply

Mar. 27, 2000

Approved by : Katsuhiro Kizumii
Design Manager

Prepared by : T. Ohara
Design Engineer

コーセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Power)	2
入力電流 (負荷特性)	
3. Input Power (by Load Power)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Power)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Power)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	10
瞬時停電保障	
10. Load Regulation	12
静的負荷変動	
11. Ripple Voltage (by Load Current)	13
リップル電圧 (負荷特性)	
12. Ripple-Noise	15
リップルノイズ	
13. Overcurrent Protection	17
過電流保護	
14. Overvoltage Protection	18
過電圧保護	
15. Inrush Current	19
突入電流	
16. Dynamic Load Responce	20
動的負荷変動	
17. Rise and Fall Time	22
立ち上り、立下り時間	
18. Ambient Temperature Drift	24
周囲温度変動	
19. Minimum Input Voltage for Regulated Output Voltage	25
最低レギュレーション電圧	
20. Ripple Voltage (by Ambient Temperature)	26
リップル電圧 (周囲温度特性)	
21. Time Lapse Drift	27
経時ドリフト	
22. Output Voltage Accuracy	28
定電圧精度	
23. Harmonic Current	29
高調波電流	
24. Oscillator Frequency	31
発振周波数	
25. Condensation	32
結露特性	
26. Leakage Current	33
漏洩電流	
27. Line Noise Tolerance	34
入力雑音耐量	
28. Conducted Emission	35
雑音端子電圧	
29. Figure of Testing Circuitry	36
測定回路図	

(Final Page 37)

COSEL

Model	LEB150F-0524	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	V1: +5.0V5A																																		
1. Graph			2. Values																																
<p style="text-align: center;">□ Load 50% △ Load 100%</p> <p style="text-align: center;">[V]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>5.063</td><td>5.050</td></tr> <tr><td>80</td><td>5.063</td><td>5.050</td></tr> <tr><td>85</td><td>5.063</td><td>5.050</td></tr> <tr><td>90</td><td>5.063</td><td>5.050</td></tr> <tr><td>100</td><td>5.063</td><td>5.050</td></tr> <tr><td>110</td><td>5.063</td><td>5.050</td></tr> <tr><td>120</td><td>5.063</td><td>5.050</td></tr> <tr><td>132</td><td>5.063</td><td>5.050</td></tr> <tr><td>140</td><td>5.063</td><td>5.050</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	5.063	5.050	80	5.063	5.050	85	5.063	5.050	90	5.063	5.050	100	5.063	5.050	110	5.063	5.050	120	5.063	5.050	132	5.063	5.050	140	5.063	5.050
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	5.063	5.050																																	
80	5.063	5.050																																	
85	5.063	5.050																																	
90	5.063	5.050																																	
100	5.063	5.050																																	
110	5.063	5.050																																	
120	5.063	5.050																																	
132	5.063	5.050																																	
140	5.063	5.050																																	
Object																																			
1. Graph			2. Values																																
<p style="text-align: center;">□ Load 50% △ Load 100%</p> <p style="text-align: center;">[V]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>24.034</td><td>24.023</td></tr> <tr><td>80</td><td>24.033</td><td>24.023</td></tr> <tr><td>85</td><td>24.034</td><td>24.023</td></tr> <tr><td>90</td><td>24.033</td><td>24.024</td></tr> <tr><td>100</td><td>24.034</td><td>24.024</td></tr> <tr><td>110</td><td>24.034</td><td>24.024</td></tr> <tr><td>120</td><td>24.034</td><td>24.024</td></tr> <tr><td>132</td><td>24.033</td><td>24.024</td></tr> <tr><td>140</td><td>24.033</td><td>24.024</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	24.034	24.023	80	24.033	24.023	85	24.034	24.023	90	24.033	24.024	100	24.034	24.024	110	24.034	24.024	120	24.034	24.024	132	24.033	24.024	140	24.033	24.024
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	24.034	24.023																																	
80	24.033	24.023																																	
85	24.034	24.023																																	
90	24.033	24.024																																	
100	24.034	24.024																																	
110	24.034	24.024																																	
120	24.034	24.024																																	
132	24.033	24.024																																	
140	24.033	24.024																																	
Note: Slanted line shows the range of the rated input voltage.																																			
(注)斜線は定格入力電圧範囲を示す。																																			

COSSEL

Model	LEB150F-0524	Temperature	25°C																																																							
Item	Input Current (by Load Power) 入力電流 (負荷特性)	Testing Circuitry	Figure A																																																							
Output																																																										
1. Graph	<p>—△— Input Volt. 85V —□— Input Volt. 100V —○— Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Power [W]</th> <th>Input Current 85V [A]</th> <th>Input Current 100V [A]</th> <th>Input Current 132V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.168</td><td>0.152</td><td>0.128</td></tr> <tr><td>30</td><td>0.634</td><td>0.544</td><td>0.425</td></tr> <tr><td>60</td><td>1.046</td><td>0.890</td><td>0.684</td></tr> <tr><td>90</td><td>1.456</td><td>1.233</td><td>0.939</td></tr> <tr><td>120</td><td>1.887</td><td>1.593</td><td>1.206</td></tr> <tr><td>150</td><td>2.317</td><td>1.951</td><td>1.470</td></tr> <tr><td>165</td><td>2.537</td><td>2.138</td><td>1.605</td></tr> </tbody> </table>			Load Power [W]	Input Current 85V [A]	Input Current 100V [A]	Input Current 132V [A]	0	0.168	0.152	0.128	30	0.634	0.544	0.425	60	1.046	0.890	0.684	90	1.456	1.233	0.939	120	1.887	1.593	1.206	150	2.317	1.951	1.470	165	2.537	2.138	1.605																							
Load Power [W]	Input Current 85V [A]	Input Current 100V [A]	Input Current 132V [A]																																																							
0	0.168	0.152	0.128																																																							
30	0.634	0.544	0.425																																																							
60	1.046	0.890	0.684																																																							
90	1.456	1.233	0.939																																																							
120	1.887	1.593	1.206																																																							
150	2.317	1.951	1.470																																																							
165	2.537	2.138	1.605																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.168</td><td>0.152</td><td>0.128</td></tr> <tr><td>30</td><td>0.634</td><td>0.544</td><td>0.425</td></tr> <tr><td>60</td><td>1.046</td><td>0.890</td><td>0.684</td></tr> <tr><td>90</td><td>1.456</td><td>1.233</td><td>0.939</td></tr> <tr><td>120</td><td>1.887</td><td>1.593</td><td>1.206</td></tr> <tr><td>150</td><td>2.317</td><td>1.951</td><td>1.470</td></tr> <tr><td>165</td><td>2.537</td><td>2.138</td><td>1.605</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Power [W]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.168	0.152	0.128	30	0.634	0.544	0.425	60	1.046	0.890	0.684	90	1.456	1.233	0.939	120	1.887	1.593	1.206	150	2.317	1.951	1.470	165	2.537	2.138	1.605	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Power [W]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	0.168	0.152	0.128																																																							
30	0.634	0.544	0.425																																																							
60	1.046	0.890	0.684																																																							
90	1.456	1.233	0.939																																																							
120	1.887	1.593	1.206																																																							
150	2.317	1.951	1.470																																																							
165	2.537	2.138	1.605																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load power.

(注) 斜線は定格出力電力範囲を示す。

COSEL

Model	LEB150F-0524	Temperature	25°C																																																			
Item	Input Power (by Load Power) 入力電力 (負荷特性)	Testing Circuitry	Figure A																																																			
Output																																																						
1. Graph	<p>Input Volt. 85V Input Volt. 100V Input Volt. 132V</p> <p>Load Power [W]</p> <p>Input Power [W]</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>11.52</td><td>11.76</td><td>11.97</td></tr> <tr><td>30</td><td>50.10</td><td>49.94</td><td>49.66</td></tr> <tr><td>60</td><td>85.37</td><td>84.74</td><td>83.80</td></tr> <tr><td>90</td><td>120.58</td><td>119.38</td><td>117.90</td></tr> <tr><td>120</td><td>157.60</td><td>155.70</td><td>153.60</td></tr> <tr><td>150</td><td>194.40</td><td>191.90</td><td>188.90</td></tr> <tr><td>165</td><td>213.30</td><td>210.70</td><td>206.80</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Power [W]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	11.52	11.76	11.97	30	50.10	49.94	49.66	60	85.37	84.74	83.80	90	120.58	119.38	117.90	120	157.60	155.70	153.60	150	194.40	191.90	188.90	165	213.30	210.70	206.80	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Power [W]	Input Power [W]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	11.52	11.76	11.97																																																			
30	50.10	49.94	49.66																																																			
60	85.37	84.74	83.80																																																			
90	120.58	119.38	117.90																																																			
120	157.60	155.70	153.60																																																			
150	194.40	191.90	188.90																																																			
165	213.30	210.70	206.80																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load power.

(注)斜線は定格出力電力範囲を示す。

COSEL

Model	LEB150F-0524		Temperature Testing Circuitry 25°C Figure A																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)																																		
Object	_____																																		
1. Graph																																			
[%]		Load 50%	2. Values																																
		Load 100%	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>74.4</td><td>77.2</td></tr> <tr><td>80</td><td>74.7</td><td>78.1</td></tr> <tr><td>85</td><td>75.1</td><td>78.4</td></tr> <tr><td>90</td><td>75.3</td><td>78.9</td></tr> <tr><td>100</td><td>75.7</td><td>79.5</td></tr> <tr><td>110</td><td>76.1</td><td>79.9</td></tr> <tr><td>120</td><td>76.4</td><td>80.4</td></tr> <tr><td>132</td><td>76.7</td><td>80.7</td></tr> <tr><td>140</td><td>76.9</td><td>80.9</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	74.4	77.2	80	74.7	78.1	85	75.1	78.4	90	75.3	78.9	100	75.7	79.5	110	76.1	79.9	120	76.4	80.4	132	76.7	80.7	140	76.9	80.9
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	74.4	77.2																																	
80	74.7	78.1																																	
85	75.1	78.4																																	
90	75.3	78.9																																	
100	75.7	79.5																																	
110	76.1	79.9																																	
120	76.4	80.4																																	
132	76.7	80.7																																	
140	76.9	80.9																																	
Efficiency		Input Voltage [V]																																	
70 75 80 85 90 100 110 120 130 140 150		70 75 80 85 90 100 110 120 130 140 150																																	
58 62 66 70 74 78 82 86		58 62 66 70 74 78 82 86																																	
Note: Slanted line shows the range of the rated input voltage.																																			
(注)斜線は定格入力電圧範囲を示す。																																			

COSEL

Model	LEB150F-0524	Temperature	25°C																																																			
Item	Efficiency (by Load Power) 効率(負荷特性)	Testing Circuitry	Figure A																																																			
Output	—																																																					
1. Graph		2. Values																																																				
<p>The graph plots Efficiency [%] on the y-axis (30 to 90) against Load Power [W] on the x-axis (0 to 200). Three curves are shown for Input Volt. 85V (triangles), Input Volt. 100V (squares), and Input Volt. 132V (circles). All curves show efficiency increasing with load power. A slanted line indicates the rated load power range, which is approximately between 100W and 165W.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>30</td><td>62.6</td><td>63.2</td><td>63.6</td></tr> <tr><td>60</td><td>72.5</td><td>73.2</td><td>74.2</td></tr> <tr><td>90</td><td>76.0</td><td>77.0</td><td>78.0</td></tr> <tr><td>120</td><td>77.5</td><td>78.5</td><td>79.6</td></tr> <tr><td>150</td><td>78.1</td><td>79.2</td><td>80.4</td></tr> <tr><td>165</td><td>78.2</td><td>79.3</td><td>80.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Power [W]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	30	62.6	63.2	63.6	60	72.5	73.2	74.2	90	76.0	77.0	78.0	120	77.5	78.5	79.6	150	78.1	79.2	80.4	165	78.2	79.3	80.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Power [W]	Efficiency [%]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
30	62.6	63.2	63.6																																																			
60	72.5	73.2	74.2																																																			
90	76.0	77.0	78.0																																																			
120	77.5	78.5	79.6																																																			
150	78.1	79.2	80.4																																																			
165	78.2	79.3	80.8																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load power.

(注)斜線は定格出力電力範囲を示す。



Model	LEB150F-0524		Temperature Testing Circuitry	25°C Figure A																															
Item	Power Factor (by Input Voltage) 力率(入力電圧特性)																																		
Object	<hr/>			<hr/>																															
1. Graph	<p style="text-align: center;">Load 50% □ Load 100% △</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Power Factor (Load 50%)</th> <th>Power Factor (Load 100%)</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.98</td><td>0.99</td></tr> <tr><td>80</td><td>0.97</td><td>0.99</td></tr> <tr><td>85</td><td>0.97</td><td>0.99</td></tr> <tr><td>90</td><td>0.97</td><td>0.99</td></tr> <tr><td>100</td><td>0.97</td><td>0.99</td></tr> <tr><td>110</td><td>0.96</td><td>0.98</td></tr> <tr><td>120</td><td>0.95</td><td>0.98</td></tr> <tr><td>130</td><td>0.94</td><td>0.98</td></tr> <tr><td>140</td><td>0.94</td><td>0.97</td></tr> </tbody> </table>	Input Voltage [V]		Power Factor (Load 50%)	Power Factor (Load 100%)	75	0.98	0.99	80	0.97	0.99	85	0.97	0.99	90	0.97	0.99	100	0.97	0.99	110	0.96	0.98	120	0.95	0.98	130	0.94	0.98	140	0.94	0.97	<hr/>		
Input Voltage [V]	Power Factor (Load 50%)	Power Factor (Load 100%)																																	
75	0.98	0.99																																	
80	0.97	0.99																																	
85	0.97	0.99																																	
90	0.97	0.99																																	
100	0.97	0.99																																	
110	0.96	0.98																																	
120	0.95	0.98																																	
130	0.94	0.98																																	
140	0.94	0.97																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.98</td><td>0.99</td></tr> <tr><td>80</td><td>0.97</td><td>0.99</td></tr> <tr><td>85</td><td>0.97</td><td>0.99</td></tr> <tr><td>90</td><td>0.97</td><td>0.99</td></tr> <tr><td>100</td><td>0.97</td><td>0.99</td></tr> <tr><td>110</td><td>0.96</td><td>0.98</td></tr> <tr><td>120</td><td>0.95</td><td>0.98</td></tr> <tr><td>132</td><td>0.95</td><td>0.98</td></tr> <tr><td>140</td><td>0.94</td><td>0.97</td></tr> </tbody> </table>	Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.98	0.99	80	0.97	0.99	85	0.97	0.99	90	0.97	0.99	100	0.97	0.99	110	0.96	0.98	120	0.95	0.98	132	0.95	0.98	140	0.94	0.97	<hr/>	
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
75	0.98	0.99																																	
80	0.97	0.99																																	
85	0.97	0.99																																	
90	0.97	0.99																																	
100	0.97	0.99																																	
110	0.96	0.98																																	
120	0.95	0.98																																	
132	0.95	0.98																																	
140	0.94	0.97																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LEB150F-0524	Temperature	25°C																																																							
Item	Power Factor (by Load Power) 力率 (負荷特性)	Testing Circuitry	Figure A																																																							
Output																																																										
1. Graph	<p style="text-align: center;">—△— Input Volt. 85V -□- Input Volt. 100V -○- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Power [W]</th> <th>Power Factor at 85V</th> <th>Power Factor at 100V</th> <th>Power Factor at 132V</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.80</td><td>0.78</td><td>0.71</td></tr> <tr><td>30</td><td>0.93</td><td>0.92</td><td>0.88</td></tr> <tr><td>60</td><td>0.96</td><td>0.95</td><td>0.93</td></tr> <tr><td>90</td><td>0.97</td><td>0.97</td><td>0.95</td></tr> <tr><td>120</td><td>0.98</td><td>0.98</td><td>0.96</td></tr> <tr><td>150</td><td>0.99</td><td>0.99</td><td>0.97</td></tr> <tr><td>165</td><td>0.99</td><td>0.99</td><td>0.97</td></tr> </tbody> </table>			Load Power [W]	Power Factor at 85V	Power Factor at 100V	Power Factor at 132V	0	0.80	0.78	0.71	30	0.93	0.92	0.88	60	0.96	0.95	0.93	90	0.97	0.97	0.95	120	0.98	0.98	0.96	150	0.99	0.99	0.97	165	0.99	0.99	0.97																							
Load Power [W]	Power Factor at 85V	Power Factor at 100V	Power Factor at 132V																																																							
0	0.80	0.78	0.71																																																							
30	0.93	0.92	0.88																																																							
60	0.96	0.95	0.93																																																							
90	0.97	0.97	0.95																																																							
120	0.98	0.98	0.96																																																							
150	0.99	0.99	0.97																																																							
165	0.99	0.99	0.97																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.80</td><td>0.78</td><td>0.71</td></tr> <tr><td>30</td><td>0.93</td><td>0.92</td><td>0.88</td></tr> <tr><td>60</td><td>0.96</td><td>0.95</td><td>0.93</td></tr> <tr><td>90</td><td>0.97</td><td>0.97</td><td>0.95</td></tr> <tr><td>120</td><td>0.98</td><td>0.98</td><td>0.96</td></tr> <tr><td>150</td><td>0.99</td><td>0.99</td><td>0.97</td></tr> <tr><td>165</td><td>0.99</td><td>0.99</td><td>0.97</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Power [W]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.80	0.78	0.71	30	0.93	0.92	0.88	60	0.96	0.95	0.93	90	0.97	0.97	0.95	120	0.98	0.98	0.96	150	0.99	0.99	0.97	165	0.99	0.99	0.97	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Power [W]	Power Factor																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	0.80	0.78	0.71																																																							
30	0.93	0.92	0.88																																																							
60	0.96	0.95	0.93																																																							
90	0.97	0.97	0.95																																																							
120	0.98	0.98	0.96																																																							
150	0.99	0.99	0.97																																																							
165	0.99	0.99	0.97																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load power.

(注) 斜線は定格出力電力範囲を示す。

COSEL

Model	LEB150F-0524	Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																	
Object	V1:+5.0V5A																																	
1. Graph	<p style="text-align: center;">□ Load 50% △ Load 100%</p> <p style="text-align: center;">[mS]</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Hold-up Time [mS] (Load 50%)</th> <th>Hold-up Time [mS] (Load 100%)</th> </tr> </thead> <tbody> <tr><td>80</td><td>~150</td><td>~80</td></tr> <tr><td>85</td><td>~200</td><td>~80</td></tr> <tr><td>90</td><td>~200</td><td>~80</td></tr> <tr><td>100</td><td>~200</td><td>~80</td></tr> <tr><td>110</td><td>~200</td><td>~80</td></tr> <tr><td>120</td><td>~200</td><td>~80</td></tr> <tr><td>130</td><td>~200</td><td>~80</td></tr> <tr><td>140</td><td>~200</td><td>~80</td></tr> </tbody> </table>	Input Voltage [V]	Hold-up Time [mS] (Load 50%)	Hold-up Time [mS] (Load 100%)	80	~150	~80	85	~200	~80	90	~200	~80	100	~200	~80	110	~200	~80	120	~200	~80	130	~200	~80	140	~200	~80	2. Values					
Input Voltage [V]	Hold-up Time [mS] (Load 50%)	Hold-up Time [mS] (Load 100%)																																
80	~150	~80																																
85	~200	~80																																
90	~200	~80																																
100	~200	~80																																
110	~200	~80																																
120	~200	~80																																
130	~200	~80																																
140	~200	~80																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>—</td><td>—</td></tr> <tr><td>80</td><td>169</td><td>70</td></tr> <tr><td>85</td><td>170</td><td>71</td></tr> <tr><td>90</td><td>171</td><td>73</td></tr> <tr><td>100</td><td>173</td><td>74</td></tr> <tr><td>110</td><td>175</td><td>76</td></tr> <tr><td>120</td><td>176</td><td>77</td></tr> <tr><td>132</td><td>177</td><td>78</td></tr> <tr><td>140</td><td>178</td><td>79</td></tr> </tbody> </table>	Input Voltage [V]	Hold-up Time [mS]		Load 50%	Load 100%	75	—	—	80	169	70	85	170	71	90	171	73	100	173	74	110	175	76	120	176	77	132	177	78	140	178	79
Input Voltage [V]	Hold-up Time [mS]																																	
	Load 50%	Load 100%																																
75	—	—																																
80	169	70																																
85	170	71																																
90	171	73																																
100	173	74																																
110	175	76																																
120	176	77																																
132	177	78																																
140	178	79																																
		<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																

COSEL

Model	LEB150F-0524	Temperature	25°C																																
Item	Hold-Up Time 出力保持時間	Testing Circuitry	Figure A																																
Object	V2: +24.0V 6A																																		
1. Graph																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>—</td><td>—</td></tr> <tr><td>80</td><td>49</td><td>25</td></tr> <tr><td>85</td><td>50</td><td>26</td></tr> <tr><td>90</td><td>51</td><td>27</td></tr> <tr><td>100</td><td>52</td><td>29</td></tr> <tr><td>110</td><td>53</td><td>30</td></tr> <tr><td>120</td><td>54</td><td>32</td></tr> <tr><td>132</td><td>56</td><td>32</td></tr> <tr><td>140</td><td>56</td><td>33</td></tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	—	—	80	49	25	85	50	26	90	51	27	100	52	29	110	53	30	120	54	32	132	56	32	140	56	33
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	—	—																																	
80	49	25																																	
85	50	26																																	
90	51	27																																	
100	52	29																																	
110	53	30																																	
120	54	32																																	
132	56	32																																	
140	56	33																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LEB150F-0524	Temperature	25°C																																																					
Item	Instantaneous Interruption Compensation 瞬時停電保障	Testing Circuitry	Figure A																																																					
Object	V1: +5.0V 5A	2. Values																																																						
1. Graph																																																								
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.8</td><td>414</td><td>418</td><td>422</td></tr> <tr><td>1.6</td><td>236</td><td>240</td><td>246</td></tr> <tr><td>2.4</td><td>164</td><td>165</td><td>171</td></tr> <tr><td>3.2</td><td>121</td><td>123</td><td>128</td></tr> <tr><td>4.0</td><td>78</td><td>89</td><td>95</td></tr> <tr><td>4.8</td><td>47</td><td>56</td><td>60</td></tr> <tr><td>5.0</td><td>45</td><td>47</td><td>55</td></tr> <tr><td>5.5</td><td>36</td><td>39</td><td>43</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	—	—	—	0.8	414	418	422	1.6	236	240	246	2.4	164	165	171	3.2	121	123	128	4.0	78	89	95	4.8	47	56	60	5.0	45	47	55	5.5	36	39	43	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0.0	—	—	—																																																					
0.8	414	418	422																																																					
1.6	236	240	246																																																					
2.4	164	165	171																																																					
3.2	121	123	128																																																					
4.0	78	89	95																																																					
4.8	47	56	60																																																					
5.0	45	47	55																																																					
5.5	36	39	43																																																					
—	—	—	—																																																					
—	—	—	—																																																					
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																								

COSSEL

Model	LEB150F-0524	Temperature Testing Circuitry	25°C Figure A																														
Item	Instantaneous Interruption Compensation 瞬時停電保障																																
Object	V2: +24.0V 6A	2. Values																															
1. Graph	<p>—△— Input Volt. 85 V —□— Input Volt. 100 V —○— Input Volt. 132 V</p> <table border="1"> <caption>Data points estimated from Figure 1 graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>85[V] [ms]</th> <th>100[V] [ms]</th> <th>132[V] [ms]</th> </tr> </thead> <tbody> <tr><td>1.0</td><td>80</td><td>81</td><td>90</td></tr> <tr><td>2.0</td><td>45</td><td>46</td><td>56</td></tr> <tr><td>3.0</td><td>37</td><td>38</td><td>46</td></tr> <tr><td>4.0</td><td>30</td><td>31</td><td>37</td></tr> <tr><td>5.0</td><td>22</td><td>27</td><td>31</td></tr> <tr><td>6.0</td><td>19</td><td>22</td><td>22</td></tr> <tr><td>6.6</td><td>14</td><td>20</td><td>22</td></tr> </tbody> </table>	Load Current [A]	85[V] [ms]	100[V] [ms]	132[V] [ms]	1.0	80	81	90	2.0	45	46	56	3.0	37	38	46	4.0	30	31	37	5.0	22	27	31	6.0	19	22	22	6.6	14	20	22
Load Current [A]	85[V] [ms]	100[V] [ms]	132[V] [ms]																														
1.0	80	81	90																														
2.0	45	46	56																														
3.0	37	38	46																														
4.0	30	31	37																														
5.0	22	27	31																														
6.0	19	22	22																														
6.6	14	20	22																														

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。
 (注)斜線は定格負荷電流範囲を示す。

COSSEL

Model	LEB150F-0524	Temperature Testing Circuitry	25°C Figure A																																															
Item	Load Regulation 静的負荷変動																																																	
Object	V1:+5.0V5A																																																	
1. Graph	<p>Output Voltage [V] vs Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V 																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.074</td><td>5.074</td><td>5.074</td></tr> <tr><td>0.8</td><td>5.072</td><td>5.072</td><td>5.072</td></tr> <tr><td>1.6</td><td>5.068</td><td>5.068</td><td>5.068</td></tr> <tr><td>2.4</td><td>5.064</td><td>5.064</td><td>5.064</td></tr> <tr><td>3.2</td><td>5.060</td><td>5.060</td><td>5.060</td></tr> <tr><td>4.0</td><td>5.056</td><td>5.056</td><td>5.056</td></tr> <tr><td>4.8</td><td>5.051</td><td>5.051</td><td>5.051</td></tr> <tr><td>5.0</td><td>5.050</td><td>5.051</td><td>5.050</td></tr> <tr><td>5.5</td><td>5.047</td><td>5.047</td><td>5.048</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	5.074	5.074	5.074	0.8	5.072	5.072	5.072	1.6	5.068	5.068	5.068	2.4	5.064	5.064	5.064	3.2	5.060	5.060	5.060	4.0	5.056	5.056	5.056	4.8	5.051	5.051	5.051	5.0	5.050	5.051	5.050	5.5	5.047	5.047	5.048	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.0	5.074	5.074	5.074																																															
0.8	5.072	5.072	5.072																																															
1.6	5.068	5.068	5.068																																															
2.4	5.064	5.064	5.064																																															
3.2	5.060	5.060	5.060																																															
4.0	5.056	5.056	5.056																																															
4.8	5.051	5.051	5.051																																															
5.0	5.050	5.051	5.050																																															
5.5	5.047	5.047	5.048																																															
—	—	—	—																																															
Object	V2:+24.0V6A																																																	
1. Graph	<p>Output Voltage [V] vs Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V 																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.046</td><td>24.045</td><td>24.045</td></tr> <tr><td>1.0</td><td>24.041</td><td>24.041</td><td>24.041</td></tr> <tr><td>2.0</td><td>24.038</td><td>24.038</td><td>24.038</td></tr> <tr><td>3.0</td><td>24.035</td><td>24.035</td><td>24.035</td></tr> <tr><td>4.0</td><td>24.032</td><td>24.032</td><td>24.032</td></tr> <tr><td>5.0</td><td>24.029</td><td>24.029</td><td>24.029</td></tr> <tr><td>6.0</td><td>24.026</td><td>24.026</td><td>24.026</td></tr> <tr><td>6.6</td><td>24.025</td><td>24.024</td><td>24.024</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	24.046	24.045	24.045	1.0	24.041	24.041	24.041	2.0	24.038	24.038	24.038	3.0	24.035	24.035	24.035	4.0	24.032	24.032	24.032	5.0	24.029	24.029	24.029	6.0	24.026	24.026	24.026	6.6	24.025	24.024	24.024	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.0	24.046	24.045	24.045																																															
1.0	24.041	24.041	24.041																																															
2.0	24.038	24.038	24.038																																															
3.0	24.035	24.035	24.035																																															
4.0	24.032	24.032	24.032																																															
5.0	24.029	24.029	24.029																																															
6.0	24.026	24.026	24.026																																															
6.6	24.025	24.024	24.024																																															
—	—	—	—																																															
—	—	—	—																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																		

COSEL

Model	LEB150F-0524	Temperature	25°C																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷特性)	Testing Circuitry	Figure A																																						
Object	V1:+5.0V5A																																								
1. Graph	<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 100 mV, and the X-axis ranges from 0 to 6 A. Two sets of data points are plotted: Input Volt. 85V (triangles) and Input Volt. 132V (circles). Both sets show a low ripple voltage (around 10 mV) up to approximately 4 A, after which the ripple voltage increases sharply, reaching about 90 mV at 5.5 A for the 85V input and about 15 mV at 5.5 A for the 132V input.</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>10</td> <td>10</td> </tr> <tr> <td>1.0</td> <td>10</td> <td>10</td> </tr> <tr> <td>2.0</td> <td>10</td> <td>10</td> </tr> <tr> <td>3.0</td> <td>10</td> <td>10</td> </tr> <tr> <td>4.0</td> <td>10</td> <td>10</td> </tr> <tr> <td>5.0</td> <td>15</td> <td>15</td> </tr> <tr> <td>5.5</td> <td>15</td> <td>15</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	10	10	1.0	10	10	2.0	10	10	3.0	10	10	4.0	10	10	5.0	15	15	5.5	15	15	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Voltage [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.0	10	10																																							
1.0	10	10																																							
2.0	10	10																																							
3.0	10	10																																							
4.0	10	10																																							
5.0	15	15																																							
5.5	15	15																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p></p> <p>Fig. Complex Ripple Wave Form</p> <p>図 リップル波形詳細図</p>																																									

COSEL

Model	LEB150F-0524	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)	Testing Circuitry	Figure A																																						
Object	V2: +24.0 V 6A																																								
1. Graph																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>1.2</td><td>15</td><td>15</td></tr> <tr><td>2.4</td><td>25</td><td>25</td></tr> <tr><td>3.6</td><td>30</td><td>30</td></tr> <tr><td>4.8</td><td>30</td><td>30</td></tr> <tr><td>6.0</td><td>35</td><td>35</td></tr> <tr><td>6.6</td><td>35</td><td>35</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	10	10	1.2	15	15	2.4	25	25	3.6	30	30	4.8	30	30	6.0	35	35	6.6	35	35	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Voltage [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.0	10	10																																							
1.2	15	15																																							
2.4	25	25																																							
3.6	30	30																																							
4.8	30	30																																							
6.0	35	35																																							
6.6	35	35																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form</p> <p>図 リップル波形詳細図</p>																																									

COSEL

Model	LEB150F-0524	Temperature	25°C
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A
Object	V1: +5.0V 5A		
1. Graph	<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The Y-axis ranges from 0 to 100 mV, and the X-axis ranges from 0 to 6 A. Two horizontal lines at approximately 75 mV represent Input Volt. 85V and Input Volt. 132V. A slanted line shows the range of the rated load current.</p>		
2. Values	Load Current [A]	Ripple-Noise [mV]	
		Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	75	75	
1.0	75	75	
2.0	75	75	
3.0	75	75	
4.0	75	75	
5.0	75	75	
5.5	75	75	
—	—	—	
—	—	—	
—	—	—	
—	—	—	

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期

T2: Due to Switching
スイッチング周期




Fig. Complex Ripple Wave Form
図 リップル波形詳細図


COSEL

Model	LEB150F-0524	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	V2: +24.0 V 6A	2. Values																																							
1. Graph	<table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 85V)</th> <th>Ripple-Noise [mV] (Input Volt. 132V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>50</td><td>50</td></tr> <tr><td>1.2</td><td>60</td><td>60</td></tr> <tr><td>2.4</td><td>65</td><td>65</td></tr> <tr><td>3.6</td><td>75</td><td>75</td></tr> <tr><td>4.8</td><td>80</td><td>80</td></tr> <tr><td>6.0</td><td>95</td><td>95</td></tr> <tr><td>6.6</td><td>95</td><td>95</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV] (Input Volt. 85V)	Ripple-Noise [mV] (Input Volt. 132V)	0.0	50	50	1.2	60	60	2.4	65	65	3.6	75	75	4.8	80	80	6.0	95	95	6.6	95	95														
Load Current [A]	Ripple-Noise [mV] (Input Volt. 85V)	Ripple-Noise [mV] (Input Volt. 132V)																																							
0.0	50	50																																							
1.2	60	60																																							
2.4	65	65																																							
3.6	75	75																																							
4.8	80	80																																							
6.0	95	95																																							
6.6	95	95																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>50</td><td>50</td></tr> <tr><td>1.2</td><td>60</td><td>60</td></tr> <tr><td>2.4</td><td>65</td><td>65</td></tr> <tr><td>3.6</td><td>75</td><td>75</td></tr> <tr><td>4.8</td><td>80</td><td>80</td></tr> <tr><td>6.0</td><td>95</td><td>95</td></tr> <tr><td>6.6</td><td>95</td><td>95</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	50	50	1.2	60	60	2.4	65	65	3.6	75	75	4.8	80	80	6.0	95	95	6.6	95	95	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.0	50	50																																							
1.2	60	60																																							
2.4	65	65																																							
3.6	75	75																																							
4.8	80	80																																							
6.0	95	95																																							
6.6	95	95																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
3. Definition	<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																								
4. Waveform	<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL


Model	LEB150F-0524	Temperature 25°C Testing Circuitry Figure A																																																									
Item	Overcurrent Protection 過電流保護																																																										
Object	V1: +5.0V5A																																																										
1. Graph	<p>[V] Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>6.99</td><td>7.09</td><td>7.18</td></tr> <tr><td>4.75</td><td>6.86</td><td>6.95</td><td>7.04</td></tr> <tr><td>4.50</td><td>6.73</td><td>6.81</td><td>6.90</td></tr> <tr><td>4.00</td><td>6.43</td><td>6.50</td><td>6.57</td></tr> <tr><td>3.50</td><td>6.12</td><td>6.18</td><td>6.25</td></tr> <tr><td>3.00</td><td>5.77</td><td>5.82</td><td>5.88</td></tr> <tr><td>2.50</td><td>5.39</td><td>5.44</td><td>5.49</td></tr> <tr><td>2.00</td><td>4.99</td><td>5.04</td><td>5.08</td></tr> <tr><td>1.50</td><td>4.58</td><td>4.62</td><td>4.66</td></tr> <tr><td>1.00</td><td>4.12</td><td>4.15</td><td>4.19</td></tr> <tr><td>0.50</td><td>3.62</td><td>3.66</td><td>3.70</td></tr> <tr><td>0.00</td><td>5.54</td><td>5.66</td><td>5.78</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	5.00	6.99	7.09	7.18	4.75	6.86	6.95	7.04	4.50	6.73	6.81	6.90	4.00	6.43	6.50	6.57	3.50	6.12	6.18	6.25	3.00	5.77	5.82	5.88	2.50	5.39	5.44	5.49	2.00	4.99	5.04	5.08	1.50	4.58	4.62	4.66	1.00	4.12	4.15	4.19	0.50	3.62	3.66	3.70	0.00	5.54	5.66	5.78
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
5.00	6.99	7.09	7.18																																																								
4.75	6.86	6.95	7.04																																																								
4.50	6.73	6.81	6.90																																																								
4.00	6.43	6.50	6.57																																																								
3.50	6.12	6.18	6.25																																																								
3.00	5.77	5.82	5.88																																																								
2.50	5.39	5.44	5.49																																																								
2.00	4.99	5.04	5.08																																																								
1.50	4.58	4.62	4.66																																																								
1.00	4.12	4.15	4.19																																																								
0.50	3.62	3.66	3.70																																																								
0.00	5.54	5.66	5.78																																																								
Object	V2: +24.0V6A	<p>1. Graph</p> <p>[V] Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 16.8V to 0V.</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>24.00</td><td>12.08</td><td>12.36</td><td>12.84</td></tr> <tr><td>22.80</td><td>12.54</td><td>12.79</td><td>12.88</td></tr> <tr><td>21.60</td><td>12.73</td><td>12.88</td><td>12.94</td></tr> <tr><td>19.20</td><td>12.97</td><td>13.02</td><td>13.01</td></tr> <tr><td>16.80</td><td>13.05</td><td>13.07</td><td>13.07</td></tr> <tr><td>14.40</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>12.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>9.60</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>7.20</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>4.80</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>2.40</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	24.00	12.08	12.36	12.84	22.80	12.54	12.79	12.88	21.60	12.73	12.88	12.94	19.20	12.97	13.02	13.01	16.80	13.05	13.07	13.07	14.40	—	—	—	12.00	—	—	—	9.60	—	—	—	7.20	—	—	—	4.80	—	—	—	2.40	—	—	—	0.00	—	—	—
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
24.00	12.08	12.36	12.84																																																								
22.80	12.54	12.79	12.88																																																								
21.60	12.73	12.88	12.94																																																								
19.20	12.97	13.02	13.01																																																								
16.80	13.05	13.07	13.07																																																								
14.40	—	—	—																																																								
12.00	—	—	—																																																								
9.60	—	—	—																																																								
7.20	—	—	—																																																								
4.80	—	—	—																																																								
2.40	—	—	—																																																								
0.00	—	—	—																																																								

COSEL

Model	LEB150F-0524																																																					
Item	Overvoltage Protection 過電圧保護																																																					
Object	V2: +24.0 V 6A																																																					
Testing Circuitry Figure A																																																						
1. Graph	<p style="text-align: center;"> Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V </p>  <p style="text-align: center;">Operating Point [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>29.7</td><td>29.6</td><td>29.6</td></tr> <tr><td>-10</td><td>29.8</td><td>29.8</td><td>29.7</td></tr> <tr><td>0</td><td>30.1</td><td>30.0</td><td>30.0</td></tr> <tr><td>10</td><td>30.3</td><td>30.2</td><td>30.2</td></tr> <tr><td>20</td><td>30.5</td><td>30.4</td><td>30.4</td></tr> <tr><td>25</td><td>30.6</td><td>30.5</td><td>30.5</td></tr> <tr><td>35</td><td>30.8</td><td>30.8</td><td>30.7</td></tr> <tr><td>45</td><td>30.9</td><td>30.9</td><td>31.0</td></tr> <tr><td>55</td><td>31.2</td><td>31.2</td><td>31.1</td></tr> <tr><td>70</td><td>31.5</td><td>31.5</td><td>31.5</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	29.7	29.6	29.6	-10	29.8	29.8	29.7	0	30.1	30.0	30.0	10	30.3	30.2	30.2	20	30.5	30.4	30.4	25	30.6	30.5	30.5	35	30.8	30.8	30.7	45	30.9	30.9	31.0	55	31.2	31.2	31.1	70	31.5	31.5	31.5	—	—	—	—
Ambient Temperature [°C]	Operating Point [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	29.7	29.6	29.6																																																			
-10	29.8	29.8	29.7																																																			
0	30.1	30.0	30.0																																																			
10	30.3	30.2	30.2																																																			
20	30.5	30.4	30.4																																																			
25	30.6	30.5	30.5																																																			
35	30.8	30.8	30.7																																																			
45	30.9	30.9	31.0																																																			
55	31.2	31.2	31.1																																																			
70	31.5	31.5	31.5																																																			
—	—	—	—																																																			

COSEL


Model	LEB150F-0524	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	<hr/>		





Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current

① 12.70 [A]

② 9.50 [A]



COSEL


COSEL

COSEL

Model	LEB150F-0524
Item	Rise and Fall Time 立上り、立下り時間
Object	_____


Temperature 25°C
Testing Circuitry Figure ALoad Power 100 %
Input Volt. 100 V


1. Graph



2. Values

Output	Time	T d	T r	T s	T h	T f	[mS]
V1		29.0	11.5	40.5	72.0	83.8	
V2		350.0	13.0	363.0	26.5	25.8	
-		-	-	-	-	-	
-		-	-	-	-	-	



COSEL

COSEL

Model	LEB150F-0524	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	V1:+5.0V5A																																																						
1. Graph																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>5.037</td><td>5.037</td><td>5.037</td></tr> <tr><td>-10</td><td>5.040</td><td>5.040</td><td>5.040</td></tr> <tr><td>0</td><td>5.041</td><td>5.042</td><td>5.042</td></tr> <tr><td>10</td><td>5.043</td><td>5.043</td><td>5.044</td></tr> <tr><td>20</td><td>5.046</td><td>5.046</td><td>5.046</td></tr> <tr><td>25</td><td>5.048</td><td>5.049</td><td>5.048</td></tr> <tr><td>35</td><td>5.051</td><td>5.050</td><td>5.051</td></tr> <tr><td>45</td><td>5.050</td><td>5.049</td><td>5.050</td></tr> <tr><td>55</td><td>5.049</td><td>5.049</td><td>5.049</td></tr> <tr><td>70</td><td>5.047</td><td>5.047</td><td>5.047</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	5.037	5.037	5.037	-10	5.040	5.040	5.040	0	5.041	5.042	5.042	10	5.043	5.043	5.044	20	5.046	5.046	5.046	25	5.048	5.049	5.048	35	5.051	5.050	5.051	45	5.050	5.049	5.050	55	5.049	5.049	5.049	70	5.047	5.047	5.047	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
-20	5.037	5.037	5.037																																																				
-10	5.040	5.040	5.040																																																				
0	5.041	5.042	5.042																																																				
10	5.043	5.043	5.044																																																				
20	5.046	5.046	5.046																																																				
25	5.048	5.049	5.048																																																				
35	5.051	5.050	5.051																																																				
45	5.050	5.049	5.050																																																				
55	5.049	5.049	5.049																																																				
70	5.047	5.047	5.047																																																				
—	—	—	—																																																				
Object	V2:+24.0V6A																																																						
1. Graph																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>23.967</td><td>23.968</td><td>23.968</td></tr> <tr><td>-10</td><td>23.978</td><td>23.979</td><td>23.979</td></tr> <tr><td>0</td><td>23.988</td><td>23.988</td><td>23.989</td></tr> <tr><td>10</td><td>23.999</td><td>23.999</td><td>24.000</td></tr> <tr><td>20</td><td>24.010</td><td>24.011</td><td>24.011</td></tr> <tr><td>25</td><td>24.018</td><td>24.018</td><td>24.019</td></tr> <tr><td>35</td><td>24.023</td><td>24.023</td><td>24.024</td></tr> <tr><td>45</td><td>24.026</td><td>24.026</td><td>24.026</td></tr> <tr><td>55</td><td>24.023</td><td>24.023</td><td>24.024</td></tr> <tr><td>70</td><td>24.020</td><td>24.020</td><td>24.021</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	23.967	23.968	23.968	-10	23.978	23.979	23.979	0	23.988	23.988	23.989	10	23.999	23.999	24.000	20	24.010	24.011	24.011	25	24.018	24.018	24.019	35	24.023	24.023	24.024	45	24.026	24.026	24.026	55	24.023	24.023	24.024	70	24.020	24.020	24.021	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
-20	23.967	23.968	23.968																																																				
-10	23.978	23.979	23.979																																																				
0	23.988	23.988	23.989																																																				
10	23.999	23.999	24.000																																																				
20	24.010	24.011	24.011																																																				
25	24.018	24.018	24.019																																																				
35	24.023	24.023	24.024																																																				
45	24.026	24.026	24.026																																																				
55	24.023	24.023	24.024																																																				
70	24.020	24.020	24.021																																																				
—	—	—	—																																																				
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																																							



COSEL

Model	LEB150F-0524																																								
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	Testing Circuitry	Figure A																																						
Object	V1:+5.0V5A																																								
1. Graph	<p style="text-align: center;">□ Load 50% △ Load 100%</p>	2. Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>56</td><td>74</td></tr> <tr><td>-10</td><td>56</td><td>74</td></tr> <tr><td>0</td><td>56</td><td>75</td></tr> <tr><td>10</td><td>56</td><td>75</td></tr> <tr><td>20</td><td>56</td><td>75</td></tr> <tr><td>25</td><td>56</td><td>75</td></tr> <tr><td>35</td><td>55</td><td>75</td></tr> <tr><td>45</td><td>55</td><td>75</td></tr> <tr><td>55</td><td>56</td><td>75</td></tr> <tr><td>70</td><td>57</td><td>75</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	56	74	-10	56	74	0	56	75	10	56	75	20	56	75	25	56	75	35	55	75	45	55	75	55	56	75	70	57	75	—	—	—	
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	56	74																																							
-10	56	74																																							
0	56	75																																							
10	56	75																																							
20	56	75																																							
25	56	75																																							
35	55	75																																							
45	55	75																																							
55	56	75																																							
70	57	75																																							
—	—	—																																							
Object	V2:+24.0V6A	2. Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>73</td><td>74</td></tr> <tr><td>-10</td><td>73</td><td>74</td></tr> <tr><td>0</td><td>74</td><td>74</td></tr> <tr><td>10</td><td>74</td><td>75</td></tr> <tr><td>20</td><td>74</td><td>75</td></tr> <tr><td>25</td><td>74</td><td>75</td></tr> <tr><td>35</td><td>74</td><td>75</td></tr> <tr><td>45</td><td>74</td><td>75</td></tr> <tr><td>55</td><td>74</td><td>75</td></tr> <tr><td>70</td><td>74</td><td>75</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	73	74	-10	73	74	0	74	74	10	74	75	20	74	75	25	74	75	35	74	75	45	74	75	55	74	75	70	74	75	—	—	—	
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	73	74																																							
-10	73	74																																							
0	74	74																																							
10	74	75																																							
20	74	75																																							
25	74	75																																							
35	74	75																																							
45	74	75																																							
55	74	75																																							
70	74	75																																							
—	—	—																																							
		<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																							

COSEL

Model	LEB150F-0524																																								
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A																																							
Object	V1: +5.0V5A																																								
1. Graph																																									
		----- □ ----- Load 50%	----- △ ----- Load 100%																																						
		[mV]	[°C]																																						
<p>Input Volt. 100 V</p>																																									
2. Values																																									
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>35</td><td>45</td></tr> <tr><td>-10</td><td>25</td><td>35</td></tr> <tr><td>0</td><td>20</td><td>25</td></tr> <tr><td>10</td><td>15</td><td>20</td></tr> <tr><td>20</td><td>10</td><td>15</td></tr> <tr><td>25</td><td>10</td><td>15</td></tr> <tr><td>35</td><td>10</td><td>15</td></tr> <tr><td>45</td><td>10</td><td>15</td></tr> <tr><td>55</td><td>10</td><td>15</td></tr> <tr><td>70</td><td>10</td><td>15</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Ripple Output Voltage [mV]		Load 50%	Load 100%	-20	35	45	-10	25	35	0	20	25	10	15	20	20	10	15	25	10	15	35	10	15	45	10	15	55	10	15	70	10	15	—	—	—
Ambient Temperature [°C]	Ripple Output Voltage [mV]																																								
	Load 50%	Load 100%																																							
-20	35	45																																							
-10	25	35																																							
0	20	25																																							
10	15	20																																							
20	10	15																																							
25	10	15																																							
35	10	15																																							
45	10	15																																							
55	10	15																																							
70	10	15																																							
—	—	—																																							
1. Graph																																									
		----- □ ----- Load 50%	----- △ ----- Load 100%																																						
		[mV]	[°C]																																						
<p>Input Volt. 100 V</p>																																									
2. Values																																									
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>80</td><td>90</td></tr> <tr><td>-10</td><td>60</td><td>70</td></tr> <tr><td>0</td><td>45</td><td>50</td></tr> <tr><td>10</td><td>45</td><td>50</td></tr> <tr><td>20</td><td>40</td><td>45</td></tr> <tr><td>25</td><td>40</td><td>45</td></tr> <tr><td>35</td><td>40</td><td>45</td></tr> <tr><td>45</td><td>35</td><td>40</td></tr> <tr><td>55</td><td>30</td><td>35</td></tr> <tr><td>70</td><td>30</td><td>35</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Ripple Output Voltage [mV]		Load 50%	Load 100%	-20	80	90	-10	60	70	0	45	50	10	45	50	20	40	45	25	40	45	35	40	45	45	35	40	55	30	35	70	30	35	—	—	—
Ambient Temperature [°C]	Ripple Output Voltage [mV]																																								
	Load 50%	Load 100%																																							
-20	80	90																																							
-10	60	70																																							
0	45	50																																							
10	45	50																																							
20	40	45																																							
25	40	45																																							
35	40	45																																							
45	35	40																																							
55	30	35																																							
70	30	35																																							
—	—	—																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									
(注)斜線は定格周囲温度範囲を示す。																																									

COSEL

Model	LEB150F-0524	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	V1:+5.0V5A																								
1. Graph			2. Values																						
 <p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.049</td></tr> <tr><td>0.5</td><td>5.048</td></tr> <tr><td>1.0</td><td>5.048</td></tr> <tr><td>2.0</td><td>5.048</td></tr> <tr><td>3.0</td><td>5.048</td></tr> <tr><td>4.0</td><td>5.049</td></tr> <tr><td>5.0</td><td>5.049</td></tr> <tr><td>6.0</td><td>5.049</td></tr> <tr><td>7.0</td><td>5.049</td></tr> <tr><td>8.0</td><td>5.049</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.049	0.5	5.048	1.0	5.048	2.0	5.048	3.0	5.048	4.0	5.049	5.0	5.049	6.0	5.049	7.0	5.049	8.0	5.049
Time since start [H]	Output Voltage [V]																								
0.0	5.049																								
0.5	5.048																								
1.0	5.048																								
2.0	5.048																								
3.0	5.048																								
4.0	5.049																								
5.0	5.049																								
6.0	5.049																								
7.0	5.049																								
8.0	5.049																								
Object			2. Values																						
 <p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>23.999</td></tr> <tr><td>0.5</td><td>24.015</td></tr> <tr><td>1.0</td><td>24.016</td></tr> <tr><td>2.0</td><td>24.017</td></tr> <tr><td>3.0</td><td>24.017</td></tr> <tr><td>4.0</td><td>24.018</td></tr> <tr><td>5.0</td><td>24.018</td></tr> <tr><td>6.0</td><td>24.018</td></tr> <tr><td>7.0</td><td>24.019</td></tr> <tr><td>8.0</td><td>24.019</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	23.999	0.5	24.015	1.0	24.016	2.0	24.017	3.0	24.017	4.0	24.018	5.0	24.018	6.0	24.018	7.0	24.019	8.0	24.019
Time since start [H]	Output Voltage [V]																								
0.0	23.999																								
0.5	24.015																								
1.0	24.016																								
2.0	24.017																								
3.0	24.017																								
4.0	24.018																								
5.0	24.018																								
6.0	24.018																								
7.0	24.019																								
8.0	24.019																								



Model	LEB150F-0524	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~45 °C

Input Voltage : 85~132 V

Load Current (V1) : 0~5 A

(V2) : 0~6 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage)/2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~45 °C

入力電圧 85~132 V

負荷電流 (V1) 0~5 A

(V2) 0~6 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値)/2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$


2. Values

Object	V1:+5.0V5A	<table border="1"> <thead> <tr> <th>Item</th><th>Temperature [°C]</th><th>Input Voltage [V]</th><th>Output Current [A]</th><th>Output Voltage [V]</th><th>Output Voltage Accuracy [mV]</th><th>Output Voltage Accuracy(Ration) [%]</th></tr> </thead> <tbody> <tr> <td>Maximum Voltage</td><td>45</td><td>132</td><td>0</td><td>5.076</td><td rowspan="2">±18</td><td rowspan="2">±0.4</td></tr> <tr> <td>Minimum Voltage</td><td>-10</td><td>100</td><td>5</td><td>5.041</td></tr> </tbody> </table>	Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]	Maximum Voltage	45	132	0	5.076	±18	±0.4	Minimum Voltage	-10	100	5	5.041
Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]															
Maximum Voltage	45	132	0	5.076	±18	±0.4															
Minimum Voltage	-10	100	5	5.041																	
Object	V2:+24.0V6A																				
<table border="1"> <thead> <tr> <th>Item</th><th>Temperature [°C]</th><th>Input Voltage [V]</th><th>Output Current [A]</th><th>Output Voltage [V]</th><th>Output Voltage Accuracy [mV]</th><th>Output Voltage Accuracy(Ration) [%]</th></tr> </thead> <tbody> <tr> <td>Maximum Voltage</td><td>25</td><td>85</td><td>0</td><td>24.046</td><td rowspan="2">±34</td><td rowspan="2">±0.2</td></tr> <tr> <td>Minimum Voltage</td><td>-10</td><td>85</td><td>6</td><td>23.978</td></tr> </tbody> </table>		Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]	Maximum Voltage	25	85	0	24.046	±34	±0.2	Minimum Voltage	-10	85	6	23.978	
Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]															
Maximum Voltage	25	85	0	24.046	±34	±0.2															
Minimum Voltage	-10	85	6	23.978																	

COSEL


Model	LEB150F-0524	Temperature	25°C
Item	Harmonic Current 高調波電流	Testing Circuitry	Figure E
Object	—		

1. Input Current Waveform



Conditions	Values
Input Voltage [V]	99.6
Input Current [A]	1.946
Active Power [W]	191.7
Apparent Power [VA]	193.9
Frequency [Hz]	60
Power Factor	0.989
Output Power [W]	150

2. Harmonic Current




Harmonics order 高調波次数	Limits 限度値 [A]	Values 測定値 [A]
1	—	1.92300
2	—	0.00400
3	5.31124	0.24200
4	—	0.00200
5	2.63253	0.13800
6	—	0.00100
7	1.77811	0.06900
8	—	0.00100
9	0.92369	0.03000
10	—	0.00100
11	0.76205	0.00900
12	—	0.00100
13	0.48494	0.01100
14	—	0.00100
15	0.34639	0.01900
16	—	0.00100
17	0.30563	0.01600
18	—	0.00000
19	0.27346	0.01000
20	—	0.00000
21	0.24742	0.00700
22	—	0.00000
23	0.22590	0.00700
24	—	0.00000
25	0.20783	0.01000
26	—	0.00100
27	0.19244	0.01000
28	—	0.00000
29	0.17916	0.00700
30	—	0.00100
31	0.16761	0.00400
32	—	0.00000
33	0.15745	0.00300
34	—	0.00000
35	0.14845	0.00200
36	—	0.00100
37	0.14043	0.00200
38	—	0.00000
39	0.13323	0.00200
40	—	0.00100

COSEL


Model	LEB150F-0524	Temperature Testing Circuitry	25°C Figure E
Item	Harmonic Current 高調波電流		
Object	—		

1. Input Current Waveform



Conditions	Values
Input Voltage [V]	100
Input Current [A]	1.014
Active Power [W]	97.9
Apparent Power [VA]	101.5
Frequency [Hz]	60
Power Factor	0.965
Output Power [W]	75

2. Harmonic Current



Harmonics order 高調波次数	Limits 限度値 [A]	Values 測定値 [A]
1	—	0.98200
2	—	0.00200
3	5.29000	0.23100
4	—	0.00000
5	2.62200	0.09200
6	—	0.00100
7	1.77100	0.01500
8	—	0.00000
9	0.92000	0.01700
10	—	0.00000
11	0.75900	0.01500
12	—	0.00100
13	0.48300	0.00400
14	—	0.00100
15	0.34500	0.00700
16	—	0.00100
17	0.30441	0.01100
18	—	0.00000
19	0.27237	0.00800
20	—	0.00000
21	0.24643	0.00600
22	—	0.00000
23	0.22500	0.00800
24	—	0.00000
25	0.20700	0.00800
26	—	0.00100
27	0.19167	0.00500
28	—	0.00100
29	0.17845	0.00400
30	—	0.00100
31	0.16694	0.00400
32	—	0.00000
33	0.15682	0.00400
34	—	0.00000
35	0.14786	0.00200
36	—	0.00000
37	0.13986	0.00100
38	—	0.00000
39	0.13269	0.00100
40	—	0.00000

COSEL

Model	LEB150F-0524	Temperature	25°C																																																			
Item	Oscillator Frequency 発振周波数	Testing Circuitry	Figure A																																																			
Object	V1:+5.0V5A																																																					
1. Graph																																																						
<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V 			2. Values																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Oscillator Frequency [KHz]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.8</td><td>368</td><td>370</td><td>371</td></tr> <tr><td>1.6</td><td>263</td><td>264</td><td>265</td></tr> <tr><td>2.4</td><td>202</td><td>204</td><td>204</td></tr> <tr><td>3.2</td><td>161</td><td>164</td><td>165</td></tr> <tr><td>4.0</td><td>134</td><td>138</td><td>139</td></tr> <tr><td>4.8</td><td>116</td><td>118</td><td>118</td></tr> <tr><td>5.0</td><td>113</td><td>115</td><td>116</td></tr> <tr><td>5.5</td><td>104</td><td>106</td><td>107</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Oscillator Frequency [KHz]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.8	368	370	371	1.6	263	264	265	2.4	202	204	204	3.2	161	164	165	4.0	134	138	139	4.8	116	118	118	5.0	113	115	116	5.5	104	106	107	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Oscillator Frequency [KHz]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.8	368	370	371																																																			
1.6	263	264	265																																																			
2.4	202	204	204																																																			
3.2	161	164	165																																																			
4.0	134	138	139																																																			
4.8	116	118	118																																																			
5.0	113	115	116																																																			
5.5	104	106	107																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																						



Model	LEB150F-0524	Testing Circuitry Figure A
Item	Condensation 結露特性	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Object	V1:+5.0V5A	
Item	Data	Testing Conditions
Output Voltage [V]	5.114	Input Volt.: 100V, Load Current:5A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:5A
Load Regulation [mV]	23	Input Volt.: 100V, Load Current:0~5A

Object	V2:+24.0V6A	
Item	Data	Testing Conditions
Output Voltage [V]	24.069	Input Volt.: 100V, Load Current:6A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:6A
Load Regulation [mV]	19	Input Volt.: 100V, Load Current:0~6A



Model	LEB150F-0524	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
85 [V]	100 [V]	132 [V]	
(A) DENTORI	0.15	0.18	0.24
(B) IEC60950	0.15	0.18	0.24

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
170 [V]	230 [V]	264 [V]	
(B) IEC60950	—	—	—



Model	LEB150F-0524	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure C
Object	V1:+5.0V5A		

1. Results

Conditions

Input Voltage : 100 V Pulse Input Duration: 1 min. or more
 Pulse Voltage : 2000 V Load : 100 %
 Pulse Cycle : 10 mS

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY		
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

Object	V2:+24.0V6A
--------	-------------

1. Results

Conditions

Input Voltage : 100 V Pulse Input Duration: 1 min. or more
 Pulse Voltage : 2000 V Load : 100 %
 Pulse Cycle : 10 mS

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY		
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

COSEL

Model	LEB150F-0524	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	_____		

1. Graph

Remarks


Input Volt. 100 V (VCCI Class B)

120 V (FCC Class B)


Load 100 %

Limit1: [VCCI] Class B(QP)

Limit2: [VCCI] Class B(Ave.)



Limit1: [FCC Part15] Class B



COSEL





Figure B (DENTORI)




Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E