

DATA SHEET			Date	Mar.23,2000
Model	LEB150F-0524		Temp.	25 °C
Test	Vibration/impact test 振動・衝撃試験		Humid.	45 %Rh
			Tested by	T.Ohara

- Method
Vibration/impact test complies with JIS C 0911 (Vibration), JIS C 0912 (Impact)
JIS C 0911 (振動), JIS C 0912 (衝撃) に準ずる
- Conditions
 - Frequency : 10~150 Hz
(Vibration) 3 minutes period
周波数 (振動)
 - Direction・Time : 60 minutes along X, Y and Z axis (Vibration)
方向・時間 11mS, once each X, Y and Z axis (Impact)
- Conditions of Acceptability
 - No degradation of performance or loss of function after test.
試験後、諸機能が正常であること
 - No remakably damage of appearance.
外観上著しい損傷がないこと
 - No looseness or a crack at solder joint.
はんだ付け、圧着など電氣的接合部分にクラックや緩みの発生がないこと
- Result
 - Vibration limit test

No.	Gravity [G]	Result	Note
1	3	OK	
2	—	—	
3	—	—	

All are satisfactory to item 3: OK
 - Impact test

No.	Gravity [G]	Result	Note
1	30	OK	
2	—	—	
3	—	—	

All are satisfactory to item 3: OK