

TEST DATA OF LEP150F-36

(AC100V INPUT)

Regulated DC Power Supply
Apr. 16. 2003

Approved by : D. Ishibashi Design Manager
D. ishibashi

Prepared by : M. Hamaguchi Design Engineer
M. hamaguchi

コーセル株式会社
COSEL CO.,LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Current)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	9
瞬時停電保障	
10. Load Regulation	10
静的負荷変動	
11. Ripple Voltage (by Load Current)	11
リップル電圧 (負荷特性)	
12. Ripple-Noise	12
リップルノイズ	
13. Overcurrent Protection	13
過電流保護	
14. Overvoltage Protection	14
過電圧保護	
15. Inrush Current	15
突入電流	
16. Dynamic Load Response	16
動的負荷変動	
17. Rise and Fall Time	17
立上り、立下り時間	
18. Ambient Temperature Drift	18
周囲温度変動	
19. Minimum Input Voltage for Regulated Output Voltage	19
最低レギュレーション電圧	
20. Ripple Voltage (by Ambient Temperature)	20
リップル電圧 (周囲温度特性)	
21. Time Lapse Drift	21
経時ドリフト	
22. Output Voltage Accuracy	22
定電圧精度	
23. Harmonic Current	23
高調波電流	
24. Leakage Current	25
漏洩電流	
25. Line Noise Tolerance	26
入力雑音耐量	
26. Conducted Emission	27
雑音端子電圧	
27. Figure of Testing Circuitry	28
測定回路図	

(Final Page 29)


COSEL

Model	LEP150F-36																																		
Item	Line Regulation 静の入力変動	Temperature	25℃																																
Object	+36V4.2A	Testing Circuitry	Figure A																																
1. Graph		2. Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>75</td><td>35.993</td><td>35.991</td></tr><tr><td>80</td><td>35.993</td><td>35.992</td></tr><tr><td>85</td><td>35.993</td><td>35.992</td></tr><tr><td>90</td><td>35.993</td><td>35.992</td></tr><tr><td>100</td><td>35.993</td><td>35.992</td></tr><tr><td>110</td><td>35.993</td><td>35.992</td></tr><tr><td>120</td><td>35.993</td><td>35.992</td></tr><tr><td>132</td><td>35.993</td><td>35.992</td></tr><tr><td>140</td><td>35.993</td><td>35.992</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	35.993	35.991	80	35.993	35.992	85	35.993	35.992	90	35.993	35.992	100	35.993	35.992	110	35.993	35.992	120	35.993	35.992	132	35.993	35.992	140	35.993	35.992		
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	35.993	35.991																																	
80	35.993	35.992																																	
85	35.993	35.992																																	
90	35.993	35.992																																	
100	35.993	35.992																																	
110	35.993	35.992																																	
120	35.993	35.992																																	
132	35.993	35.992																																	
140	35.993	35.992																																	

COSEL

Model		LEP150F-36		Temperature		25℃																																																				
Item		Input Current (by Load Current) 入力電流 (負荷特性)		Testing Circuitry		Figure A																																																				
Object																																																										
1. Graph				2. Values																																																						
<div><div><div>—△—</div><div>Input Volt. 85V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 132V</div></div></div> <p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.00</td><td>0.113</td><td>0.107</td><td>0.101</td></tr><tr><td>0.80</td><td>0.497</td><td>0.424</td><td>0.337</td></tr><tr><td>1.60</td><td>0.889</td><td>0.754</td><td>0.573</td></tr><tr><td>2.40</td><td>1.278</td><td>1.085</td><td>0.820</td></tr><tr><td>3.20</td><td>1.680</td><td>1.419</td><td>1.068</td></tr><tr><td>4.00</td><td>2.080</td><td>1.755</td><td>1.316</td></tr><tr><td>4.20</td><td>2.182</td><td>1.838</td><td>1.373</td></tr><tr><td>4.62</td><td>2.394</td><td>2.014</td><td>1.514</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>				Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.113	0.107	0.101	0.80	0.497	0.424	0.337	1.60	0.889	0.754	0.573	2.40	1.278	1.085	0.820	3.20	1.680	1.419	1.068	4.00	2.080	1.755	1.316	4.20	2.182	1.838	1.373	4.62	2.394	2.014	1.514	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	0.113	0.107	0.101																																																							
0.80	0.497	0.424	0.337																																																							
1.60	0.889	0.754	0.573																																																							
2.40	1.278	1.085	0.820																																																							
3.20	1.680	1.419	1.068																																																							
4.00	2.080	1.755	1.316																																																							
4.20	2.182	1.838	1.373																																																							
4.62	2.394	2.014	1.514																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							

COSEL

Model		LEP150F-36		Temperature25℃ Testing CircuitryFigure A																																																				
Item		Input Power (by Load Current) 入力電力（負荷特性）																																																						
Object		_____																																																						
1. Graph		<div>—△— Input Volt. 85V ---□--- Input Volt. 100V -·-○-·- Input Volt. 132V</div> 		2. Values																																																				
				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.00</td><td>7.7</td><td>7.8</td><td>7.9</td></tr><tr><td>0.80</td><td>40.5</td><td>40.1</td><td>40.1</td></tr><tr><td>1.60</td><td>73.1</td><td>72.5</td><td>71.9</td></tr><tr><td>2.40</td><td>105.7</td><td>105.0</td><td>103.9</td></tr><tr><td>3.20</td><td>139.2</td><td>137.8</td><td>136.2</td></tr><tr><td>4.00</td><td>172.8</td><td>171.3</td><td>168.6</td></tr><tr><td>4.20</td><td>181.2</td><td>179.4</td><td>176.7</td></tr><tr><td>4.62</td><td>198.9</td><td>197.1</td><td>194.4</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr></table>		Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	7.7	7.8	7.9	0.80	40.5	40.1	40.1	1.60	73.1	72.5	71.9	2.40	105.7	105.0	103.9	3.20	139.2	137.8	136.2	4.00	172.8	171.3	168.6	4.20	181.2	179.4	176.7	4.62	198.9	197.1	194.4	--	—	—	—	--	—	—	—	--	—	—	—
Load Current [A]	Input Power [W]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0.00	7.7	7.8	7.9																																																					
0.80	40.5	40.1	40.1																																																					
1.60	73.1	72.5	71.9																																																					
2.40	105.7	105.0	103.9																																																					
3.20	139.2	137.8	136.2																																																					
4.00	172.8	171.3	168.6																																																					
4.20	181.2	179.4	176.7																																																					
4.62	198.9	197.1	194.4																																																					
--	—	—	—																																																					
--	—	—	—																																																					
--	—	—	—																																																					
Note: Slanted line shows the range of the rated load current.																																																								
(注) 斜線は定格負荷電流範囲を示す。																																																								

COSEL

Model		LEP150F-36	
Item		Efficiency (by Input Voltage) 効率（入力電圧特性）	
Object			
1. Graph		2. Values	

Efficiency [%]

---□--- Load 50%

—△— Load 100%

86

82

78

74

70

66

62

58

70

90

110

130

150

Input Voltage [V]

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	78.3	80.9
80	78.6	81.7
85	78.7	82.1
90	79.1	82.5
100	79.3	83.0
110	79.7	83.6
120	80.0	83.9
132	80.2	84.3
140	80.3	84.5

COSEL

Model		LEP150F-36		Temperature		25℃																																																				
Item		Efficiency (by Load Current) 効率 (負荷特性)		Testing Circuitry		Figure A																																																				
Object																																																										
1. Graph				2. Values																																																						
<div><div><div>—△—</div><div>Input Volt. 85V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 132V</div></div></div> <table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr></thead><tbody><tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr><tr><td>0.80</td><td>66.2</td><td>66.9</td><td>67.0</td></tr><tr><td>1.60</td><td>75.9</td><td>76.6</td><td>77.2</td></tr><tr><td>2.40</td><td>79.7</td><td>80.3</td><td>81.1</td></tr><tr><td>3.20</td><td>81.1</td><td>81.9</td><td>82.9</td></tr><tr><td>4.00</td><td>82.0</td><td>82.7</td><td>84.0</td></tr><tr><td>4.20</td><td>82.1</td><td>83.0</td><td>84.2</td></tr><tr><td>4.62</td><td>82.4</td><td>83.1</td><td>84.3</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>				Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.80	66.2	66.9	67.0	1.60	75.9	76.6	77.2	2.40	79.7	80.3	81.1	3.20	81.1	81.9	82.9	4.00	82.0	82.7	84.0	4.20	82.1	83.0	84.2	4.62	82.4	83.1	84.3	--	—	—	—	--	—	—	—	--	—	—	—				
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	—	—	—																																																							
0.80	66.2	66.9	67.0																																																							
1.60	75.9	76.6	77.2																																																							
2.40	79.7	80.3	81.1																																																							
3.20	81.1	81.9	82.9																																																							
4.00	82.0	82.7	84.0																																																							
4.20	82.1	83.0	84.2																																																							
4.62	82.4	83.1	84.3																																																							
--	—	—	—																																																							
--	—	—	—																																																							
--	—	—	—																																																							

COSEL

Model		LEP150F-36	
Item		Power Factor (by Input Voltage) 力率（入力電圧特性）	
Object			

1. Graph

□

Load 50%

△

Load 100%

Power Factor

1.0

0.9

0.8

0.7

0.6

0.5

0.4

70

90


110

130

150


Input Voltage [V]

COSEL

Model		LEP150F-36		Temperature		25℃																																																				
Item		Power Factor (by Load Current) 力率（負荷特性）		Testing Circuitry		Figure A																																																				
Object																																																										
1. Graph				2. Values																																																						
<div><div><div>—△—</div><div>Input Volt. 85V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 132V</div></div></div>  <div>Power Factor</div> <div>Load Current [A]</div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Power Factor</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.00</td><td>0.801</td><td>0.725</td><td>0.589</td></tr><tr><td>0.80</td><td>0.960</td><td>0.946</td><td>0.904</td></tr><tr><td>1.60</td><td>0.967</td><td>0.962</td><td>0.949</td></tr><tr><td>2.40</td><td>0.973</td><td>0.969</td><td>0.960</td></tr><tr><td>3.20</td><td>0.975</td><td>0.972</td><td>0.967</td></tr><tr><td>4.00</td><td>0.978</td><td>0.978</td><td>0.971</td></tr><tr><td>4.20</td><td>0.978</td><td>0.978</td><td>0.973</td></tr><tr><td>4.62</td><td>0.978</td><td>0.977</td><td>0.973</td></tr><tr><td>---</td><td>—</td><td>—</td><td>—</td></tr><tr><td>---</td><td>—</td><td>—</td><td>—</td></tr><tr><td>---</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.801	0.725	0.589	0.80	0.960	0.946	0.904	1.60	0.967	0.962	0.949	2.40	0.973	0.969	0.960	3.20	0.975	0.972	0.967	4.00	0.978	0.978	0.971	4.20	0.978	0.978	0.973	4.62	0.978	0.977	0.973	---	—	—	—	---	—	—	—	---	—	—	—
Load Current [A]	Power Factor																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	0.801	0.725	0.589																																																							
0.80	0.960	0.946	0.904																																																							
1.60	0.967	0.962	0.949																																																							
2.40	0.973	0.969	0.960																																																							
3.20	0.975	0.972	0.967																																																							
4.00	0.978	0.978	0.971																																																							
4.20	0.978	0.978	0.973																																																							
4.62	0.978	0.977	0.973																																																							
---	—	—	—																																																							
---	—	—	—																																																							
---	—	—	—																																																							
Note: Slanted line shows the range of the rated load current.																																																										
(注) 斜線は定格負荷電流範囲を示す。																																																										

Temperature	25°C
Testing Circuitry	Figure A

2. Values



出力保持時間とは、入力電圧断から出力電圧が
定電圧精度の範囲を保持しているところまでの時間。
(注) 斜線は定格入力電圧範囲を示す。



COSEL

Model		LEP150F-36		Temperature		25℃																																																				
Item		Instantaneous Interruption Compensation 瞬時停電保障		Testing Circuitry		Figure A																																																				
Object		+36V4.2A																																																								
1. Graph				2. Values																																																						
<div><div><div>—△—</div><div>Input Volt. 85V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 132V</div></div></div> <div><div><div>Instantaneous Compensation Time [mS]</div><div>1000</div><div>100</div><div>10</div><div>1</div></div><div><div>0.0</div><div>1.0</div><div>2.0</div><div>3.0</div><div>4.0</div><div>5.0</div></div><div><div>Load Current [A]</div></div></div> <div><div>Note: Slanted line shows the range of the rated load current.</div><div>(注) 斜線は定格負荷電流範囲を示す。</div></div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [mS]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr><tr><td>0.80</td><td>172</td><td>180</td><td>190</td></tr><tr><td>1.60</td><td>79</td><td>87</td><td>96</td></tr><tr><td>2.40</td><td>46</td><td>48</td><td>60</td></tr><tr><td>3.20</td><td>45</td><td>47</td><td>47</td></tr><tr><td>4.00</td><td>38</td><td>38</td><td>40</td></tr><tr><td>4.20</td><td>37</td><td>35</td><td>39</td></tr><tr><td>4.62</td><td>28</td><td>37</td><td>35</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr><tr><td>--</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.80	172	180	190	1.60	79	87	96	2.40	46	48	60	3.20	45	47	47	4.00	38	38	40	4.20	37	35	39	4.62	28	37	35	--	—	—	—	--	—	—	—	--	—	—	—
Load Current [A]	Time [mS]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	—	—	—																																																							
0.80	172	180	190																																																							
1.60	79	87	96																																																							
2.40	46	48	60																																																							
3.20	45	47	47																																																							
4.00	38	38	40																																																							
4.20	37	35	39																																																							
4.62	28	37	35																																																							
--	—	—	—																																																							
--	—	—	—																																																							
--	—	—	—																																																							


COSEL

Model		LEP150F-36		Temperature25℃ Testing CircuitryFigure A																																														
Item		Load Regulation 静的負荷変動																																																
Object		+36V4.2A																																																
1. Graph		<div><div><div>—△—</div><div>---□---</div><div>---○---</div></div><div><div>Input Volt. 85V</div><div>Input Volt. 100V</div><div>Input Volt. 132V</div></div></div> <div><table><thead><tr><th>Load Current [A]</th><th>85[V] Output [V]</th><th>100[V] Output [V]</th><th>132[V] Output [V]</th></tr></thead><tbody><tr><td>0.00</td><td>35.998</td><td>35.998</td><td>35.998</td></tr><tr><td>0.80</td><td>35.995</td><td>35.995</td><td>35.995</td></tr><tr><td>1.60</td><td>35.994</td><td>35.994</td><td>35.994</td></tr><tr><td>2.40</td><td>35.994</td><td>35.994</td><td>35.994</td></tr><tr><td>3.20</td><td>35.993</td><td>35.993</td><td>35.993</td></tr><tr><td>4.00</td><td>35.993</td><td>35.993</td><td>35.993</td></tr><tr><td>4.20</td><td>35.993</td><td>35.993</td><td>35.993</td></tr><tr><td>4.62</td><td>35.993</td><td>35.993</td><td>35.993</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></tbody></table></div> <div><p>Note: Slanted line shows the range of the rated load current.</p><p>(注) 斜線は定格負荷電流範囲を示す。</p></div>		Load Current [A]	85[V] Output [V]	100[V] Output [V]	132[V] Output [V]	0.00	35.998	35.998	35.998	0.80	35.995	35.995	35.995	1.60	35.994	35.994	35.994	2.40	35.994	35.994	35.994	3.20	35.993	35.993	35.993	4.00	35.993	35.993	35.993	4.20	35.993	35.993	35.993	4.62	35.993	35.993	35.993	--	--	--	--	--	--	--	--	2. Values		
Load Current [A]	85[V] Output [V]	100[V] Output [V]	132[V] Output [V]																																															
0.00	35.998	35.998	35.998																																															
0.80	35.995	35.995	35.995																																															
1.60	35.994	35.994	35.994																																															
2.40	35.994	35.994	35.994																																															
3.20	35.993	35.993	35.993																																															
4.00	35.993	35.993	35.993																																															
4.20	35.993	35.993	35.993																																															
4.62	35.993	35.993	35.993																																															
--	--	--	--																																															
--	--	--	--																																															
		<table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr></thead><tbody><tr><td>0.00</td><td>35.998</td><td>35.998</td><td>35.998</td></tr><tr><td>0.80</td><td>35.995</td><td>35.995</td><td>35.995</td></tr><tr><td>1.60</td><td>35.994</td><td>35.994</td><td>35.994</td></tr><tr><td>2.40</td><td>35.994</td><td>35.994</td><td>35.994</td></tr><tr><td>3.20</td><td>35.993</td><td>35.993</td><td>35.993</td></tr><tr><td>4.00</td><td>35.993</td><td>35.993</td><td>35.993</td></tr><tr><td>4.20</td><td>35.993</td><td>35.993</td><td>35.993</td></tr><tr><td>4.62</td><td>35.993</td><td>35.993</td><td>35.993</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></tbody></table>		Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	35.998	35.998	35.998	0.80	35.995	35.995	35.995	1.60	35.994	35.994	35.994	2.40	35.994	35.994	35.994	3.20	35.993	35.993	35.993	4.00	35.993	35.993	35.993	4.20	35.993	35.993	35.993	4.62	35.993	35.993	35.993	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.00	35.998	35.998	35.998																																															
0.80	35.995	35.995	35.995																																															
1.60	35.994	35.994	35.994																																															
2.40	35.994	35.994	35.994																																															
3.20	35.993	35.993	35.993																																															
4.00	35.993	35.993	35.993																																															
4.20	35.993	35.993	35.993																																															
4.62	35.993	35.993	35.993																																															
--	--	--	--																																															
--	--	--	--																																															

COSEL

<div>Model</div> <div>LEP150F-36</div>		<div>Temperature</div> <div>25°C</div> <div>Testing Circuitry</div> <div>Figure A</div>																																						
Item	<div>Ripple Voltage (by Load Current)</div> <div>リップル電圧 (負荷特性)</div>																																							
Object	+36V4.2A																																							
<div>1. Graph</div> <div> <div>—△— Input Volt. 85V</div> <div>---○--- Input Volt. 132V</div>  </div> <div> <div>Ripple Voltage is shown as p-p in the figure below.</div> <div>Note: Slanted line shows the range of the rated load current.</div> <div>リップル電圧は、下図 p-p 値で示される。</div> <div>(注) 斜線は定格負荷電流範囲を示す。</div> </div> <div> <div>T1: Due to AC Input Line 入力商用周期</div> <div>T2: Due to Switching スイッチング周期</div>  </div> <div> <div>Fig. Complex Ripple Wave Form</div> <div>図 リップル波形詳細図</div> </div>		<div>2. Values</div> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr> <tr> <th>Input Volt. 85 [V]</th><th>Input Volt. 132 [V]</th></tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>0.80</td><td>25</td><td>25</td></tr> <tr><td>1.60</td><td>25</td><td>25</td></tr> <tr><td>2.40</td><td>30</td><td>30</td></tr> <tr><td>3.20</td><td>30</td><td>30</td></tr> <tr><td>4.00</td><td>35</td><td>35</td></tr> <tr><td>4.20</td><td>35</td><td>35</td></tr> <tr><td>4.62</td><td>40</td><td>40</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	15	15	0.80	25	25	1.60	25	25	2.40	30	30	3.20	30	30	4.00	35	35	4.20	35	35	4.62	40	40	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.00	15	15																																						
0.80	25	25																																						
1.60	25	25																																						
2.40	30	30																																						
3.20	30	30																																						
4.00	35	35																																						
4.20	35	35																																						
4.62	40	40																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						

COSEL






Model	LEP150F-36
Item	Overcurrent Protection 過電流保護
Object	+36V4.2A

1. Graph

_____	Input Volt.	85V
_____	Input Volt.	100V
_____	Input Volt.	132V



Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

Intermittent operation occurs when the output voltage is from 28V to 0V.

28V～0V間は、間欠モードとなる。

Temperature	25°C
Testing Circuitry	Figure A


2. Values

[illegible]

COSEL

Model	LEP150F-36
Item	Overvoltage Protection 過電圧保護
Object	+36V/4.2A

1. Graph
- △— Input Volt. 85V
 ---□--- Input Volt. 100V
 -●- Input Volt. 132V



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。


Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	44.74	44.45	44.51
-10	45.04	45.10	45.10
0	45.39	45.45	45.45
10	45.80	45.80	45.80
25	46.39	46.39	46.39
40	46.85	46.85	46.85
45	47.03	47.03	47.03
50	47.26	47.26	47.26
60	47.61	47.61	47.61
70	48.02	47.96	48.02
--	—	—	—


COSEL

Model	LEP150F-36	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	_____		



Input Voltage 100 V
Frequency 60 Hz
Load 100 %
Inrush Current

- ① 16.7 [A]
② 14.3 [A]





Model	LEP150F-36	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response 動的負荷変動	
Object	+36V4.2A	


Input Volt. 100 V
Cycle 1000 ms

Load Current




Min. Load (0A) ←→
Load 100% (4.2A)

100 mV/div




10 ms/div




10 ms/div

Min. Load (0A) ←→
Load 50% (2.1A)


100 mV/div



10 ms/div




10 ms/div

COSEL

COSEL

Model	LEP150F-36
Item	Ambient Temperature Drift 周囲温度変動
Object	+36V4.2A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A


2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	36.001	36.002	36.002
-10	36.003	36.003	36.004
0	36.002	36.003	36.003
10	36.005	36.006	36.006
25	36.009	36.010	36.011
40	36.014	36.015	36.015
45	36.011	36.012	36.012
50	36.007	36.008	36.009
60	36.000	36.000	36.000
70	35.990	35.990	35.990
--	—	—	—

COSEL

Model	LEP150F-36
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+36V4.2A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A


2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	63	64
-10	63	64
0	63	64
10	63	64
25	63	64
40	63	64
45	63	64
50	63	64
60	63	64
70	63	64
--	—	—

COSEL

Model	LEP150F-36
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+36V4.2A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	65	80
-10	50	60
0	40	45
10	30	35
25	25	30
40	25	30
50	25	30
60	25	30
70	25	25
--	--	--
--	--	--

COSEL

Model	LEP150F-36																								
Item	Time Lapse Drift 経時ドリフト	Temperature	25℃																						
Object	+36V4.2A	Testing Circuitry	Figure A																						
1. Graph		2. Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 100V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>35.987</td></tr><tr><td>0.5</td><td>35.994</td></tr><tr><td>1.0</td><td>35.994</td></tr><tr><td>2.0</td><td>35.995</td></tr><tr><td>3.0</td><td>35.995</td></tr><tr><td>4.0</td><td>35.995</td></tr><tr><td>5.0</td><td>35.996</td></tr><tr><td>6.0</td><td>35.996</td></tr><tr><td>7.0</td><td>35.996</td></tr><tr><td>8.0</td><td>35.996</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	35.987	0.5	35.994	1.0	35.994	2.0	35.995	3.0	35.995	4.0	35.995	5.0	35.996	6.0	35.996	7.0	35.996	8.0	35.996
Time since start [H]	Output Voltage [V]																								
0.0	35.987																								
0.5	35.994																								
1.0	35.994																								
2.0	35.995																								
3.0	35.995																								
4.0	35.995																								
5.0	35.996																								
6.0	35.996																								
7.0	35.996																								
8.0	35.996																								



Model		LEP150F-36	Testing Circuitry Figure A
Item		Output Voltage Accuracy 定電圧精度	
Object		+36V4.2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 ~ 45°C

Input Voltage : 85 ~ 132V

Load Current : 0 ~ 4.2A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage}}{\text{Rated Output Voltage}} \times 100$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -10 ~ 45°C

入力電圧 : 85 ~ 132V

負荷電流 : 0 ~ 4.2A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	85	0	36.019	±8	±0.1
Minimum Voltage	-10	85	4.2	36.004		


COSEL

Model	LEP150F-36	Temperature	25°C
Item	Harmonic Current 高調波電流	Testing Circuitry	Figure E
Object			

1. Input Current Waveform


— Input Current
 — Envelope of the input current to classify equipment as Class D
 クラスDの機器を決定するための入力電流包絡線

1 A/div



Conditions	Values
Input Voltage [V]	99.7
Input Current [A]	1.798
Active Power [W]	174.8
Apparent Power [VA]	179.3
Frequency [Hz]	60
Power Factor	0.975
Output Power [W]	151.2

2. Harmonic Current



— Harmonic Current
 高調波電流
 — Limits for Class A equipment
 クラスAの機器に対する限度値

Harmonics order 高調波次数	Limits 限度値 [A]	Values 測定値 [A]
1	—	1.75300
2	—	0.00100
3	5.30592	0.37900
4	—	0.00000
5	2.62989	0.10700
6	—	0.00000
7	1.77633	0.01000
8	—	0.00000
9	0.92277	0.01100
10	—	0.00000
11	0.76128	0.02500
12	—	0.00000
13	0.48445	0.01900
14	—	0.00000
15	0.34604	0.00800
16	—	0.00000
17	0.30533	0.00400
18	—	0.00000
19	0.27319	0.00700
20	—	0.00000
21	0.24717	0.01100
22	—	0.00000
23	0.22568	0.01200
24	—	0.00000
25	0.20762	0.01400
26	—	0.00000
27	0.19224	0.00800
28	—	0.00000
29	0.17899	0.01100
30	—	0.00000
31	0.16744	0.00900
32	—	0.00000
33	0.15729	0.00900
34	—	0.00000
35	0.14830	0.00500
36	—	0.00000
37	0.14029	0.00400
38	—	0.00000
39	0.13309	0.00200
40	—	0.00000


COSEL

Model	LEP150F-36	Temperature	25°C
Item	Harmonic Current 高調波電流	Testing Circuitry	Figure E
Object			


1. Input Current Waveform

— Input Current
 — Envelope of the input current to classify equipment as Class D
 クラスDの機器を決定するための入力電流包絡線

1 A/div



2. Harmonic Current



— Harmonic Current
 高調波電流
 — Limits for Class A equipment
 クラスAの機器に対する限度値

Conditions	Values
Input Voltage [V]	100.1
Input Current [A]	0.945
Active Power [W]	90.7
Apparent Power [VA]	94.6
Frequency [Hz]	60
Power Factor	0.959
Output Power [W]	75.6

Harmonics order 高調波次数	Limits 限度値 [A]	Values 測定値 [A]
1	—	0.90860
2	—	0.00040
3	5.28472	0.25620
4	—	0.00030
5	2.61938	0.02300
6	—	0.00030
7	1.76923	0.00530
8	—	0.00000
9	0.91908	0.01170
10	—	0.00000
11	0.75824	0.01410
12	—	0.00010
13	0.48252	0.01550
14	—	0.00010
15	0.34466	0.00910
16	—	0.00000
17	0.30411	0.00410
18	—	0.00010
19	0.27210	0.00100
20	—	0.00010
21	0.24618	0.00710
22	—	0.00010
23	0.22478	0.00640
24	—	0.00000
25	0.20679	0.00240
26	—	0.00010
27	0.19148	0.00170
28	—	0.00010
29	0.17827	0.00410
30	—	0.00010
31	0.16677	0.00300
32	—	0.00000
33	0.15666	0.00300
34	—	0.00000
35	0.14771	0.00390
36	—	0.00000
37	0.13973	0.00230
38	—	0.00010
39	0.13256	0.00260
40	—	0.00000



Model		LEP150F-36	Temperature 25°C Testing Circuitry Figure B
Item		Leakage Current 漏洩電流	
Object			

1. Results

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
	85 [V]	100 [V]	132 [V]
(A) DEN-AN	0.15	0.18	0.24
(B) IEC60950	0.15	0.18	0.24

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
	170 [V]	230 [V]	264 [V]
(B) IEC60950	—	—	—

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の一相について測定し、その大きい方を漏洩電流測定値とする。

COSEL

Model	LEP150F-36	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure C
Object	+36V4.2A		

1. Conditions

- Input Voltage : 100 V
- Pulse Voltage : 2000 V
- Pulse Cycle : 10 mS
- Pulse Input Duration : 1 min. or more
- Load : 100 %

2. Results

Pulse Width [nS]	MODE		No protection failure should occur	DC-like Regulation of Output Voltage
		POLARITY	保護回路の誤動作がない	出力電圧の直流的変動
50	COMMON	+	OK	no fluctuation
		—	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		—	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		—	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		—	OK	no fluctuation

COSEL

Model	LEP150F-36	Temperature	25°C
Item	Conducted Emission 雑音端子電圧	Testing Circuitry	Figure D
Object			

1. Graph

Remarks


Input Volt. 100V (VCCI Class B)

120V (FCC Class B)


Load 100%

Limit1: [VCCI] Class B(QP)

Limit2: [VCCI] Class B(Ave.)



Limit: [FCC Part15] Class B







Figure B (DEN-AN)




Figure B (IEC60950)




Figure C




Figure D




Figure E