



TEST DATA OF LFA10F-3R3-Y

Regulated DC Power Supply

Approved by :  Yoshiaki Shimizu Design Manager

Prepared by : *Yuki Nakamura*
Yuki Nakamura Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Oversupply Protection	23
24.Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model	LFA10F-3R3-Y																																																																																				
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																																																		
Object	_____	_____	_____																																																																																		
1.Graph	<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 200V ---○--- Input Volt. 230V </p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.012</td><td>0.008</td><td>0.008</td></tr> <tr><td>0.4</td><td>0.056</td><td>0.035</td><td>0.032</td></tr> <tr><td>0.8</td><td>0.090</td><td>0.056</td><td>0.051</td></tr> <tr><td>1.2</td><td>0.122</td><td>0.076</td><td>0.069</td></tr> <tr><td>1.6</td><td>0.153</td><td>0.095</td><td>0.087</td></tr> <tr><td>2.0</td><td>0.183</td><td>0.114</td><td>0.103</td></tr> <tr><td>2.2</td><td>0.199</td><td>0.123</td><td>0.112</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0.0	0.012	0.008	0.008	0.4	0.056	0.035	0.032	0.8	0.090	0.056	0.051	1.2	0.122	0.076	0.069	1.6	0.153	0.095	0.087	2.0	0.183	0.114	0.103	2.2	0.199	0.123	0.112	2.Values																																																			
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																																																		
0.0	0.012	0.008	0.008																																																																																		
0.4	0.056	0.035	0.032																																																																																		
0.8	0.090	0.056	0.051																																																																																		
1.2	0.122	0.076	0.069																																																																																		
1.6	0.153	0.095	0.087																																																																																		
2.0	0.183	0.114	0.103																																																																																		
2.2	0.199	0.123	0.112																																																																																		
1.Graph	<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 200V ---○--- Input Volt. 230V </p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.012</td><td>0.008</td><td>0.008</td></tr> <tr><td>0.4</td><td>0.056</td><td>0.035</td><td>0.032</td></tr> <tr><td>0.8</td><td>0.090</td><td>0.056</td><td>0.051</td></tr> <tr><td>1.2</td><td>0.122</td><td>0.076</td><td>0.069</td></tr> <tr><td>1.6</td><td>0.153</td><td>0.095</td><td>0.087</td></tr> <tr><td>2.0</td><td>0.183</td><td>0.114</td><td>0.103</td></tr> <tr><td>2.2</td><td>0.199</td><td>0.123</td><td>0.112</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0.0	0.012	0.008	0.008	0.4	0.056	0.035	0.032	0.8	0.090	0.056	0.051	1.2	0.122	0.076	0.069	1.6	0.153	0.095	0.087	2.0	0.183	0.114	0.103	2.2	0.199	0.123	0.112	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.012</td><td>0.008</td><td>0.008</td></tr> <tr><td>0.4</td><td>0.056</td><td>0.035</td><td>0.032</td></tr> <tr><td>0.8</td><td>0.090</td><td>0.056</td><td>0.051</td></tr> <tr><td>1.2</td><td>0.122</td><td>0.076</td><td>0.069</td></tr> <tr><td>1.6</td><td>0.153</td><td>0.095</td><td>0.087</td></tr> <tr><td>2.0</td><td>0.183</td><td>0.114</td><td>0.103</td></tr> <tr><td>2.2</td><td>0.199</td><td>0.123</td><td>0.112</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.012	0.008	0.008	0.4	0.056	0.035	0.032	0.8	0.090	0.056	0.051	1.2	0.122	0.076	0.069	1.6	0.153	0.095	0.087	2.0	0.183	0.114	0.103	2.2	0.199	0.123	0.112	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																																																		
0.0	0.012	0.008	0.008																																																																																		
0.4	0.056	0.035	0.032																																																																																		
0.8	0.090	0.056	0.051																																																																																		
1.2	0.122	0.076	0.069																																																																																		
1.6	0.153	0.095	0.087																																																																																		
2.0	0.183	0.114	0.103																																																																																		
2.2	0.199	0.123	0.112																																																																																		
Load Current [A]	Input Current [A]																																																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																																																		
0.0	0.012	0.008	0.008																																																																																		
0.4	0.056	0.035	0.032																																																																																		
0.8	0.090	0.056	0.051																																																																																		
1.2	0.122	0.076	0.069																																																																																		
1.6	0.153	0.095	0.087																																																																																		
2.0	0.183	0.114	0.103																																																																																		
2.2	0.199	0.123	0.112																																																																																		
--	-	-	-																																																																																		
--	-	-	-																																																																																		
--	-	-	-																																																																																		
--	-	-	-																																																																																		
Note:	Slanted line shows the range of the rated load current.																																																																																				


COSEL

Model	LFA10F-3R3-Y																																																		
Item	Input Power (by Load Current)																																																		
Object	<u> </u>																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.40</td><td>0.37</td><td>0.38</td></tr> <tr><td>0.4</td><td>2.40</td><td>2.46</td><td>2.48</td></tr> <tr><td>0.8</td><td>4.18</td><td>4.26</td><td>4.28</td></tr> <tr><td>1.2</td><td>6.01</td><td>5.99</td><td>5.99</td></tr> <tr><td>1.6</td><td>7.84</td><td>7.78</td><td>7.86</td></tr> <tr><td>2.0</td><td>9.77</td><td>9.71</td><td>9.70</td></tr> <tr><td>2.2</td><td>10.75</td><td>10.56</td><td>10.61</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.40	0.37	0.38	0.4	2.40	2.46	2.48	0.8	4.18	4.26	4.28	1.2	6.01	5.99	5.99	1.6	7.84	7.78	7.86	2.0	9.77	9.71	9.70	2.2	10.75	10.56	10.61	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																
0.0	0.40	0.37	0.38																																																
0.4	2.40	2.46	2.48																																																
0.8	4.18	4.26	4.28																																																
1.2	6.01	5.99	5.99																																																
1.6	7.84	7.78	7.86																																																
2.0	9.77	9.71	9.70																																																
2.2	10.75	10.56	10.61																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
2.Values																																																			
Note: Slanted line shows the range of the rated load current.																																																			

COSEL

Model	LFA10F-3R3-Y																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>64.9</td><td>66.4</td> </tr> <tr> <td>85</td><td>65.3</td><td>67.4</td> </tr> <tr> <td>100</td><td>65.8</td><td>68.1</td> </tr> <tr> <td>120</td><td>65.3</td><td>68.6</td> </tr> <tr> <td>200</td><td>64.9</td><td>68.6</td> </tr> <tr> <td>230</td><td>63.9</td><td>68.4</td> </tr> <tr> <td>264</td><td>62.9</td><td>68.4</td> </tr> <tr> <td>280</td><td>62.6</td><td>68.3</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	64.9	66.4	85	65.3	67.4	100	65.8	68.1	120	65.3	68.6	200	64.9	68.6	230	63.9	68.4	264	62.9	68.4	280	62.6	68.3	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	64.9	66.4																																
85	65.3	67.4																																
100	65.8	68.1																																
120	65.3	68.6																																
200	64.9	68.6																																
230	63.9	68.4																																
264	62.9	68.4																																
280	62.6	68.3																																
--	-	-																																

COSEL

Model	LFA10F-3R3-Y																																																					
Item	Efficiency (by Load Current)	Temperature	25°C																																																			
Object	Testing Circuitry	Figure A																																																				
1.Graph	—△— Input Volt. 100V - - □--- Input Volt. 200V - - ○--- Input Volt. 230V																																																					
	 <p>The graph shows efficiency increasing with load current for all input voltages. The 100V curve is the highest, followed by 230V, and then 200V. A slanted line on the right side of the graph indicates the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.4</td><td>55.3</td><td>53.9</td><td>53.5</td></tr> <tr> <td>0.8</td><td>63.5</td><td>62.3</td><td>62.0</td></tr> <tr> <td>1.2</td><td>66.3</td><td>66.5</td><td>66.5</td></tr> <tr> <td>1.6</td><td>67.7</td><td>68.3</td><td>67.6</td></tr> <tr> <td>2.0</td><td>68.1</td><td>68.6</td><td>68.4</td></tr> <tr> <td>2.2</td><td>67.9</td><td>69.1</td><td>68.8</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	0.4	55.3	53.9	53.5	0.8	63.5	62.3	62.0	1.2	66.3	66.5	66.5	1.6	67.7	68.3	67.6	2.0	68.1	68.6	68.4	2.2	67.9	69.1	68.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
0.4	55.3	53.9	53.5																																																			
0.8	63.5	62.3	62.0																																																			
1.2	66.3	66.5	66.5																																																			
1.6	67.7	68.3	67.6																																																			
2.0	68.1	68.6	68.4																																																			
2.2	67.9	69.1	68.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL




Model	LFA10F-3R3-Y																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1.Graph																																		
<p>Graph showing Power Factor vs Input Voltage for LFA10F-3R3-Y at 25°C. The Y-axis is Power Factor (0.2 to 0.8) and the X-axis is Input Voltage [V] (50 to 300). Two series are plotted: Load 50% (dashed line with squares) and Load 100% (solid line with triangles). Both curves show a decreasing trend as input voltage increases. A slanted line indicates the rated input voltage range.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>0.526</td><td>0.587</td> </tr> <tr> <td>85</td><td>0.504</td><td>0.563</td> </tr> <tr> <td>100</td><td>0.478</td><td>0.532</td> </tr> <tr> <td>120</td><td>0.452</td><td>0.501</td> </tr> <tr> <td>200</td><td>0.387</td><td>0.425</td> </tr> <tr> <td>230</td><td>0.372</td><td>0.407</td> </tr> <tr> <td>264</td><td>0.358</td><td>0.390</td> </tr> <tr> <td>280</td><td>0.352</td><td>0.384</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.526	0.587	85	0.504	0.563	100	0.478	0.532	120	0.452	0.501	200	0.387	0.425	230	0.372	0.407	264	0.358	0.390	280	0.352	0.384	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.526	0.587																																
85	0.504	0.563																																
100	0.478	0.532																																
120	0.452	0.501																																
200	0.387	0.425																																
230	0.372	0.407																																
264	0.358	0.390																																
280	0.352	0.384																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	LFA10F-3R3-Y																																																					
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
Object	Testing Circuitry	Figure A																																																				
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V</th> <th>Input Volt. 200V</th> <th>Input Volt. 230V</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.328</td><td>0.240</td><td>0.221</td></tr> <tr><td>0.4</td><td>0.429</td><td>0.348</td><td>0.336</td></tr> <tr><td>0.8</td><td>0.465</td><td>0.377</td><td>0.362</td></tr> <tr><td>1.2</td><td>0.493</td><td>0.396</td><td>0.380</td></tr> <tr><td>1.6</td><td>0.514</td><td>0.411</td><td>0.395</td></tr> <tr><td>2.0</td><td>0.533</td><td>0.425</td><td>0.407</td></tr> <tr><td>2.2</td><td>0.541</td><td>0.431</td><td>0.413</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V	0.0	0.328	0.240	0.221	0.4	0.429	0.348	0.336	0.8	0.465	0.377	0.362	1.2	0.493	0.396	0.380	1.6	0.514	0.411	0.395	2.0	0.533	0.425	0.407	2.2	0.541	0.431	0.413																			
Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V																																																			
0.0	0.328	0.240	0.221																																																			
0.4	0.429	0.348	0.336																																																			
0.8	0.465	0.377	0.362																																																			
1.2	0.493	0.396	0.380																																																			
1.6	0.514	0.411	0.395																																																			
2.0	0.533	0.425	0.407																																																			
2.2	0.541	0.431	0.413																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.328</td><td>0.240</td><td>0.221</td></tr> <tr><td>0.4</td><td>0.429</td><td>0.348</td><td>0.336</td></tr> <tr><td>0.8</td><td>0.465</td><td>0.377</td><td>0.362</td></tr> <tr><td>1.2</td><td>0.493</td><td>0.396</td><td>0.380</td></tr> <tr><td>1.6</td><td>0.514</td><td>0.411</td><td>0.395</td></tr> <tr><td>2.0</td><td>0.533</td><td>0.425</td><td>0.407</td></tr> <tr><td>2.2</td><td>0.541</td><td>0.431</td><td>0.413</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.328	0.240	0.221	0.4	0.429	0.348	0.336	0.8	0.465	0.377	0.362	1.2	0.493	0.396	0.380	1.6	0.514	0.411	0.395	2.0	0.533	0.425	0.407	2.2	0.541	0.431	0.413	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.328	0.240	0.221																																																			
0.4	0.429	0.348	0.336																																																			
0.8	0.465	0.377	0.362																																																			
1.2	0.493	0.396	0.380																																																			
1.6	0.514	0.411	0.395																																																			
2.0	0.533	0.425	0.407																																																			
2.2	0.541	0.431	0.413																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	LFA10F-3R3-Y	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	<hr/>		





Model	LFA10F-3R3-Y	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

[mA]

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
DEN-AN	Both phases	0.07	0.14	0.16	Operation
	One of phase	0.13	0.27	0.33	stand by
IEC60950-1	Both phases	0.09	0.19	0.20	Operation
	One of phase	0.13	0.28	0.31	stand by

The value for "One phase" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	LFA10F-3R3-Y
Item	Line Regulation
Object	+3.3V2A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	3.315	3.311
85	3.315	3.311
100	3.315	3.311
120	3.315	3.311
200	3.315	3.311
230	3.315	3.311
264	3.315	3.311
280	3.315	3.311
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	LFA10F-3R3-Y																																																					
Item	Load Regulation																																																					
Object	+3.3V2A																																																					
1.Graph	—△— Input Volt. 100V ---□--- Input Volt. 200V —·○— Input Volt. 230V	2.Values																																																				
	<p>The graph plots Output Voltage [V] on the y-axis (3.24 to 3.38) against Load Current [A] on the x-axis (0.0 to 2.0). Three data series are shown for input voltages of 100V, 200V, and 230V. All series show a slight decrease in output voltage as load current increases, but remain relatively flat around 3.318V. A slanted line is drawn through the data points, representing the rated load current range.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.318</td><td>3.318</td><td>3.318</td></tr> <tr><td>0.4</td><td>3.316</td><td>3.316</td><td>3.316</td></tr> <tr><td>0.8</td><td>3.315</td><td>3.315</td><td>3.315</td></tr> <tr><td>1.2</td><td>3.313</td><td>3.313</td><td>3.313</td></tr> <tr><td>1.6</td><td>3.312</td><td>3.312</td><td>3.312</td></tr> <tr><td>2.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>2.2</td><td>3.309</td><td>3.310</td><td>3.310</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	3.318	3.318	3.318	0.4	3.316	3.316	3.316	0.8	3.315	3.315	3.315	1.2	3.313	3.313	3.313	1.6	3.312	3.312	3.312	2.0	3.310	3.310	3.310	2.2	3.309	3.310	3.310	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	3.318	3.318	3.318																																																			
0.4	3.316	3.316	3.316																																																			
0.8	3.315	3.315	3.315																																																			
1.2	3.313	3.313	3.313																																																			
1.6	3.312	3.312	3.312																																																			
2.0	3.310	3.310	3.310																																																			
2.2	3.309	3.310	3.310																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.


COSEL

COSEL

Model	LFA10F-3R3-Y
Item	Ripple Voltage (by Load Current)
Object	+3.3V2A

Temperature 25°C
Testing Circuitry Figure C

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	35	65
0.4	10	75
0.8	15	15
1.2	20	20
1.6	25	25
2.0	25	25
2.2	25	25
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	LFA10F-3R3-Y
Item	Ripple-Noise
Object	+3.3V2A

Temperature 25°C
Testing Circuitry Figure C

1.Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	35	65
0.4	10	75
0.8	15	20
1.2	20	25
1.6	30	30
2.0	30	30
2.2	30	30
--	-	-
--	-	-
--	-	-
--	-	-

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	LFA10F-3R3-Y
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V2A

1. Graph




Testing Circuitry Figure C

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	110	110
-10	75	75
0	50	50
25	25	25
50	25	20
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-20	3.307	3.307	3.307
-10	3.308	3.308	3.308
0	3.310	3.310	3.310
10	3.310	3.310	3.310
20	3.311	3.311	3.311
25	3.311	3.311	3.311
30	3.311	3.311	3.311
40	3.310	3.310	3.310
50	3.310	3.310	3.310
60	3.309	3.309	3.309
--	-	-	-



Model	LFA10F-3R3-Y	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 2A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	30	264	0	3.318	±5	±0.2
Minimum Voltage	-10	85	2	3.308		


COSEL

Model	LFA10F-3R3-Y	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+3.3V2A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.310</td></tr> <tr><td>0.5</td><td>3.310</td></tr> <tr><td>1.0</td><td>3.310</td></tr> <tr><td>2.0</td><td>3.310</td></tr> <tr><td>3.0</td><td>3.310</td></tr> <tr><td>4.0</td><td>3.310</td></tr> <tr><td>5.0</td><td>3.310</td></tr> <tr><td>6.0</td><td>3.310</td></tr> <tr><td>7.0</td><td>3.310</td></tr> <tr><td>8.0</td><td>3.311</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	3.310	0.5	3.310	1.0	3.310	2.0	3.310	3.0	3.310	4.0	3.310	5.0	3.310	6.0	3.310	7.0	3.310	8.0	3.311
Time since start [H]	Output Voltage [V]																								
0.0	3.310																								
0.5	3.310																								
1.0	3.310																								
2.0	3.310																								
3.0	3.310																								
4.0	3.310																								
5.0	3.310																								
6.0	3.310																								
7.0	3.310																								
8.0	3.311																								
* The characteristic of AC200V is equal.																									

COSEL


Model	LFA10F-3R3-Y	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+3.3V2A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		176.5	3.0	179.5	35.5	22.5	
200 V		175.5	3.0	178.5	172.0	24.0	




COSEL

Model	LFA10F-3R3-Y
Item	Hold-Up Time
Object	+3.3V2A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	36	10
85	50	23
100	74	31
120	111	49
200	337	171
230	453	230
264	605	316
280	685	359
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	LFA10F-3R3-Y																																																					
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+3.3V2A																																																					
1.Graph	<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 200V ---○--- Input Volt. 230V </p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>200V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>0.4</td><td>164</td><td>714</td><td>990</td></tr> <tr><td>0.8</td><td>92</td><td>411</td><td>550</td></tr> <tr><td>1.2</td><td>63</td><td>287</td><td>386</td></tr> <tr><td>1.6</td><td>47</td><td>219</td><td>295</td></tr> <tr><td>2.0</td><td>31</td><td>171</td><td>230</td></tr> </tbody> </table>	Load Current [A]	100V [ms]	200V [ms]	230V [ms]	0.4	164	714	990	0.8	92	411	550	1.2	63	287	386	1.6	47	219	295	2.0	31	171	230	2.Values																												
Load Current [A]	100V [ms]	200V [ms]	230V [ms]																																																			
0.4	164	714	990																																																			
0.8	92	411	550																																																			
1.2	63	287	386																																																			
1.6	47	219	295																																																			
2.0	31	171	230																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.4</td><td>164</td><td>714</td><td>990</td></tr> <tr><td>0.8</td><td>92</td><td>411</td><td>550</td></tr> <tr><td>1.2</td><td>63</td><td>287</td><td>386</td></tr> <tr><td>1.6</td><td>47</td><td>219</td><td>295</td></tr> <tr><td>2.0</td><td>31</td><td>171</td><td>230</td></tr> <tr><td>2.2</td><td>26</td><td>153</td><td>208</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	0.4	164	714	990	0.8	92	411	550	1.2	63	287	386	1.6	47	219	295	2.0	31	171	230	2.2	26	153	208	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
0.4	164	714	990																																																			
0.8	92	411	550																																																			
1.2	63	287	386																																																			
1.6	47	219	295																																																			
2.0	31	171	230																																																			
2.2	26	153	208																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
			<p>Note: Slanted line shows the range of the rated load current.</p>																																																			



Model	LFA10F-3R3-Y
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V2A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	34	44
-10	34	44
0	34	44
10	34	44
20	34	44
25	33	44
30	33	44
40	33	44
50	33	44
60	33	44
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL


Model	LFA10F-3R3-Y																																										
Item	Overcurrent Protection	Temperature 25°C Testing Circuitry Figure A																																									
Object	+3.3V2A																																										
1.Graph																																											
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 200V</p>																																											
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is less than rated output voltage.</p>																																											
2.Values																																											
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>3.300</td><td>4.02</td><td>4.80</td></tr> <tr><td>3.135</td><td>-</td><td>-</td></tr> <tr><td>2.970</td><td>-</td><td>-</td></tr> <tr><td>2.640</td><td>-</td><td>-</td></tr> <tr><td>2.310</td><td>-</td><td>-</td></tr> <tr><td>1.980</td><td>-</td><td>-</td></tr> <tr><td>1.650</td><td>-</td><td>-</td></tr> <tr><td>1.320</td><td>-</td><td>-</td></tr> <tr><td>0.990</td><td>-</td><td>-</td></tr> <tr><td>0.660</td><td>-</td><td>-</td></tr> <tr><td>0.330</td><td>-</td><td>-</td></tr> <tr><td>0.000</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 200[V]	3.300	4.02	4.80	3.135	-	-	2.970	-	-	2.640	-	-	2.310	-	-	1.980	-	-	1.650	-	-	1.320	-	-	0.990	-	-	0.660	-	-	0.330	-	-	0.000	-	-
Output Voltage [V]	Load Current [A]																																										
	Input Volt. 100[V]	Input Volt. 200[V]																																									
3.300	4.02	4.80																																									
3.135	-	-																																									
2.970	-	-																																									
2.640	-	-																																									
2.310	-	-																																									
1.980	-	-																																									
1.650	-	-																																									
1.320	-	-																																									
0.990	-	-																																									
0.660	-	-																																									
0.330	-	-																																									
0.000	-	-																																									

COSEL

Model	LFA10F-3R3-Y
Item	Overvoltage Protection
Object	+3.3V2A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-20	4.93	4.93
-10	4.86	4.86
0	4.79	4.79
10	4.79	4.79
20	4.72	4.72
25	4.72	4.72
30	4.72	4.72
40	4.65	4.65
50	4.58	4.58
60	4.58	4.58
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)




Figure C