

TEST DATA OF LFA150F-12

Regulated DC Power Supply
November 10, 2010

Approved by : *Yoshiaki Shimizu*
Yoshiaki Shimizu Design Manager

Prepared by : *Daisuke Sumiwa*
Daisuke Sumiwa Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 25)



Model		LFA150F-12		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 100V - - - □ - - - Input Volt. 200V - · - ○ - · - - Input Volt. 230V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.093</td><td>0.119</td><td>0.130</td></tr> <tr><td>2.5</td><td>0.434</td><td>0.259</td><td>0.247</td></tr> <tr><td>5.0</td><td>0.772</td><td>0.414</td><td>0.379</td></tr> <tr><td>7.5</td><td>1.118</td><td>0.577</td><td>0.519</td></tr> <tr><td>10.0</td><td>1.469</td><td>0.743</td><td>0.662</td></tr> <tr><td>12.5</td><td>1.820</td><td>0.914</td><td>0.810</td></tr> <tr><td>13.8</td><td>2.018</td><td>1.003</td><td>0.887</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.093	0.119	0.130	2.5	0.434	0.259	0.247	5.0	0.772	0.414	0.379	7.5	1.118	0.577	0.519	10.0	1.469	0.743	0.662	12.5	1.820	0.914	0.810	13.8	2.018	1.003	0.887	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	0.093	0.119	0.130																																																					
2.5	0.434	0.259	0.247																																																					
5.0	0.772	0.414	0.379																																																					
7.5	1.118	0.577	0.519																																																					
10.0	1.469	0.743	0.662																																																					
12.5	1.820	0.914	0.810																																																					
13.8	2.018	1.003	0.887																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		LFA150F-12		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		<p>—△— Input Volt. 100V</p> <p>---□--- Input Volt. 200V</p> <p>---○--- Input Volt. 230V</p>		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>6.0</td><td>6.4</td><td>6.7</td></tr> <tr><td>2.5</td><td>41.3</td><td>40.7</td><td>40.7</td></tr> <tr><td>5.0</td><td>75.6</td><td>73.3</td><td>73.2</td></tr> <tr><td>7.5</td><td>110.3</td><td>106.9</td><td>106.6</td></tr> <tr><td>10.0</td><td>145.8</td><td>140.8</td><td>140.3</td></tr> <tr><td>12.5</td><td>181.2</td><td>175.4</td><td>174.5</td></tr> <tr><td>13.8</td><td>200.7</td><td>193.4</td><td>192.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	6.0	6.4	6.7	2.5	41.3	40.7	40.7	5.0	75.6	73.3	73.2	7.5	110.3	106.9	106.6	10.0	145.8	140.8	140.3	12.5	181.2	175.4	174.5	13.8	200.7	193.4	192.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	6.0	6.4	6.7																																																					
2.5	41.3	40.7	40.7																																																					
5.0	75.6	73.3	73.2																																																					
7.5	110.3	106.9	106.6																																																					
10.0	145.8	140.8	140.3																																																					
12.5	181.2	175.4	174.5																																																					
13.8	200.7	193.4	192.5																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		LFA150F-12																																	
Item		Efficiency (by Input Voltage)																																	
Object																																			
1.Graph		Temperature 25°C Testing Circuitry Figure A																																	
<p>---□--- Load 50% —△— Load 100%</p>		2.Values																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>79.4</td> <td>80.3</td> </tr> <tr> <td>85</td> <td>79.9</td> <td>81.2</td> </tr> <tr> <td>100</td> <td>80.9</td> <td>82.5</td> </tr> <tr> <td>120</td> <td>81.4</td> <td>83.2</td> </tr> <tr> <td>200</td> <td>82.8</td> <td>85.2</td> </tr> <tr> <td>230</td> <td>83.1</td> <td>85.6</td> </tr> <tr> <td>264</td> <td>83.3</td> <td>86.0</td> </tr> <tr> <td>280</td> <td>83.2</td> <td>86.0</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	79.4	80.3	85	79.9	81.2	100	80.9	82.5	120	81.4	83.2	200	82.8	85.2	230	83.1	85.6	264	83.3	86.0	280	83.2	86.0	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	79.4	80.3																																	
85	79.9	81.2																																	
100	80.9	82.5																																	
120	81.4	83.2																																	
200	82.8	85.2																																	
230	83.1	85.6																																	
264	83.3	86.0																																	
280	83.2	86.0																																	
--	-	-																																	



Model		LFA150F-12		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 100V - - □ - - Input Volt. 200V - · ○ · - - Input Volt. 230V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.5</td><td>72.3</td><td>73.3</td><td>73.3</td></tr> <tr><td>5.0</td><td>79.0</td><td>81.4</td><td>81.6</td></tr> <tr><td>7.5</td><td>81.2</td><td>83.8</td><td>84.0</td></tr> <tr><td>10.0</td><td>81.9</td><td>84.8</td><td>85.1</td></tr> <tr><td>12.5</td><td>82.5</td><td>85.2</td><td>85.6</td></tr> <tr><td>13.8</td><td>82.1</td><td>85.2</td><td>85.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	2.5	72.3	73.3	73.3	5.0	79.0	81.4	81.6	7.5	81.2	83.8	84.0	10.0	81.9	84.8	85.1	12.5	82.5	85.2	85.6	13.8	82.1	85.2	85.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	-	-	-																																																					
2.5	72.3	73.3	73.3																																																					
5.0	79.0	81.4	81.6																																																					
7.5	81.2	83.8	84.0																																																					
10.0	81.9	84.8	85.1																																																					
12.5	82.5	85.2	85.6																																																					
13.8	82.1	85.2	85.6																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								






Model		LFA150F-12																																	
Item		Power Factor (by Input Voltage)																																	
Object																																			
1.Graph		2.Values																																	
<p>Legend: - - - □ - - - Load 50% - - - △ - - - Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>0.994</td> <td>0.998</td> </tr> <tr> <td>85</td> <td>0.989</td> <td>0.998</td> </tr> <tr> <td>100</td> <td>0.984</td> <td>0.996</td> </tr> <tr> <td>120</td> <td>0.977</td> <td>0.991</td> </tr> <tr> <td>200</td> <td>0.912</td> <td>0.960</td> </tr> <tr> <td>230</td> <td>0.871</td> <td>0.936</td> </tr> <tr> <td>264</td> <td>0.816</td> <td>0.899</td> </tr> <tr> <td>280</td> <td>0.785</td> <td>0.875</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.994	0.998	85	0.989	0.998	100	0.984	0.996	120	0.977	0.991	200	0.912	0.960	230	0.871	0.936	264	0.816	0.899	280	0.785	0.875	--	-	-
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
75	0.994	0.998																																	
85	0.989	0.998																																	
100	0.984	0.996																																	
120	0.977	0.991																																	
200	0.912	0.960																																	
230	0.871	0.936																																	
264	0.816	0.899																																	
280	0.785	0.875																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model		LFA150F-12		Temperature		25°C																																																				
Item		Power Factor (by Load Current)		Testing Circuitry		Figure A																																																				
Object																																																										
1.Graph				2.Values																																																						
<p> —△— Input Volt. 100V - - - □ - - - Input Volt. 200V - - - ○ - - - Input Volt. 230V </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.646</td><td>0.270</td><td>0.223</td></tr> <tr><td>2.5</td><td>0.954</td><td>0.786</td><td>0.715</td></tr> <tr><td>5.0</td><td>0.979</td><td>0.886</td><td>0.840</td></tr> <tr><td>7.5</td><td>0.987</td><td>0.926</td><td>0.893</td></tr> <tr><td>10.0</td><td>0.993</td><td>0.947</td><td>0.921</td></tr> <tr><td>12.5</td><td>0.996</td><td>0.960</td><td>0.936</td></tr> <tr><td>13.8</td><td>0.996</td><td>0.963</td><td>0.943</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.646	0.270	0.223	2.5	0.954	0.786	0.715	5.0	0.979	0.886	0.840	7.5	0.987	0.926	0.893	10.0	0.993	0.947	0.921	12.5	0.996	0.960	0.936	13.8	0.996	0.963	0.943	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																									
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																							
0.0	0.646	0.270	0.223																																																							
2.5	0.954	0.786	0.715																																																							
5.0	0.979	0.886	0.840																																																							
7.5	0.987	0.926	0.893																																																							
10.0	0.993	0.947	0.921																																																							
12.5	0.996	0.960	0.936																																																							
13.8	0.996	0.963	0.943																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
<p>Note: Slanted line shows the range of the rated load current.</p>																																																										



COSEL			
Model	LFA150F-12	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





COSEL		
Model	LFA150F-12	Temperature 25°C Testing Circuitry Figure B
Item	Leakage Current	
Object	_____	

1.Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	230 [V]	
DEN-AN	Both phases	0.27	0.40	0.44	Operation
	One of phases	0.23	0.51	0.60	Stand by
IEC60950-1	Both phases	0.16	0.35	0.41	Operation
	One of phases	0.24	0.52	0.61	Stand by

The value for "One of phases" is the reference value only.

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.



COSEL																																			
Model	LFA150F-12	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V12.5A																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>12.009</td><td>12.003</td></tr> <tr><td>85</td><td>12.009</td><td>12.003</td></tr> <tr><td>100</td><td>12.009</td><td>12.003</td></tr> <tr><td>120</td><td>12.009</td><td>12.003</td></tr> <tr><td>200</td><td>12.009</td><td>12.003</td></tr> <tr><td>230</td><td>12.009</td><td>12.003</td></tr> <tr><td>264</td><td>12.009</td><td>12.003</td></tr> <tr><td>280</td><td>12.009</td><td>12.003</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	12.009	12.003	85	12.009	12.003	100	12.009	12.003	120	12.009	12.003	200	12.009	12.003	230	12.009	12.003	264	12.009	12.003	280	12.009	12.003	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	12.009	12.003																																	
85	12.009	12.003																																	
100	12.009	12.003																																	
120	12.009	12.003																																	
200	12.009	12.003																																	
230	12.009	12.003																																	
264	12.009	12.003																																	
280	12.009	12.003																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



<p>Model LFA150F-12</p>		<p>Temperature 25°C</p>																																																				
<p>Item Load Regulation</p>		<p>Testing Circuitry Figure A</p>																																																				
<p>Object +12V12.5A</p>																																																						
<p>1.Graph</p> <p> —△— Input Volt. 100V - - - □ - - - Input Volt. 200V - · - ○ - · - - Input Volt. 230V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.017</td><td>12.017</td><td>12.017</td></tr> <tr><td>2.5</td><td>12.014</td><td>12.014</td><td>12.014</td></tr> <tr><td>5.0</td><td>12.011</td><td>12.011</td><td>12.011</td></tr> <tr><td>7.5</td><td>12.008</td><td>12.008</td><td>12.008</td></tr> <tr><td>10.0</td><td>12.006</td><td>12.006</td><td>12.006</td></tr> <tr><td>12.5</td><td>12.003</td><td>12.003</td><td>12.003</td></tr> <tr><td>13.8</td><td>12.002</td><td>12.002</td><td>12.002</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	12.017	12.017	12.017	2.5	12.014	12.014	12.014	5.0	12.011	12.011	12.011	7.5	12.008	12.008	12.008	10.0	12.006	12.006	12.006	12.5	12.003	12.003	12.003	13.8	12.002	12.002	12.002	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	12.017	12.017	12.017																																																			
2.5	12.014	12.014	12.014																																																			
5.0	12.011	12.011	12.011																																																			
7.5	12.008	12.008	12.008																																																			
10.0	12.006	12.006	12.006																																																			
12.5	12.003	12.003	12.003																																																			
13.8	12.002	12.002	12.002																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						




Model	LFA150F-12	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V12.5A		

Input Volt. 100 V
Cycle 1000 ms


Response. $t_1=t_2=50\mu\text{s}$. Typ



Min. Load (0A) ←→
Load 100% (12.5A)




4 ms/div




4 ms/div

Min. Load (0A) ←→
Load 50% (6.25A)



4 ms/div



4 ms/div




COSEL																																									
Model	LFA150F-12	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure C																																						
Object	+12V12.5A																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 100V</p> <p>-·-○-·- Input Volt. 230V</p> </div> <p style="text-align: center;">Ripple Voltage [mV]</p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>2.5</td><td>20</td><td>20</td></tr> <tr><td>5.0</td><td>20</td><td>20</td></tr> <tr><td>7.5</td><td>25</td><td>25</td></tr> <tr><td>10.0</td><td>30</td><td>30</td></tr> <tr><td>12.5</td><td>30</td><td>30</td></tr> <tr><td>13.8</td><td>40</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 230 [V]	0.0	10	10	2.5	20	20	5.0	20	20	7.5	25	25	10.0	30	30	12.5	30	30	13.8	40	40	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 100 [V]	Input Volt. 230 [V]																																							
0.0	10	10																																							
2.5	20	20																																							
5.0	20	20																																							
7.5	25	25																																							
10.0	30	30																																							
12.5	30	30																																							
13.8	40	40																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<div style="text-align: center;"> <p>T1: Due to AC Input Line</p> <p>T2: Due to Switching</p> </div> <p style="text-align: center;">Ripple [mVp-p]</p> <p style="text-align: center;">T1</p> <p style="text-align: center;">T2</p>																																									
<p>Fig. Complex Ripple Wave Form</p>																																									



Model	LFA150F-12
Item	Ripple-Noise
Object	+12V12.5A

Temperature 25°C
Testing Circuitry Figure C

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.0	30	30
2.5	45	45
5.0	50	50
7.5	60	60
10.0	65	65
12.5	70	70
13.8	70	70
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.




Fig. Complex Ripple Wave Form



<p>Model LFA150F-12</p> <p>Item Ripple Voltage (by Ambient Temp.)</p> <p>Object +12V12.5A</p>		<p>Testing Circuitry Figure C</p>																																												
<p>1.Graph</p> <p> ---□--- Input Volt. 100V —△— Input Volt. 230V </p> <p>Y-axis: Ripple Voltage [mV] (0 to 200) X-axis: Ambient Temperature [°C] (-40 to 60) Load 100 %</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>50</td><td>50</td></tr> <tr><td>-10</td><td>45</td><td>45</td></tr> <tr><td>0</td><td>40</td><td>40</td></tr> <tr><td>25</td><td>30</td><td>30</td></tr> <tr><td>40</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 230 [V]	-30	50	50	-10	45	45	0	40	40	25	30	30	40	30	30	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																													
	Input Volt. 100 [V]	Input Volt. 230 [V]																																												
-30	50	50																																												
-10	45	45																																												
0	40	40																																												
25	30	30																																												
40	30	30																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
<p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																														




Model	LFA150F-12
Item	Ambient Temperature Drift
Object	+12V12.5A

Testing Circuitry Figure A

1.Graph

—△— Input Volt. 100V
 - - - □ - - - Input Volt. 200V
 - · - ○ - · - - Input Volt. 230V



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-20	11.973	11.973	11.974
-10	11.993	11.993	11.993
0	11.996	11.996	11.996
10	11.999	12.000	12.000
20	12.002	12.002	12.002
25	12.003	12.003	12.003
30	12.004	12.004	12.004
40	12.004	12.004	12.004
50	12.002	12.001	12.001
60	11.999	11.999	11.998
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



COSEL		
Model	LFA150F-12	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V12.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 40°C

Input Voltage : 85 - 264V

Load Current : 0 - 12.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	40	85	0	12.019	±13	±0.1
Minimum Voltage	-10	85	12.5	11.993		




COSEL																								
Model	LFA150F-12	Temperature 25°C Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+12V12.5A																							
1.Graph <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 100V Load 100%</p>		2.Values <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.005</td></tr> <tr><td>0.5</td><td>12.003</td></tr> <tr><td>1.0</td><td>12.003</td></tr> <tr><td>2.0</td><td>12.003</td></tr> <tr><td>3.0</td><td>12.003</td></tr> <tr><td>4.0</td><td>12.003</td></tr> <tr><td>5.0</td><td>12.003</td></tr> <tr><td>6.0</td><td>12.003</td></tr> <tr><td>7.0</td><td>12.003</td></tr> <tr><td>8.0</td><td>12.003</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.005	0.5	12.003	1.0	12.003	2.0	12.003	3.0	12.003	4.0	12.003	5.0	12.003	6.0	12.003	7.0	12.003	8.0	12.003
Time since start [H]	Output Voltage [V]																							
0.0	12.005																							
0.5	12.003																							
1.0	12.003																							
2.0	12.003																							
3.0	12.003																							
4.0	12.003																							
5.0	12.003																							
6.0	12.003																							
7.0	12.003																							
8.0	12.003																							
* The characteristic of AC230V is equal.																								




Model	LFA150F-12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V12.5A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		210.5	9.0	219.5	30.5	11.5
230 V		191.5	9.5	201.0	34.5	11.5





Model		LFA150F-12	Temperature		25°C																																
Item		Hold-Up Time	Testing Circuitry		Figure A																																
Object		+12V12.5A																																			
1.Graph			2.Values																																		
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>60</td><td>26</td></tr> <tr><td>85</td><td>62</td><td>28</td></tr> <tr><td>100</td><td>63</td><td>30</td></tr> <tr><td>120</td><td>65</td><td>31</td></tr> <tr><td>200</td><td>70</td><td>34</td></tr> <tr><td>230</td><td>71</td><td>35</td></tr> <tr><td>264</td><td>72</td><td>36</td></tr> <tr><td>280</td><td>73</td><td>36</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	60	26	85	62	28	100	63	30	120	65	31	200	70	34	230	71	35	264	72	36	280	73	36	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																				
	Load 50%	Load 100%																																			
75	60	26																																			
85	62	28																																			
100	63	30																																			
120	65	31																																			
200	70	34																																			
230	71	35																																			
264	72	36																																			
280	73	36																																			
--	-	-																																			
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																					



Model		LFA150F-12		Temperature 25°C																																																				
Item		Instantaneous Interruption Compensation		Testing Circuitry Figure A																																																				
Object		+12V12.5A																																																						
1.Graph		—△— Input Volt. 100V - - - □ - - - Input Volt. 200V ···○··· Input Volt. 230V		2.Values																																																				
Instantaneous Compensation Time [ms]			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.5</td><td>131</td><td>163</td><td>164</td></tr> <tr><td>5.0</td><td>71</td><td>86</td><td>88</td></tr> <tr><td>7.5</td><td>47</td><td>56</td><td>55</td></tr> <tr><td>10.0</td><td>37</td><td>39</td><td>40</td></tr> <tr><td>12.5</td><td>29</td><td>33</td><td>34</td></tr> <tr><td>13.8</td><td>26</td><td>30</td><td>31</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	2.5	131	163	164	5.0	71	86	88	7.5	47	56	55	10.0	37	39	40	12.5	29	33	34	13.8	26	30	31	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
			Load Current [A]	Time [ms]																																																				
				Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
			0.0	-	-	-																																																		
			2.5	131	163	164																																																		
			5.0	71	86	88																																																		
			7.5	47	56	55																																																		
			10.0	37	39	40																																																		
			12.5	29	33	34																																																		
			13.8	26	30	31																																																		
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



COSEL																																								
Model	LFA150F-12																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+12V12.5A																																							
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>49</td><td>64</td></tr> <tr><td>-10</td><td>49</td><td>65</td></tr> <tr><td>0</td><td>49</td><td>66</td></tr> <tr><td>10</td><td>50</td><td>67</td></tr> <tr><td>20</td><td>51</td><td>67</td></tr> <tr><td>25</td><td>51</td><td>68</td></tr> <tr><td>30</td><td>51</td><td>69</td></tr> <tr><td>40</td><td>52</td><td>69</td></tr> <tr><td>50</td><td>52</td><td>70</td></tr> <tr><td>60</td><td>53</td><td>70</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	49	64	-10	49	65	0	49	66	10	50	67	20	51	67	25	51	68	30	51	69	40	52	69	50	52	70	60	53	70	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-20	49	64																																						
-10	49	65																																						
0	49	66																																						
10	50	67																																						
20	51	67																																						
25	51	68																																						
30	51	69																																						
40	52	69																																						
50	52	70																																						
60	53	70																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								




COSEL																																												
Model	LFA150F-12	Temperature	25°C																																									
Item	Overcurrent Protection	Testing Circuitry	Figure A																																									
Object	+12V12.5A																																											
<p>1. Graph</p> <div style="text-align: right;"> <p>— Input Volt. 100V</p> <p>— Input Volt. 230V</p> </div> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>14.21</td><td>14.20</td></tr> <tr><td>11.4</td><td>15.43</td><td>15.35</td></tr> <tr><td>10.8</td><td>14.21</td><td>14.20</td></tr> <tr><td>9.6</td><td>15.41</td><td>15.33</td></tr> <tr><td>8.4</td><td>15.54</td><td>15.43</td></tr> <tr><td>7.2</td><td>15.59</td><td>15.46</td></tr> <tr><td>6.0</td><td>15.61</td><td>15.46</td></tr> <tr><td>4.8</td><td>15.60</td><td>15.47</td></tr> <tr><td>3.6</td><td>15.70</td><td>15.63</td></tr> <tr><td>2.4</td><td>15.84</td><td>15.79</td></tr> <tr><td>1.2</td><td>15.97</td><td>15.92</td></tr> <tr><td>0.0</td><td>15.58</td><td>15.70</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	12.0	14.21	14.20	11.4	15.43	15.35	10.8	14.21	14.20	9.6	15.41	15.33	8.4	15.54	15.43	7.2	15.59	15.46	6.0	15.61	15.46	4.8	15.60	15.47	3.6	15.70	15.63	2.4	15.84	15.79	1.2	15.97	15.92	0.0	15.58	15.70
Output Voltage [V]	Load Current [A]																																											
	Input Volt. 100[V]	Input Volt. 230[V]																																										
12.0	14.21	14.20																																										
11.4	15.43	15.35																																										
10.8	14.21	14.20																																										
9.6	15.41	15.33																																										
8.4	15.54	15.43																																										
7.2	15.59	15.46																																										
6.0	15.61	15.46																																										
4.8	15.60	15.47																																										
3.6	15.70	15.63																																										
2.4	15.84	15.79																																										
1.2	15.97	15.92																																										
0.0	15.58	15.70																																										



Model	LFA150F-12
Item	Overvoltage Protection
Object	+12V12.5A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-20	14.91	14.91
-10	15.02	15.02
0	15.14	15.14
10	15.26	15.26
20	15.31	15.26
25	15.31	15.31
30	15.31	15.31
40	15.43	15.43
50	15.55	15.55
60	15.60	15.60
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)




Figure C