



DATA SHEET		Date	18-Feb-08
Model	LGA240A-24	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Y.Ishikawa



Frequency [MHz]	Meter Reading (Ave.) [dBμV]	Meter Reading (QP) [dBμV]	Factor [dB]	Level(Ave.) [dBμV]	Level(QP) [dBμV]	Line	Limit(Ave.) [dBμV]	Limit(QP) [dBμV]	Margin(Ave.) [dB]	Margin(QP) [dB]
0.2675	28.7	31.8	10	38.7	41.8	VA	51.2	61.2	12.5	19.4
19.5586	22.3	27.8	10.8	33.1	38.6	VA	50	60	16.9	21.4
0.2678	30.1	33.7	10	40.1	43.7	VB	51.2	61.2	11.1	17.5
0.5331	26.7	28	10.1	36.8	38.1	VB	46	56	9.2	17.9
0.9356	24.5	25	10.1	34.6	35.1	VB	46	56	11.4	20.9
2.0051	20.6	23.3	10.2	30.8	33.5	VB	46	56	15.2	22.5



Frequency [MHz]	Meter Reading (QP) [dBμV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBμV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBμV/m]	Margin [dB]
36.649	50.4	BL	14.9	-32.2	33.1	123	102	Vert.	40	6.9
41.622	53	BL	12.1	-32.2	32.9	29	100	Vert.	40	7.1

## DATA SHEET

Model	Circuit used for measurement
Test	EMI Line conduction & Radiated emission

### 1. Line conduction



### 2. Radiated emission

