



TEST DATA OF LGA75A-12

Regulated DC Power Supply
April 4, 2008

Approved by : Yoshiaki Shimizu
Yoshiaki Shimizu Design Manager

Prepared by : Yousuke Murata
Yousuke Murata Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Ovvervoltage Protection	23
24.Figure of Testing Circuitry	24


(Final Page 25)

COSEL

Model	LGA75A-12																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr> <tr> <th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr> </thead> <tbody> <tr> <td>0.00</td><td>0.058</td><td>0.059</td><td>0.059</td></tr> <tr> <td>1.20</td><td>0.422</td><td>0.380</td><td>0.324</td></tr> <tr> <td>2.40</td><td>0.749</td><td>0.667</td><td>0.555</td></tr> <tr> <td>3.60</td><td>1.082</td><td>0.959</td><td>0.789</td></tr> <tr> <td>4.80</td><td>1.413</td><td>1.252</td><td>1.024</td></tr> <tr> <td>6.00</td><td>1.744</td><td>1.535</td><td>1.252</td></tr> <tr> <td>6.30</td><td>1.827</td><td>1.613</td><td>1.317</td></tr> <tr> <td>6.93</td><td>2.000</td><td>1.764</td><td>1.436</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.058	0.059	0.059	1.20	0.422	0.380	0.324	2.40	0.749	0.667	0.555	3.60	1.082	0.959	0.789	4.80	1.413	1.252	1.024	6.00	1.744	1.535	1.252	6.30	1.827	1.613	1.317	6.93	2.000	1.764	1.436	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	0.058	0.059	0.059																																																			
1.20	0.422	0.380	0.324																																																			
2.40	0.749	0.667	0.555																																																			
3.60	1.082	0.959	0.789																																																			
4.80	1.413	1.252	1.024																																																			
6.00	1.744	1.535	1.252																																																			
6.30	1.827	1.613	1.317																																																			
6.93	2.000	1.764	1.436																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LGA75A-12																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																			
Object	—	—	—																																			
1.Graph	—△— Input Volt. 85V ---□--- Input Volt. 100V -·○--- Input Volt. 132V	2.Values																																				
<table border="1"> <caption>Data points from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (85V)</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (132V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1.7</td><td>2.0</td><td>2.6</td></tr> <tr><td>1.20</td><td>18.8</td><td>18.9</td><td>19.9</td></tr> <tr><td>2.40</td><td>35.4</td><td>35.5</td><td>36.3</td></tr> <tr><td>3.60</td><td>52.3</td><td>52.2</td><td>52.8</td></tr> <tr><td>4.80</td><td>69.5</td><td>69.2</td><td>69.6</td></tr> <tr><td>6.00</td><td>87.0</td><td>86.7</td><td>87.0</td></tr> <tr><td>6.30</td><td>91.5</td><td>90.9</td><td>90.9</td></tr> <tr><td>6.93</td><td>100.8</td><td>100.2</td><td>100.0</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (85V)	Input Power [W] (100V)	Input Power [W] (132V)	0.00	1.7	2.0	2.6	1.20	18.8	18.9	19.9	2.40	35.4	35.5	36.3	3.60	52.3	52.2	52.8	4.80	69.5	69.2	69.6	6.00	87.0	86.7	87.0	6.30	91.5	90.9	90.9	6.93	100.8	100.2	100.0
Load Current [A]	Input Power [W] (85V)	Input Power [W] (100V)	Input Power [W] (132V)																																			
0.00	1.7	2.0	2.6																																			
1.20	18.8	18.9	19.9																																			
2.40	35.4	35.5	36.3																																			
3.60	52.3	52.2	52.8																																			
4.80	69.5	69.2	69.6																																			
6.00	87.0	86.7	87.0																																			
6.30	91.5	90.9	90.9																																			
6.93	100.8	100.2	100.0																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																						

COSEL

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	82.3	81.9
80	82.7	82.5
85	82.9	82.9
90	83.0	83.1
100	82.9	83.4
110	82.5	83.6
120	82.2	83.6
132	81.6	83.5
140	81.2	83.3

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	LGA75A-12																																	
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																															
Object	_____																																	
1.Graph	<p>—▲— Input Volt. 85V - - □ - - Input Volt. 100V - - ○ - - Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [85V] (%)</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [132V] (%)</th> </tr> </thead> <tbody> <tr><td>1.20</td><td>78.0</td><td>77.5</td><td>73.6</td></tr> <tr><td>2.40</td><td>82.0</td><td>81.9</td><td>80.0</td></tr> <tr><td>3.60</td><td>83.0</td><td>83.2</td><td>82.2</td></tr> <tr><td>4.80</td><td>83.2</td><td>83.5</td><td>83.1</td></tr> <tr><td>6.00</td><td>83.0</td><td>83.3</td><td>83.0</td></tr> <tr><td>6.30</td><td>82.9</td><td>83.4</td><td>83.4</td></tr> <tr><td>6.93</td><td>82.7</td><td>83.2</td><td>83.3</td></tr> </tbody> </table>	Load Current [A]	Efficiency [85V] (%)	Efficiency [100V] (%)	Efficiency [132V] (%)	1.20	78.0	77.5	73.6	2.40	82.0	81.9	80.0	3.60	83.0	83.2	82.2	4.80	83.2	83.5	83.1	6.00	83.0	83.3	83.0	6.30	82.9	83.4	83.4	6.93	82.7	83.2	83.3	2.Values
Load Current [A]	Efficiency [85V] (%)	Efficiency [100V] (%)	Efficiency [132V] (%)																															
1.20	78.0	77.5	73.6																															
2.40	82.0	81.9	80.0																															
3.60	83.0	83.2	82.2																															
4.80	83.2	83.5	83.1																															
6.00	83.0	83.3	83.0																															
6.30	82.9	83.4	83.4																															
6.93	82.7	83.2	83.3																															

Note: Slanted line shows the range of the rated load current.


Load Current [A]	Efficiency [%]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	-	-	-
1.20	78.0	77.5	73.6
2.40	82.0	81.9	80.0
3.60	83.0	83.2	82.2
4.80	83.2	83.5	83.1
6.00	83.0	83.3	83.0
6.30	82.9	83.4	83.4
6.93	82.7	83.2	83.3
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	LGA75A-12																																
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																															
Object	<hr/>																																
1. Graph																																	
		2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.577</td><td>0.611</td></tr> <tr><td>80</td><td>0.567</td><td>0.598</td></tr> <tr><td>85</td><td>0.559</td><td>0.587</td></tr> <tr><td>90</td><td>0.551</td><td>0.578</td></tr> <tr><td>100</td><td>0.537</td><td>0.562</td></tr> <tr><td>110</td><td>0.525</td><td>0.547</td></tr> <tr><td>120</td><td>0.513</td><td>0.535</td></tr> <tr><td>132</td><td>0.502</td><td>0.522</td></tr> <tr><td>140</td><td>0.495</td><td>0.514</td></tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.577	0.611	80	0.567	0.598	85	0.559	0.587	90	0.551	0.578	100	0.537	0.562	110	0.525	0.547	120	0.513	0.535	132	0.502	0.522	140	0.495	0.514
Input Voltage [V]	Power Factor																																
	Load 50%	Load 100%																															
75	0.577	0.611																															
80	0.567	0.598																															
85	0.559	0.587																															
90	0.551	0.578																															
100	0.537	0.562																															
110	0.525	0.547																															
120	0.513	0.535																															
132	0.502	0.522																															
140	0.495	0.514																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	

COSEL

Model	LGA75A-12																																																							
Item	Power Factor (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																					
Object	—	—	—																																																					
1.Graph	—△— Input Volt. 85V ---□--- Input Volt. 100V -·○-· Input Volt. 132V	2.Values																																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.352</td><td>0.338</td><td>0.331</td></tr> <tr><td>1.20</td><td>0.523</td><td>0.497</td><td>0.464</td></tr> <tr><td>2.40</td><td>0.555</td><td>0.530</td><td>0.495</td></tr> <tr><td>3.60</td><td>0.567</td><td>0.543</td><td>0.506</td></tr> <tr><td>4.80</td><td>0.577</td><td>0.552</td><td>0.514</td></tr> <tr><td>6.00</td><td>0.586</td><td>0.563</td><td>0.524</td></tr> <tr><td>6.30</td><td>0.587</td><td>0.562</td><td>0.522</td></tr> <tr><td>6.93</td><td>0.592</td><td>0.567</td><td>0.526</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.352	0.338	0.331	1.20	0.523	0.497	0.464	2.40	0.555	0.530	0.495	3.60	0.567	0.543	0.506	4.80	0.577	0.552	0.514	6.00	0.586	0.563	0.524	6.30	0.587	0.562	0.522	6.93	0.592	0.567	0.526	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0.00	0.352	0.338	0.331																																																					
1.20	0.523	0.497	0.464																																																					
2.40	0.555	0.530	0.495																																																					
3.60	0.567	0.543	0.506																																																					
4.80	0.577	0.552	0.514																																																					
6.00	0.586	0.563	0.524																																																					
6.30	0.587	0.562	0.522																																																					
6.93	0.592	0.567	0.526																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								

COSEL



Model	LGA75A-12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 100 [V]	Input Volt. 120 [V]	Input Volt. 132 [V]
(A)DEN-AN	0.08	0.10	0.12
(B)IEC60950	0.09	0.11	0.12

frequency 60Hz

Standards	Leakage Current [mA]		
	Input Volt. [V]	Input Volt. [V]	Input Volt. [V]
(B)IEC60950	-	-	-


2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	LGA75A-12																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+12V6.3A																																	
1. Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: --- □--- Load 50% —△— Load 100%</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>12.292</td><td>12.284</td></tr> <tr><td>80</td><td>12.291</td><td>12.284</td></tr> <tr><td>85</td><td>12.291</td><td>12.284</td></tr> <tr><td>90</td><td>12.290</td><td>12.284</td></tr> <tr><td>100</td><td>12.290</td><td>12.284</td></tr> <tr><td>110</td><td>12.290</td><td>12.284</td></tr> <tr><td>120</td><td>12.290</td><td>12.284</td></tr> <tr><td>132</td><td>12.290</td><td>12.283</td></tr> <tr><td>140</td><td>12.290</td><td>12.282</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	12.292	12.284	80	12.291	12.284	85	12.291	12.284	90	12.290	12.284	100	12.290	12.284	110	12.290	12.284	120	12.290	12.284	132	12.290	12.283	140	12.290	12.282
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	12.292	12.284																																
80	12.291	12.284																																
85	12.291	12.284																																
90	12.290	12.284																																
100	12.290	12.284																																
110	12.290	12.284																																
120	12.290	12.284																																
132	12.290	12.283																																
140	12.290	12.282																																

COSEL

Model	LGA75A-12																																																					
Item	Load Regulation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+12V6.3A																																																					
1.Graph	<p>—▲— Input Volt. 85V - - - □--- Input Volt. 100V - - - ○--- Input Volt. 132V</p> 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>12.292</td><td>12.292</td><td>12.292</td></tr> <tr> <td>1.20</td><td>12.289</td><td>12.289</td><td>12.290</td></tr> <tr> <td>2.40</td><td>12.287</td><td>12.288</td><td>12.288</td></tr> <tr> <td>3.60</td><td>12.286</td><td>12.286</td><td>12.287</td></tr> <tr> <td>4.80</td><td>12.284</td><td>12.285</td><td>12.285</td></tr> <tr> <td>6.00</td><td>12.283</td><td>12.283</td><td>12.283</td></tr> <tr> <td>6.30</td><td>12.282</td><td>12.283</td><td>12.283</td></tr> <tr> <td>6.93</td><td>12.281</td><td>12.282</td><td>12.282</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	12.292	12.292	12.292	1.20	12.289	12.289	12.290	2.40	12.287	12.288	12.288	3.60	12.286	12.286	12.287	4.80	12.284	12.285	12.285	6.00	12.283	12.283	12.283	6.30	12.282	12.283	12.283	6.93	12.281	12.282	12.282	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	12.292	12.292	12.292																																																			
1.20	12.289	12.289	12.290																																																			
2.40	12.287	12.288	12.288																																																			
3.60	12.286	12.286	12.287																																																			
4.80	12.284	12.285	12.285																																																			
6.00	12.283	12.283	12.283																																																			
6.30	12.282	12.283	12.283																																																			
6.93	12.281	12.282	12.282																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

COSEL


Model	LGA75A-12																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure C																																						
Object	+12V6.3A																																							
1. Graph																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>10</td><td>10</td></tr> <tr> <td>1.20</td><td>15</td><td>15</td></tr> <tr> <td>2.40</td><td>20</td><td>15</td></tr> <tr> <td>3.60</td><td>20</td><td>15</td></tr> <tr> <td>4.80</td><td>25</td><td>15</td></tr> <tr> <td>6.00</td><td>30</td><td>15</td></tr> <tr> <td>6.30</td><td>30</td><td>15</td></tr> <tr> <td>6.93</td><td>35</td><td>15</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	10	10	1.20	15	15	2.40	20	15	3.60	20	15	4.80	25	15	6.00	30	15	6.30	30	15	6.93	35	15	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.00	10	10																																						
1.20	15	15																																						
2.40	20	15																																						
3.60	20	15																																						
4.80	25	15																																						
6.00	30	15																																						
6.30	30	15																																						
6.93	35	15																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	LGA75A-12																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure C																																						
Object	+12V6.3A																																							
1. Graph																																								
		2. Values																																						
<p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>25</td></tr> <tr><td>1.20</td><td>25</td><td>30</td></tr> <tr><td>2.40</td><td>35</td><td>40</td></tr> <tr><td>3.60</td><td>45</td><td>45</td></tr> <tr><td>4.80</td><td>50</td><td>45</td></tr> <tr><td>6.00</td><td>55</td><td>50</td></tr> <tr><td>6.30</td><td>55</td><td>50</td></tr> <tr><td>6.93</td><td>60</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	10	25	1.20	25	30	2.40	35	40	3.60	45	45	4.80	50	45	6.00	55	50	6.30	55	50	6.93	60	50	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.00	10	25																																						
1.20	25	30																																						
2.40	35	40																																						
3.60	45	45																																						
4.80	50	45																																						
6.00	55	50																																						
6.30	55	50																																						
6.93	60	50																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
Fig. Complex Ripple Wave Form																																								

COSEL

Model	LGA75A-12	Testing Circuitry FigureC																												
Item	Ripple Voltage (by Ambient Temp.)																													
Object	+12V6.3A																													
1. Graph		2. Values																												
<p>Graph showing Ripple Voltage [mV] vs Ambient Temperature [°C]. The graph shows two curves: one for AC Input Line Ripple (T1) and one for Switching Ripple (T2). A slanted line indicates the rated ambient temperature range.</p> <p>Input Volt. 100V Input Load. 100%</p>		<table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>90</td></tr> <tr><td>-10</td><td>40</td></tr> <tr><td>0</td><td>40</td></tr> <tr><td>25</td><td>25</td></tr> <tr><td>50</td><td>20</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]	-30	90	-10	40	0	40	25	25	50	20	--	-	--	-	--	-	--	-	--	-	--	-	--	-	--	-
Ambient Temperature [°C]	Ripple Voltage [mV]																													
-30	90																													
-10	40																													
0	40																													
25	25																													
50	20																													
--	-																													
--	-																													
--	-																													
--	-																													
--	-																													
--	-																													
--	-																													
--	-																													
<p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p>																												

COSEL


Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	12.306	12.307	12.307
-10	12.302	12.302	12.302
0	12.298	12.299	12.298
10	12.294	12.295	12.295
20	12.291	12.291	12.291
25	12.288	12.289	12.289
30	12.286	12.286	12.286
40	12.282	12.282	12.282
50	12.272	12.272	12.272
60	12.263	12.263	12.263
--	-	-	-



Model	LGA75A-12	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V6.3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 ~ 50°C

Input Voltage : 85 ~ 132V

Load Current : 0 ~ 6.3A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	132	0	12.311	+20	± 0.2
Minimum Voltage	50	132	6.3	12.272		


COSEL

Model LGA75A-12

Item Time Lapse Drift

Object +12V6.3A

1. Graph

Temperature 25°C
Testing Circuitry Figure A

2. Values

Time since start [H]	Output Voltage [V]
0.0	12.294
0.5	12.279
1.0	12.279
2.0	12.280
3.0	12.280
4.0	12.280
5.0	12.280
6.0	12.280
7.0	12.280
8.0	12.279

COSEL


Model LGA75A-12

Item Rise and Fall Time

Object +12V6.3A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		70.3	9.0	79.3	54.4	11.8	
100 %		70.0	8.8	78.8	25.8	6.2	



COSEL

Model	LGA75A-12	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time																																		
Object	+12V6.3A																																		
1. Graph			2. Values																																
<p>Graph showing Hold-Up Time [ms] vs Input Voltage [V]. The Y-axis is logarithmic, ranging from 1 to 1000 ms. The X-axis ranges from 70 to 150 V. Two curves are plotted: Load 50% (dashed line with squares) and Load 100% (solid line with triangles). Both curves show an increase in hold-up time as input voltage decreases below the rated range (indicated by a slanted line between ~85V and ~110V).</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>21</td><td>9</td></tr> <tr><td>80</td><td>27</td><td>12</td></tr> <tr><td>85</td><td>33</td><td>15</td></tr> <tr><td>90</td><td>40</td><td>19</td></tr> <tr><td>100</td><td>55</td><td>26</td></tr> <tr><td>110</td><td>72</td><td>35</td></tr> <tr><td>120</td><td>90</td><td>44</td></tr> <tr><td>132</td><td>115</td><td>56</td></tr> <tr><td>140</td><td>132</td><td>65</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	21	9	80	27	12	85	33	15	90	40	19	100	55	26	110	72	35	120	90	44	132	115	56	140	132	65
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	21	9																																	
80	27	12																																	
85	33	15																																	
90	40	19																																	
100	55	26																																	
110	72	35																																	
120	90	44																																	
132	115	56																																	
140	132	65																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	LGA75A-12																																																					
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+12V6.3A																																																					
1.Graph	<p>—▲— Input Volt. 85V - - □--- Input Volt. 100V - - ○--- Input Volt. 132V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>1.20</td><td>88</td><td>140</td><td>288</td></tr> <tr> <td>2.40</td><td>44</td><td>73</td><td>152</td></tr> <tr> <td>3.60</td><td>29</td><td>48</td><td>101</td></tr> <tr> <td>4.80</td><td>21</td><td>35</td><td>76</td></tr> <tr> <td>6.00</td><td>14</td><td>28</td><td>60</td></tr> <tr> <td>6.30</td><td>14</td><td>26</td><td>56</td></tr> <tr> <td>6.93</td><td>13</td><td>23</td><td>51</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	-	-	-	1.20	88	140	288	2.40	44	73	152	3.60	29	48	101	4.80	21	35	76	6.00	14	28	60	6.30	14	26	56	6.93	13	23	51	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	-	-	-																																																			
1.20	88	140	288																																																			
2.40	44	73	152																																																			
3.60	29	48	101																																																			
4.80	21	35	76																																																			
6.00	14	28	60																																																			
6.30	14	26	56																																																			
6.93	13	23	51																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LGA75A-12																																								
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																							
Object	+12V6.3A																																								
1. Graph																																									
			2. Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>60</td><td>66</td> </tr> <tr> <td>-10</td><td>59</td><td>65</td> </tr> <tr> <td>0</td><td>59</td><td>65</td> </tr> <tr> <td>10</td><td>58</td><td>65</td> </tr> <tr> <td>20</td><td>58</td><td>65</td> </tr> <tr> <td>25</td><td>58</td><td>64</td> </tr> <tr> <td>30</td><td>58</td><td>64</td> </tr> <tr> <td>40</td><td>58</td><td>64</td> </tr> <tr> <td>50</td><td>58</td><td>64</td> </tr> <tr> <td>60</td><td>57</td><td>64</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	60	66	-10	59	65	0	59	65	10	58	65	20	58	65	25	58	64	30	58	64	40	58	64	50	58	64	60	57	64	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	60	66																																							
-10	59	65																																							
0	59	65																																							
10	58	65																																							
20	58	65																																							
25	58	64																																							
30	58	64																																							
40	58	64																																							
50	58	64																																							
60	57	64																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

COSEL

Model	LGA75A-12																																																									
Item	Overcurrent Protection																																																									
Object	+12V6.3A																																																									
1.Graph	<p>Legend: Input Volt. 85V, Input Volt. 100V, Input Volt. 132V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																									
Temperature Testing Circuitry	25°C Figure A																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>7.69</td><td>7.62</td><td>7.64</td></tr> <tr><td>11.4</td><td>7.70</td><td>7.64</td><td>7.66</td></tr> <tr><td>10.8</td><td>7.72</td><td>7.67</td><td>7.70</td></tr> <tr><td>9.6</td><td>7.77</td><td>7.73</td><td>7.78</td></tr> <tr><td>8.4</td><td>7.81</td><td>7.79</td><td>7.85</td></tr> <tr><td>7.2</td><td>7.86</td><td>7.84</td><td>7.89</td></tr> <tr><td>6.0</td><td>7.96</td><td>7.96</td><td>8.00</td></tr> <tr><td>4.8</td><td>7.96</td><td>7.97</td><td>8.09</td></tr> <tr><td>3.6</td><td>8.02</td><td>8.03</td><td>8.18</td></tr> <tr><td>2.4</td><td>8.06</td><td>8.09</td><td>8.24</td></tr> <tr><td>1.2</td><td>8.07</td><td>8.09</td><td>8.18</td></tr> <tr><td>0.0</td><td>7.85</td><td>7.82</td><td>7.88</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	12.0	7.69	7.62	7.64	11.4	7.70	7.64	7.66	10.8	7.72	7.67	7.70	9.6	7.77	7.73	7.78	8.4	7.81	7.79	7.85	7.2	7.86	7.84	7.89	6.0	7.96	7.96	8.00	4.8	7.96	7.97	8.09	3.6	8.02	8.03	8.18	2.4	8.06	8.09	8.24	1.2	8.07	8.09	8.18	0.0	7.85	7.82	7.88
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
12.0	7.69	7.62	7.64																																																							
11.4	7.70	7.64	7.66																																																							
10.8	7.72	7.67	7.70																																																							
9.6	7.77	7.73	7.78																																																							
8.4	7.81	7.79	7.85																																																							
7.2	7.86	7.84	7.89																																																							
6.0	7.96	7.96	8.00																																																							
4.8	7.96	7.97	8.09																																																							
3.6	8.02	8.03	8.18																																																							
2.4	8.06	8.09	8.24																																																							
1.2	8.07	8.09	8.18																																																							
0.0	7.85	7.82	7.88																																																							

COSEL


Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	15.32	15.32	15.32
-10	15.39	15.39	15.39
0	15.53	15.53	15.53
10	15.60	15.60	15.60
20	15.67	15.67	15.67
25	15.74	15.74	15.74
30	15.81	15.81	15.81
40	15.88	15.88	15.88
50	16.02	16.02	16.02
60	16.09	16.09	16.09
--	-	-	-

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950 -1)


COSEL

Figure C