


DATA SHEET		Date	28-Feb-08
Model	LGA75A-5	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	Y.Murata

LINE CONDUCTION

Model Name : LGA75A-5
 Model No. :
 Serial No. :
 Points : 5
 Detector : PEAK/QP/Ave.
 Line Mode : VA/VB
 Power Supply : AC 100V 60Hz
 Limit1: [EN 55022] Class B(QP)
 Limit2: [EN 55022] Class B(Ave.)

Temp. : 25degreeC
 Humi. : 45%
 Date : 2008/2/28 9:32
 Test Equip. : R3132,ESPC
 Load Line : 150mm
 Comment :




Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]
0.1506	27.3	45.5	9.8	37.1	55.3	VA	56	66	18.9	10.7
0.2749	19.3	32.7	9.8	29.1	42.5	VB	51	61	21.9	18.5
0.3691	16.4	27	9.9	26.3	36.9	VA	48.5	58.5	22.2	21.6
3.8778	18.6	25.7	10	28.6	35.7	VA	46	56	17.4	20.3
11.9032	26.8	29.6	10.1	36.9	39.7	VB	50	60	13.1	20.3

RADIATED EMISSION

Model Name : LGA75A-5
 Model No. :
 Serial No. :
 Points : 5
 Detector : PEAK/QP
 Polarization : Hori. & Vert.
 Power Supply : AC100V 60Hz
 Limit: [EN 55022] Class B<3m>

Temp. : 25 degreeC
 Humi. : 45 %
 Date : 2008/2/28 16:51
 Test Equip. : R3132,ESPC
 Load Line : 150 mm
 Comment :



Frequency [MHz]	Meter Reading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]
41.87	48.3	BL	12	-32.2	28.1	213	101	Vert.	40	11.9
54.715	59.9	BL	5.8	-32.1	33.6	205	115	Vert.	40	6.4
66.756	55.3	BL	5	-32	28.3	90	113	Vert.	40	11.7

DATA SHEET

Model	Circuit used for measurement
Test	EMI Line conduction & Radiated emission

1. Line conduction



2. Radiated emission

