

TEST DATA OF LHA10F-15

Regulated DC Power Supply
February 2, 2022

Approved by : _____ Tetsukazu Okamoto

Design Manager

Prepared by : _____ Naofumi Nakada

Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple-Noise (by Load Current)	9
10.Ambient Temperature Drift	10
11.Rise and Fall Time	11
12.Hold-Up Time	12
13.Instantaneous Interruption Compensation	13
14.Minimum Input Voltage for Regulated Output Voltage	14
15.Overcurrent Protection	15
16.Overvoltage Protection	16
17.Figure of Testing Circuitry	17

(Final Page 18)

COSEL

Model	LHA10F-15																																																			
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																	
Object	_____	_____	_____																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.008</td><td>0.006</td><td>0.005</td></tr> <tr><td>0.10</td><td>0.049</td><td>0.032</td><td>0.029</td></tr> <tr><td>0.20</td><td>0.084</td><td>0.051</td><td>0.049</td></tr> <tr><td>0.30</td><td>0.116</td><td>0.074</td><td>0.067</td></tr> <tr><td>0.40</td><td>0.146</td><td>0.094</td><td>0.085</td></tr> <tr><td>0.50</td><td>0.176</td><td>0.115</td><td>0.101</td></tr> <tr><td>0.60</td><td>0.203</td><td>0.128</td><td>0.118</td></tr> <tr><td>0.70</td><td>0.233</td><td>0.153</td><td>0.133</td></tr> <tr><td>0.77</td><td>0.252</td><td>0.159</td><td>0.143</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.008	0.006	0.005	0.10	0.049	0.032	0.029	0.20	0.084	0.051	0.049	0.30	0.116	0.074	0.067	0.40	0.146	0.094	0.085	0.50	0.176	0.115	0.101	0.60	0.203	0.128	0.118	0.70	0.233	0.153	0.133	0.77	0.252	0.159	0.143	--	-	-	-	--	-	-	-	2.Values		
Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																	
0.00	0.008	0.006	0.005																																																	
0.10	0.049	0.032	0.029																																																	
0.20	0.084	0.051	0.049																																																	
0.30	0.116	0.074	0.067																																																	
0.40	0.146	0.094	0.085																																																	
0.50	0.176	0.115	0.101																																																	
0.60	0.203	0.128	0.118																																																	
0.70	0.233	0.153	0.133																																																	
0.77	0.252	0.159	0.143																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Note: Slanted line shows the range of the rated load current.

COSEL




Model	LHA10F-15																																																					
Item	Efficiency (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____	_____	_____																																																			
1.Graph																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.10</td><td>74.7</td><td>72.5</td><td>71.0</td></tr> <tr> <td>0.20</td><td>78.5</td><td>77.7</td><td>77.1</td></tr> <tr> <td>0.30</td><td>80.6</td><td>80.6</td><td>80.6</td></tr> <tr> <td>0.40</td><td>80.7</td><td>80.7</td><td>80.7</td></tr> <tr> <td>0.50</td><td>81.4</td><td>81.6</td><td>81.7</td></tr> <tr> <td>0.60</td><td>82.0</td><td>82.7</td><td>82.7</td></tr> <tr> <td>0.70</td><td>81.2</td><td>83.3</td><td>83.3</td></tr> <tr> <td>0.77</td><td>80.9</td><td>83.0</td><td>83.2</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.10	74.7	72.5	71.0	0.20	78.5	77.7	77.1	0.30	80.6	80.6	80.6	0.40	80.7	80.7	80.7	0.50	81.4	81.6	81.7	0.60	82.0	82.7	82.7	0.70	81.2	83.3	83.3	0.77	80.9	83.0	83.2	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.10	74.7	72.5	71.0																																																			
0.20	78.5	77.7	77.1																																																			
0.30	80.6	80.6	80.6																																																			
0.40	80.7	80.7	80.7																																																			
0.50	81.4	81.6	81.7																																																			
0.60	82.0	82.7	82.7																																																			
0.70	81.2	83.3	83.3																																																			
0.77	80.9	83.0	83.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LHA10F-15																																																					
Item	Power Factor (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____	_____	_____																																																			
1.Graph	—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V																																																					
	<p>Power Factor</p> <p>Load Current [A]</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.311</td><td>0.252</td><td>0.190</td></tr> <tr> <td>0.10</td><td>0.416</td><td>0.330</td><td>0.321</td></tr> <tr> <td>0.20</td><td>0.455</td><td>0.363</td><td>0.351</td></tr> <tr> <td>0.30</td><td>0.484</td><td>0.391</td><td>0.372</td></tr> <tr> <td>0.40</td><td>0.507</td><td>0.403</td><td>0.383</td></tr> <tr> <td>0.50</td><td>0.527</td><td>0.411</td><td>0.396</td></tr> <tr> <td>0.60</td><td>0.543</td><td>0.429</td><td>0.408</td></tr> <tr> <td>0.70</td><td>0.558</td><td>0.435</td><td>0.417</td></tr> <tr> <td>0.77</td><td>0.567</td><td>0.440</td><td>0.424</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.311	0.252	0.190	0.10	0.416	0.330	0.321	0.20	0.455	0.363	0.351	0.30	0.484	0.391	0.372	0.40	0.507	0.403	0.383	0.50	0.527	0.411	0.396	0.60	0.543	0.429	0.408	0.70	0.558	0.435	0.417	0.77	0.567	0.440	0.424	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.311	0.252	0.190																																																			
0.10	0.416	0.330	0.321																																																			
0.20	0.455	0.363	0.351																																																			
0.30	0.484	0.391	0.372																																																			
0.40	0.507	0.403	0.383																																																			
0.50	0.527	0.411	0.396																																																			
0.60	0.543	0.429	0.408																																																			
0.70	0.558	0.435	0.417																																																			
0.77	0.567	0.440	0.424																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LHA10F-15	Temperature Testing Circuitry Figure A	25° C
Item	Inrush Current		
Object	_____		





Model	LHA10F-15	Temperature Testing Circuitry	25°C Figure B	
Item	Leakage Current			
Object	_____			

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure B-1	Both phases	0.03	0.09	0.09	Operation
		One of phases	0.05	0.13	0.13	Stand by
IEC62368-1	Figure B-2	Both phases	0.03	0.09	0.09	Operation
		One of phases	0.05	0.13	0.13	Stand by
	Figure B-3	Both phases	0.03	0.09	0.09	Operation
		One of phases	0.05	0.13	0.13	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	LHA10F-15																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+15V0.7A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: --- □--- Load 50% —△— Load 100%</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>15.037</td><td>15.035</td></tr> <tr> <td>90</td><td>15.037</td><td>15.035</td></tr> <tr> <td>100</td><td>15.037</td><td>15.035</td></tr> <tr> <td>120</td><td>15.038</td><td>15.036</td></tr> <tr> <td>200</td><td>15.038</td><td>15.036</td></tr> <tr> <td>230</td><td>15.038</td><td>15.036</td></tr> <tr> <td>264</td><td>15.038</td><td>15.037</td></tr> <tr> <td>280</td><td>15.038</td><td>15.037</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	15.037	15.035	90	15.037	15.035	100	15.037	15.035	120	15.038	15.036	200	15.038	15.036	230	15.038	15.036	264	15.038	15.037	280	15.038	15.037	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	15.037	15.035																																
90	15.037	15.035																																
100	15.037	15.035																																
120	15.038	15.036																																
200	15.038	15.036																																
230	15.038	15.036																																
264	15.038	15.037																																
280	15.038	15.037																																
--	-	-																																

COSEL




Model	LHA10F-15																																																						
Item	Load Regulation	Temperature Testing Circuitry	25°C Figure A																																																				
Object	+15V0.7A																																																						
1.Graph	<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 200V ---○--- Input Volt. 230V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.039</td><td>15.040</td><td>15.040</td></tr> <tr><td>0.10</td><td>15.038</td><td>15.038</td><td>15.038</td></tr> <tr><td>0.20</td><td>15.037</td><td>15.038</td><td>15.038</td></tr> <tr><td>0.30</td><td>15.037</td><td>15.038</td><td>15.038</td></tr> <tr><td>0.40</td><td>15.036</td><td>15.037</td><td>15.037</td></tr> <tr><td>0.50</td><td>15.036</td><td>15.037</td><td>15.037</td></tr> <tr><td>0.60</td><td>15.036</td><td>15.036</td><td>15.036</td></tr> <tr><td>0.70</td><td>15.035</td><td>15.036</td><td>15.036</td></tr> <tr><td>0.77</td><td>15.035</td><td>15.036</td><td>15.036</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	15.039	15.040	15.040	0.10	15.038	15.038	15.038	0.20	15.037	15.038	15.038	0.30	15.037	15.038	15.038	0.40	15.036	15.037	15.037	0.50	15.036	15.037	15.037	0.60	15.036	15.036	15.036	0.70	15.035	15.036	15.036	0.77	15.035	15.036	15.036	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	15.039	15.040	15.040																																																				
0.10	15.038	15.038	15.038																																																				
0.20	15.037	15.038	15.038																																																				
0.30	15.037	15.038	15.038																																																				
0.40	15.036	15.037	15.037																																																				
0.50	15.036	15.037	15.037																																																				
0.60	15.036	15.036	15.036																																																				
0.70	15.035	15.036	15.036																																																				
0.77	15.035	15.036	15.036																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.

COSEL

Model	LHA10F-15	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.7A		

Input Volt. 230 V
 Cycle 1000 ms




COSEL

Model	LHA10F-15
Item	Ripple-Noise(by Load Current)
Object	+15V0.7A

 Temperature 25°C
 Testing Circuitry Figure C

1.Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

 Note: Slanted line shows the range of the rated load current.
 T1: Due to AC Input Line
 T2: Due to Switching

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.00	10	90
0.10	10	15
0.20	15	10
0.30	15	10
0.40	35	10
0.50	40	30
0.60	40	30
0.70	45	35
0.77	50	35
--	-	-
--	-	-





Fig. Complex Ripple Wave Form

COSEL

Model	LHA10F-15
Item	Ambient Temperature Drift
Object	+15V0.7A



Testing Circuitry Figure A

2.Values


Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-20	14.991	14.992	14.992
-15	14.998	14.999	14.999
-10	15.004	15.005	15.006
0	15.017	15.018	15.018
25	15.035	15.036	15.036
40	15.041	15.042	15.042
50	15.043	15.045	15.045
55	15.045	15.046	15.046
60	15.047	15.048	15.048
70	15.048	15.049	15.049
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL


Model	LHA10F-15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.7A		

1. Graph



2. Values


Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		11.9	9.7	21.6	28.5	17.3	
230 V		11.3	8.7	20.0	182.3	18.8	



COSEL

Model	LHA10F-15	Temperature	25°C
Item	Hold-Up Time	Testing Circuitry	Figure A
Object	+15V0.7A		

1.Graph



2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	42	17
90	48	20
100	61	27
120	92	42
200	274	131
230	366	179
264	489	244
280	554	278
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	LHA10F-15																																																					
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+15V0.7A																																																					
1.Graph	<p style="text-align: center;"> △ Input Volt. 100V □ Input Volt. 200V ○ Input Volt. 230V </p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>200V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>0.10</td><td>150</td><td>1000</td><td>1200</td></tr> <tr><td>0.20</td><td>100</td><td>500</td><td>600</td></tr> <tr><td>0.30</td><td>80</td><td>300</td><td>350</td></tr> <tr><td>0.40</td><td>60</td><td>200</td><td>250</td></tr> <tr><td>0.50</td><td>50</td><td>150</td><td>200</td></tr> <tr><td>0.60</td><td>40</td><td>120</td><td>150</td></tr> <tr><td>0.70</td><td>30</td><td>100</td><td>120</td></tr> <tr><td>0.77</td><td>25</td><td>80</td><td>100</td></tr> </tbody> </table>	Load Current [A]	100V [ms]	200V [ms]	230V [ms]	0.10	150	1000	1200	0.20	100	500	600	0.30	80	300	350	0.40	60	200	250	0.50	50	150	200	0.60	40	120	150	0.70	30	100	120	0.77	25	80	100																	
Load Current [A]	100V [ms]	200V [ms]	230V [ms]																																																			
0.10	150	1000	1200																																																			
0.20	100	500	600																																																			
0.30	80	300	350																																																			
0.40	60	200	250																																																			
0.50	50	150	200																																																			
0.60	40	120	150																																																			
0.70	30	100	120																																																			
0.77	25	80	100																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.10</td><td>205</td><td>990</td><td>1162</td></tr> <tr><td>0.20</td><td>107</td><td>421</td><td>623</td></tr> <tr><td>0.30</td><td>72</td><td>307</td><td>423</td></tr> <tr><td>0.40</td><td>53</td><td>226</td><td>320</td></tr> <tr><td>0.50</td><td>42</td><td>179</td><td>258</td></tr> <tr><td>0.60</td><td>34</td><td>150</td><td>215</td></tr> <tr><td>0.70</td><td>27</td><td>131</td><td>179</td></tr> <tr><td>0.77</td><td>24</td><td>115</td><td>161</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.10	205	990	1162	0.20	107	421	623	0.30	72	307	423	0.40	53	226	320	0.50	42	179	258	0.60	34	150	215	0.70	27	131	179	0.77	24	115	161	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.10	205	990	1162																																																			
0.20	107	421	623																																																			
0.30	72	307	423																																																			
0.40	53	226	320																																																			
0.50	42	179	258																																																			
0.60	34	150	215																																																			
0.70	27	131	179																																																			
0.77	24	115	161																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


COSEL

Model LHA10F-15

Item Minimum Input Voltage
for Regulated Output Voltage

Object +15V0.7A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	31	56
-15	31	55
-10	31	55
0	30	54
25	30	51
40	30	50
50	30	50
55	30	50
60	30	50
70	30	50
--	-	-

COSEL

Model	LHA10F-15
Item	Overcurrent Protection
Object	+15V0.7A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

Overcurrent protection is Hiccup mode.

2. Values


Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
15.00	1.04	1.01
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

COSEL

Model	LHA10F-15
Item	Overshoot Protection
Object	+15V0.7A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-20	22.43	21.99
-15	22.38	21.98
-10	22.37	21.95
0	22.30	21.82
10	22.30	21.82
20	22.23	21.82
30	22.22	21.78
40	22.18	21.76
50	22.15	21.72
60	22.10	21.71
70	-	-

Note: Slanted line shows the range of the rated ambient temperature.




Figure A




Figure B-1 (DEN-AN)




Figure B-2 (IEC62368-1 refer to IEC60990 Fig.4)

COSEL





Figure B-3 (IEC62368-1 refer to IEC60990 Fig.5)



$C1 = 0.1 \mu F$
(Ceramic capacitor)

$C2 = 22 \mu F$
(Electrolytic capacitor)

Figure C