



DATA SHEET

Model	LHA30F-5	Date	10-Oct-19
Test	EMI Line conduction & Radiated emission	Temp.	25 degreeC
		Humid.	40 %RH
		Tested by	Y.Haginaka




Frequency MHz	Line	Level dB(μV)	Limit dB(μV)	Margin dB	Pass/Fail	Remark
		QP	AV	QP	AV	
0.636	N	40.7	39.9	56	46	15.3
19.805	N	47.4	36.5	60	50	12.6
0.254	L1	49.6	44.4	61.6	51.6	12
0.318	L1	46.5	43.5	59.8	49.8	13.3
0.891	L1	39.4	38.5	56	46	16.6




Frequency MHz	Polarization	Stability	Level dB(μV/m)	Limit dB(μV/m)	Margin dB	Pass/Fail	Height cm	Angle deg	Remark
			QP	QP	QP				
185.122	H	Stable	29.1	40	10.9	Pass	199.7	16.3	
34.931	V	Stable	29.1	40	10.9	Pass	100.2	345.2	

DATA SHEET		Date	10-Oct-19
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Y.Haginaka

1. Line conduction



2. Radiated emission



Conditions

Test : EMI
Model Name : LHA30F

Photographs of test set-up

1.LINE CONDUCTION



2.RADIATED EMISSION

