



DATA SHEET			Date	11-Oct-19
Model	LHA50F-48		Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission		Humid.	40 %RH
			Tested by	Y.Haginaka




Frequency	Line	Level		Limit		Margin		Pass/Fail	Remark
MHz		dB(μV)		dB(μV)		dB			
		QP	AV	QP	AV	QP	AV		
4.073	L1	41.2	27.9	56	46	14.8	18.1	Pass	
15.287	L1	42.6	31.4	60	50	17.4	18.6	Pass	




Frequency	Polarization	Stability	Level	Limit	Margin	Pass/Fail	Height	Angle	Remark
MHz			dB(μV/m)	dB(μV/m)	dB				
			QP	QP	QP		cm	deg	
179.446	H	Stable	33.1	40	6.9	Pass	146.6	218.6	
166.745	H	Stable	31.3	40	8.7	Pass	172.5	185.3	

DATA SHEET		Date	11-Oct-19
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Y.Haginaka

1. Line conduction



2. Radiated emission



Conditions

Test : EMI
Model Name : LHA50F

Photographs of test set-up

1.LINE CONDUCTION



2.RADIATED EMISSION

