



TEST DATA OF LHA75F-36

Regulated DC Power Supply
September 25, 2019

Approved by : Junya Kaneda
Junya Kaneda Design Manager

Prepared by : Shuto Takai
Shuto Takai Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple-Noise (by Load Current)	9
10.Ambient Temperature Drift	10
11.Rise and Fall Time	11
12.Hold-Up Time	12
13.Instantaneous Interruption Compensation	13
14.Minimum Input Voltage for Regulated Output Voltage	14
15.Overcurrent Protection	15
16.Overvoltage Protection	16
17.Figure of Testing Circuitry	17

(Final Page 18)

COSEL

Model	LHA75F-36
Item	Input Current (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values


Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	0.058	0.100	0.114
0.40	0.216	0.183	0.185
0.80	0.373	0.255	0.249
1.20	0.531	0.325	0.312
1.60	0.692	0.398	0.375
2.00	0.855	0.476	0.440
2.10	0.895	0.495	0.456
2.31	0.983	0.535	0.492
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL




Model	LHA75F-36																																																					
Item	Efficiency (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____	_____	_____																																																			
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Input Volt. 100V Input Volt. 200V Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.40</td><td>78.7</td><td>77.6</td><td>76.2</td></tr> <tr> <td>0.80</td><td>84.2</td><td>85.0</td><td>84.3</td></tr> <tr> <td>1.20</td><td>86.2</td><td>87.4</td><td>87.3</td></tr> <tr> <td>1.60</td><td>87.0</td><td>88.6</td><td>88.6</td></tr> <tr> <td>2.00</td><td>87.5</td><td>89.1</td><td>89.4</td></tr> <tr> <td>2.10</td><td>87.6</td><td>89.2</td><td>89.5</td></tr> <tr> <td>2.31</td><td>87.6</td><td>89.5</td><td>89.6</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.40	78.7	77.6	76.2	0.80	84.2	85.0	84.3	1.20	86.2	87.4	87.3	1.60	87.0	88.6	88.6	2.00	87.5	89.1	89.4	2.10	87.6	89.2	89.5	2.31	87.6	89.5	89.6	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.40	78.7	77.6	76.2																																																			
0.80	84.2	85.0	84.3																																																			
1.20	86.2	87.4	87.3																																																			
1.60	87.0	88.6	88.6																																																			
2.00	87.5	89.1	89.4																																																			
2.10	87.6	89.2	89.5																																																			
2.31	87.6	89.5	89.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LHA75F-36																																																					
Item	Power Factor (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph																																																						
—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V			2.Values																																																			
 <p>Note: Slanted line shows the range of the rated load current.</p>																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.230</td><td>0.050</td><td>0.045</td></tr> <tr> <td>0.40</td><td>0.861</td><td>0.514</td><td>0.449</td></tr> <tr> <td>0.80</td><td>0.931</td><td>0.676</td><td>0.604</td></tr> <tr> <td>1.20</td><td>0.957</td><td>0.770</td><td>0.698</td></tr> <tr> <td>1.60</td><td>0.969</td><td>0.827</td><td>0.763</td></tr> <tr> <td>2.00</td><td>0.975</td><td>0.860</td><td>0.806</td></tr> <tr> <td>2.10</td><td>0.977</td><td>0.867</td><td>0.815</td></tr> <tr> <td>2.31</td><td>0.979</td><td>0.879</td><td>0.830</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.230	0.050	0.045	0.40	0.861	0.514	0.449	0.80	0.931	0.676	0.604	1.20	0.957	0.770	0.698	1.60	0.969	0.827	0.763	2.00	0.975	0.860	0.806	2.10	0.977	0.867	0.815	2.31	0.979	0.879	0.830	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.230	0.050	0.045																																																			
0.40	0.861	0.514	0.449																																																			
0.80	0.931	0.676	0.604																																																			
1.20	0.957	0.770	0.698																																																			
1.60	0.969	0.827	0.763																																																			
2.00	0.975	0.860	0.806																																																			
2.10	0.977	0.867	0.815																																																			
2.31	0.979	0.879	0.830																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	LHA75F-36	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current		
Object	_____		





Model	LHA75F-36	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	<hr/>		

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure B-1	Both phases	0.13	0.34	0.36	Operation
		One of phases	0.26	0.67	0.71	Stand by
IEC62368-1	Figure B-2	Both phases	0.11	0.28	0.29	Operation
		One of phases	0.21	0.56	0.58	Stand by
	Figure B-3	Both phases	0.11	0.28	0.30	Operation
		One of phases	0.21	0.55	0.58	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL


Model	LHA75F-36																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+36V2.1A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>36.390</td> <td>-</td> </tr> <tr> <td>90</td> <td>36.390</td> <td>36.388</td> </tr> <tr> <td>100</td> <td>36.390</td> <td>36.388</td> </tr> <tr> <td>120</td> <td>36.390</td> <td>36.388</td> </tr> <tr> <td>200</td> <td>36.390</td> <td>36.388</td> </tr> <tr> <td>230</td> <td>36.390</td> <td>36.388</td> </tr> <tr> <td>264</td> <td>36.390</td> <td>36.388</td> </tr> <tr> <td>280</td> <td>36.390</td> <td>36.388</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	36.390	-	90	36.390	36.388	100	36.390	36.388	120	36.390	36.388	200	36.390	36.388	230	36.390	36.388	264	36.390	36.388	280	36.390	36.388	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	36.390	-																																
90	36.390	36.388																																
100	36.390	36.388																																
120	36.390	36.388																																
200	36.390	36.388																																
230	36.390	36.388																																
264	36.390	36.388																																
280	36.390	36.388																																
--	-	-																																

COSEL


Model	LHA75F-36																																																					
Item	Load Regulation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+36V2.1A																																																					
1.Graph																																																						
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 																																																						
Note: Slanted line shows the range of the rated load current.																																																						
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>36.389</td><td>36.389</td><td>36.389</td></tr> <tr> <td>0.40</td><td>36.392</td><td>36.392</td><td>36.392</td></tr> <tr> <td>0.80</td><td>36.391</td><td>36.391</td><td>36.391</td></tr> <tr> <td>1.20</td><td>36.390</td><td>36.390</td><td>36.390</td></tr> <tr> <td>1.60</td><td>36.390</td><td>36.390</td><td>36.390</td></tr> <tr> <td>2.00</td><td>36.388</td><td>36.388</td><td>36.388</td></tr> <tr> <td>2.10</td><td>36.387</td><td>36.387</td><td>36.387</td></tr> <tr> <td>2.31</td><td>36.387</td><td>36.387</td><td>36.387</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	36.389	36.389	36.389	0.40	36.392	36.392	36.392	0.80	36.391	36.391	36.391	1.20	36.390	36.390	36.390	1.60	36.390	36.390	36.390	2.00	36.388	36.388	36.388	2.10	36.387	36.387	36.387	2.31	36.387	36.387	36.387	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	36.389	36.389	36.389																																																			
0.40	36.392	36.392	36.392																																																			
0.80	36.391	36.391	36.391																																																			
1.20	36.390	36.390	36.390																																																			
1.60	36.390	36.390	36.390																																																			
2.00	36.388	36.388	36.388																																																			
2.10	36.387	36.387	36.387																																																			
2.31	36.387	36.387	36.387																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL


Model	LHA75F-36
Item	Dynamic Load Response
Object	+36V2.1A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 230 V
Cycle 1000 ms

Min.Load (0A)↔ Load 50% (1.05A)



Load 50% (1.05A)↔ Load 100% (2.1A)




COSEL

Model	LHA75F-36
Item	Ripple-Noise (by Load Current)
Object	+36V2.1A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.00	175	175
0.40	25	25
0.80	30	30
1.20	40	40
1.60	50	50
2.00	60	60
2.10	65	65
2.31	85	85
--	-	-
--	-	-
--	-	-

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	LHA75F-36
Item	Ambient Temperature Drift
Object	+36V2.1A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-20	36.314	36.314	36.314
-15	36.329	36.329	36.329
-10	36.342	36.342	36.342
0	36.362	36.362	36.362
25	36.387	36.387	36.387
40	36.391	36.391	36.391
50	36.390	36.390	36.390
60	36.384	36.384	36.384
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	LHA75F-36
Item	Rise and Fall Time
Object	+36V2.1A

Temperature
Testing Circuitry 25°C
Figure A


1. Graph



2. Values

[ms]


Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		98.5	13.5	112.0	27.1	16.0
230 V		86.5	13.5	100.0	27.2	16.0



COSEL

Model	LHA75F-36	Temperature	25°C
Item	Hold-Up Time	Testing Circuitry	Figure A
Object	+36V2.1A		

1. Graph



2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	53	-
90	53	27
100	53	27
120	53	27
200	53	27
230	53	27
264	53	27
280	55	28
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	LHA75F-36																																																						
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																				
Object	+36V2.1A																																																						
1.Graph																																																							
			2.Values																																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.40</td><td>126</td><td>131</td><td>135</td></tr> <tr> <td>0.80</td><td>31</td><td>69</td><td>70</td></tr> <tr> <td>1.20</td><td>31</td><td>46</td><td>46</td></tr> <tr> <td>1.60</td><td>31</td><td>36</td><td>36</td></tr> <tr> <td>2.00</td><td>27</td><td>29</td><td>29</td></tr> <tr> <td>2.10</td><td>26</td><td>26</td><td>27</td></tr> <tr> <td>2.31</td><td>22</td><td>23</td><td>23</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.40	126	131	135	0.80	31	69	70	1.20	31	46	46	1.60	31	36	36	2.00	27	29	29	2.10	26	26	27	2.31	22	23	23	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Time [ms]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	-	-	-																																																				
0.40	126	131	135																																																				
0.80	31	69	70																																																				
1.20	31	46	46																																																				
1.60	31	36	36																																																				
2.00	27	29	29																																																				
2.10	26	26	27																																																				
2.31	22	23	23																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated load current.																																																							

COSEL

Model	LHA75F-36
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+36V2.1A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	65	64
-15	65	64
-10	65	64
0	65	64
25	65	64
40	65	64
50	65	64
60	65	64
--	-	-
--	-	-
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	LHA75F-36
Item	Overcurrent Protection
Object	+36V2.1A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

Overcurrent protection is Hiccup mode.

2. Values


Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
36.0	2.64	2.64
34.2	-	-
32.4	-	-
28.8	-	-
25.2	-	-
21.6	-	-
18.0	-	-
14.4	-	-
10.8	-	-
7.2	-	-
3.6	-	-
0.0	-	-

COSEL

Model	LHA75F-36
Item	Overvoltage Protection
Object	+36V2.1A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-20	43.94	43.94
-15	44.16	44.16
-10	44.30	44.30
0	44.65	44.65
25	45.63	45.63
40	46.19	46.19
50	46.55	46.55
60	46.97	46.97
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.




Figure A




Figure B-1 (DEN-AN)




Figure B-2 (IEC62368-1 refer to IEC60990 Fig.4)




Figure B-3 (IEC62368-1 refer to IEC60990 Fig.5)




Figure C