



## ***EXTRA TEST DATA OF LHP150F-42-Y***

*Regulated DC Power Supply  
Mar, 20, 2025*

**COSEL CO.,LTD.**






## CONTENTS

1.Inrush Current (enlargement) . . . . .	1
2.Dynamic Line Regulation . . . . .	2
3.Hiccup cycle (by Overcurrent Protection) . . . . .	3
4.Power Consumption (by Input Voltage) . . . . .	4
5.Figure of Testing Circuitry . . . . .	6

(Final Page 6)






Model		LHP150F-42-Y	Temperature 25°C Testing Circuitry A
Item		Inrush Current (enlargement)	
Object		_____	





Model		LHP150F-42-Y	Temperature 25°C Testing Circuitry A
Item		Dynamic Line Regulation	
Object		_____	






<b>COSEL</b>		Temperature 25°C Testing Circuitry A Load : Short
Model	LHP150F-42-Y	
Item	Hiccup cycle (by Overcurrent Protection)	
Object	_____	

Output Current [5A/div]

GND



Input Voltage : 100V

Short-circuit current : 18.6A


ON Time : 3ms

Hiccup mode time : 200ms

Time [100ms/div]

Output Current [5A/div]

GND




Input Voltage : 230V

Short-circuit current : 18.4A

ON Time : 3ms

Hiccup mode time : 200ms

Time [100ms/div]





<b>COSEL</b>																
Model	LHP150F-42-RY															
Item	Input voltage - Power consumption	Temperature 25°C Testing Circuitry -														
Object	_____	Load :0%														
<p>1.Graph</p> <p>2.Values</p> <table border="1"> <thead> <tr> <th>Input voltage [V]</th> <th>Power consumption [W]</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>1.21</td> </tr> <tr> <td>100</td> <td>0.77</td> </tr> <tr> <td>115</td> <td>0.66</td> </tr> <tr> <td>200</td> <td>0.83</td> </tr> <tr> <td>230</td> <td>0.94</td> </tr> <tr> <td>264</td> <td>1.36</td> </tr> </tbody> </table>		Input voltage [V]	Power consumption [W]	85	1.21	100	0.77	115	0.66	200	0.83	230	0.94	264	1.36	
Input voltage [V]	Power consumption [W]															
85	1.21															
100	0.77															
115	0.66															
200	0.83															
230	0.94															
264	1.36															
<p>Reducing standby power is possible by OFF signal of the remote control.</p>																

**COSEL**

<b>COSEL</b>																	
Model	LHP150F-42-R2Y	Temperature	25°C														
Item	Input voltage - Power consumption	Testing Circuitry	-														
Object	_____	Load :0%															
1.Graph		2.Values															
<p>Power consumption [W]</p> <p>Input Voltage [V]</p>		<table border="1"> <thead> <tr> <th>Input voltage [V]</th> <th>Power consumption [W]</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>0.25</td> </tr> <tr> <td>100</td> <td>0.27</td> </tr> <tr> <td>115</td> <td>0.29</td> </tr> <tr> <td>200</td> <td>0.49</td> </tr> <tr> <td>230</td> <td>0.56</td> </tr> <tr> <td>264</td> <td>0.67</td> </tr> </tbody> </table>		Input voltage [V]	Power consumption [W]	85	0.25	100	0.27	115	0.29	200	0.49	230	0.56	264	0.67
Input voltage [V]	Power consumption [W]																
85	0.25																
100	0.27																
115	0.29																
200	0.49																
230	0.56																
264	0.67																
<p>Reducing standby power is possible by OFF signal of the remote control.</p>																	




Figure A