



DATA SHEET		Date	07-May-14
Model	LMA100F-24-Y	Temp.	25 degreeC
Test	EMI	Humid.	40 %RH
	Line conduction & Radiated emission	Tested by	T.Hayashi




Frequency MHz	Line Phase	Reading dB(μV)		Factor dB	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/ Fail	Remark
		QP	AV		QP	AV	QP	AV	QP	AV		
0.17741	VA	42.2	38.4	7.1	49.3	45.5	64.6	54.6	15.3	9.1	Pass	
2.70771	VB	30.4	28.2	7.8	38.2	36	56	46	17.8	10.0	Pass	
15.6046	VB	33.3	30.0	10.2	43.5	40.2	60	50	16.5	9.8	Pass	



Frequency MHz	Polariz ation	Stability	Reading dB(μV)	Space Loss dB	Level dB(m W)	Limit dB(m W)	Margin dB	Pass/ Fail	Height cm	Angle deg	Remark
			QP		QP	QP					
37.264	V	Stable	48.2	-14.3	33.9	40	6.1	Pass	105	10	
73.33	V	Stable	50.8	-19	31.8	40	8.2	Pass	99	23	
147.964	H	Stable	44	-11.6	32.4	40	7.6	Pass	200	128	

DATA SHEET		Date	07-May-14
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	T.Hayashi

1. Line conduction



2. Radiated emission

