

TEST DATA OF MGFS102415

Regulated DC Power Supply
December 13, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) 1

2.Input Current (by Load Current) 2

3.Input Power (by Load Current) 3

4.Efficiency (by Input Voltage) 4

5.Efficiency (by Load Current) 5

6.Line Regulation 6

7.Load Regulation 7

8.Dynamic Load Response 8

9.Ripple Voltage (by Load Current) 9

10.Ripple-Noise 10

11.Ripple Voltage (by Ambient Temperature) 11

12.Ambient Temperature Drift 12

13.Output Voltage Accuracy 13

14.Time Lapse Drift 14

15.Rise and Fall Time 15

16.Minimum Input Voltage for Regulated Output Voltage 16

17.Overcurrent Protection 17

18.Switching frequency (by Load Current) 18

19.Figure of Testing Circuitry 19

(Final Page 19)




Model		MGFS102415		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph			—△— Load 100% - - - □ - - Load 50% - · - ○ - · - Load 0%																																																																																	
			2.Values																																																																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.003</td><td>0.004</td><td>0.003</td></tr> <tr><td>8.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>8.2</td><td>0.036</td><td>0.742</td><td>1.492</td></tr> <tr><td>8.4</td><td>0.036</td><td>0.724</td><td>1.467</td></tr> <tr><td>8.6</td><td>0.035</td><td>0.705</td><td>1.429</td></tr> <tr><td>8.8</td><td>0.034</td><td>0.688</td><td>1.389</td></tr> <tr><td>9.0</td><td>0.034</td><td>0.673</td><td>1.354</td></tr> <tr><td>12.0</td><td>0.028</td><td>0.500</td><td>1.002</td></tr> <tr><td>18.0</td><td>0.021</td><td>0.334</td><td>0.656</td></tr> <tr><td>24.0</td><td>0.015</td><td>0.251</td><td>0.495</td></tr> <tr><td>30.0</td><td>0.006</td><td>0.203</td><td>0.394</td></tr> <tr><td>36.0</td><td>0.005</td><td>0.172</td><td>0.332</td></tr> <tr><td>40.0</td><td>0.005</td><td>0.157</td><td>0.299</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	6.0	0.003	0.004	0.003	8.0	0.003	0.003	0.003	8.2	0.036	0.742	1.492	8.4	0.036	0.724	1.467	8.6	0.035	0.705	1.429	8.8	0.034	0.688	1.389	9.0	0.034	0.673	1.354	12.0	0.028	0.500	1.002	18.0	0.021	0.334	0.656	24.0	0.015	0.251	0.495	30.0	0.006	0.203	0.394	36.0	0.005	0.172	0.332	40.0	0.005	0.157	0.299	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
6.0	0.003	0.004	0.003																																																																																	
8.0	0.003	0.003	0.003																																																																																	
8.2	0.036	0.742	1.492																																																																																	
8.4	0.036	0.724	1.467																																																																																	
8.6	0.035	0.705	1.429																																																																																	
8.8	0.034	0.688	1.389																																																																																	
9.0	0.034	0.673	1.354																																																																																	
12.0	0.028	0.500	1.002																																																																																	
18.0	0.021	0.334	0.656																																																																																	
24.0	0.015	0.251	0.495																																																																																	
30.0	0.006	0.203	0.394																																																																																	
36.0	0.005	0.172	0.332																																																																																	
40.0	0.005	0.157	0.299																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
Note: Slanted line shows the range of the rated input voltage.																																																																																				



Model	MGFS102415
Item	Input Current (by Load Current)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

- 1.Graph
- △— Input Volt. 9V
 - Input Volt. 12V
 - *·-·-·- Input Volt. 18V
 - Input Volt. 24V
 - ◇--- Input Volt. 36V



Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Input Current [A]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.00	0.034	0.028	0.021	0.015	0.005
0.14	0.284	0.215	0.146	0.112	0.079
0.28	0.542	0.405	0.272	0.205	0.141
0.42	0.813	0.603	0.400	0.300	0.204
0.56	1.087	0.803	0.531	0.398	0.267
0.63	1.238	0.904	0.596	0.446	0.300
0.70	- ※	1.002	0.656	0.495	0.332
0.77	- ※	1.111	0.728	0.542	0.364
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.



Model		MGFS102415		Temperature 25°C																																																																														
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<p> —△— Input Volt. 9V - - - □ - - - Input Volt. 12V - · · * · · - · - Input Volt. 18V - · · ○ · · - · - Input Volt. 24V - - - ◇ - - - Input Volt. 36V </p>		2.Values																																																																														
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.30</td><td>0.34</td><td>0.38</td><td>0.36</td><td>0.19</td></tr> <tr><td>0.14</td><td>2.53</td><td>2.56</td><td>2.62</td><td>2.68</td><td>2.84</td></tr> <tr><td>0.28</td><td>4.82</td><td>4.83</td><td>4.86</td><td>4.90</td><td>5.08</td></tr> <tr><td>0.42</td><td>7.20</td><td>7.16</td><td>7.15</td><td>7.17</td><td>7.34</td></tr> <tr><td>0.56</td><td>9.61</td><td>9.51</td><td>9.48</td><td>9.49</td><td>9.62</td></tr> <tr><td>0.63</td><td>10.92</td><td>10.70</td><td>10.65</td><td>10.65</td><td>10.78</td></tr> <tr><td>0.70</td><td>- ※</td><td>11.90</td><td>11.81</td><td>11.82</td><td>11.93</td></tr> <tr><td>0.77</td><td>- ※</td><td>13.14</td><td>12.97</td><td>12.96</td><td>13.09</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.30	0.34	0.38	0.36	0.19	0.14	2.53	2.56	2.62	2.68	2.84	0.28	4.82	4.83	4.86	4.90	5.08	0.42	7.20	7.16	7.15	7.17	7.34	0.56	9.61	9.51	9.48	9.49	9.62	0.63	10.92	10.70	10.65	10.65	10.78	0.70	- ※	11.90	11.81	11.82	11.93	0.77	- ※	13.14	12.97	12.96	13.09	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Power [W]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.00	0.30	0.34	0.38	0.36	0.19																																																																													
0.14	2.53	2.56	2.62	2.68	2.84																																																																													
0.28	4.82	4.83	4.86	4.90	5.08																																																																													
0.42	7.20	7.16	7.15	7.17	7.34																																																																													
0.56	9.61	9.51	9.48	9.49	9.62																																																																													
0.63	10.92	10.70	10.65	10.65	10.78																																																																													
0.70	- ※	11.90	11.81	11.82	11.93																																																																													
0.77	- ※	13.14	12.97	12.96	13.09																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>				<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																														



COSEL																																		
Model	MGFS102415																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	_____																																	
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>8.6</td> <td>87.7</td> <td>87.3 ※1</td> </tr> <tr> <td>9.0</td> <td>87.8</td> <td>87.7 ※1</td> </tr> <tr> <td>12.0</td> <td>88.0</td> <td>88.5</td> </tr> <tr> <td>15.0</td> <td>87.8</td> <td>89.0</td> </tr> <tr> <td>18.0</td> <td>87.7</td> <td>89.2</td> </tr> <tr> <td>24.0</td> <td>87.2</td> <td>89.2</td> </tr> <tr> <td>30.0</td> <td>86.3</td> <td>89.0</td> </tr> <tr> <td>36.0</td> <td>85.1</td> <td>88.3</td> </tr> <tr> <td>40.0</td> <td>83.8</td> <td>87.9</td> </tr> </tbody> </table> <p style="text-align: right;">※1: Load 80%</p>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.6	87.7	87.3 ※1	9.0	87.8	87.7 ※1	12.0	88.0	88.5	15.0	87.8	89.0	18.0	87.7	89.2	24.0	87.2	89.2	30.0	86.3	89.0	36.0	85.1	88.3	40.0	83.8	87.9
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
8.6	87.7	87.3 ※1																																
9.0	87.8	87.7 ※1																																
12.0	88.0	88.5																																
15.0	87.8	89.0																																
18.0	87.7	89.2																																
24.0	87.2	89.2																																
30.0	86.3	89.0																																
36.0	85.1	88.3																																
40.0	83.8	87.9																																



Model		MGFS102415		Temperature 25°C																																																																														
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>-·-·*·-·- Input Volt. 18V</p> <p>-·-·○-·- Input Volt. 24V</p> <p>---◇--- Input Volt. 36V</p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.14</td><td>83.6</td><td>82.4</td><td>80.5</td><td>78.6</td><td>74.3</td></tr> <tr><td>0.28</td><td>87.5</td><td>87.3</td><td>86.8</td><td>86.0</td><td>83.0</td></tr> <tr><td>0.42</td><td>87.8</td><td>88.3</td><td>88.5</td><td>88.2</td><td>86.2</td></tr> <tr><td>0.56</td><td>87.7</td><td>88.7</td><td>88.9</td><td>88.8</td><td>87.6</td></tr> <tr><td>0.63</td><td>86.8</td><td>88.6</td><td>89.1</td><td>89.0</td><td>88.0</td></tr> <tr><td>0.70</td><td>- ※</td><td>88.5</td><td>89.2</td><td>89.2</td><td>88.3</td></tr> <tr><td>0.77</td><td>- ※</td><td>88.2</td><td>89.3</td><td>89.4</td><td>88.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	-	-	0.14	83.6	82.4	80.5	78.6	74.3	0.28	87.5	87.3	86.8	86.0	83.0	0.42	87.8	88.3	88.5	88.2	86.2	0.56	87.7	88.7	88.9	88.8	87.6	0.63	86.8	88.6	89.1	89.0	88.0	0.70	- ※	88.5	89.2	89.2	88.3	0.77	- ※	88.2	89.3	89.4	88.5	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.14	83.6	82.4	80.5	78.6	74.3																																																																													
0.28	87.5	87.3	86.8	86.0	83.0																																																																													
0.42	87.8	88.3	88.5	88.2	86.2																																																																													
0.56	87.7	88.7	88.9	88.8	87.6																																																																													
0.63	86.8	88.6	89.1	89.0	88.0																																																																													
0.70	- ※	88.5	89.2	89.2	88.3																																																																													
0.77	- ※	88.2	89.3	89.4	88.5																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>				<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																														



COSEL																																			
Model	MGFS102415	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+15V0.7A																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>8.6</td> <td>15.030</td> <td>- ※</td> </tr> <tr> <td>9.0</td> <td>15.031</td> <td>- ※</td> </tr> <tr> <td>12.0</td> <td>15.031</td> <td>15.030</td> </tr> <tr> <td>15.0</td> <td>15.032</td> <td>15.031</td> </tr> <tr> <td>18.0</td> <td>15.031</td> <td>15.030</td> </tr> <tr> <td>24.0</td> <td>15.031</td> <td>15.030</td> </tr> <tr> <td>30.0</td> <td>15.031</td> <td>15.030</td> </tr> <tr> <td>36.0</td> <td>15.031</td> <td>15.030</td> </tr> <tr> <td>40.0</td> <td>15.031</td> <td>15.030</td> </tr> </tbody> </table> <p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.6	15.030	- ※	9.0	15.031	- ※	12.0	15.031	15.030	15.0	15.032	15.031	18.0	15.031	15.030	24.0	15.031	15.030	30.0	15.031	15.030	36.0	15.031	15.030	40.0	15.031	15.030
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
8.6	15.030	- ※																																	
9.0	15.031	- ※																																	
12.0	15.031	15.030																																	
15.0	15.032	15.031																																	
18.0	15.031	15.030																																	
24.0	15.031	15.030																																	
30.0	15.031	15.030																																	
36.0	15.031	15.030																																	
40.0	15.031	15.030																																	




COSEL																																																																																			
Model	MGFS102415	Temperature	25°C																																																																																
Item	Load Regulation	Testing Circuitry	Figure A																																																																																
Object	+15V0.7A																																																																																		
1.Graph	<p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>-··*·-·- Input Volt. 18V</p> <p>-··○-·- Input Volt. 24V</p> <p>---◇--- Input Volt. 36V</p>	2.Values																																																																																	
<p>Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.041</td><td>15.040</td><td>15.040</td><td>15.040</td><td>15.040</td></tr> <tr><td>0.14</td><td>15.038</td><td>15.038</td><td>15.038</td><td>15.037</td><td>15.036</td></tr> <tr><td>0.28</td><td>15.036</td><td>15.036</td><td>15.036</td><td>15.035</td><td>15.034</td></tr> <tr><td>0.42</td><td>15.033</td><td>15.034</td><td>15.034</td><td>15.033</td><td>15.032</td></tr> <tr><td>0.56</td><td>15.030</td><td>15.031</td><td>15.032</td><td>15.031</td><td>15.030</td></tr> <tr><td>0.63</td><td>15.028</td><td>15.030</td><td>15.031</td><td>15.030</td><td>15.030</td></tr> <tr><td>0.70</td><td>- ※</td><td>15.029</td><td>15.030</td><td>15.030</td><td>15.030</td></tr> <tr><td>0.77</td><td>- ※</td><td>15.028</td><td>15.029</td><td>15.028</td><td>15.027</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	15.041	15.040	15.040	15.040	15.040	0.14	15.038	15.038	15.038	15.037	15.036	0.28	15.036	15.036	15.036	15.035	15.034	0.42	15.033	15.034	15.034	15.033	15.032	0.56	15.030	15.031	15.032	15.031	15.030	0.63	15.028	15.030	15.031	15.030	15.030	0.70	- ※	15.029	15.030	15.030	15.030	0.77	- ※	15.028	15.029	15.028	15.027	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
	Load Current [A]	Output Voltage [V]																																																																																	
		Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
	0.00	15.041	15.040	15.040	15.040	15.040																																																																													
	0.14	15.038	15.038	15.038	15.037	15.036																																																																													
	0.28	15.036	15.036	15.036	15.035	15.034																																																																													
	0.42	15.033	15.034	15.034	15.033	15.032																																																																													
	0.56	15.030	15.031	15.032	15.031	15.030																																																																													
	0.63	15.028	15.030	15.031	15.030	15.030																																																																													
	0.70	- ※	15.029	15.030	15.030	15.030																																																																													
	0.77	- ※	15.028	15.029	15.028	15.027																																																																													
	--	-	-	-	-	-																																																																													
	--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																														
		<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																	




Model	MGFS102415	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.7A		

Input Volt. 24 V
Cycle 100 ms




Min. Load (0A) ←→
Load 100% (0.7A)

500 mV/div




2 ms/div




2 ms/div

Min. Load (0A) ←→
Load 50% (0.35A)

500 mV/div




2 ms/div




2 ms/div

Load 50% (0.35A) ←→
Load 100% (0.7A)

500 mV/div



2 ms/div



2 ms/div




<p>Model MGFS102415</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item</p>	<p>Ripple Voltage (by Load Current)</p>																																							
<p>Object</p>	<p>+15V0.7A</p>																																							
<p>1.Graph</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>—△— Input Volt. 12V</p> <p>-·-○-·- Input Volt. 36V</p> </div> </div>		<p>2.Values</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>40</td></tr> <tr><td>0.14</td><td>5</td><td>5</td></tr> <tr><td>0.28</td><td>5</td><td>10</td></tr> <tr><td>0.42</td><td>5</td><td>10</td></tr> <tr><td>0.56</td><td>10</td><td>10</td></tr> <tr><td>0.63</td><td>15</td><td>10</td></tr> <tr><td>0.70</td><td>20</td><td>10</td></tr> <tr><td>0.77</td><td>30</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.00	5	40	0.14	5	5	0.28	5	10	0.42	5	10	0.56	10	10	0.63	15	10	0.70	20	10	0.77	30	10	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 12 [V]	Input Volt. 36 [V]																																						
0.00	5	40																																						
0.14	5	5																																						
0.28	5	10																																						
0.42	5	10																																						
0.56	10	10																																						
0.63	15	10																																						
0.70	20	10																																						
0.77	30	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								



Model	MGFS102415	Temperature	25°C
Item	Ripple-Noise	Testing Circuitry	Figure B
Object	+15V0.7A		

1.Graph



Measured by 100 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 12 [V]	Input Volt. 36 [V]
0.00	5	45
0.14	10	10
0.28	10	15
0.42	15	15
0.56	15	15
0.63	20	15
0.70	25	15
0.77	30	20
--	-	-
--	-	-
--	-	-




COSEL																																								
Model	MGFS102415																																							
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure B																																						
Object	+15V0.7A																																							
<p>1.Graph</p> <p style="text-align: center;">Ambient Temperature [°C] Input Volt. 24V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>5</td><td>10</td></tr> <tr><td>-40</td><td>5</td><td>5</td></tr> <tr><td>-20</td><td>5</td><td>10</td></tr> <tr><td>0</td><td>5</td><td>10</td></tr> <tr><td>25</td><td>5</td><td>10</td></tr> <tr><td>55</td><td>5</td><td>10</td></tr> <tr><td>65</td><td>5</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	5	10	-40	5	5	-20	5	10	0	5	10	25	5	10	55	5	10	65	5	10	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	5	10																																						
-40	5	5																																						
-20	5	10																																						
0	5	10																																						
25	5	10																																						
55	5	10																																						
65	5	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



Model	MGFS102415
Item	Ambient Temperature Drift
Object	+15V0.7A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	14.910	14.909	14.911	14.912	14.912
-40	14.951	14.950	14.952	14.953	14.953
-20	14.985	14.984	14.986	14.986	14.986
0	15.009	15.008	15.010	15.010	15.010
25	15.028	15.027	15.030	15.030	15.030
55	15.035	15.034	15.035	15.035	15.034
65	15.034	15.034	15.035	15.034	15.034
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of Input Volt. 9V, Load 80%.
Other case Load 100%.



COSEL		Testing Circuitry Figure A
Model	MGFS102415	
Item	Output Voltage Accuracy	
Object	+15V0.7A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

- Temperature : -40 - 55°C
- Input Voltage : 12 - 36V
- Load Current : 0 - 0.7A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	55	36	0	15.046	±48	±0.3
Minimum Voltage	-40	12	0.7	14.950		




COSEL																									
Model	MGFS102415	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.7A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.023</td></tr> <tr><td>0.5</td><td>15.031</td></tr> <tr><td>1.0</td><td>15.031</td></tr> <tr><td>2.0</td><td>15.031</td></tr> <tr><td>3.0</td><td>15.031</td></tr> <tr><td>4.0</td><td>15.031</td></tr> <tr><td>5.0</td><td>15.031</td></tr> <tr><td>6.0</td><td>15.031</td></tr> <tr><td>7.0</td><td>15.031</td></tr> <tr><td>8.0</td><td>15.031</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	15.023	0.5	15.031	1.0	15.031	2.0	15.031	3.0	15.031	4.0	15.031	5.0	15.031	6.0	15.031	7.0	15.031	8.0	15.031
Time since start [H]	Output Voltage [V]																								
0.0	15.023																								
0.5	15.031																								
1.0	15.031																								
2.0	15.031																								
3.0	15.031																								
4.0	15.031																								
5.0	15.031																								
6.0	15.031																								
7.0	15.031																								
8.0	15.031																								



Model	MGFS102415	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.7A		


1.Graph

Input Volt. 24 V



2.Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.4	0.4	1.8	0.2	3.0
100 %		1.5	0.5	2.0	0.1	1.5






Model		MGFS102415
Item		Minimum Input Voltage for Regulated Output Voltage
Object		+15V0.7A

Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	7.6	7.6
-40	7.6	7.6
-20	7.6	7.6
0	7.6	7.6
25	7.6	7.6
55	7.5	7.5
65	7.5	7.5
--	-	-
--	-	-
--	-	-
--	-	-



<p>Model MGFS102415</p>		<p>Temperature 25°C</p>																																																																																				
<p>Item Overcurrent Protection</p>		<p>Testing Circuitry Figure A</p>																																																																																				
<p>Object +15V0.7A</p>																																																																																						
<p>1.Graph</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>— Input Volt. 9V</p> <p>— Input Volt. 12V</p> <p>— Input Volt. 18V</p> <p>— Input Volt. 24V</p> <p>— Input Volt. 36V</p> </div> </div> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Maximum output current at minimum input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>14.3</td><td>0.751</td><td>0.857</td><td>0.926</td><td>0.891</td><td>0.873</td></tr> <tr><td>13.5</td><td>0.781</td><td>0.883</td><td>0.953</td><td>0.914</td><td>0.891</td></tr> <tr><td>12.0</td><td>0.849</td><td>0.949</td><td>1.013</td><td>0.963</td><td>0.926</td></tr> <tr><td>10.5</td><td>0.924</td><td>1.024</td><td>1.074</td><td>1.013</td><td>0.966</td></tr> <tr><td>9.0</td><td>1.009</td><td>1.102</td><td>1.134</td><td>1.066</td><td>1.011</td></tr> <tr><td>7.5</td><td>1.102</td><td>1.183</td><td>1.200</td><td>1.121</td><td>1.056</td></tr> <tr><td>6.0</td><td>1.168</td><td>1.276</td><td>1.273</td><td>1.181</td><td>1.106</td></tr> <tr><td>4.5</td><td>1.254</td><td>1.377</td><td>1.364</td><td>1.252</td><td>1.163</td></tr> <tr><td>3.0</td><td>1.412</td><td>1.482</td><td>1.483</td><td>1.340</td><td>1.225</td></tr> <tr><td>1.5</td><td>1.546</td><td>1.620</td><td>1.562</td><td>1.406</td><td>1.276</td></tr> <tr><td>0.0</td><td>1.707</td><td>1.660</td><td>1.552</td><td>1.391</td><td>1.246</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	14.3	0.751	0.857	0.926	0.891	0.873	13.5	0.781	0.883	0.953	0.914	0.891	12.0	0.849	0.949	1.013	0.963	0.926	10.5	0.924	1.024	1.074	1.013	0.966	9.0	1.009	1.102	1.134	1.066	1.011	7.5	1.102	1.183	1.200	1.121	1.056	6.0	1.168	1.276	1.273	1.181	1.106	4.5	1.254	1.377	1.364	1.252	1.163	3.0	1.412	1.482	1.483	1.340	1.225	1.5	1.546	1.620	1.562	1.406	1.276	0.0	1.707	1.660	1.552	1.391	1.246	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																																	
14.3	0.751	0.857	0.926	0.891	0.873																																																																																	
13.5	0.781	0.883	0.953	0.914	0.891																																																																																	
12.0	0.849	0.949	1.013	0.963	0.926																																																																																	
10.5	0.924	1.024	1.074	1.013	0.966																																																																																	
9.0	1.009	1.102	1.134	1.066	1.011																																																																																	
7.5	1.102	1.183	1.200	1.121	1.056																																																																																	
6.0	1.168	1.276	1.273	1.181	1.106																																																																																	
4.5	1.254	1.377	1.364	1.252	1.163																																																																																	
3.0	1.412	1.482	1.483	1.340	1.225																																																																																	
1.5	1.546	1.620	1.562	1.406	1.276																																																																																	
0.0	1.707	1.660	1.552	1.391	1.246																																																																																	
--	-	-	-	-	-																																																																																	



Model		MGFS102415		Temperature 25°C																																																																														
Item		Switching frequency (by Load Current)		Testing Circuitry Figure A																																																																														
Object		+15V0.7A																																																																																
1.Graph		<p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>-·*·- Input Volt. 18V</p> <p>-·○·- Input Volt. 24V</p> <p>--◇-- Input Volt. 36V</p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>740</td><td>833</td><td>950</td><td>1014</td><td>1020</td></tr> <tr><td>0.14</td><td>394</td><td>486</td><td>617</td><td>694</td><td>772</td></tr> <tr><td>0.28</td><td>268</td><td>345</td><td>457</td><td>528</td><td>608</td></tr> <tr><td>0.42</td><td>202</td><td>266</td><td>363</td><td>427</td><td>503</td></tr> <tr><td>0.56</td><td>161</td><td>216</td><td>301</td><td>358</td><td>427</td></tr> <tr><td>0.63</td><td>147</td><td>199</td><td>279</td><td>333</td><td>400</td></tr> <tr><td>0.70</td><td>- ※</td><td>182</td><td>256</td><td>309</td><td>372</td></tr> <tr><td>0.77</td><td>- ※</td><td>169</td><td>239</td><td>288</td><td>350</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	740	833	950	1014	1020	0.14	394	486	617	694	772	0.28	268	345	457	528	608	0.42	202	266	363	427	503	0.56	161	216	301	358	427	0.63	147	199	279	333	400	0.70	- ※	182	256	309	372	0.77	- ※	169	239	288	350	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Current [A]	Input Current [A]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.00	740	833	950	1014	1020																																																																													
0.14	394	486	617	694	772																																																																													
0.28	268	345	457	528	608																																																																													
0.42	202	266	363	427	503																																																																													
0.56	161	216	301	358	427																																																																													
0.63	147	199	279	333	400																																																																													
0.70	- ※	182	256	309	372																																																																													
0.77	- ※	169	239	288	350																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p> <p>When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>				<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																														




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)