

TEST DATA OF MGFS10243R3

Regulated DC Power Supply
December 13, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	MGFS10243R3
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
6.0	0.003	0.003	0.003
8.0	0.003	0.003	0.003
8.2	0.040	0.625	1.269
8.4	0.039	0.610	1.234
8.6	0.039	0.595	1.202
8.8	0.037	0.580	1.172
9.0	0.037	0.568	1.144
12.0	0.031	0.423	0.851
18.0	0.025	0.283	0.557
24.0	0.021	0.213	0.416
30.0	0.018	0.172	0.332
36.0	0.005	0.145	0.279
40.0	0.005	0.132	0.252
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGFS10243R3																																																																												
Item	Input Current (by Load Current)																																																																												
Object	_____																																																																												
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 9V - -□-- Input Volt. 12V - ·*·— Input Volt. 18V - ·○·— Input Volt. 24V - ·◇·— Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.037</td><td>0.031</td><td>0.025</td><td>0.021</td><td>0.005</td></tr> <tr><td>0.52</td><td>0.244</td><td>0.186</td><td>0.128</td><td>0.097</td><td>0.068</td></tr> <tr><td>1.04</td><td>0.461</td><td>0.345</td><td>0.232</td><td>0.176</td><td>0.119</td></tr> <tr><td>1.56</td><td>0.689</td><td>0.511</td><td>0.339</td><td>0.255</td><td>0.172</td></tr> <tr><td>2.08</td><td>0.919</td><td>0.681</td><td>0.448</td><td>0.336</td><td>0.225</td></tr> <tr><td>2.34</td><td>1.045</td><td>0.765</td><td>0.505</td><td>0.377</td><td>0.252</td></tr> <tr><td>2.60</td><td>- *</td><td>0.851</td><td>0.557</td><td>0.416</td><td>0.279</td></tr> <tr><td>2.86</td><td>- *</td><td>0.940</td><td>0.618</td><td>0.460</td><td>0.308</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.037	0.031	0.025	0.021	0.005	0.52	0.244	0.186	0.128	0.097	0.068	1.04	0.461	0.345	0.232	0.176	0.119	1.56	0.689	0.511	0.339	0.255	0.172	2.08	0.919	0.681	0.448	0.336	0.225	2.34	1.045	0.765	0.505	0.377	0.252	2.60	- *	0.851	0.557	0.416	0.279	2.86	- *	0.940	0.618	0.460	0.308	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																								
0.00	0.037	0.031	0.025	0.021	0.005																																																																								
0.52	0.244	0.186	0.128	0.097	0.068																																																																								
1.04	0.461	0.345	0.232	0.176	0.119																																																																								
1.56	0.689	0.511	0.339	0.255	0.172																																																																								
2.08	0.919	0.681	0.448	0.336	0.225																																																																								
2.34	1.045	0.765	0.505	0.377	0.252																																																																								
2.60	- *	0.851	0.557	0.416	0.279																																																																								
2.86	- *	0.940	0.618	0.460	0.308																																																																								
--	-	-	-	-	-																																																																								
--	-	-	-	-	-																																																																								
--	-	-	-	-	-																																																																								
2.Values																																																																													



Note: Slanted line shows the range of the rated load current.

* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS10243R3																																																																								
Item	Input Power (by Load Current)																																																																								
Object	_____																																																																								
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.33</td><td>0.38</td><td>0.44</td><td>0.52</td><td>0.19</td></tr> <tr><td>0.52</td><td>2.18</td><td>2.21</td><td>2.28</td><td>2.33</td><td>2.44</td></tr> <tr><td>1.04</td><td>4.10</td><td>4.10</td><td>4.14</td><td>4.21</td><td>4.30</td></tr> <tr><td>1.56</td><td>6.10</td><td>6.06</td><td>6.06</td><td>6.09</td><td>6.21</td></tr> <tr><td>2.08</td><td>8.16</td><td>8.06</td><td>8.00</td><td>8.02</td><td>8.09</td></tr> <tr><td>2.34</td><td>9.23</td><td>9.08</td><td>9.01</td><td>9.01</td><td>9.06</td></tr> <tr><td>2.60</td><td>-</td><td>10.11</td><td>10.01</td><td>10.00</td><td>10.03</td></tr> <tr><td>2.86</td><td>-</td><td>11.17</td><td>11.01</td><td>10.99</td><td>11.06</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.33	0.38	0.44	0.52	0.19	0.52	2.18	2.21	2.28	2.33	2.44	1.04	4.10	4.10	4.14	4.21	4.30	1.56	6.10	6.06	6.06	6.09	6.21	2.08	8.16	8.06	8.00	8.02	8.09	2.34	9.23	9.08	9.01	9.01	9.06	2.60	-	10.11	10.01	10.00	10.03	2.86	-	11.17	11.01	10.99	11.06	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																				
0.00	0.33	0.38	0.44	0.52	0.19																																																																				
0.52	2.18	2.21	2.28	2.33	2.44																																																																				
1.04	4.10	4.10	4.14	4.21	4.30																																																																				
1.56	6.10	6.06	6.06	6.09	6.21																																																																				
2.08	8.16	8.06	8.00	8.02	8.09																																																																				
2.34	9.23	9.08	9.01	9.01	9.06																																																																				
2.60	-	10.11	10.01	10.00	10.03																																																																				
2.86	-	11.17	11.01	10.99	11.06																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
2.Values																																																																									
Note: Slanted line shows the range of the rated load current.	<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																								

COSEL

Model	MGFS10243R3																																
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																															
Object																																	
1.Graph																																	
<p>The graph plots Efficiency [%] on the y-axis (55 to 95) against Input Voltage [V] on the x-axis (0 to 50). Two sets of data points are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight decrease in efficiency as input voltage increases. Two vertical slanted lines are drawn across the graph, one on the left between approximately 10V and 12V, and one on the right between approximately 32V and 38V, indicating the rated input voltage range.</p>																																	
2.Values																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.6</td><td>85.3</td><td>84.5 ※1</td></tr> <tr><td>9.0</td><td>85.4</td><td>84.8 ※1</td></tr> <tr><td>12.0</td><td>85.5</td><td>85.5</td></tr> <tr><td>15.0</td><td>85.4</td><td>86.1</td></tr> <tr><td>18.0</td><td>85.1</td><td>86.3</td></tr> <tr><td>24.0</td><td>84.6</td><td>86.5</td></tr> <tr><td>30.0</td><td>83.7</td><td>86.4</td></tr> <tr><td>36.0</td><td>82.2</td><td>86.2</td></tr> <tr><td>40.0</td><td>81.6</td><td>85.6</td></tr> </tbody> </table> <p>※1 : Load 80%</p>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.6	85.3	84.5 ※1	9.0	85.4	84.8 ※1	12.0	85.5	85.5	15.0	85.4	86.1	18.0	85.1	86.3	24.0	84.6	86.5	30.0	83.7	86.4	36.0	82.2	86.2	40.0	81.6	85.6
Input Voltage [V]	Efficiency [%]																																
	Load 50%	Load 100%																															
8.6	85.3	84.5 ※1																															
9.0	85.4	84.8 ※1																															
12.0	85.5	85.5																															
15.0	85.4	86.1																															
18.0	85.1	86.3																															
24.0	84.6	86.5																															
30.0	83.7	86.4																															
36.0	82.2	86.2																															
40.0	81.6	85.6																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	

COSEL


Model	MGFS10243R3																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.52</td> <td>79.4</td> <td>78.2</td> <td>75.7</td> <td>74.3</td> <td>70.9</td> </tr> <tr> <td>1.04</td> <td>84.4</td> <td>84.5</td> <td>83.6</td> <td>82.3</td> <td>80.5</td> </tr> <tr> <td>1.56</td> <td>85.1</td> <td>85.7</td> <td>85.8</td> <td>85.3</td> <td>83.6</td> </tr> <tr> <td>2.08</td> <td>84.8</td> <td>85.9</td> <td>86.5</td> <td>86.3</td> <td>85.5</td> </tr> <tr> <td>2.34</td> <td>84.3</td> <td>85.7</td> <td>86.4</td> <td>86.4</td> <td>85.9</td> </tr> <tr> <td>2.60</td> <td>-</td> <td>※</td> <td>85.5</td> <td>86.3</td> <td>86.5</td> </tr> <tr> <td>2.86</td> <td>-</td> <td>※</td> <td>85.1</td> <td>86.3</td> <td>86.5</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Efficiency [%]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	-	-	-	-	-	0.52	79.4	78.2	75.7	74.3	70.9	1.04	84.4	84.5	83.6	82.3	80.5	1.56	85.1	85.7	85.8	85.3	83.6	2.08	84.8	85.9	86.5	86.3	85.5	2.34	84.3	85.7	86.4	86.4	85.9	2.60	-	※	85.5	86.3	86.5	2.86	-	※	85.1	86.3	86.5	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.52	79.4	78.2	75.7	74.3	70.9																																																																													
1.04	84.4	84.5	83.6	82.3	80.5																																																																													
1.56	85.1	85.7	85.8	85.3	83.6																																																																													
2.08	84.8	85.9	86.5	86.3	85.5																																																																													
2.34	84.3	85.7	86.4	86.4	85.9																																																																													
2.60	-	※	85.5	86.3	86.5																																																																													
2.86	-	※	85.1	86.3	86.5																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																		

COSEL

Model	MGFS10243R3
Item	Line Regulation
Object	+3.3V2.6A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	3.326	- *
9.0	3.326	- *
12.0	3.326	3.323
15.0	3.326	3.323
18.0	3.326	3.323
24.0	3.326	3.323
30.0	3.326	3.323
36.0	3.326	3.323
40.0	3.326	3.323

Note: Slanted line shows the range of the rated input voltage.

* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS10243R3																																																																																	
Item	Load Regulation																																																																																	
Object	+3.3V2.6A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>3.330</td> <td>3.330</td> <td>3.330</td> <td>3.330</td> <td>3.330</td> </tr> <tr> <td>0.52</td> <td>3.328</td> <td>3.328</td> <td>3.329</td> <td>3.329</td> <td>3.329</td> </tr> <tr> <td>1.04</td> <td>3.327</td> <td>3.327</td> <td>3.327</td> <td>3.327</td> <td>3.327</td> </tr> <tr> <td>1.56</td> <td>3.325</td> <td>3.326</td> <td>3.326</td> <td>3.325</td> <td>3.325</td> </tr> <tr> <td>2.08</td> <td>3.324</td> <td>3.324</td> <td>3.324</td> <td>3.324</td> <td>3.324</td> </tr> <tr> <td>2.34</td> <td>3.323</td> <td>3.323</td> <td>3.323</td> <td>3.324</td> <td>3.324</td> </tr> <tr> <td>2.60</td> <td>-</td> <td>3.323</td> <td>3.323</td> <td>3.323</td> <td>3.323</td> </tr> <tr> <td>2.86</td> <td>-</td> <td>3.322</td> <td>3.322</td> <td>3.322</td> <td>3.322</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	3.330	3.330	3.330	3.330	3.330	0.52	3.328	3.328	3.329	3.329	3.329	1.04	3.327	3.327	3.327	3.327	3.327	1.56	3.325	3.326	3.326	3.325	3.325	2.08	3.324	3.324	3.324	3.324	3.324	2.34	3.323	3.323	3.323	3.324	3.324	2.60	-	3.323	3.323	3.323	3.323	2.86	-	3.322	3.322	3.322	3.322	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	3.330	3.330	3.330	3.330	3.330																																																																													
0.52	3.328	3.328	3.329	3.329	3.329																																																																													
1.04	3.327	3.327	3.327	3.327	3.327																																																																													
1.56	3.325	3.326	3.326	3.325	3.325																																																																													
2.08	3.324	3.324	3.324	3.324	3.324																																																																													
2.34	3.323	3.323	3.323	3.324	3.324																																																																													
2.60	-	3.323	3.323	3.323	3.323																																																																													
2.86	-	3.322	3.322	3.322	3.322																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFS10243R3	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+3.3V2.6A	

Input Volt. 24 V
 Cycle 100 ms



Min.Load (0A)↔
 Load 100% (2.6A)

200 mV/div

100 μ s/div100 μ s/div

Min.Load (0A)↔
 Load 50% (1.3A)

200 mV/div

100 μ s/div100 μ s/div

Load 50% (1.3A)↔
 Load 100% (2.6A)

200 mV/div

100 μ s/div100 μ s/div

COSEL

Model	MGFS10243R3																																																																													
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																																																												
Object	+3.3V2.6A																																																																													
1.Graph																																																																														
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 300 mV, and the X-axis ranges from 0.0 to 3.2 A. Two curves are plotted: one for Input Volt. 12V (solid line with triangle markers) and one for Input Volt. 36V (dashed line with circle markers). Both curves show a sharp increase in ripple voltage as load current increases beyond the rated range (around 2.6A). A slanted line indicates the rated load current range.</p>		2.Values																																																																												
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>70</td> <td>95</td> </tr> <tr> <td>0.52</td> <td>5</td> <td>5</td> </tr> <tr> <td>1.04</td> <td>5</td> <td>5</td> </tr> <tr> <td>1.56</td> <td>10</td> <td>5</td> </tr> <tr> <td>2.08</td> <td>10</td> <td>10</td> </tr> <tr> <td>2.34</td> <td>10</td> <td>10</td> </tr> <tr> <td>2.60</td> <td>15</td> <td>10</td> </tr> <tr> <td>2.86</td> <td>20</td> <td>10</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.00	70	95	0.52	5	5	1.04	5	5	1.56	10	5	2.08	10	10	2.34	10	10	2.60	15	10	2.86	20	10	--	-	-	--	-	-	--	-	-	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>70</td> <td>95</td> </tr> <tr> <td>0.52</td> <td>5</td> <td>5</td> </tr> <tr> <td>1.04</td> <td>5</td> <td>5</td> </tr> <tr> <td>1.56</td> <td>10</td> <td>5</td> </tr> <tr> <td>2.08</td> <td>10</td> <td>10</td> </tr> <tr> <td>2.34</td> <td>10</td> <td>10</td> </tr> <tr> <td>2.60</td> <td>15</td> <td>10</td> </tr> <tr> <td>2.86</td> <td>20</td> <td>10</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.00	70	95	0.52	5	5	1.04	5	5	1.56	10	5	2.08	10	10	2.34	10	10	2.60	15	10	2.86	20	10	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																																																													
	Input Volt. 12 [V]	Input Volt. 36 [V]																																																																												
0.00	70	95																																																																												
0.52	5	5																																																																												
1.04	5	5																																																																												
1.56	10	5																																																																												
2.08	10	10																																																																												
2.34	10	10																																																																												
2.60	15	10																																																																												
2.86	20	10																																																																												
--	-	-																																																																												
--	-	-																																																																												
--	-	-																																																																												
Load Current [A]	Ripple Voltage [mV]																																																																													
	Input Volt. 12 [V]	Input Volt. 36 [V]																																																																												
0.00	70	95																																																																												
0.52	5	5																																																																												
1.04	5	5																																																																												
1.56	10	5																																																																												
2.08	10	10																																																																												
2.34	10	10																																																																												
2.60	15	10																																																																												
2.86	20	10																																																																												
--	-	-																																																																												
--	-	-																																																																												
--	-	-																																																																												
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																																																														
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																																																														


COSEL

Model	MGFS10243R3																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+3.3V2.6A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 300 mV, and the X-axis ranges from 0.0 to 3.2 A. Two curves are plotted: one for Input Volt. 12V (solid line with open circles) and one for Input Volt. 36V (dashed line with open circles). Both curves show a minimum noise level around 0.5-0.8A and then increase as load current increases beyond 1.6A. A slanted line indicates the rated load current range.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>70</td> <td>95</td> </tr> <tr> <td>0.52</td> <td>5</td> <td>5</td> </tr> <tr> <td>1.04</td> <td>5</td> <td>5</td> </tr> <tr> <td>1.56</td> <td>10</td> <td>10</td> </tr> <tr> <td>2.08</td> <td>15</td> <td>15</td> </tr> <tr> <td>2.34</td> <td>15</td> <td>15</td> </tr> <tr> <td>2.60</td> <td>20</td> <td>15</td> </tr> <tr> <td>2.86</td> <td>25</td> <td>15</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.00	70	95	0.52	5	5	1.04	5	5	1.56	10	10	2.08	15	15	2.34	15	15	2.60	20	15	2.86	25	15	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 12 [V]	Input Volt. 36 [V]																																						
0.00	70	95																																						
0.52	5	5																																						
1.04	5	5																																						
1.56	10	10																																						
2.08	15	15																																						
2.34	15	15																																						
2.60	20	15																																						
2.86	25	15																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								

COSEL

Model	MGFS10243R3
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V2.6A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	50	10
-40	5	10
-20	5	10
0	5	5
25	5	5
55	5	5
65	5	5
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGFS10243R3
Item	Ambient Temperature Drift
Object	+3.3V2.6A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-60	3.319	3.319	3.319	3.319	3.320
-40	3.321	3.321	3.321	3.321	3.321
-20	3.322	3.322	3.322	3.322	3.322
0	3.323	3.323	3.323	3.323	3.323
25	3.323	3.323	3.323	3.323	3.323
55	3.324	3.324	3.324	3.324	3.324
65	3.323	3.323	3.323	3.323	3.323
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of Input Volt. 9V, Load 80%.
Other case Load 100%.



Model	MGFS10243R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V2.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 12 - 36V

Load Current : 0 - 2.6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	55	36	0	3.331	± 5	± 0.2
Minimum Voltage	0	12	2.6	3.321		

COSEL

Model	MGFS10243R3
Item	Time Lapse Drift
Object	+3.3V2.6A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph


 Input Volt. 24V
 Load 100%

2.Values


Time since start [H]	Output Voltage [V]
0.0	3.322
0.5	3.323
1.0	3.323
2.0	3.323
3.0	3.323
4.0	3.323
5.0	3.323
6.0	3.323
7.0	3.323
8.0	3.323

COSEL

Model	MGFS10243R3
Item	Rise and Fall Time
Object	+3.3V2.6A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.4	0.3	1.7	0.1	0.6	
100 %		1.4	0.3	1.7	0.1	0.4	




COSEL

Model	MGFS10243R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V2.6A

Testing Circuitry Figure A

1. Graph




Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	7.6	7.6
-40	7.6	7.6
-20	7.6	7.6
0	7.6	7.6
25	7.6	7.6
55	7.5	7.5
65	7.5	7.5
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGFS10243R3
Item	Overcurrent Protection
Object	+3.3V2.6A



Note: Slanted line shows the range of the rated load current.

Maximum output current at minimum input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]				
	9[V]	12[V]	18[V]	24[V]	36[V]
3.14	2.955	3.219	3.314	3.340	3.405
2.97	3.068	3.327	3.416	3.420	3.470
2.64	3.315	3.567	3.630	3.593	3.596
2.31	3.576	3.847	3.855	3.779	3.729
1.98	3.911	4.153	4.080	3.964	3.860
1.65	4.289	4.459	4.295	4.100	3.953
1.32	4.415	4.587	4.414	4.233	4.083
0.99	4.593	4.740	4.532	4.341	4.175
0.66	4.936	5.044	4.750	4.533	4.348
0.33	5.274	5.427	5.046	4.767	4.549
0.00	5.058	5.289	5.373	5.016	4.720
--	-	-	-	-	-

COSEL

Model	MGFS10243R3																																																																																	
Item	Switching frequency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object	+3.3V2.6A																																																																																	
1.Graph																																																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>648</td> <td>781</td> <td>906</td> <td>990</td> <td>1051</td> </tr> <tr> <td>0.52</td> <td>463</td> <td>574</td> <td>719</td> <td>813</td> <td>907</td> </tr> <tr> <td>1.04</td> <td>322</td> <td>412</td> <td>544</td> <td>630</td> <td>724</td> </tr> <tr> <td>1.56</td> <td>244</td> <td>321</td> <td>436</td> <td>513</td> <td>601</td> </tr> <tr> <td>2.08</td> <td>196</td> <td>262</td> <td>363</td> <td>432</td> <td>515</td> </tr> <tr> <td>2.34</td> <td>179</td> <td>241</td> <td>337</td> <td>403</td> <td>483</td> </tr> <tr> <td>2.60</td> <td>-</td> <td>221</td> <td>310</td> <td>373</td> <td>451</td> </tr> <tr> <td>2.86</td> <td>-</td> <td>204</td> <td>290</td> <td>350</td> <td>424</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	648	781	906	990	1051	0.52	463	574	719	813	907	1.04	322	412	544	630	724	1.56	244	321	436	513	601	2.08	196	262	363	432	515	2.34	179	241	337	403	483	2.60	-	221	310	373	451	2.86	-	204	290	350	424	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	648	781	906	990	1051																																																																													
0.52	463	574	719	813	907																																																																													
1.04	322	412	544	630	724																																																																													
1.56	244	321	436	513	601																																																																													
2.08	196	262	363	432	515																																																																													
2.34	179	241	337	403	483																																																																													
2.60	-	221	310	373	451																																																																													
2.86	-	204	290	350	424																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	When load current is low, MG operates intermittently, so switching frequency would not become constant.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)