

TEST DATA OF MGFS10483R3

Regulated DC Power Supply
December 28, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	MGFS10483R3
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
16.0	0.003	0.003	0.004
16.2	0.003	0.003	0.003
16.4	0.003	0.004	0.003
16.6	0.019	0.307	0.587
16.8	0.019	0.304	0.584
17.0	0.019	0.301	0.581
18.0	0.018	0.283	0.568
24.0	0.015	0.211	0.420
36.0	0.011	0.142	0.279
48.0	0.010	0.107	0.209
60.0	0.009	0.087	0.168
76.0	0.008	0.071	0.134
80.0	0.008	0.067	0.128
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGFS10483R3																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	—△— Input Volt. 18V - - -□- - Input Volt. 24V - - *- - Input Volt. 36V - - ○- - Input Volt. 48V - - ◇- - Input Volt. 76V																																																																																	
2.Values																																																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.018</td> <td>0.015</td> <td>0.011</td> <td>0.010</td> <td>0.008</td> </tr> <tr> <td>0.52</td> <td>0.122</td> <td>0.092</td> <td>0.063</td> <td>0.048</td> <td>0.033</td> </tr> <tr> <td>1.04</td> <td>0.230</td> <td>0.172</td> <td>0.116</td> <td>0.088</td> <td>0.058</td> </tr> <tr> <td>1.56</td> <td>0.341</td> <td>0.253</td> <td>0.169</td> <td>0.127</td> <td>0.084</td> </tr> <tr> <td>2.08</td> <td>0.457</td> <td>0.338</td> <td>0.224</td> <td>0.168</td> <td>0.108</td> </tr> <tr> <td>2.34</td> <td>0.512</td> <td>0.381</td> <td>0.252</td> <td>0.189</td> <td>0.121</td> </tr> <tr> <td>2.60</td> <td>- *</td> <td>0.420</td> <td>0.279</td> <td>0.209</td> <td>0.134</td> </tr> <tr> <td>2.86</td> <td>- *</td> <td>0.468</td> <td>0.308</td> <td>0.231</td> <td>0.147</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>						Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.018	0.015	0.011	0.010	0.008	0.52	0.122	0.092	0.063	0.048	0.033	1.04	0.230	0.172	0.116	0.088	0.058	1.56	0.341	0.253	0.169	0.127	0.084	2.08	0.457	0.338	0.224	0.168	0.108	2.34	0.512	0.381	0.252	0.189	0.121	2.60	- *	0.420	0.279	0.209	0.134	2.86	- *	0.468	0.308	0.231	0.147	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	0.018	0.015	0.011	0.010	0.008																																																																													
0.52	0.122	0.092	0.063	0.048	0.033																																																																													
1.04	0.230	0.172	0.116	0.088	0.058																																																																													
1.56	0.341	0.253	0.169	0.127	0.084																																																																													
2.08	0.457	0.338	0.224	0.168	0.108																																																																													
2.34	0.512	0.381	0.252	0.189	0.121																																																																													
2.60	- *	0.420	0.279	0.209	0.134																																																																													
2.86	- *	0.468	0.308	0.231	0.147																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note: Slanted line shows the range of the rated load current. ※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																		

COSEL


Model	MGFS10483R3																																																																																	
Item	Input Power (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.32</td><td>0.36</td><td>0.44</td><td>0.51</td><td>0.68</td></tr> <tr><td>0.52</td><td>2.19</td><td>2.20</td><td>2.26</td><td>2.29</td><td>2.51</td></tr> <tr><td>1.04</td><td>4.12</td><td>4.12</td><td>4.18</td><td>4.24</td><td>4.39</td></tr> <tr><td>1.56</td><td>6.10</td><td>6.06</td><td>6.08</td><td>6.12</td><td>6.37</td></tr> <tr><td>2.08</td><td>8.18</td><td>8.09</td><td>8.08</td><td>8.09</td><td>8.21</td></tr> <tr><td>2.34</td><td>9.17</td><td>9.12</td><td>9.06</td><td>9.08</td><td>9.23</td></tr> <tr><td>2.60</td><td>-</td><td>10.14</td><td>10.05</td><td>10.06</td><td>10.25</td></tr> <tr><td>2.86</td><td>-</td><td>11.20</td><td>11.09</td><td>11.10</td><td>11.20</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.32	0.36	0.44	0.51	0.68	0.52	2.19	2.20	2.26	2.29	2.51	1.04	4.12	4.12	4.18	4.24	4.39	1.56	6.10	6.06	6.08	6.12	6.37	2.08	8.18	8.09	8.08	8.09	8.21	2.34	9.17	9.12	9.06	9.08	9.23	2.60	-	10.14	10.05	10.06	10.25	2.86	-	11.20	11.09	11.10	11.20	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	0.32	0.36	0.44	0.51	0.68																																																																													
0.52	2.19	2.20	2.26	2.29	2.51																																																																													
1.04	4.12	4.12	4.18	4.24	4.39																																																																													
1.56	6.10	6.06	6.08	6.12	6.37																																																																													
2.08	8.18	8.09	8.08	8.09	8.21																																																																													
2.34	9.17	9.12	9.06	9.08	9.23																																																																													
2.60	-	10.14	10.05	10.06	10.25																																																																													
2.86	-	11.20	11.09	11.10	11.20																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.32</td><td>0.36</td><td>0.44</td><td>0.51</td><td>0.68</td></tr> <tr><td>0.52</td><td>2.19</td><td>2.20</td><td>2.26</td><td>2.29</td><td>2.51</td></tr> <tr><td>1.04</td><td>4.12</td><td>4.12</td><td>4.18</td><td>4.24</td><td>4.39</td></tr> <tr><td>1.56</td><td>6.10</td><td>6.06</td><td>6.08</td><td>6.12</td><td>6.37</td></tr> <tr><td>2.08</td><td>8.18</td><td>8.09</td><td>8.08</td><td>8.09</td><td>8.21</td></tr> <tr><td>2.34</td><td>9.17</td><td>9.12</td><td>9.06</td><td>9.08</td><td>9.23</td></tr> <tr><td>2.60</td><td>-</td><td>10.14</td><td>10.05</td><td>10.06</td><td>10.25</td></tr> <tr><td>2.86</td><td>-</td><td>11.20</td><td>11.09</td><td>11.10</td><td>11.20</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.32	0.36	0.44	0.51	0.68	0.52	2.19	2.20	2.26	2.29	2.51	1.04	4.12	4.12	4.18	4.24	4.39	1.56	6.10	6.06	6.08	6.12	6.37	2.08	8.18	8.09	8.08	8.09	8.21	2.34	9.17	9.12	9.06	9.08	9.23	2.60	-	10.14	10.05	10.06	10.25	2.86	-	11.20	11.09	11.10	11.20	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Power [W]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	0.32	0.36	0.44	0.51	0.68																																																																													
0.52	2.19	2.20	2.26	2.29	2.51																																																																													
1.04	4.12	4.12	4.18	4.24	4.39																																																																													
1.56	6.10	6.06	6.08	6.12	6.37																																																																													
2.08	8.18	8.09	8.08	8.09	8.21																																																																													
2.34	9.17	9.12	9.06	9.08	9.23																																																																													
2.60	-	10.14	10.05	10.06	10.25																																																																													
2.86	-	11.20	11.09	11.10	11.20																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note: Slanted line shows the range of the rated load current.	<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																	

COSEL

Model	MGFS10483R3
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	85.0	84.4 ※1
18	85.0	84.8 ※1
24	85.3	85.5
30	85.1	85.9
36	84.9	86.2
48	84.2	86.1
60	83.0	86.0
76	80.7	84.6
80	79.7	84.2

※1: Load 80%

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	MGFS10483R3																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 18V - - □ - - Input Volt. 24V - - * - - Input Volt. 36V - - ○ - - Input Volt. 48V - - ◇ - - Input Volt. 76V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.52</td> <td>79.2</td> <td>78.6</td> <td>76.9</td> <td>75.6</td> <td>69.1</td> </tr> <tr> <td>1.04</td> <td>84.2</td> <td>84.3</td> <td>83.0</td> <td>81.9</td> <td>79.1</td> </tr> <tr> <td>1.56</td> <td>85.3</td> <td>85.8</td> <td>85.6</td> <td>85.0</td> <td>81.7</td> </tr> <tr> <td>2.08</td> <td>84.8</td> <td>85.7</td> <td>85.9</td> <td>85.7</td> <td>84.5</td> </tr> <tr> <td>2.34</td> <td>84.5</td> <td>85.6</td> <td>86.1</td> <td>86.0</td> <td>84.6</td> </tr> <tr> <td>2.60</td> <td>- *</td> <td>85.5</td> <td>86.2</td> <td>86.1</td> <td>84.6</td> </tr> <tr> <td>2.86</td> <td>- *</td> <td>85.1</td> <td>86.0</td> <td>85.9</td> <td>85.1</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	-	-	0.52	79.2	78.6	76.9	75.6	69.1	1.04	84.2	84.3	83.0	81.9	79.1	1.56	85.3	85.8	85.6	85.0	81.7	2.08	84.8	85.7	85.9	85.7	84.5	2.34	84.5	85.6	86.1	86.0	84.6	2.60	- *	85.5	86.2	86.1	84.6	2.86	- *	85.1	86.0	85.9	85.1	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.52	79.2	78.6	76.9	75.6	69.1																																																																													
1.04	84.2	84.3	83.0	81.9	79.1																																																																													
1.56	85.3	85.8	85.6	85.0	81.7																																																																													
2.08	84.8	85.7	85.9	85.7	84.5																																																																													
2.34	84.5	85.6	86.1	86.0	84.6																																																																													
2.60	- *	85.5	86.2	86.1	84.6																																																																													
2.86	- *	85.1	86.0	85.9	85.1																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFS10483R3
Item	Line Regulation
Object	+3.3V2.6A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated input voltage.


2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	3.333	- *
18	3.333	- *
24	3.333	3.329
30	3.333	3.329
36	3.333	3.329
48	3.333	3.329
60	3.333	3.329
76	3.333	3.329
80	3.333	3.329

* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS10483R3
Item	Load Regulation
Object	+3.3V2.6A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0.00	3.337	3.337	3.337	3.337	3.337
0.52	3.335	3.335	3.335	3.335	3.335
1.04	3.334	3.334	3.334	3.334	3.334
1.56	3.332	3.332	3.332	3.332	3.332
2.08	3.331	3.331	3.331	3.331	3.331
2.34	3.330	3.330	3.330	3.330	3.330
2.60	-	3.329	3.329	3.329	3.329
2.86	-	3.328	3.329	3.329	3.329
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS10483R3	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+3.3V2.6A	

Input Volt. 48 V
 Cycle 100 ms



Min.Load (0A)↔
 Load 100% (2.6A)

200 mV/div

100 μ s/div100 μ s/div

Min.Load (0A)↔
 Load 50% (1.3A)

200 mV/div

100 μ s/div100 μ s/div

Load 50% (1.3A)↔
 Load 100% (2.6A)

200 mV/div

100 μ s/div100 μ s/div

COSEL


Model	MGFS10483R3																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+3.3V2.6A																																							
1.Graph																																								
		2.Values																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 24 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>80</td><td>5</td></tr> <tr> <td>0.52</td><td>5</td><td>5</td></tr> <tr> <td>1.04</td><td>5</td><td>5</td></tr> <tr> <td>1.56</td><td>10</td><td>5</td></tr> <tr> <td>2.08</td><td>10</td><td>10</td></tr> <tr> <td>2.34</td><td>15</td><td>10</td></tr> <tr> <td>2.60</td><td>20</td><td>10</td></tr> <tr> <td>2.86</td><td>20</td><td>10</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 24 [V]	Input Volt. 76 [V]	0.00	80	5	0.52	5	5	1.04	5	5	1.56	10	5	2.08	10	10	2.34	15	10	2.60	20	10	2.86	20	10	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 24 [V]	Input Volt. 76 [V]																																						
0.00	80	5																																						
0.52	5	5																																						
1.04	5	5																																						
1.56	10	5																																						
2.08	10	10																																						
2.34	15	10																																						
2.60	20	10																																						
2.86	20	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple [mVp-p]</p>																																								
Fig.Complex Ripple Wave Form																																								

COSEL

Model	MGFS10483R3
Item	Ripple-Noise
Object	+3.3V2.6A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph




2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 24 [V]	Input Volt. 76 [V]
0.00	80	5
0.52	10	10
1.04	10	10
1.56	15	10
2.08	20	15
2.34	20	15
2.60	20	15
2.86	25	15
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.
 Ripple Noise[mVp-p]




COSEL

Model	MGFS10483R3
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V2.6A

Testing Circuitry Figure B

1. Graph



2. Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	10
-40	10	10
-20	10	5
0	10	5
25	10	5
55	10	5
65	10	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGFS10483R3
Item	Ambient Temperature Drift
Object	+3.3V2.6A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	3.334	3.334	3.334	3.334	3.334
-40	3.334	3.334	3.334	3.334	3.334
-20	3.332	3.332	3.332	3.332	3.332
0	3.330	3.330	3.330	3.330	3.330
25	3.329	3.329	3.329	3.329	3.329
55	3.328	3.328	3.328	3.328	3.328
65	3.327	3.327	3.327	3.327	3.327
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of Input Volt. 18V, Load 80%.
Other case Load 100%.



Model	MGFS10483R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V2.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 24 - 76V

Load Current : 0 - 2.6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	-40	76	0	3.341	± 7	± 0.2
Minimum Voltage	55	76	2.6	3.328		

COSEL

Model	MGFS10483R3
Item	Time Lapse Drift
Object	+3.3V2.6A

Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values


Time since start [H]	Output Voltage [V]
0.0	3.329
0.5	3.330
1.0	3.329
2.0	3.330
3.0	3.330
4.0	3.330
5.0	3.330
6.0	3.330
7.0	3.330
8.0	3.330

COSEL

Model	MGFS10483R3
Item	Rise and Fall Time
Object	+3.3V2.6A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.5	0.2	1.7	0.1	0.7
100 %		1.4	0.3	1.7	0.1	0.4




COSEL

Model	MGFS10483R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V2.6A

Testing Circuitry Figure A

1. Graph




Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	15.0	15.1
-40	14.9	15.0
-20	14.9	15.0
0	14.8	14.9
25	14.8	14.9
55	14.6	14.8
65	14.5	14.6
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGFS10483R3
Item	Overcurrent Protection
Object	+3.3V2.6A



Note: Slanted line shows the range of the rated load current.

Maximum output current at minimum input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
3.14	2.702	3.158	3.385	3.316	3.354
2.97	2.819	3.266	3.502	3.415	3.430
2.64	3.067	3.525	3.752	3.622	3.581
2.31	3.361	3.823	3.998	3.824	3.704
1.98	3.688	4.167	4.277	4.056	3.855
1.65	4.073	4.517	4.551	4.270	4.024
1.32	4.265	4.682	4.704	4.438	4.150
0.99	4.410	4.854	4.861	4.551	4.273
0.66	4.757	5.180	5.138	4.793	4.485
0.33	5.063	5.593	5.532	5.117	4.754
0.00	5.064	5.401	5.309	5.382	4.925
--	-	-	-	-	-

COSEL

Model	MGFS10483R3																																																																																	
Item	Switching frequency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object	+3.3V2.6A																																																																																	
1.Graph																																																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>438</td> <td>521</td> <td>602</td> <td>680</td> <td>740</td> </tr> <tr> <td>0.52</td> <td>361</td> <td>450</td> <td>553</td> <td>613</td> <td>690</td> </tr> <tr> <td>1.04</td> <td>267</td> <td>339</td> <td>435</td> <td>493</td> <td>570</td> </tr> <tr> <td>1.56</td> <td>210</td> <td>272</td> <td>361</td> <td>417</td> <td>493</td> </tr> <tr> <td>2.08</td> <td>173</td> <td>228</td> <td>307</td> <td>362</td> <td>434</td> </tr> <tr> <td>2.34</td> <td>160</td> <td>212</td> <td>287</td> <td>340</td> <td>410</td> </tr> <tr> <td>2.60</td> <td>-</td> <td>195</td> <td>267</td> <td>318</td> <td>386</td> </tr> <tr> <td>2.86</td> <td>-</td> <td>182</td> <td>252</td> <td>299</td> <td>366</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	438	521	602	680	740	0.52	361	450	553	613	690	1.04	267	339	435	493	570	1.56	210	272	361	417	493	2.08	173	228	307	362	434	2.34	160	212	287	340	410	2.60	-	195	267	318	386	2.86	-	182	252	299	366	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	438	521	602	680	740																																																																													
0.52	361	450	553	613	690																																																																													
1.04	267	339	435	493	570																																																																													
1.56	210	272	361	417	493																																																																													
2.08	173	228	307	362	434																																																																													
2.34	160	212	287	340	410																																																																													
2.60	-	195	267	318	386																																																																													
2.86	-	182	252	299	366																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	When load current is low, MG operates intermittently, so switching frequency would not become constant.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)