

# TEST DATA OF MGFS1R52412

Regulated DC Power Supply  
December 29, 2016

Approved by : Takayuki Fukuda  
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi  
Takaaki Sekiguchi Design Engineer

**COSEL CO.,LTD.**

CONTENTS

1.Input Current (by Input Voltage) . . . . . 1

2.Input Current (by Load Current) . . . . . 2

3.Input Power (by Load Current) . . . . . 3

4.Efficiency (by Input Voltage) . . . . . 4

5.Efficiency (by Load Current) . . . . . 5

6.Line Regulation . . . . . 6

7.Load Regulation . . . . . 7

8.Dynamic Load Response . . . . . 8

9.Ripple Voltage (by Load Current) . . . . . 9

10.Ripple-Noise . . . . . 10

11.Ripple Voltage (by Ambient Temperature) . . . . . 11

12.Ambient Temperature Drift . . . . . 12

13.Output Voltage Accuracy . . . . . 13

14.Time Lapse Drift . . . . . 14

15.Rise and Fall Time . . . . . 15

16.Minimum Input Voltage for Regulated Output Voltage . . . . . 16

17.Overcurrent Protection . . . . . 17

18.Switching frequency (by Load Current) . . . . . 18

19.Figure of Testing Circuitry . . . . . 19

(Final Page 19)



Model		MGFS1R52412		Temperature	25°C																																																																															
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																															
Object		_____																																																																																		
1.Graph			—△— Load 100% - - - □ - - Load 50% - · - ○ - · - Load 0%	2.Values																																																																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>8.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>8.2</td><td>0.004</td><td>0.004</td><td>0.003</td></tr> <tr><td>8.4</td><td>0.003</td><td>0.003</td><td>0.004</td></tr> <tr><td>8.6</td><td>0.014</td><td>0.114</td><td>0.222</td></tr> <tr><td>8.8</td><td>0.014</td><td>0.111</td><td>0.216</td></tr> <tr><td>9.0</td><td>0.014</td><td>0.109</td><td>0.211</td></tr> <tr><td>12.0</td><td>0.012</td><td>0.084</td><td>0.156</td></tr> <tr><td>18.0</td><td>0.009</td><td>0.056</td><td>0.105</td></tr> <tr><td>24.0</td><td>0.008</td><td>0.043</td><td>0.079</td></tr> <tr><td>30.0</td><td>0.007</td><td>0.035</td><td>0.064</td></tr> <tr><td>36.0</td><td>0.005</td><td>0.031</td><td>0.054</td></tr> <tr><td>40.0</td><td>0.004</td><td>0.028</td><td>0.049</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	6.0	0.003	0.003	0.003	8.0	0.003	0.003	0.003	8.2	0.004	0.004	0.003	8.4	0.003	0.003	0.004	8.6	0.014	0.114	0.222	8.8	0.014	0.111	0.216	9.0	0.014	0.109	0.211	12.0	0.012	0.084	0.156	18.0	0.009	0.056	0.105	24.0	0.008	0.043	0.079	30.0	0.007	0.035	0.064	36.0	0.005	0.031	0.054	40.0	0.004	0.028	0.049	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
6.0	0.003	0.003	0.003																																																																																	
8.0	0.003	0.003	0.003																																																																																	
8.2	0.004	0.004	0.003																																																																																	
8.4	0.003	0.003	0.004																																																																																	
8.6	0.014	0.114	0.222																																																																																	
8.8	0.014	0.111	0.216																																																																																	
9.0	0.014	0.109	0.211																																																																																	
12.0	0.012	0.084	0.156																																																																																	
18.0	0.009	0.056	0.105																																																																																	
24.0	0.008	0.043	0.079																																																																																	
30.0	0.007	0.035	0.064																																																																																	
36.0	0.005	0.031	0.054																																																																																	
40.0	0.004	0.028	0.049																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
Note: Slanted line shows the range of the rated input voltage.																																																																																				



Model		MGFS1R52412		Temperature 25°C																																																																														
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<ul style="list-style-type: none"> <li>—△— Input Volt. 9V</li> <li>---□--- Input Volt. 12V</li> <li>-·-·*·-·-·- Input Volt. 18V</li> <li>-·-·○-·-·- Input Volt. 24V</li> <li>-·-·◇-·-·- Input Volt. 36V</li> </ul>		2.Values																																																																														
<p>Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.014</td><td>0.012</td><td>0.009</td><td>0.008</td><td>0.005</td></tr> <tr><td>0.026</td><td>0.052</td><td>0.040</td><td>0.028</td><td>0.022</td><td>0.016</td></tr> <tr><td>0.052</td><td>0.089</td><td>0.068</td><td>0.047</td><td>0.036</td><td>0.026</td></tr> <tr><td>0.078</td><td>0.129</td><td>0.097</td><td>0.066</td><td>0.051</td><td>0.035</td></tr> <tr><td>0.104</td><td>0.169</td><td>0.126</td><td>0.085</td><td>0.065</td><td>0.045</td></tr> <tr><td>0.130</td><td>0.211</td><td>0.156</td><td>0.105</td><td>0.079</td><td>0.054</td></tr> <tr><td>0.143</td><td>0.232</td><td>0.171</td><td>0.114</td><td>0.086</td><td>0.059</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	0.014	0.012	0.009	0.008	0.005	0.026	0.052	0.040	0.028	0.022	0.016	0.052	0.089	0.068	0.047	0.036	0.026	0.078	0.129	0.097	0.066	0.051	0.035	0.104	0.169	0.126	0.085	0.065	0.045	0.130	0.211	0.156	0.105	0.079	0.054	0.143	0.232	0.171	0.114	0.086	0.059	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Current [A]	Input Current [A]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.000	0.014	0.012	0.009	0.008	0.005																																																																													
0.026	0.052	0.040	0.028	0.022	0.016																																																																													
0.052	0.089	0.068	0.047	0.036	0.026																																																																													
0.078	0.129	0.097	0.066	0.051	0.035																																																																													
0.104	0.169	0.126	0.085	0.065	0.045																																																																													
0.130	0.211	0.156	0.105	0.079	0.054																																																																													
0.143	0.232	0.171	0.114	0.086	0.059																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													



Model		MGFS1R52412		Temperature 25°C																																																																														
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<ul style="list-style-type: none"> <li>—△— Input Volt. 9V</li> <li>---□--- Input Volt. 12V</li> <li>-·-·*·-·-·- Input Volt. 18V</li> <li>-·-·○-·-·- Input Volt. 24V</li> <li>-·-·◇-·-·- Input Volt. 36V</li> </ul>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.12</td><td>0.14</td><td>0.16</td><td>0.18</td><td>0.15</td></tr> <tr><td>0.026</td><td>0.46</td><td>0.47</td><td>0.50</td><td>0.52</td><td>0.59</td></tr> <tr><td>0.052</td><td>0.80</td><td>0.82</td><td>0.85</td><td>0.86</td><td>0.93</td></tr> <tr><td>0.078</td><td>1.15</td><td>1.16</td><td>1.18</td><td>1.21</td><td>1.25</td></tr> <tr><td>0.104</td><td>1.51</td><td>1.51</td><td>1.52</td><td>1.55</td><td>1.61</td></tr> <tr><td>0.130</td><td>1.88</td><td>1.86</td><td>1.88</td><td>1.89</td><td>1.95</td></tr> <tr><td>0.143</td><td>2.07</td><td>2.04</td><td>2.04</td><td>2.06</td><td>2.14</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	0.12	0.14	0.16	0.18	0.15	0.026	0.46	0.47	0.50	0.52	0.59	0.052	0.80	0.82	0.85	0.86	0.93	0.078	1.15	1.16	1.18	1.21	1.25	0.104	1.51	1.51	1.52	1.55	1.61	0.130	1.88	1.86	1.88	1.89	1.95	0.143	2.07	2.04	2.04	2.06	2.14	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Current [A]	Input Power [W]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.000	0.12	0.14	0.16	0.18	0.15																																																																													
0.026	0.46	0.47	0.50	0.52	0.59																																																																													
0.052	0.80	0.82	0.85	0.86	0.93																																																																													
0.078	1.15	1.16	1.18	1.21	1.25																																																																													
0.104	1.51	1.51	1.52	1.55	1.61																																																																													
0.130	1.88	1.86	1.88	1.89	1.95																																																																													
0.143	2.07	2.04	2.04	2.06	2.14																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note: Slanted line shows the range of the rated load current.																																																																																		



Model		MGFS1R52412		Temperature	25°C																																
Item		Efficiency (by Input Voltage)		Testing Circuitry	Figure A																																
Object																																					
1.Graph			2.Values																																		
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.6</td><td>79.8</td><td>82.8</td></tr> <tr><td>9.0</td><td>79.8</td><td>83.3</td></tr> <tr><td>12.0</td><td>79.5</td><td>84.0</td></tr> <tr><td>15.0</td><td>77.9</td><td>84.3</td></tr> <tr><td>18.0</td><td>77.3</td><td>84.2</td></tr> <tr><td>24.0</td><td>75.1</td><td>83.0</td></tr> <tr><td>30.0</td><td>73.6</td><td>81.9</td></tr> <tr><td>36.0</td><td>71.2</td><td>80.3</td></tr> <tr><td>40.0</td><td>69.2</td><td>79.1</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.6	79.8	82.8	9.0	79.8	83.3	12.0	79.5	84.0	15.0	77.9	84.3	18.0	77.3	84.2	24.0	75.1	83.0	30.0	73.6	81.9	36.0	71.2	80.3	40.0	69.2	79.1
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
8.6	79.8	82.8																																			
9.0	79.8	83.3																																			
12.0	79.5	84.0																																			
15.0	77.9	84.3																																			
18.0	77.3	84.2																																			
24.0	75.1	83.0																																			
30.0	73.6	81.9																																			
36.0	71.2	80.3																																			
40.0	69.2	79.1																																			




Model		MGFS1R52412		Temperature	25°C																																																																													
Item		Efficiency (by Load Current)		Testing Circuitry	Figure A																																																																													
Object		_____																																																																																
1.Graph		<ul style="list-style-type: none"> <li>—△— Input Volt. 9V</li> <li>---□--- Input Volt. 12V</li> <li>-·-·*·-·- Input Volt. 18V</li> <li>-·-·○-·-·- Input Volt. 24V</li> <li>-·-·◇-·-·- Input Volt. 36V</li> </ul>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.026</td><td>66.3</td><td>66.6</td><td>62.7</td><td>59.1</td><td>52.9</td></tr> <tr><td>0.052</td><td>78.2</td><td>75.6</td><td>73.9</td><td>72.7</td><td>67.0</td></tr> <tr><td>0.078</td><td>81.5</td><td>80.8</td><td>79.4</td><td>77.3</td><td>74.9</td></tr> <tr><td>0.104</td><td>82.5</td><td>82.8</td><td>81.9</td><td>81.2</td><td>78.5</td></tr> <tr><td>0.130</td><td>83.3</td><td>84.0</td><td>84.2</td><td>83.0</td><td>80.3</td></tr> <tr><td>0.143</td><td>83.2</td><td>84.1</td><td>84.0</td><td>83.6</td><td>80.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-	-	-	-	-	0.026	66.3	66.6	62.7	59.1	52.9	0.052	78.2	75.6	73.9	72.7	67.0	0.078	81.5	80.8	79.4	77.3	74.9	0.104	82.5	82.8	81.9	81.2	78.5	0.130	83.3	84.0	84.2	83.0	80.3	0.143	83.2	84.1	84.0	83.6	80.5	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.000	-	-	-	-	-																																																																													
0.026	66.3	66.6	62.7	59.1	52.9																																																																													
0.052	78.2	75.6	73.9	72.7	67.0																																																																													
0.078	81.5	80.8	79.4	77.3	74.9																																																																													
0.104	82.5	82.8	81.9	81.2	78.5																																																																													
0.130	83.3	84.0	84.2	83.0	80.3																																																																													
0.143	83.2	84.1	84.0	83.6	80.5																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																		



Model	MGFS1R52412
Item	Line Regulation
Object	+12V0.13A

Temperature 25°C  
Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	12.017	12.014
9.0	12.017	12.014
12.0	12.017	12.015
15.0	12.017	12.015
18.0	12.017	12.015
24.0	12.017	12.015
30.0	12.017	12.015
36.0	12.016	12.014
40.0	12.017	12.015




Model		MGFS1R52412		Temperature 25°C																																																																												
Item		Load Regulation		Testing Circuitry Figure A																																																																												
Object		+12V0.13A																																																																														
1.Graph		<ul style="list-style-type: none"> <li>—△— Input Volt. 9V</li> <li>---□--- Input Volt. 12V</li> <li>---*--- Input Volt. 18V</li> <li>---○--- Input Volt. 24V</li> <li>---◇--- Input Volt. 36V</li> </ul>		2.Values																																																																												
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.021</td><td>12.021</td><td>12.021</td><td>12.020</td><td>12.021</td></tr> <tr><td>0.026</td><td>12.019</td><td>12.019</td><td>12.019</td><td>12.019</td><td>12.019</td></tr> <tr><td>0.052</td><td>12.018</td><td>12.019</td><td>12.018</td><td>12.018</td><td>12.018</td></tr> <tr><td>0.078</td><td>12.017</td><td>12.017</td><td>12.017</td><td>12.017</td><td>12.017</td></tr> <tr><td>0.104</td><td>12.016</td><td>12.016</td><td>12.016</td><td>12.016</td><td>12.015</td></tr> <tr><td>0.130</td><td>12.014</td><td>12.015</td><td>12.015</td><td>12.015</td><td>12.014</td></tr> <tr><td>0.143</td><td>12.013</td><td>12.014</td><td>12.014</td><td>12.014</td><td>12.014</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	12.021	12.021	12.021	12.020	12.021	0.026	12.019	12.019	12.019	12.019	12.019	0.052	12.018	12.019	12.018	12.018	12.018	0.078	12.017	12.017	12.017	12.017	12.017	0.104	12.016	12.016	12.016	12.016	12.015	0.130	12.014	12.015	12.015	12.015	12.014	0.143	12.013	12.014	12.014	12.014	12.014	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																											
0.000	12.021	12.021	12.021	12.020	12.021																																																																											
0.026	12.019	12.019	12.019	12.019	12.019																																																																											
0.052	12.018	12.019	12.018	12.018	12.018																																																																											
0.078	12.017	12.017	12.017	12.017	12.017																																																																											
0.104	12.016	12.016	12.016	12.016	12.015																																																																											
0.130	12.014	12.015	12.015	12.015	12.014																																																																											
0.143	12.013	12.014	12.014	12.014	12.014																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Note: Slanted line shows the range of the rated load current.																																																																																



Model		MGFS1R52412	
Item		Dynamic Load Response	Temperature 25°C
Object		+12V0.13A	Testing Circuitry Figure A


Input Volt. 24 V  
Cycle 100 ms

t1,t2 = 100 μs




Min.Load (0A) ←→  
Load 100% (0.13A)

100 mV/div




4 ms/div




4 ms/div

Min.Load (0A) ←→  
Load 50% (0.065A)

100 mV/div




4 ms/div




4 ms/div

Load 50% (0.065A) ←→  
Load 100% (0.13A)

100 mV/div



4 ms/div



4 ms/div



<p>Model MGFS1R52412</p> <p>Item Ripple Voltage (by Load Current)</p> <p>Object +12V0.13A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>             —△— Input Volt. 9V              - - ○ - - Input Volt. 36V         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>15</td></tr> <tr><td>0.026</td><td>15</td><td>10</td></tr> <tr><td>0.052</td><td>25</td><td>10</td></tr> <tr><td>0.078</td><td>30</td><td>15</td></tr> <tr><td>0.104</td><td>50</td><td>20</td></tr> <tr><td>0.130</td><td>70</td><td>25</td></tr> <tr><td>0.143</td><td>80</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.000	5	15	0.026	15	10	0.052	25	10	0.078	30	15	0.104	50	20	0.130	70	25	0.143	80	35	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.000	5	15																																						
0.026	15	10																																						
0.052	25	10																																						
0.078	30	15																																						
0.104	50	20																																						
0.130	70	25																																						
0.143	80	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope.                  Ripple Voltage is shown as p-p in the figure below.                  Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								



<p>Model MGFS1R52412</p> <p>Item Ripple-Noise</p> <p>Object +12V0.13A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>             —△— Input Volt. 9V              - - ○ - - Input Volt. 36V         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>15</td></tr> <tr><td>0.026</td><td>20</td><td>15</td></tr> <tr><td>0.052</td><td>25</td><td>15</td></tr> <tr><td>0.078</td><td>35</td><td>15</td></tr> <tr><td>0.104</td><td>55</td><td>25</td></tr> <tr><td>0.130</td><td>80</td><td>35</td></tr> <tr><td>0.143</td><td>85</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.000	5	15	0.026	20	15	0.052	25	15	0.078	35	15	0.104	55	25	0.130	80	35	0.143	85	40	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.000	5	15																																						
0.026	20	15																																						
0.052	25	15																																						
0.078	35	15																																						
0.104	55	25																																						
0.130	80	35																																						
0.143	85	40																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope.                  Ripple-Noise is shown as p-p in the figure below.                  Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								




Model		MGFS1R52412	Testing Circuitry Figure B																																					
Item		Ripple Voltage (by Ambient Temp.)																																						
Object		+12V0.13A																																						
1.Graph		<div style="text-align: right;">                     ---□--- Load 50%                      —△— Load 100%                 </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Input Volt. 24V</p>																																						
2.Values		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>25</td><td>45</td></tr> <tr><td>-40</td><td>20</td><td>40</td></tr> <tr><td>-20</td><td>15</td><td>40</td></tr> <tr><td>0</td><td>15</td><td>35</td></tr> <tr><td>25</td><td>15</td><td>35</td></tr> <tr><td>85</td><td>15</td><td>35</td></tr> <tr><td>90</td><td>15</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	25	45	-40	20	40	-20	15	40	0	15	35	25	15	35	85	15	35	90	15	35	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	25	45																																						
-40	20	40																																						
-20	15	40																																						
0	15	35																																						
25	15	35																																						
85	15	35																																						
90	15	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.																																								



Model	MGFS1R52412
Item	Ambient Temperature Drift
Object	+12V0.13A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	11.923	11.925	11.925	11.925	11.926
-40	11.956	11.957	11.957	11.957	11.957
-20	11.981	11.983	11.982	11.982	11.982
0	11.998	11.999	11.999	11.999	11.999
25	12.014	12.015	12.015	12.015	12.014
85	12.011	12.012	12.012	12.012	12.012
90	12.009	12.010	12.010	12.010	12.010
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



<b>COSEL</b>		
Model	MGFS1R52412	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V0.13A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 9 - 36V

Load Current : 0 - 0.13A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ratio) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	75	36	0	12.023	±34	±0.3
Minimum Voltage	-40	9	0.13	11.956		



<b>COSEL</b>																								
Model	MGFS1R52412																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+12V0.13A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.012</td></tr> <tr><td>0.5</td><td>12.014</td></tr> <tr><td>1.0</td><td>12.014</td></tr> <tr><td>2.0</td><td>12.014</td></tr> <tr><td>3.0</td><td>12.013</td></tr> <tr><td>4.0</td><td>12.014</td></tr> <tr><td>5.0</td><td>12.013</td></tr> <tr><td>6.0</td><td>12.013</td></tr> <tr><td>7.0</td><td>12.013</td></tr> <tr><td>8.0</td><td>12.013</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.012	0.5	12.014	1.0	12.014	2.0	12.014	3.0	12.013	4.0	12.014	5.0	12.013	6.0	12.013	7.0	12.013	8.0	12.013
Time since start [H]	Output Voltage [V]																							
0.0	12.012																							
0.5	12.014																							
1.0	12.014																							
2.0	12.014																							
3.0	12.013																							
4.0	12.014																							
5.0	12.013																							
6.0	12.013																							
7.0	12.013																							
8.0	12.013																							




Model		MGFS1R52412	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		+12V0.13A		



2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	1.6	0.9	2.5	0.4	7.6
100 %	1.6	1.2	2.8	0.3	3.8

[ms]





<b>COSEL</b>																																								
Model	MGFS1R52412																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+12V0.13A																																							
<p>1.Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>7.4</td><td>7.4</td></tr> <tr><td>-40</td><td>7.4</td><td>7.4</td></tr> <tr><td>-20</td><td>7.4</td><td>7.4</td></tr> <tr><td>0</td><td>7.4</td><td>7.4</td></tr> <tr><td>25</td><td>7.4</td><td>7.4</td></tr> <tr><td>85</td><td>7.3</td><td>7.4</td></tr> <tr><td>90</td><td>7.3</td><td>7.3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	7.4	7.4	-40	7.4	7.4	-20	7.4	7.4	0	7.4	7.4	25	7.4	7.4	85	7.3	7.4	90	7.3	7.3	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-60	7.4	7.4																																						
-40	7.4	7.4																																						
-20	7.4	7.4																																						
0	7.4	7.4																																						
25	7.4	7.4																																						
85	7.3	7.4																																						
90	7.3	7.3																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model MGFS1R52412</p>		<p>Temperature 25°C</p>																																																																																				
<p>Item Overcurrent Protection</p>		<p>Testing Circuitry Figure A</p>																																																																																				
<p>Object +12V0.13A</p>																																																																																						
<p>1.Graph</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>— Input Volt. 9V</p> <p>— Input Volt. 12V</p> <p>— Input Volt. 18V</p> <p>— Input Volt. 24V</p> <p>— Input Volt. 36V</p> </div> </div> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.162</td><td>0.171</td><td>0.168</td><td>0.167</td><td>0.168</td></tr> <tr><td>10.8</td><td>0.170</td><td>0.178</td><td>0.175</td><td>0.173</td><td>0.172</td></tr> <tr><td>9.6</td><td>0.185</td><td>0.194</td><td>0.191</td><td>0.185</td><td>0.183</td></tr> <tr><td>8.4</td><td>0.204</td><td>0.212</td><td>0.205</td><td>0.198</td><td>0.195</td></tr> <tr><td>7.2</td><td>0.224</td><td>0.232</td><td>0.220</td><td>0.212</td><td>0.206</td></tr> <tr><td>6.0</td><td>0.248</td><td>0.253</td><td>0.237</td><td>0.226</td><td>0.219</td></tr> <tr><td>4.8</td><td>0.276</td><td>0.276</td><td>0.255</td><td>0.243</td><td>0.234</td></tr> <tr><td>3.6</td><td>0.307</td><td>0.303</td><td>0.276</td><td>0.260</td><td>0.249</td></tr> <tr><td>2.4</td><td>0.344</td><td>0.334</td><td>0.299</td><td>0.280</td><td>0.265</td></tr> <tr><td>1.2</td><td>0.387</td><td>0.369</td><td>0.323</td><td>0.299</td><td>0.280</td></tr> <tr><td>0.0</td><td>0.416</td><td>0.377</td><td>0.312</td><td>0.281</td><td>0.259</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	11.4	0.162	0.171	0.168	0.167	0.168	10.8	0.170	0.178	0.175	0.173	0.172	9.6	0.185	0.194	0.191	0.185	0.183	8.4	0.204	0.212	0.205	0.198	0.195	7.2	0.224	0.232	0.220	0.212	0.206	6.0	0.248	0.253	0.237	0.226	0.219	4.8	0.276	0.276	0.255	0.243	0.234	3.6	0.307	0.303	0.276	0.260	0.249	2.4	0.344	0.334	0.299	0.280	0.265	1.2	0.387	0.369	0.323	0.299	0.280	0.0	0.416	0.377	0.312	0.281	0.259	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																																	
11.4	0.162	0.171	0.168	0.167	0.168																																																																																	
10.8	0.170	0.178	0.175	0.173	0.172																																																																																	
9.6	0.185	0.194	0.191	0.185	0.183																																																																																	
8.4	0.204	0.212	0.205	0.198	0.195																																																																																	
7.2	0.224	0.232	0.220	0.212	0.206																																																																																	
6.0	0.248	0.253	0.237	0.226	0.219																																																																																	
4.8	0.276	0.276	0.255	0.243	0.234																																																																																	
3.6	0.307	0.303	0.276	0.260	0.249																																																																																	
2.4	0.344	0.334	0.299	0.280	0.265																																																																																	
1.2	0.387	0.369	0.323	0.299	0.280																																																																																	
0.0	0.416	0.377	0.312	0.281	0.259																																																																																	
--	-	-	-	-	-																																																																																	



Model		MGFS1R52412		Temperature 25°C																																																																												
Item		Switching frequency (by Load Current)		Testing Circuitry Figure A																																																																												
Object		+12V0.13A																																																																														
1.Graph		<p>                     —△— Input Volt. 9V                      - - - □ - - - Input Volt. 12V                      - · · * · · - · - Input Volt. 18V                      - · - ○ - · - - Input Volt. 24V                      - - ◇ - - - Input Volt. 36V                 </p>		2.Values																																																																												
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>563</td><td>638</td><td>740</td><td>780</td><td>770</td></tr> <tr><td>0.026</td><td>380</td><td>463</td><td>570</td><td>636</td><td>700</td></tr> <tr><td>0.052</td><td>290</td><td>365</td><td>466</td><td>532</td><td>599</td></tr> <tr><td>0.078</td><td>232</td><td>300</td><td>395</td><td>457</td><td>525</td></tr> <tr><td>0.104</td><td>193</td><td>254</td><td>342</td><td>400</td><td>466</td></tr> <tr><td>0.130</td><td>165</td><td>221</td><td>301</td><td>355</td><td>418</td></tr> <tr><td>0.143</td><td>153</td><td>206</td><td>283</td><td>337</td><td>399</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	563	638	740	780	770	0.026	380	463	570	636	700	0.052	290	365	466	532	599	0.078	232	300	395	457	525	0.104	193	254	342	400	466	0.130	165	221	301	355	418	0.143	153	206	283	337	399	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																											
0.000	563	638	740	780	770																																																																											
0.026	380	463	570	636	700																																																																											
0.052	290	365	466	532	599																																																																											
0.078	232	300	395	457	525																																																																											
0.104	193	254	342	400	466																																																																											
0.130	165	221	301	355	418																																																																											
0.143	153	206	283	337	399																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
<p>Note: Slanted line shows the range of the rated load current.</p> <p>When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>																																																																																




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)