

TEST DATA OF MGFS3243R3

Regulated DC Power Supply
January 6, 2017

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	MGFS3243R3
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
6.0	0.003	0.003	0.003
8.0	0.004	0.003	0.003
8.2	0.004	0.003	0.004
8.4	0.016	0.210	0.432
8.6	0.015	0.202	0.418
8.8	0.015	0.200	0.411
9.0	0.014	0.194	0.401
12.0	0.012	0.145	0.290
18.0	0.010	0.096	0.189
24.0	0.006	0.073	0.142
30.0	0.003	0.059	0.113
36.0	0.005	0.051	0.096
40.0	0.004	0.047	0.086
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGFS3243R3																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 9V - -□-- Input Volt. 12V - ·*·— Input Volt. 18V - ·○·— Input Volt. 24V - ·◇·— Input Volt. 36V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.014</td> <td>0.012</td> <td>0.010</td> <td>0.005</td> <td>0.003</td> </tr> <tr> <td>0.16</td> <td>0.084</td> <td>0.064</td> <td>0.044</td> <td>0.034</td> <td>0.025</td> </tr> <tr> <td>0.32</td> <td>0.157</td> <td>0.118</td> <td>0.079</td> <td>0.060</td> <td>0.042</td> </tr> <tr> <td>0.48</td> <td>0.233</td> <td>0.173</td> <td>0.115</td> <td>0.087</td> <td>0.061</td> </tr> <tr> <td>0.64</td> <td>0.315</td> <td>0.231</td> <td>0.152</td> <td>0.114</td> <td>0.077</td> </tr> <tr> <td>0.72</td> <td>0.359</td> <td>0.261</td> <td>0.171</td> <td>0.128</td> <td>0.086</td> </tr> <tr> <td>0.80</td> <td>- *</td> <td>0.291</td> <td>0.190</td> <td>0.142</td> <td>0.096</td> </tr> <tr> <td>0.88</td> <td>- *</td> <td>0.322</td> <td>0.209</td> <td>0.155</td> <td>0.105</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.014	0.012	0.010	0.005	0.003	0.16	0.084	0.064	0.044	0.034	0.025	0.32	0.157	0.118	0.079	0.060	0.042	0.48	0.233	0.173	0.115	0.087	0.061	0.64	0.315	0.231	0.152	0.114	0.077	0.72	0.359	0.261	0.171	0.128	0.086	0.80	- *	0.291	0.190	0.142	0.096	0.88	- *	0.322	0.209	0.155	0.105	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	0.014	0.012	0.010	0.005	0.003																																																																													
0.16	0.084	0.064	0.044	0.034	0.025																																																																													
0.32	0.157	0.118	0.079	0.060	0.042																																																																													
0.48	0.233	0.173	0.115	0.087	0.061																																																																													
0.64	0.315	0.231	0.152	0.114	0.077																																																																													
0.72	0.359	0.261	0.171	0.128	0.086																																																																													
0.80	- *	0.291	0.190	0.142	0.096																																																																													
0.88	- *	0.322	0.209	0.155	0.105																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL


Model	MGFS3243R3																																																																																		
Item	Input Power (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																														
Object	<hr/>																																																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.13</td><td>0.16</td><td>0.17</td><td>0.12</td><td>0.11</td></tr> <tr><td>0.16</td><td>0.75</td><td>0.77</td><td>0.79</td><td>0.82</td><td>0.89</td></tr> <tr><td>0.32</td><td>1.41</td><td>1.41</td><td>1.43</td><td>1.44</td><td>1.51</td></tr> <tr><td>0.48</td><td>2.09</td><td>2.07</td><td>2.07</td><td>2.08</td><td>2.18</td></tr> <tr><td>0.64</td><td>2.81</td><td>2.75</td><td>2.73</td><td>2.73</td><td>2.78</td></tr> <tr><td>0.72</td><td>3.20</td><td>3.11</td><td>3.07</td><td>3.07</td><td>3.12</td></tr> <tr><td>0.80</td><td>-</td><td>3.47</td><td>3.41</td><td>3.40</td><td>3.46</td></tr> <tr><td>0.88</td><td>-</td><td>3.83</td><td>3.74</td><td>3.72</td><td>3.78</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.13	0.16	0.17	0.12	0.11	0.16	0.75	0.77	0.79	0.82	0.89	0.32	1.41	1.41	1.43	1.44	1.51	0.48	2.09	2.07	2.07	2.08	2.18	0.64	2.81	2.75	2.73	2.73	2.78	0.72	3.20	3.11	3.07	3.07	3.12	0.80	-	3.47	3.41	3.40	3.46	0.88	-	3.83	3.74	3.72	3.78	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	<hr/>									
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
0.00	0.13	0.16	0.17	0.12	0.11																																																																														
0.16	0.75	0.77	0.79	0.82	0.89																																																																														
0.32	1.41	1.41	1.43	1.44	1.51																																																																														
0.48	2.09	2.07	2.07	2.08	2.18																																																																														
0.64	2.81	2.75	2.73	2.73	2.78																																																																														
0.72	3.20	3.11	3.07	3.07	3.12																																																																														
0.80	-	3.47	3.41	3.40	3.46																																																																														
0.88	-	3.83	3.74	3.72	3.78																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.13</td><td>0.16</td><td>0.17</td><td>0.12</td><td>0.11</td></tr> <tr><td>0.16</td><td>0.75</td><td>0.77</td><td>0.79</td><td>0.82</td><td>0.89</td></tr> <tr><td>0.32</td><td>1.41</td><td>1.41</td><td>1.43</td><td>1.44</td><td>1.51</td></tr> <tr><td>0.48</td><td>2.09</td><td>2.07</td><td>2.07</td><td>2.08</td><td>2.18</td></tr> <tr><td>0.64</td><td>2.81</td><td>2.75</td><td>2.73</td><td>2.73</td><td>2.78</td></tr> <tr><td>0.72</td><td>3.20</td><td>3.11</td><td>3.07</td><td>3.07</td><td>3.12</td></tr> <tr><td>0.80</td><td>-</td><td>3.47</td><td>3.41</td><td>3.40</td><td>3.46</td></tr> <tr><td>0.88</td><td>-</td><td>3.83</td><td>3.74</td><td>3.72</td><td>3.78</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.13	0.16	0.17	0.12	0.11	0.16	0.75	0.77	0.79	0.82	0.89	0.32	1.41	1.41	1.43	1.44	1.51	0.48	2.09	2.07	2.07	2.08	2.18	0.64	2.81	2.75	2.73	2.73	2.78	0.72	3.20	3.11	3.07	3.07	3.12	0.80	-	3.47	3.41	3.40	3.46	0.88	-	3.83	3.74	3.72	3.78	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	<hr/>				
Load Current [A]	Input Power [W]																																																																																		
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
0.00	0.13	0.16	0.17	0.12	0.11																																																																														
0.16	0.75	0.77	0.79	0.82	0.89																																																																														
0.32	1.41	1.41	1.43	1.44	1.51																																																																														
0.48	2.09	2.07	2.07	2.08	2.18																																																																														
0.64	2.81	2.75	2.73	2.73	2.78																																																																														
0.72	3.20	3.11	3.07	3.07	3.12																																																																														
0.80	-	3.47	3.41	3.40	3.46																																																																														
0.88	-	3.83	3.74	3.72	3.78																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Note: Slanted line shows the range of the rated load current.	<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>	<hr/>																																																																																	

COSEL

Model	MGFS3243R3
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8.6	75.0	75.0
9.0	76.1	75.4
12.0	76.4	76.3
15.0	76.2	77.6
18.0	75.5	78.0
24.0	75.1	78.3
30.0	73.6	77.7
36.0	72.0	77.3
40.0	71.7	76.9

※1: Load 80%

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGFS3243R3																																																																																	
Item	Efficiency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object	<hr/>																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <p>Efficiency [%]</p> <p>Load Current [A]</p>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.16</td><td>70.1</td><td>68.9</td><td>67.1</td><td>65.0</td><td>59.9</td></tr> <tr><td>0.32</td><td>75.2</td><td>75.3</td><td>74.4</td><td>73.6</td><td>70.3</td></tr> <tr><td>0.48</td><td>76.2</td><td>77.0</td><td>77.0</td><td>76.4</td><td>74.0</td></tr> <tr><td>0.64</td><td>75.4</td><td>77.1</td><td>77.5</td><td>77.6</td><td>76.3</td></tr> <tr><td>0.72</td><td>74.6</td><td>76.7</td><td>77.6</td><td>77.7</td><td>76.6</td></tr> <tr><td>0.80</td><td>-</td><td>76.3</td><td>78.0</td><td>78.3</td><td>77.3</td></tr> <tr><td>0.88</td><td>-</td><td>76.0</td><td>77.9</td><td>78.5</td><td>77.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Efficiency [%]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	-	-	-	-	-	0.16	70.1	68.9	67.1	65.0	59.9	0.32	75.2	75.3	74.4	73.6	70.3	0.48	76.2	77.0	77.0	76.4	74.0	0.64	75.4	77.1	77.5	77.6	76.3	0.72	74.6	76.7	77.6	77.7	76.6	0.80	-	76.3	78.0	78.3	77.3	0.88	-	76.0	77.9	78.5	77.1	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.16	70.1	68.9	67.1	65.0	59.9																																																																													
0.32	75.2	75.3	74.4	73.6	70.3																																																																													
0.48	76.2	77.0	77.0	76.4	74.0																																																																													
0.64	75.4	77.1	77.5	77.6	76.3																																																																													
0.72	74.6	76.7	77.6	77.7	76.6																																																																													
0.80	-	76.3	78.0	78.3	77.3																																																																													
0.88	-	76.0	77.9	78.5	77.1																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFS3243R3																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+3.3V0.8A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.6</td><td>3.313</td><td>- *</td></tr> <tr><td>9.0</td><td>3.313</td><td>- *</td></tr> <tr><td>12.0</td><td>3.313</td><td>3.311</td></tr> <tr><td>15.0</td><td>3.313</td><td>3.311</td></tr> <tr><td>18.0</td><td>3.313</td><td>3.311</td></tr> <tr><td>24.0</td><td>3.313</td><td>3.311</td></tr> <tr><td>30.0</td><td>3.313</td><td>3.311</td></tr> <tr><td>36.0</td><td>3.313</td><td>3.311</td></tr> <tr><td>40.0</td><td>3.313</td><td>3.311</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.6	3.313	- *	9.0	3.313	- *	12.0	3.313	3.311	15.0	3.313	3.311	18.0	3.313	3.311	24.0	3.313	3.311	30.0	3.313	3.311	36.0	3.313	3.311	40.0	3.313	3.311
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
8.6	3.313	- *																																
9.0	3.313	- *																																
12.0	3.313	3.311																																
15.0	3.313	3.311																																
18.0	3.313	3.311																																
24.0	3.313	3.311																																
30.0	3.313	3.311																																
36.0	3.313	3.311																																
40.0	3.313	3.311																																
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																		

COSEL

Model	MGFS3243R3																																																																																	
Item	Load Regulation																																																																																	
Object	+3.3V0.8A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																	
Temperature Testing Circuitry	25°C Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>3.314</td> <td>3.314</td> <td>3.314</td> <td>3.314</td> <td>3.314</td> </tr> <tr> <td>0.16</td> <td>3.314</td> <td>3.314</td> <td>3.314</td> <td>3.313</td> <td>3.313</td> </tr> <tr> <td>0.32</td> <td>3.313</td> <td>3.313</td> <td>3.313</td> <td>3.313</td> <td>3.313</td> </tr> <tr> <td>0.48</td> <td>3.312</td> <td>3.312</td> <td>3.313</td> <td>3.313</td> <td>3.312</td> </tr> <tr> <td>0.64</td> <td>3.312</td> <td>3.312</td> <td>3.312</td> <td>3.312</td> <td>3.312</td> </tr> <tr> <td>0.72</td> <td>3.311</td> <td>3.311</td> <td>3.312</td> <td>3.312</td> <td>3.311</td> </tr> <tr> <td>0.80</td> <td>-</td> <td>3.311</td> <td>3.311</td> <td>3.311</td> <td>3.311</td> </tr> <tr> <td>0.88</td> <td>-</td> <td>3.311</td> <td>3.311</td> <td>3.311</td> <td>3.311</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	3.314	3.314	3.314	3.314	3.314	0.16	3.314	3.314	3.314	3.313	3.313	0.32	3.313	3.313	3.313	3.313	3.313	0.48	3.312	3.312	3.313	3.313	3.312	0.64	3.312	3.312	3.312	3.312	3.312	0.72	3.311	3.311	3.312	3.312	3.311	0.80	-	3.311	3.311	3.311	3.311	0.88	-	3.311	3.311	3.311	3.311	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	3.314	3.314	3.314	3.314	3.314																																																																													
0.16	3.314	3.314	3.314	3.313	3.313																																																																													
0.32	3.313	3.313	3.313	3.313	3.313																																																																													
0.48	3.312	3.312	3.313	3.313	3.312																																																																													
0.64	3.312	3.312	3.312	3.312	3.312																																																																													
0.72	3.311	3.311	3.312	3.312	3.311																																																																													
0.80	-	3.311	3.311	3.311	3.311																																																																													
0.88	-	3.311	3.311	3.311	3.311																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL


Model	MGFS3243R3	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+3.3V0.8A	

Input Volt. 24 V
 Cycle 100 ms




Min.Load (0A)↔
 Load 100% (0.8A)

100 mV/div
 400 μ s/div

400 μ s/div


Min.Load (0A)↔
 Load 50% (0.4A)

100 mV/div
 400 μ s/div

400 μ s/div

Load 50% (0.4A)↔
 Load 100% (0.8A)

100 mV/div
 400 μ s/div

400 μ s/div

COSEL


Model	MGFS3243R3																																								
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																							
Object	+3.3V0.8A																																								
1.Graph																																									
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0.0 to 1.0 A. Two curves are plotted: one for Input Volt. 12V (solid line with triangle markers) and one for Input Volt. 36V (dashed line with circle markers). Both curves show an increase in ripple voltage as load current increases. A slanted line indicates the rated load current range.</p>		2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>5</td> <td>15</td> </tr> <tr> <td>0.16</td> <td>5</td> <td>10</td> </tr> <tr> <td>0.32</td> <td>25</td> <td>10</td> </tr> <tr> <td>0.48</td> <td>30</td> <td>15</td> </tr> <tr> <td>0.64</td> <td>45</td> <td>20</td> </tr> <tr> <td>0.72</td> <td>60</td> <td>30</td> </tr> <tr> <td>0.80</td> <td>70</td> <td>40</td> </tr> <tr> <td>0.88</td> <td>90</td> <td>50</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.00	5	15	0.16	5	10	0.32	25	10	0.48	30	15	0.64	45	20	0.72	60	30	0.80	70	40	0.88	90	50	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 12 [V]	Input Volt. 36 [V]																																							
0.00	5	15																																							
0.16	5	10																																							
0.32	25	10																																							
0.48	30	15																																							
0.64	45	20																																							
0.72	60	30																																							
0.80	70	40																																							
0.88	90	50																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.																																									
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																									

COSEL

Model	MGFS3243R3
Item	Ripple-Noise
Object	+3.3V0.8A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 12 [V]	Input Volt. 36 [V]
0.00	10	15
0.16	10	15
0.32	30	15
0.48	35	15
0.64	50	25
0.72	65	35
0.80	80	45
0.88	100	55
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGFS3243R3
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V0.8A

Testing Circuitry Figure B

1. Graph



2. Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	20	60
-40	15	50
-20	15	45
0	10	45
25	10	40
75	10	40
85	10	40
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGFS3243R3
Item	Ambient Temperature Drift
Object	+3.3V0.8A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-60	3.301	3.300	3.302	3.302	3.303
-40	3.306	3.306	3.307	3.307	3.307
-20	3.311	3.310	3.311	3.311	3.311
0	3.313	3.312	3.313	3.313	3.313
25	3.310	3.311	3.311	3.311	3.311
75	3.307	3.307	3.307	3.307	3.307
85	3.305	3.305	3.305	3.304	3.304
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of Input Volt. 9V, Load 80%.
Other case Load 100%.



Model	MGFS3243R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V0.8A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 75°C

Input Voltage : 12 - 36V

Load Current : 0 - 0.8A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	25	12	0	3.315	± 5	± 0.2
Minimum Voltage	-40	12	0.8	3.306		

COSEL

Model	MGFS3243R3
Item	Time Lapse Drift
Object	+3.3V0.8A

Temperature 25°C
 Testing Circuitry Figure A

1.Graph



Input Volt. 24V
 Load 100%

2.Values


Time since start [H]	Output Voltage [V]
0.0	3.311
0.5	3.312
1.0	3.311
2.0	3.311
3.0	3.311
4.0	3.312
5.0	3.311
6.0	3.311
7.0	3.311
8.0	3.311

COSEL

Model	MGFS3243R3
Item	Rise and Fall Time
Object	+3.3V0.8A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.2	0.2	1.4	0.2	1.9
100 %		1.2	0.2	1.4	0.1	0.5




COSEL

Model	MGFS3243R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V0.8A

Testing Circuitry Figure A

1. Graph




Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	7.4	7.5
-40	7.4	7.4
-20	7.4	7.4
0	7.4	7.4
25	7.3	7.4
75	7.3	7.4
85	7.3	7.4
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGFS3243R3
Item	Overcurrent Protection
Object	+3.3V0.8A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]				
	9[V]	12[V]	18[V]	24[V]	36[V]
3.14	0.856	0.980	1.037	1.002	1.003
2.97	0.882	1.010	1.064	1.025	1.022
2.64	0.938	1.075	1.121	1.074	1.061
2.31	1.008	1.148	1.180	1.125	1.108
1.98	1.090	1.227	1.247	1.183	1.157
1.65	1.181	1.311	1.314	1.241	1.205
1.32	1.278	1.404	1.389	1.305	1.257
0.99	1.392	1.505	1.472	1.368	1.311
0.66	1.519	1.614	1.554	1.435	1.362
0.33	1.657	1.731	1.631	1.491	1.400
0.00	1.739	1.735	1.568	1.410	1.302
--	-	-	-	-	-

Note: Slanted line shows the range of the rated load current.

Maximum output current at minimum input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS3243R3	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Switching frequency (by Load Current)																																																																															
Object	+3.3V0.8A																																																																															
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <p>Note: Slanted line shows the range of the rated load current.</p> <p>When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>750</td> <td>840</td> <td>950</td> <td>1040</td> <td>960</td> </tr> <tr> <td>0.16</td> <td>421</td> <td>518</td> <td>639</td> <td>708</td> <td>782</td> </tr> <tr> <td>0.32</td> <td>290</td> <td>373</td> <td>481</td> <td>548</td> <td>623</td> </tr> <tr> <td>0.48</td> <td>219</td> <td>289</td> <td>384</td> <td>446</td> <td>520</td> </tr> <tr> <td>0.64</td> <td>174</td> <td>235</td> <td>320</td> <td>376</td> <td>444</td> </tr> <tr> <td>0.72</td> <td>159</td> <td>216</td> <td>297</td> <td>351</td> <td>416</td> </tr> <tr> <td>0.80</td> <td>-</td> <td>197</td> <td>274</td> <td>325</td> <td>389</td> </tr> <tr> <td>0.88</td> <td>-</td> <td>182</td> <td>255</td> <td>304</td> <td>365</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	750	840	950	1040	960	0.16	421	518	639	708	782	0.32	290	373	481	548	623	0.48	219	289	384	446	520	0.64	174	235	320	376	444	0.72	159	216	297	351	416	0.80	-	197	274	325	389	0.88	-	182	255	304	365	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																											
0.00	750	840	950	1040	960																																																																											
0.16	421	518	639	708	782																																																																											
0.32	290	373	481	548	623																																																																											
0.48	219	289	384	446	520																																																																											
0.64	174	235	320	376	444																																																																											
0.72	159	216	297	351	416																																																																											
0.80	-	197	274	325	389																																																																											
0.88	-	182	255	304	365																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
	<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																															




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)