

TEST DATA OF MGFS34805

Regulated DC Power Supply
January 11, 2017

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	MGFS34805
Item	Input Current (by Input Voltage)
Object	_____




Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A


2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
16.0	0.003	0.003	0.003
16.2	0.004	0.003	0.004
16.4	0.009	0.119	0.237
16.6	0.008	0.117	0.236
16.8	0.008	0.116	0.235
17.0	0.008	0.114	0.233
18.0	0.008	0.108	0.218
24.0	0.006	0.081	0.158
36.0	0.005	0.054	0.104
48.0	0.004	0.041	0.078
60.0	0.003	0.033	0.064
76.0	0.003	0.028	0.052
80.0	0.003	0.027	0.048
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGFS34805	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Current (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 18V - -□--- Input Volt. 24V - ·*·— Input Volt. 36V - ·○·— Input Volt. 48V - ·◇·— Input Volt. 76V																																																																														
																																																																																
Note: Slanted line shows the range of the rated load current.			※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																													
2.Values																																																																																
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.008</td> <td>0.006</td> <td>0.005</td> <td>0.004</td> <td>0.003</td> </tr> <tr> <td>0.12</td> <td>0.047</td> <td>0.035</td> <td>0.025</td> <td>0.018</td> <td>0.014</td> </tr> <tr> <td>0.24</td> <td>0.087</td> <td>0.066</td> <td>0.044</td> <td>0.033</td> <td>0.023</td> </tr> <tr> <td>0.36</td> <td>0.129</td> <td>0.096</td> <td>0.064</td> <td>0.049</td> <td>0.032</td> </tr> <tr> <td>0.48</td> <td>0.173</td> <td>0.128</td> <td>0.085</td> <td>0.063</td> <td>0.042</td> </tr> <tr> <td>0.54</td> <td>0.196</td> <td>0.143</td> <td>0.094</td> <td>0.071</td> <td>0.046</td> </tr> <tr> <td>0.60</td> <td>- ※</td> <td>0.158</td> <td>0.104</td> <td>0.078</td> <td>0.052</td> </tr> <tr> <td>0.66</td> <td>- ※</td> <td>0.176</td> <td>0.116</td> <td>0.086</td> <td>0.056</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.008	0.006	0.005	0.004	0.003	0.12	0.047	0.035	0.025	0.018	0.014	0.24	0.087	0.066	0.044	0.033	0.023	0.36	0.129	0.096	0.064	0.049	0.032	0.48	0.173	0.128	0.085	0.063	0.042	0.54	0.196	0.143	0.094	0.071	0.046	0.60	- ※	0.158	0.104	0.078	0.052	0.66	- ※	0.176	0.116	0.086	0.056	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	0.008	0.006	0.005	0.004	0.003																																																																											
0.12	0.047	0.035	0.025	0.018	0.014																																																																											
0.24	0.087	0.066	0.044	0.033	0.023																																																																											
0.36	0.129	0.096	0.064	0.049	0.032																																																																											
0.48	0.173	0.128	0.085	0.063	0.042																																																																											
0.54	0.196	0.143	0.094	0.071	0.046																																																																											
0.60	- ※	0.158	0.104	0.078	0.052																																																																											
0.66	- ※	0.176	0.116	0.086	0.056																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											

COSEL


Model	MGFS34805	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Power (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 18V - -□--- Input Volt. 24V - -*--- Input Volt. 36V - -○--- Input Volt. 48V - -◇--- Input Volt. 76V																																																																														
		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.14</td> <td>0.15</td> <td>0.18</td> <td>0.17</td> <td>0.17</td> </tr> <tr> <td>0.12</td> <td>0.85</td> <td>0.85</td> <td>0.89</td> <td>0.88</td> <td>1.09</td> </tr> <tr> <td>0.24</td> <td>1.57</td> <td>1.57</td> <td>1.60</td> <td>1.60</td> <td>1.71</td> </tr> <tr> <td>0.36</td> <td>2.32</td> <td>2.30</td> <td>2.32</td> <td>2.37</td> <td>2.41</td> </tr> <tr> <td>0.48</td> <td>3.10</td> <td>3.06</td> <td>3.05</td> <td>3.01</td> <td>3.20</td> </tr> <tr> <td>0.54</td> <td>3.51</td> <td>3.43</td> <td>3.40</td> <td>3.40</td> <td>3.53</td> </tr> <tr> <td>0.60</td> <td>-</td> <td>3.80</td> <td>3.75</td> <td>3.78</td> <td>3.87</td> </tr> <tr> <td>0.66</td> <td>-</td> <td>4.21</td> <td>4.17</td> <td>4.12</td> <td>4.24</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.14	0.15	0.18	0.17	0.17	0.12	0.85	0.85	0.89	0.88	1.09	0.24	1.57	1.57	1.60	1.60	1.71	0.36	2.32	2.30	2.32	2.37	2.41	0.48	3.10	3.06	3.05	3.01	3.20	0.54	3.51	3.43	3.40	3.40	3.53	0.60	-	3.80	3.75	3.78	3.87	0.66	-	4.21	4.17	4.12	4.24	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Power [W]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	0.14	0.15	0.18	0.17	0.17																																																																											
0.12	0.85	0.85	0.89	0.88	1.09																																																																											
0.24	1.57	1.57	1.60	1.60	1.71																																																																											
0.36	2.32	2.30	2.32	2.37	2.41																																																																											
0.48	3.10	3.06	3.05	3.01	3.20																																																																											
0.54	3.51	3.43	3.40	3.40	3.53																																																																											
0.60	-	3.80	3.75	3.78	3.87																																																																											
0.66	-	4.21	4.17	4.12	4.24																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Note: Slanted line shows the range of the rated load current.		※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																														

COSEL

Model	MGFS34805
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	77.7	77.6
18	77.9	78.0
24	78.5	79.7
30	78.6	80.1
36	78.5	80.6
48	76.9	80.6
60	75.7	80.5
76	72.1	78.4
80	71.0	78.0

※1: Load 80%

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	MGFS34805																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.12</td> <td>71.5</td> <td>71.7</td> <td>68.4</td> <td>68.7</td> <td>55.8</td> </tr> <tr> <td>0.24</td> <td>76.9</td> <td>77.0</td> <td>75.9</td> <td>75.6</td> <td>70.6</td> </tr> <tr> <td>0.36</td> <td>78.4</td> <td>78.9</td> <td>78.4</td> <td>77.3</td> <td>75.4</td> </tr> <tr> <td>0.48</td> <td>78.0</td> <td>79.2</td> <td>79.3</td> <td>80.3</td> <td>76.3</td> </tr> <tr> <td>0.54</td> <td>77.5</td> <td>79.5</td> <td>80.0</td> <td>80.4</td> <td>77.2</td> </tr> <tr> <td>0.60</td> <td>-</td> <td>※</td> <td>79.7</td> <td>80.6</td> <td>80.6</td> </tr> <tr> <td>0.66</td> <td>-</td> <td>※</td> <td>79.1</td> <td>79.8</td> <td>80.7</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Efficiency [%]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	-	-	-	-	-	0.12	71.5	71.7	68.4	68.7	55.8	0.24	76.9	77.0	75.9	75.6	70.6	0.36	78.4	78.9	78.4	77.3	75.4	0.48	78.0	79.2	79.3	80.3	76.3	0.54	77.5	79.5	80.0	80.4	77.2	0.60	-	※	79.7	80.6	80.6	0.66	-	※	79.1	79.8	80.7	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.12	71.5	71.7	68.4	68.7	55.8																																																																													
0.24	76.9	77.0	75.9	75.6	70.6																																																																													
0.36	78.4	78.9	78.4	77.3	75.4																																																																													
0.48	78.0	79.2	79.3	80.3	76.3																																																																													
0.54	77.5	79.5	80.0	80.4	77.2																																																																													
0.60	-	※	79.7	80.6	80.6																																																																													
0.66	-	※	79.1	79.8	80.7																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
※	Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFS34805
Item	Line Regulation
Object	+5V0.6A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	5.039	- *
18	5.039	- *
24	5.039	5.038
30	5.039	5.039
36	5.039	5.038
48	5.039	5.038
60	5.039	5.040
76	5.039	5.039
80	5.039	5.040

Note: Slanted line shows the range of the rated input voltage.

* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS34805																																																																																	
Item	Load Regulation																																																																																	
Object	+5V0.6A																																																																																	
1.Graph																																																																																		
					2.Values																																																																													
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>5.042</td> <td>5.042</td> <td>5.042</td> <td>5.042</td> <td>5.042</td> </tr> <tr> <td>0.12</td> <td>5.041</td> <td>5.041</td> <td>5.041</td> <td>5.041</td> <td>5.041</td> </tr> <tr> <td>0.24</td> <td>5.041</td> <td>5.041</td> <td>5.041</td> <td>5.041</td> <td>5.041</td> </tr> <tr> <td>0.36</td> <td>5.040</td> <td>5.040</td> <td>5.040</td> <td>5.040</td> <td>5.040</td> </tr> <tr> <td>0.48</td> <td>5.038</td> <td>5.040</td> <td>5.040</td> <td>5.040</td> <td>5.040</td> </tr> <tr> <td>0.54</td> <td>5.038</td> <td>5.039</td> <td>5.039</td> <td>5.039</td> <td>5.039</td> </tr> <tr> <td>0.60</td> <td>-</td> <td>5.038</td> <td>5.038</td> <td>5.038</td> <td>5.039</td> </tr> <tr> <td>0.66</td> <td>-</td> <td>5.037</td> <td>5.039</td> <td>5.039</td> <td>5.039</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	5.042	5.042	5.042	5.042	5.042	0.12	5.041	5.041	5.041	5.041	5.041	0.24	5.041	5.041	5.041	5.041	5.041	0.36	5.040	5.040	5.040	5.040	5.040	0.48	5.038	5.040	5.040	5.040	5.040	0.54	5.038	5.039	5.039	5.039	5.039	0.60	-	5.038	5.038	5.038	5.039	0.66	-	5.037	5.039	5.039	5.039	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	5.042	5.042	5.042	5.042	5.042																																																																													
0.12	5.041	5.041	5.041	5.041	5.041																																																																													
0.24	5.041	5.041	5.041	5.041	5.041																																																																													
0.36	5.040	5.040	5.040	5.040	5.040																																																																													
0.48	5.038	5.040	5.040	5.040	5.040																																																																													
0.54	5.038	5.039	5.039	5.039	5.039																																																																													
0.60	-	5.038	5.038	5.038	5.039																																																																													
0.66	-	5.037	5.039	5.039	5.039																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p> <p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																		

COSEL

Model	MGFS34805	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+5V0.6A	

Input Volt. 48 V
 Cycle 100 ms



Min.Load (0A)↔
 Load 100% (0.6A)

100 mV/div

400 μ s/div400 μ s/div

Min.Load (0A)↔
 Load 50% (0.3A)

100 mV/div

400 μ s/div400 μ s/div

Load 50% (0.3A)↔
 Load 100% (0.6A)

100 mV/div


400 μ s/div400 μ s/div

COSEL

Model	MGFS34805
Item	Ripple Voltage (by Load Current)
Object	+5V0.6A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 24 [V]	Input Volt. 76 [V]
0.00	5	15
0.12	10	10
0.24	35	15
0.36	40	15
0.48	50	20
0.54	55	30
0.60	60	40
0.66	85	55
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	MGFS34805
Item	Ripple-Noise
Object	+5V0.6A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 24 [V]	Input Volt. 76 [V]
0.00	5	20
0.12	15	15
0.24	35	15
0.36	45	20
0.48	55	25
0.54	60	37.5
0.60	65	50
0.66	90	65
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGFS34805
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V0.6A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	25	65
-40	20	60
-20	20	60
0	15	55
25	15	55
75	15	55
85	15	55
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGFS34805
Item	Ambient Temperature Drift
Object	+5V0.6A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	5.000	4.999	5.002	5.002	5.003
-40	5.013	5.012	5.014	5.015	5.015
-20	5.023	5.022	5.024	5.025	5.025
0	5.031	5.030	5.032	5.032	5.033
25	5.038	5.038	5.038	5.038	5.039
75	5.040	5.039	5.041	5.041	5.041
85	5.039	5.039	5.040	5.040	5.040
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of Input Volt. 18V, Load 80%.
Other case Load 100%.



Model	MGFS34805	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V0.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 75°C

Input Voltage : 24 - 76V

Load Current : 0 - 0.6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	70	76	0	5.044	± 16	± 0.3
Minimum Voltage	-40	24	0.6	5.012		

COSEL

Model	MGFS34805
Item	Time Lapse Drift
Object	+5V0.6A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph


 Input Volt. 48V
 Load 100%

2.Values


Time since start [H]	Output Voltage [V]
0.0	5.037
0.5	5.040
1.0	5.040
2.0	5.040
3.0	5.040
4.0	5.040
5.0	5.040
6.0	5.040
7.0	5.040
8.0	5.040

COSEL

Model	MGFS34805
Item	Rise and Fall Time
Object	+5V0.6A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.2	0.4	1.6	0.2	3.2	
100 %		1.2	0.5	1.7	0.1	1.6	




COSEL

Model	MGFS34805
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V0.6A

Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	14.7	14.7
-40	14.6	14.6
-20	14.6	14.6
0	14.5	14.5
25	14.4	14.4
75	14.3	14.3
85	14.3	14.2
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGFS34805																																																																																							
Item	Overcurrent Protection																																																																																							
Object	+5V0.6A																																																																																							
1.Graph																																																																																								
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>																																																																																								
Note: Slanted line shows the range of the rated load current.																																																																																								
<p>Maximum output current at minimum input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																								
Temperature 25°C Testing Circuitry Figure A																																																																																								
2.Values																																																																																								
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>4.75</td> <td>0.655</td> <td>0.773</td> <td>0.803</td> <td>0.796</td> <td>0.819</td> </tr> <tr> <td>4.50</td> <td>0.679</td> <td>0.802</td> <td>0.830</td> <td>0.817</td> <td>0.835</td> </tr> <tr> <td>4.00</td> <td>0.735</td> <td>0.866</td> <td>0.884</td> <td>0.862</td> <td>0.863</td> </tr> <tr> <td>3.50</td> <td>0.802</td> <td>0.938</td> <td>0.942</td> <td>0.908</td> <td>0.896</td> </tr> <tr> <td>3.00</td> <td>0.878</td> <td>1.015</td> <td>0.998</td> <td>0.961</td> <td>0.942</td> </tr> <tr> <td>2.50</td> <td>0.965</td> <td>1.093</td> <td>1.062</td> <td>1.016</td> <td>0.989</td> </tr> <tr> <td>2.00</td> <td>1.061</td> <td>1.179</td> <td>1.133</td> <td>1.077</td> <td>1.040</td> </tr> <tr> <td>1.50</td> <td>1.162</td> <td>1.277</td> <td>1.211</td> <td>1.142</td> <td>1.094</td> </tr> <tr> <td>1.00</td> <td>1.282</td> <td>1.384</td> <td>1.292</td> <td>1.208</td> <td>1.146</td> </tr> <tr> <td>0.50</td> <td>1.402</td> <td>1.476</td> <td>1.351</td> <td>1.252</td> <td>1.173</td> </tr> <tr> <td>0.00</td> <td>1.413</td> <td>1.439</td> <td>1.275</td> <td>1.163</td> <td>1.072</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>						Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	4.75	0.655	0.773	0.803	0.796	0.819	4.50	0.679	0.802	0.830	0.817	0.835	4.00	0.735	0.866	0.884	0.862	0.863	3.50	0.802	0.938	0.942	0.908	0.896	3.00	0.878	1.015	0.998	0.961	0.942	2.50	0.965	1.093	1.062	1.016	0.989	2.00	1.061	1.179	1.133	1.077	1.040	1.50	1.162	1.277	1.211	1.142	1.094	1.00	1.282	1.384	1.292	1.208	1.146	0.50	1.402	1.476	1.351	1.252	1.173	0.00	1.413	1.439	1.275	1.163	1.072	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																							
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																			
4.75	0.655	0.773	0.803	0.796	0.819																																																																																			
4.50	0.679	0.802	0.830	0.817	0.835																																																																																			
4.00	0.735	0.866	0.884	0.862	0.863																																																																																			
3.50	0.802	0.938	0.942	0.908	0.896																																																																																			
3.00	0.878	1.015	0.998	0.961	0.942																																																																																			
2.50	0.965	1.093	1.062	1.016	0.989																																																																																			
2.00	1.061	1.179	1.133	1.077	1.040																																																																																			
1.50	1.162	1.277	1.211	1.142	1.094																																																																																			
1.00	1.282	1.384	1.292	1.208	1.146																																																																																			
0.50	1.402	1.476	1.351	1.252	1.173																																																																																			
0.00	1.413	1.439	1.275	1.163	1.072																																																																																			
--	-	-	-	-	-																																																																																			

COSEL

Model	MGFS34805	Temperature	25°C																																																																													
Item	Switching frequency (by Load Current)	Testing Circuitry	Figure A																																																																													
Object	+5V0.6A																																																																															
1.Graph																																																																																
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>525</td> <td>592</td> <td>673</td> <td>712</td> <td>718</td> </tr> <tr> <td>0.12</td> <td>360</td> <td>433</td> <td>527</td> <td>579</td> <td>633</td> </tr> <tr> <td>0.24</td> <td>273</td> <td>340</td> <td>430</td> <td>484</td> <td>544</td> </tr> <tr> <td>0.36</td> <td>218</td> <td>278</td> <td>363</td> <td>414</td> <td>476</td> </tr> <tr> <td>0.48</td> <td>180</td> <td>236</td> <td>314</td> <td>363</td> <td>424</td> </tr> <tr> <td>0.54</td> <td>167</td> <td>220</td> <td>295</td> <td>343</td> <td>403</td> </tr> <tr> <td>0.60</td> <td>-</td> <td>203</td> <td>276</td> <td>322</td> <td>382</td> </tr> <tr> <td>0.66</td> <td>-</td> <td>190</td> <td>260</td> <td>306</td> <td>364</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	525	592	673	712	718	0.12	360	433	527	579	633	0.24	273	340	430	484	544	0.36	218	278	363	414	476	0.48	180	236	314	363	424	0.54	167	220	295	343	403	0.60	-	203	276	322	382	0.66	-	190	260	306	364	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	525	592	673	712	718																																																																											
0.12	360	433	527	579	633																																																																											
0.24	273	340	430	484	544																																																																											
0.36	218	278	363	414	476																																																																											
0.48	180	236	314	363	424																																																																											
0.54	167	220	295	343	403																																																																											
0.60	-	203	276	322	382																																																																											
0.66	-	190	260	306	364																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Note:	Slanted line shows the range of the rated load current.																																																																															
	When load current is low, MG operates intermittently, so switching frequency would not become constant.																																																																															
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																															




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)