

TEST DATA OF MGFS3483R3

Regulated DC Power Supply
January 11, 2017

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	MGFS3483R3
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
16.0	0.003	0.003	0.003
16.2	0.003	0.003	0.004
16.4	0.008	0.109	0.222
16.6	0.008	0.107	0.218
16.8	0.008	0.106	0.216
17.0	0.008	0.104	0.213
18.0	0.008	0.098	0.199
24.0	0.006	0.073	0.145
36.0	0.004	0.049	0.096
48.0	0.003	0.038	0.072
60.0	0.003	0.031	0.058
76.0	0.003	0.025	0.047
80.0	0.003	0.025	0.045
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


COSEL

Model	MGFS3483R3	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Current (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 18V - -□--- Input Volt. 24V - ·*··· Input Volt. 36V - ·○··· Input Volt. 48V - ·◇··· Input Volt. 76V																																																																														
2.Values																																																																																
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.007</td> <td>0.006</td> <td>0.004</td> <td>0.004</td> <td>0.003</td> </tr> <tr> <td>0.16</td> <td>0.042</td> <td>0.032</td> <td>0.023</td> <td>0.017</td> <td>0.012</td> </tr> <tr> <td>0.32</td> <td>0.079</td> <td>0.060</td> <td>0.040</td> <td>0.031</td> <td>0.021</td> </tr> <tr> <td>0.48</td> <td>0.118</td> <td>0.088</td> <td>0.058</td> <td>0.044</td> <td>0.029</td> </tr> <tr> <td>0.64</td> <td>0.158</td> <td>0.117</td> <td>0.077</td> <td>0.057</td> <td>0.038</td> </tr> <tr> <td>0.72</td> <td>0.179</td> <td>0.131</td> <td>0.086</td> <td>0.064</td> <td>0.043</td> </tr> <tr> <td>0.80</td> <td>- *</td> <td>0.145</td> <td>0.095</td> <td>0.072</td> <td>0.047</td> </tr> <tr> <td>0.88</td> <td>- *</td> <td>0.161</td> <td>0.106</td> <td>0.078</td> <td>0.051</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.007	0.006	0.004	0.004	0.003	0.16	0.042	0.032	0.023	0.017	0.012	0.32	0.079	0.060	0.040	0.031	0.021	0.48	0.118	0.088	0.058	0.044	0.029	0.64	0.158	0.117	0.077	0.057	0.038	0.72	0.179	0.131	0.086	0.064	0.043	0.80	- *	0.145	0.095	0.072	0.047	0.88	- *	0.161	0.106	0.078	0.051	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	0.007	0.006	0.004	0.004	0.003																																																																											
0.16	0.042	0.032	0.023	0.017	0.012																																																																											
0.32	0.079	0.060	0.040	0.031	0.021																																																																											
0.48	0.118	0.088	0.058	0.044	0.029																																																																											
0.64	0.158	0.117	0.077	0.057	0.038																																																																											
0.72	0.179	0.131	0.086	0.064	0.043																																																																											
0.80	- *	0.145	0.095	0.072	0.047																																																																											
0.88	- *	0.161	0.106	0.078	0.051																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																

Note: Slanted line shows the range of the rated load current.

* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

COSEL


Model	MGFS3483R3																																																																																		
Item	Input Power (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																														
Object	<hr/>																																																																																		
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - *--- Input Volt. 36V - - ○--- Input Volt. 48V - - ◇--- Input Volt. 76V</p>  <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>18[V] [W]</th> <th>24[V] [W]</th> <th>36[V] [W]</th> <th>48[V] [W]</th> <th>76[V] [W]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.13</td><td>0.15</td><td>0.15</td><td>0.19</td><td>0.22</td></tr> <tr><td>0.16</td><td>0.76</td><td>0.77</td><td>0.82</td><td>0.83</td><td>0.95</td></tr> <tr><td>0.32</td><td>1.43</td><td>1.43</td><td>1.46</td><td>1.48</td><td>1.62</td></tr> <tr><td>0.48</td><td>2.12</td><td>2.10</td><td>2.08</td><td>2.11</td><td>2.20</td></tr> <tr><td>0.64</td><td>2.83</td><td>2.79</td><td>2.76</td><td>2.73</td><td>2.92</td></tr> <tr><td>0.72</td><td>3.21</td><td>3.14</td><td>3.09</td><td>3.09</td><td>3.25</td></tr> <tr><td>0.80</td><td>-</td><td>3.48</td><td>3.43</td><td>3.45</td><td>3.59</td></tr> <tr><td>0.88</td><td>-</td><td>3.86</td><td>3.80</td><td>3.77</td><td>3.91</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	18[V] [W]	24[V] [W]	36[V] [W]	48[V] [W]	76[V] [W]	0.00	0.13	0.15	0.15	0.19	0.22	0.16	0.76	0.77	0.82	0.83	0.95	0.32	1.43	1.43	1.46	1.48	1.62	0.48	2.12	2.10	2.08	2.11	2.20	0.64	2.83	2.79	2.76	2.73	2.92	0.72	3.21	3.14	3.09	3.09	3.25	0.80	-	3.48	3.43	3.45	3.59	0.88	-	3.86	3.80	3.77	3.91	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	<hr/>									
Load Current [A]	18[V] [W]	24[V] [W]	36[V] [W]	48[V] [W]	76[V] [W]																																																																														
0.00	0.13	0.15	0.15	0.19	0.22																																																																														
0.16	0.76	0.77	0.82	0.83	0.95																																																																														
0.32	1.43	1.43	1.46	1.48	1.62																																																																														
0.48	2.12	2.10	2.08	2.11	2.20																																																																														
0.64	2.83	2.79	2.76	2.73	2.92																																																																														
0.72	3.21	3.14	3.09	3.09	3.25																																																																														
0.80	-	3.48	3.43	3.45	3.59																																																																														
0.88	-	3.86	3.80	3.77	3.91																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.13</td><td>0.15</td><td>0.15</td><td>0.19</td><td>0.22</td></tr> <tr><td>0.16</td><td>0.76</td><td>0.77</td><td>0.82</td><td>0.83</td><td>0.95</td></tr> <tr><td>0.32</td><td>1.43</td><td>1.43</td><td>1.46</td><td>1.48</td><td>1.62</td></tr> <tr><td>0.48</td><td>2.12</td><td>2.10</td><td>2.08</td><td>2.11</td><td>2.20</td></tr> <tr><td>0.64</td><td>2.83</td><td>2.79</td><td>2.76</td><td>2.73</td><td>2.92</td></tr> <tr><td>0.72</td><td>3.21</td><td>3.14</td><td>3.09</td><td>3.09</td><td>3.25</td></tr> <tr><td>0.80</td><td>-</td><td>3.48</td><td>3.43</td><td>3.45</td><td>3.59</td></tr> <tr><td>0.88</td><td>-</td><td>3.86</td><td>3.80</td><td>3.77</td><td>3.91</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.13	0.15	0.15	0.19	0.22	0.16	0.76	0.77	0.82	0.83	0.95	0.32	1.43	1.43	1.46	1.48	1.62	0.48	2.12	2.10	2.08	2.11	2.20	0.64	2.83	2.79	2.76	2.73	2.92	0.72	3.21	3.14	3.09	3.09	3.25	0.80	-	3.48	3.43	3.45	3.59	0.88	-	3.86	3.80	3.77	3.91	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	<hr/>				
Load Current [A]	Input Power [W]																																																																																		
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																														
0.00	0.13	0.15	0.15	0.19	0.22																																																																														
0.16	0.76	0.77	0.82	0.83	0.95																																																																														
0.32	1.43	1.43	1.46	1.48	1.62																																																																														
0.48	2.12	2.10	2.08	2.11	2.20																																																																														
0.64	2.83	2.79	2.76	2.73	2.92																																																																														
0.72	3.21	3.14	3.09	3.09	3.25																																																																														
0.80	-	3.48	3.43	3.45	3.59																																																																														
0.88	-	3.86	3.80	3.77	3.91																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Note:	Slanted line shows the range of the rated load current.																																																																																		
	<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																		

COSEL

Model	MGFS3483R3
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	74.4	74.1 ※1
18	74.8	74.7 ※1
24	75.3	76.1
30	75.0	76.4
36	74.3	77.3
48	73.2	77.1
60	72.3	77.0
76	70.2	75.2
80	68.6	74.8

※1: Load 80%

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	MGFS3483R3																																																																																	
Item	Efficiency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object	<hr/>																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.16</td><td>69.7</td><td>68.5</td><td>64.6</td><td>63.7</td><td>55.9</td></tr> <tr><td>0.32</td><td>74.3</td><td>74.0</td><td>72.7</td><td>71.5</td><td>65.3</td></tr> <tr><td>0.48</td><td>75.0</td><td>75.6</td><td>76.5</td><td>75.3</td><td>72.1</td></tr> <tr><td>0.64</td><td>74.7</td><td>75.8</td><td>76.8</td><td>77.2</td><td>74.0</td></tr> <tr><td>0.72</td><td>74.1</td><td>76.0</td><td>77.0</td><td>77.2</td><td>74.4</td></tr> <tr><td>0.80</td><td>-</td><td>76.1</td><td>77.3</td><td>77.1</td><td>75.2</td></tr> <tr><td>0.88</td><td>-</td><td>75.4</td><td>76.6</td><td>77.3</td><td>74.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Efficiency [%]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	-	-	-	-	-	0.16	69.7	68.5	64.6	63.7	55.9	0.32	74.3	74.0	72.7	71.5	65.3	0.48	75.0	75.6	76.5	75.3	72.1	0.64	74.7	75.8	76.8	77.2	74.0	0.72	74.1	76.0	77.0	77.2	74.4	0.80	-	76.1	77.3	77.1	75.2	0.88	-	75.4	76.6	77.3	74.7	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.16	69.7	68.5	64.6	63.7	55.9																																																																													
0.32	74.3	74.0	72.7	71.5	65.3																																																																													
0.48	75.0	75.6	76.5	75.3	72.1																																																																													
0.64	74.7	75.8	76.8	77.2	74.0																																																																													
0.72	74.1	76.0	77.0	77.2	74.4																																																																													
0.80	-	76.1	77.3	77.1	75.2																																																																													
0.88	-	75.4	76.6	77.3	74.7																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFS3483R3
Item	Line Regulation
Object	+3.3V0.8A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	3.309	- *
18	3.309	- *
24	3.309	3.307
30	3.309	3.307
36	3.309	3.308
48	3.309	3.307
60	3.309	3.307
76	3.308	3.307
80	3.308	3.307

* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS3483R3																																																																																	
Item	Load Regulation																																																																																	
Object	+3.3V0.8A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																	
Temperature Testing Circuitry	25°C Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>3.310</td> <td>3.310</td> <td>3.310</td> <td>3.310</td> <td>3.310</td> </tr> <tr> <td>0.16</td> <td>3.310</td> <td>3.310</td> <td>3.310</td> <td>3.309</td> <td>3.309</td> </tr> <tr> <td>0.32</td> <td>3.309</td> <td>3.309</td> <td>3.309</td> <td>3.309</td> <td>3.309</td> </tr> <tr> <td>0.48</td> <td>3.309</td> <td>3.309</td> <td>3.309</td> <td>3.309</td> <td>3.308</td> </tr> <tr> <td>0.64</td> <td>3.308</td> <td>3.308</td> <td>3.308</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>0.72</td> <td>3.307</td> <td>3.308</td> <td>3.308</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>0.80</td> <td>-</td> <td>3.308</td> <td>3.308</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>0.88</td> <td>-</td> <td>3.307</td> <td>3.307</td> <td>3.308</td> <td>3.307</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	3.310	3.310	3.310	3.310	3.310	0.16	3.310	3.310	3.310	3.309	3.309	0.32	3.309	3.309	3.309	3.309	3.309	0.48	3.309	3.309	3.309	3.309	3.308	0.64	3.308	3.308	3.308	3.308	3.308	0.72	3.307	3.308	3.308	3.308	3.308	0.80	-	3.308	3.308	3.308	3.308	0.88	-	3.307	3.307	3.308	3.307	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	3.310	3.310	3.310	3.310	3.310																																																																													
0.16	3.310	3.310	3.310	3.309	3.309																																																																													
0.32	3.309	3.309	3.309	3.309	3.309																																																																													
0.48	3.309	3.309	3.309	3.309	3.308																																																																													
0.64	3.308	3.308	3.308	3.308	3.308																																																																													
0.72	3.307	3.308	3.308	3.308	3.308																																																																													
0.80	-	3.308	3.308	3.308	3.308																																																																													
0.88	-	3.307	3.307	3.308	3.307																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL


Model	MGFS3483R3	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+3.3V0.8A	

Input Volt. 48 V
 Cycle 100 ms




Min.Load (0A)↔
 Load 100% (0.8A)

100 mV/div
 400 μ s/div




Min.Load (0A)↔
 Load 50% (0.4A)

100 mV/div
 400 μ s/div



Load 50% (0.4A)↔
 Load 100% (0.8A)

100 mV/div
 400 μ s/div



COSEL

Model	MGFS3483R3																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+3.3V0.8A																																							
1.Graph																																								
<p>The graph plots Ripple Voltage [mV] on the Y-axis (0 to 400) against Load Current [A] on the X-axis (0.0 to 1.0). Two sets of data points are shown: one for an Input Voltage of 24V (marked with solid triangles) and another for 76V (marked with open circles). A slanted line is drawn through the data points, starting from approximately (0.05, 10) and ending at (0.85, 75), indicating the range of the rated load current.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 24 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>5</td><td>20</td></tr> <tr> <td>0.16</td><td>5</td><td>20</td></tr> <tr> <td>0.32</td><td>20</td><td>10</td></tr> <tr> <td>0.48</td><td>30</td><td>10</td></tr> <tr> <td>0.64</td><td>40</td><td>20</td></tr> <tr> <td>0.72</td><td>50</td><td>30</td></tr> <tr> <td>0.80</td><td>60</td><td>35</td></tr> <tr> <td>0.88</td><td>75</td><td>40</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 24 [V]	Input Volt. 76 [V]	0.00	5	20	0.16	5	20	0.32	20	10	0.48	30	10	0.64	40	20	0.72	50	30	0.80	60	35	0.88	75	40	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 24 [V]	Input Volt. 76 [V]																																						
0.00	5	20																																						
0.16	5	20																																						
0.32	20	10																																						
0.48	30	10																																						
0.64	40	20																																						
0.72	50	30																																						
0.80	60	35																																						
0.88	75	40																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>The figure shows a waveform with multiple sharp, narrow peaks per cycle, representing a complex ripple pattern measured by an oscilloscope.</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								


COSEL

Model	MGFS3483R3																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+3.3V0.8A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0.0 to 1.0 A. Two curves are shown: Input Volt. 24V (solid line with triangle markers) and Input Volt. 76V (dashed line with circle markers). Both curves show an increase in Ripple Voltage as Load Current increases. A slanted line indicates the rated load current range.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 24 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>5</td> <td>35</td> </tr> <tr> <td>0.16</td> <td>20</td> <td>45</td> </tr> <tr> <td>0.32</td> <td>30</td> <td>30</td> </tr> <tr> <td>0.48</td> <td>45</td> <td>40</td> </tr> <tr> <td>0.64</td> <td>65</td> <td>45</td> </tr> <tr> <td>0.72</td> <td>75</td> <td>55</td> </tr> <tr> <td>0.80</td> <td>85</td> <td>65</td> </tr> <tr> <td>0.88</td> <td>100</td> <td>70</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 24 [V]	Input Volt. 76 [V]	0.00	5	35	0.16	20	45	0.32	30	30	0.48	45	40	0.64	65	45	0.72	75	55	0.80	85	65	0.88	100	70	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 24 [V]	Input Volt. 76 [V]																																						
0.00	5	35																																						
0.16	20	45																																						
0.32	30	30																																						
0.48	45	40																																						
0.64	65	45																																						
0.72	75	55																																						
0.80	85	65																																						
0.88	100	70																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								

COSEL

Model	MGFS3483R3
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V0.8A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	15	50
-40	10	45
-20	10	45
0	10	40
25	10	40
75	10	40
85	10	40
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGFS3483R3
Item	Ambient Temperature Drift
Object	+3.3V0.8A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	3.306	3.305	3.307	3.307	3.307
-40	3.310	3.310	3.311	3.311	3.311
-20	3.313	3.313	3.314	3.314	3.314
0	3.315	3.314	3.315	3.315	3.315
25	3.314	3.314	3.314	3.314	3.314
75	3.305	3.305	3.305	3.305	3.305
85	3.303	3.303	3.303	3.302	3.302
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of Input Volt. 18V, Load 80%.
Other case Load 100%.



Model	MGFS3483R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V0.8A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 75°C

Input Voltage : 24 - 76V

Load Current : 0 - 0.8A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	0	24	0	3.317	± 6	± 0.2
Minimum Voltage	75	76	0.8	3.305		

COSEL

Model	MGFS3483R3
Item	Time Lapse Drift
Object	+3.3V0.8A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph


 Input Volt. 48V
 Load 100%

2.Values


Time since start [H]	Output Voltage [V]
0.0	3.308
0.5	3.308
1.0	3.308
2.0	3.308
3.0	3.308
4.0	3.308
5.0	3.308
6.0	3.308
7.0	3.308
8.0	3.308

COSEL

Model	MGFS3483R3
Item	Rise and Fall Time
Object	+3.3V0.8A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.2	0.2	1.4	0.2	1.9	
100 %		1.2	0.2	1.4	0.1	0.5	




COSEL

Model	MGFS3483R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V0.8A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	14.7	14.7
-40	14.6	14.6
-20	14.6	14.6
0	14.5	14.5
25	14.4	14.4
75	14.3	14.3
85	14.3	14.2
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGFS3483R3																																																																																							
Item	Overcurrent Protection																																																																																							
Object	+3.3V0.8A																																																																																							
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>																																																																																							
	<p>Note: Slanted line shows the range of the rated load current.</p> <p>Maximum output current at minimum input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																							
Temperature	25°C																																																																																							
Testing Circuitry	Figure A																																																																																							
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>3.14</td><td>0.932</td><td>1.094</td><td>1.122</td><td>1.101</td><td>1.121</td></tr> <tr><td>2.97</td><td>0.963</td><td>1.125</td><td>1.150</td><td>1.124</td><td>1.138</td></tr> <tr><td>2.64</td><td>1.032</td><td>1.206</td><td>1.213</td><td>1.177</td><td>1.169</td></tr> <tr><td>2.31</td><td>1.115</td><td>1.288</td><td>1.278</td><td>1.232</td><td>1.216</td></tr> <tr><td>1.98</td><td>1.204</td><td>1.369</td><td>1.347</td><td>1.293</td><td>1.270</td></tr> <tr><td>1.65</td><td>1.302</td><td>1.458</td><td>1.420</td><td>1.357</td><td>1.323</td></tr> <tr><td>1.32</td><td>1.404</td><td>1.557</td><td>1.497</td><td>1.425</td><td>1.382</td></tr> <tr><td>0.99</td><td>1.523</td><td>1.664</td><td>1.583</td><td>1.495</td><td>1.439</td></tr> <tr><td>0.66</td><td>1.648</td><td>1.777</td><td>1.668</td><td>1.563</td><td>1.492</td></tr> <tr><td>0.33</td><td>1.772</td><td>1.871</td><td>1.721</td><td>1.601</td><td>1.510</td></tr> <tr><td>0.00</td><td>1.817</td><td>1.841</td><td>1.646</td><td>1.499</td><td>1.391</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	3.14	0.932	1.094	1.122	1.101	1.121	2.97	0.963	1.125	1.150	1.124	1.138	2.64	1.032	1.206	1.213	1.177	1.169	2.31	1.115	1.288	1.278	1.232	1.216	1.98	1.204	1.369	1.347	1.293	1.270	1.65	1.302	1.458	1.420	1.357	1.323	1.32	1.404	1.557	1.497	1.425	1.382	0.99	1.523	1.664	1.583	1.495	1.439	0.66	1.648	1.777	1.668	1.563	1.492	0.33	1.772	1.871	1.721	1.601	1.510	0.00	1.817	1.841	1.646	1.499	1.391	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																							
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																			
3.14	0.932	1.094	1.122	1.101	1.121																																																																																			
2.97	0.963	1.125	1.150	1.124	1.138																																																																																			
2.64	1.032	1.206	1.213	1.177	1.169																																																																																			
2.31	1.115	1.288	1.278	1.232	1.216																																																																																			
1.98	1.204	1.369	1.347	1.293	1.270																																																																																			
1.65	1.302	1.458	1.420	1.357	1.323																																																																																			
1.32	1.404	1.557	1.497	1.425	1.382																																																																																			
0.99	1.523	1.664	1.583	1.495	1.439																																																																																			
0.66	1.648	1.777	1.668	1.563	1.492																																																																																			
0.33	1.772	1.871	1.721	1.601	1.510																																																																																			
0.00	1.817	1.841	1.646	1.499	1.391																																																																																			
--	-	-	-	-	-																																																																																			

COSEL

Model	MGFS3483R3	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Switching frequency (by Load Current)																																																																															
Object	+3.3V0.8A																																																																															
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>558</td> <td>622</td> <td>693</td> <td>684</td> <td>711</td> </tr> <tr> <td>0.16</td> <td>371</td> <td>440</td> <td>526</td> <td>569</td> <td>615</td> </tr> <tr> <td>0.32</td> <td>274</td> <td>338</td> <td>422</td> <td>466</td> <td>518</td> </tr> <tr> <td>0.48</td> <td>218</td> <td>274</td> <td>350</td> <td>394</td> <td>448</td> </tr> <tr> <td>0.64</td> <td>179</td> <td>230</td> <td>300</td> <td>342</td> <td>394</td> </tr> <tr> <td>0.72</td> <td>165</td> <td>214</td> <td>281</td> <td>322</td> <td>373</td> </tr> <tr> <td>0.80</td> <td>-</td> <td>198</td> <td>262</td> <td>301</td> <td>352</td> </tr> <tr> <td>0.88</td> <td>-</td> <td>185</td> <td>247</td> <td>285</td> <td>334</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	558	622	693	684	711	0.16	371	440	526	569	615	0.32	274	338	422	466	518	0.48	218	274	350	394	448	0.64	179	230	300	342	394	0.72	165	214	281	322	373	0.80	-	198	262	301	352	0.88	-	185	247	285	334	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	558	622	693	684	711																																																																											
0.16	371	440	526	569	615																																																																											
0.32	274	338	422	466	518																																																																											
0.48	218	274	350	394	448																																																																											
0.64	179	230	300	342	394																																																																											
0.72	165	214	281	322	373																																																																											
0.80	-	198	262	301	352																																																																											
0.88	-	185	247	285	334																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Note:	<p>Slanted line shows the range of the rated load current.</p> <p>When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>																																																																															
	<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																															




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)