

TEST DATA OF MGFS400512

Regulated DC Power Supply

November 29, 2018

Approved by : Junichi Hatagishi Junichi Hatagishi Design Manager

Prepared by : Shohei Mukaide
Shohei Mukaide Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	9
10.Ripple-Noise · · · · ·	10
11.Ripple Voltage (by Ambient Temperature) · · · · ·	11
12.Ambient Temperature Drift · · · · ·	12
13.Output Voltage Accuracy · · · · ·	13
14.Time Lapse Drift · · · · ·	14
15.Rise and Fall Time · · · · ·	15
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	16
17.Overcurrent Protection · · · · ·	17
18.Overvoltage Protection · · · · ·	18
19.Switching frequency (by Load Current) · · · · ·	19
20.Figure of Testing Circuitry · · · · ·	20

(Final Page 20)

COSEL

Model	MGFS400512
Item	Input Current (by Input Voltage)
Object	_____




Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values


Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
3.8	0.105	0.004	0.004
3.9	0.103	4.405	9.442
4.0	0.102	4.273	9.027
4.1	0.100	3.829	8.682
4.2	0.098	4.153	8.680
4.3	0.097	4.037	8.376
4.4	0.095	3.931	8.100
4.5	0.095	3.755	7.717
5.0	0.088	3.333	6.911
7.0	0.037	2.383	4.814
9.0	0.030	1.861	3.723
13.0	0.028	1.336	2.587
15.0	0.028	1.184	2.260
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGFS400512																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	—△— Input Volt. 4.5V - - -□--- Input Volt. 5V - - -*--- Input Volt. 7V - - -○--- Input Volt. 9V - - -◇--- Input Volt. 13V																																																																																	
																																																																																		
	Note: Slanted line shows the range of the rated load current.																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values																																																																																		
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.095</td> <td>0.088</td> <td>0.037</td> <td>0.030</td> <td>0.028</td> </tr> <tr> <td>0.50</td> <td>1.541</td> <td>1.379</td> <td>0.999</td> <td>0.800</td> <td>0.580</td> </tr> <tr> <td>1.00</td> <td>2.979</td> <td>2.714</td> <td>1.937</td> <td>1.515</td> <td>1.076</td> </tr> <tr> <td>1.25</td> <td>3.755</td> <td>3.333</td> <td>2.383</td> <td>1.861</td> <td>1.336</td> </tr> <tr> <td>1.50</td> <td>4.479</td> <td>3.971</td> <td>2.871</td> <td>2.227</td> <td>1.581</td> </tr> <tr> <td>1.75</td> <td>5.271</td> <td>4.721</td> <td>3.320</td> <td>2.599</td> <td>1.832</td> </tr> <tr> <td>2.00</td> <td>6.006</td> <td>5.427</td> <td>3.836</td> <td>2.944</td> <td>2.072</td> </tr> <tr> <td>2.50</td> <td>7.717</td> <td>6.911</td> <td>4.814</td> <td>3.723</td> <td>2.587</td> </tr> <tr> <td>2.75</td> <td>8.774</td> <td>7.591</td> <td>5.304</td> <td>4.077</td> <td>2.848</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Input Current [A]					4.5[V]	5[V]	7[V]	9[V]	13[V]	0.00	0.095	0.088	0.037	0.030	0.028	0.50	1.541	1.379	0.999	0.800	0.580	1.00	2.979	2.714	1.937	1.515	1.076	1.25	3.755	3.333	2.383	1.861	1.336	1.50	4.479	3.971	2.871	2.227	1.581	1.75	5.271	4.721	3.320	2.599	1.832	2.00	6.006	5.427	3.836	2.944	2.072	2.50	7.717	6.911	4.814	3.723	2.587	2.75	8.774	7.591	5.304	4.077	2.848	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																													
0.00	0.095	0.088	0.037	0.030	0.028																																																																													
0.50	1.541	1.379	0.999	0.800	0.580																																																																													
1.00	2.979	2.714	1.937	1.515	1.076																																																																													
1.25	3.755	3.333	2.383	1.861	1.336																																																																													
1.50	4.479	3.971	2.871	2.227	1.581																																																																													
1.75	5.271	4.721	3.320	2.599	1.832																																																																													
2.00	6.006	5.427	3.836	2.944	2.072																																																																													
2.50	7.717	6.911	4.814	3.723	2.587																																																																													
2.75	8.774	7.591	5.304	4.077	2.848																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

COSEL

Model	MGFS400512
Item	Input Power (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Power [W]				
	4.5[V]	5[V]	7[V]	9[V]	13[V]
0.00	0.43	0.45	0.26	0.27	0.37
0.50	6.96	6.96	7.09	7.26	7.54
1.00	13.62	13.59	13.56	13.67	14.07
1.25	16.92	16.85	16.80	16.93	17.42
1.50	20.37	20.25	20.10	20.16	20.60
1.75	23.95	23.75	23.45	23.45	23.81
2.00	27.56	27.34	26.85	26.78	27.08
2.50	35.22	34.76	33.84	33.58	33.68
2.75	39.42	38.57	37.41	37.04	37.05
--	-	-	-	-	-
--	-	-	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model	MGFS400512
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
4.3	89.3	84.9
4.5	89.4	85.7
5.0	89.8	87.0
7.0	90.0	89.3
9.0	89.3	90.0
11.0	88.1	89.8
13.0	86.7	89.6
15.0	85.0	88.9
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGFS400512																																																																								
Item	Efficiency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																				
Object	<u> </u>																																																																								
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 4.5V Input Volt. 5V Input Volt. 7V Input Volt. 9V Input Volt. 13V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>87.2</td><td>87.1</td><td>85.7</td><td>83.5</td><td>80.4</td></tr> <tr><td>1.00</td><td>88.8</td><td>88.9</td><td>89.2</td><td>88.5</td><td>85.9</td></tr> <tr><td>1.25</td><td>89.4</td><td>89.8</td><td>90.0</td><td>89.3</td><td>86.7</td></tr> <tr><td>1.50</td><td>89.0</td><td>89.5</td><td>90.2</td><td>90.0</td><td>88.1</td></tr> <tr><td>1.75</td><td>88.3</td><td>89.0</td><td>90.2</td><td>90.2</td><td>88.8</td></tr> <tr><td>2.00</td><td>87.7</td><td>88.4</td><td>90.0</td><td>90.2</td><td>89.2</td></tr> <tr><td>2.50</td><td>85.7</td><td>87.0</td><td>89.3</td><td>90.0</td><td>89.6</td></tr> <tr><td>2.75</td><td>84.3</td><td>86.1</td><td>88.8</td><td>89.7</td><td>89.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	4.5[V]	5[V]	7[V]	9[V]	13[V]	0.00	-	-	-	-	-	0.50	87.2	87.1	85.7	83.5	80.4	1.00	88.8	88.9	89.2	88.5	85.9	1.25	89.4	89.8	90.0	89.3	86.7	1.50	89.0	89.5	90.2	90.0	88.1	1.75	88.3	89.0	90.2	90.2	88.8	2.00	87.7	88.4	90.0	90.2	89.2	2.50	85.7	87.0	89.3	90.0	89.6	2.75	84.3	86.1	88.8	89.7	89.6	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																				
0.00	-	-	-	-	-																																																																				
0.50	87.2	87.1	85.7	83.5	80.4																																																																				
1.00	88.8	88.9	89.2	88.5	85.9																																																																				
1.25	89.4	89.8	90.0	89.3	86.7																																																																				
1.50	89.0	89.5	90.2	90.0	88.1																																																																				
1.75	88.3	89.0	90.2	90.2	88.8																																																																				
2.00	87.7	88.4	90.0	90.2	89.2																																																																				
2.50	85.7	87.0	89.3	90.0	89.6																																																																				
2.75	84.3	86.1	88.8	89.7	89.6																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
2.Values																																																																									




Note: Slanted line shows the range of the rated load current.

COSEL

Model	MGFS400512
Item	Line Regulation
Object	+12V2.5A

Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.3	12.088	12.085
4.5	12.088	12.085
5.0	12.086	12.085
7.0	12.084	12.083
9.0	12.080	12.081
11.0	12.076	12.080
13.0	12.073	12.077
15.0	12.069	12.074
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGFS400512
Item	Load Regulation
Object	+12V2.5A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]				
	4.5[V]	5[V]	7[V]	9[V]	13[V]
0.00	12.088	12.087	12.091	12.091	12.091
0.50	12.088	12.087	12.084	12.080	12.078
1.00	12.088	12.086	12.084	12.081	12.075
1.25	12.088	12.086	12.084	12.080	12.073
1.50	12.087	12.086	12.084	12.081	12.074
1.75	12.087	12.086	12.084	12.081	12.075
2.00	12.086	12.086	12.083	12.081	12.076
2.50	12.085	12.085	12.083	12.081	12.077
2.75	12.085	12.084	12.083	12.082	12.077
--	-	-	-	-	-
--	-	-	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	MGFS400512	Temperature Testing Circuitry Figure A	25°C
Item	Dynamic Load Response		Figure A
Object	+12V2.5A		


Input Volt. 5 V
 Cycle 100 ms



Min.Load (0A)↔
 Load 100% (2.5A)

200 mV/div


2 ms/div



Min.Load (0A)↔
 Load 50% (1.25A)

200 mV/div


2 ms/div



Load 50% (1.25A)↔
 Load 100% (2.5A)

200 mV/div

2 ms/div



COSEL


Model	MGFS400512																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+12V2.5A																																							
1.Graph																																								
<p>Legend: —▲— Input Volt. 4.5V -○- Input Volt. 13V </p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 13 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>5</td><td>10</td></tr> <tr> <td>0.50</td><td>10</td><td>10</td></tr> <tr> <td>1.00</td><td>10</td><td>10</td></tr> <tr> <td>1.50</td><td>5</td><td>15</td></tr> <tr> <td>2.00</td><td>20</td><td>15</td></tr> <tr> <td>2.50</td><td>40</td><td>15</td></tr> <tr> <td>2.75</td><td>55</td><td>10</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 13 [V]	0.00	5	10	0.50	10	10	1.00	10	10	1.50	5	15	2.00	20	15	2.50	40	15	2.75	55	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 13 [V]																																						
0.00	5	10																																						
0.50	10	10																																						
1.00	10	10																																						
1.50	5	15																																						
2.00	20	15																																						
2.50	40	15																																						
2.75	55	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	MGFS400512
Item	Ripple-Noise
Object	+12V2.5A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 13 [V]
0.00	10	15
0.50	15	15
1.00	15	20
1.50	15	20
2.00	20	20
2.50	40	20
2.75	60	25
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGFS400512
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V2.5A

1. Graph




Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	55
-40	10	55
-20	10	60
25	5	50
60	10	50
85	10	50
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL


Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	4.5[V]	5[V]	7[V]	9[V]	13[V]
-60	11.985	11.989	11.992	11.992	11.986
-40	12.018	12.021	12.022	12.022	12.017
-20	12.044	12.046	12.047	12.047	12.041
0	12.063	12.064	12.064	12.064	12.058
25	12.078	12.079	12.079	12.078	12.072
50	12.086	12.087	12.086	12.085	12.080
60	12.089	12.089	12.088	12.087	12.082
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFS400512	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V2.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 50°C

Input Voltage : 4.5 - 13V

Load Current : 0 - 2.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	9	0	12.095	±40	±0.3
Minimum Voltage	-40	5	0	12.015		


COSEL

Model	MGFS400512	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V2.5A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.079</td></tr> <tr><td>0.5</td><td>12.087</td></tr> <tr><td>1.0</td><td>12.087</td></tr> <tr><td>2.0</td><td>12.087</td></tr> <tr><td>3.0</td><td>12.087</td></tr> <tr><td>4.0</td><td>12.087</td></tr> <tr><td>5.0</td><td>12.087</td></tr> <tr><td>6.0</td><td>12.087</td></tr> <tr><td>7.0</td><td>12.087</td></tr> <tr><td>8.0</td><td>12.087</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.079	0.5	12.087	1.0	12.087	2.0	12.087	3.0	12.087	4.0	12.087	5.0	12.087	6.0	12.087	7.0	12.087	8.0	12.087
Time since start [H]	Output Voltage [V]																								
0.0	12.079																								
0.5	12.087																								
1.0	12.087																								
2.0	12.087																								
3.0	12.087																								
4.0	12.087																								
5.0	12.087																								
6.0	12.087																								
7.0	12.087																								
8.0	12.087																								

COSEL


Model	MGFS400512	Temperature Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+12V2.5A	

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		7.9	3.4	11.3	0.3	4.9	
100 %		7.4	4.4	11.8	0.2	1.7	




COSEL

Model	MGFS400512
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V2.5A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.5	3.8
-40	3.5	3.7
-20	3.4	3.7
0	3.7	3.8
25	3.7	3.7
50	3.7	3.8
60	3.7	3.8
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFS400512	Temperature Testing Circuitry	25°C Figure A																																																																																			
Item	Overcurrent Protection																																																																																					
Object	+12V2.5A																																																																																					
1.Graph		<p>—△— Input Volt. 4.5V —□— Input Volt. 5V —*— Input Volt. 7V —○— Input Volt. 9V —◇— Input Volt. 13V</p>																																																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation activates when overcurrent protection is activated.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>12.000</td><td>2.870</td><td>2.978</td><td>3.296</td><td>3.345</td><td>3.082</td></tr> <tr><td>11.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.200</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.200</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]					4.5[V]	5[V]	7[V]	9[V]	13[V]	12.000	2.870	2.978	3.296	3.345	3.082	11.400	-	-	-	-	-	10.800	-	-	-	-	-	9.600	-	-	-	-	-	8.400	-	-	-	-	-	7.200	-	-	-	-	-	6.000	-	-	-	-	-	4.800	-	-	-	-	-	3.600	-	-	-	-	-	2.400	-	-	-	-	-	1.200	-	-	-	-	-	0.000	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																																	
12.000	2.870	2.978	3.296	3.345	3.082																																																																																	
11.400	-	-	-	-	-																																																																																	
10.800	-	-	-	-	-																																																																																	
9.600	-	-	-	-	-																																																																																	
8.400	-	-	-	-	-																																																																																	
7.200	-	-	-	-	-																																																																																	
6.000	-	-	-	-	-																																																																																	
4.800	-	-	-	-	-																																																																																	
3.600	-	-	-	-	-																																																																																	
2.400	-	-	-	-	-																																																																																	
1.200	-	-	-	-	-																																																																																	
0.000	-	-	-	-	-																																																																																	

COSEL


Model	MGFS400512																																																				
Item	Overvoltage Protection	Temperature 25°C Testing Circuitry Figure A																																																			
Object	+12V2.5A																																																				
1.Graph																																																					
		2.Values																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Operating Point [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 13[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>135</td> <td>135</td> <td>135</td> </tr> <tr> <td>10</td> <td>129</td> <td>129</td> <td>128</td> </tr> <tr> <td>20</td> <td>129</td> <td>129</td> <td>129</td> </tr> <tr> <td>30</td> <td>129</td> <td>128</td> <td>130</td> </tr> <tr> <td>40</td> <td>128</td> <td>128</td> <td>130</td> </tr> <tr> <td>50</td> <td>128</td> <td>129</td> <td>130</td> </tr> <tr> <td>60</td> <td>129</td> <td>129</td> <td>129</td> </tr> <tr> <td>70</td> <td>129</td> <td>130</td> <td>129</td> </tr> <tr> <td>80</td> <td>130</td> <td>132</td> <td>130</td> </tr> <tr> <td>90</td> <td>130</td> <td>133</td> <td>132</td> </tr> <tr> <td>100</td> <td>- *</td> <td>- *</td> <td>133</td> </tr> </tbody> </table>			Load Ratio [%]	Operating Point [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 13[V]	0	135	135	135	10	129	129	128	20	129	129	129	30	129	128	130	40	128	128	130	50	128	129	130	60	129	129	129	70	129	130	129	80	130	132	130	90	130	133	132	100	- *	- *	133
Load Ratio [%]	Operating Point [%]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 13[V]																																																		
0	135	135	135																																																		
10	129	129	128																																																		
20	129	129	129																																																		
30	129	128	130																																																		
40	128	128	130																																																		
50	128	129	130																																																		
60	129	129	129																																																		
70	129	130	129																																																		
80	130	132	130																																																		
90	130	133	132																																																		
100	- *	- *	133																																																		
<p>*During this area, overcurrent protection activates.</p>																																																					

COSEL

Model	MGFS400512
Item	Switching frequency (by Load Current)
Object	12V2.5A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.




Figure A




Figure B (Ripple and Ripple noise Characteristic)